



Actuated Valves Product
Premium Actuated Standard Butterfly Valve - Electric

Premium Actuated Standard Butterfly Valve - Electric



Industrial grade valve with patented seat design uses no liner. Eliminates seat-creep and reduces operating torque. Full-featured actuator can be custom configured with add-on accessories.

The following Features are Standard with Electric Actuated Standard Butterfly Valve.

- Solid SS316L Stem
- ANSI Class 150 Bolt Pattern
- 150 psi @ 73°F (23°C) (Thru 12")
- 14"-100 psi, 16"-85 psi
- 18"-70 psi, 20"-24"-50 psi
- 115 VAC standard, optional voltages available
- 2-Position Operation with 2-SPDT Limit Switches
- Additional set dry contacts SPDT limit Switches
- NEMA 4 Enclosure, Powder Coated
- Basic Manual Override 1-1/2 through 4" (Declutchable Available)
- Declutchable Manual Override 6" through 12"
- Illuminated Position Indicator
- Heater

When ordering Butterfly Valves with additional Actuator Accessories add a "-A" to the end of the basic part number and see **Electric Actuator Accessories for Butterfly Valves** to order add-on Actuator Accessories separately.

EX: 41101A112-015 add the -A to create 41101A112-015-A.

PVC

Size	Buna-N O-ring	EPDM O-ring	FKM O-ring	Prod Code
1-1/2	41101A112-015* CALL	41201A112-015* CALL	41301A112-015* CALL	510
2	41101A112-020* CALL	41201A112-020* CALL	41301A112-020* CALL	510
2-1/2	41101A112-025* CALL	41201A112-025* CALL	41301A112-025* CALL	510
3	41101A112-030* CALL	41201A112-030* CALL	41301A112-030* CALL	510
4	41101A112-040* CALL	41201A112-040* CALL	41301A112-040* CALL	510
6	41101A126-060* CALL	41201A126-060* CALL	41301A126-060* CALL	510
8	41101A126-080* CALL	41201A126-080* CALL	41301A126-080* CALL	510
10	41101A126-100* CALL	41201A126-100* CALL	41301A126-100* CALL	510
12	41101A123-120* CALL	41201A123-120* CALL	41301A123-120* CALL	510

CPVC

Size	Buna-N O-ring	EPDM O-ring	FKM O-ring	Prod Code
1-1/2	41102A112-015* CALL	41202A112-015* CALL	41302A112-015* CALL	512
2	41102A112-020* CALL	41202A112-020* CALL	41302A112-020* CALL	512
2-1/2	41102A112-025* CALL	41202A112-025* CALL	41302A112-025* CALL	512
3	41102A112-030* CALL	41202A112-030* CALL	41302A112-030* CALL	512
4	41102A112-040* CALL	41202A112-040* CALL	41302A112-040* CALL	512
6	41102A126-060* CALL	41202A126-060* CALL	41302A126-060* CALL	512

CPVC (continued)

Size	Buna-N O-ring	EPDM O-ring	FKM O-ring	Prod Code
8	41102A126-080* CALL	41202A126-080* CALL	41302A126-080* CALL	512
10	41102A126-100* CALL	41202A126-100* CALL	41302A126-100* CALL	512
12	41102A123-120* CALL	41202A123-120* CALL	41302A123-120* CALL	512

Polypropylene

Size	Buna-N O-ring	EPDM O-ring	FKM O-ring	Prod Code
1-1/2	41103A112-015* CALL	41203A112-015* CALL	41303A112-015* CALL	514
2	41103A112-020* CALL	41203A112-020* CALL	41303A112-020* CALL	514
2-1/2	41103A112-025* CALL	41203A112-025* CALL	41303A112-025* CALL	512
3	41103A112-030* CALL	41203A112-030* CALL	41303A112-030* CALL	514
4	41103A112-040* CALL	41203A112-040* CALL	41303A112-040* CALL	514
6	41103A126-060* CALL	41203A126-060* CALL	41303A126-060* CALL	514
8	41103A126-080* CALL	41203A126-080* CALL	41303A126-080* CALL	514
10	41103A126-100* CALL	41203A126-100* CALL	41303A126-100* CALL	514
12	41103A123-120* CALL	41203A123-120* CALL	41303A123-120* CALL	514

14, 16, 18, 20 & 24 - Varies On Application

NOTE: Due to variations in potential system operating conditions, 14" -24" Actuated Butterfly Valve packages are sized according to application parameters. Please contact Spears® for additional information.