



## PRODUCT INFORMATION

### APPLICATION

Spears® Copper Tube Size (CTS) fittings are manufactured from chlorinated polyvinyl chloride (CPVC) for use with SDR-11 piping systems of CTS outside diameter in hot and cold water distribution systems. Check state and local codes for application and restrictions.

### CONFORMANCE STANDARDS

Spears® CPVC CTS fittings conform to ASTM D 2846 Specification for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Hot and Cold Water Distribution Systems.

### WORKING PRESSURE

Spears® CPVC CTS fittings have a continuous working pressure rating of 100 psi at 180°F (82°C) [400 psi at 73°F (23°C)].

### PRODUCT CERTIFICATION

Spears® CPVC CTS fittings and Special Reinforced (SR) Thread transition adapters are tested and certified by the National Sanitation Foundation (NSF®) to ASTM D 2846 for use in Hot and Cold Water Distribution Systems, and for safe use in potable water systems under NSF® Standard 14/61.

### TESTING

Once the system has been installed and allowed to cure properly, the system shall be tested in accordance with applicable code requirements. When testing with water (hydrostatic testing), the system must be slowly filled with water and the air bled from the highest and furthest points in the system before test pressure is applied. Failure to do so can cause damage to the piping system and could be harmful to the job site personnel should a failure occur. If a leak is found, the affected product must be cut out and discarded. A new section can be installed using couplings or other approved means.

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

### Tee

#### Socket x Socket x Socket



NSF® Certified Lead Free

|          |       |     |     |     |       |
|----------|-------|-----|-----|-----|-------|
| 4101-005 | 1/2   | 100 | 500 | 035 | 1.07  |
| 4101-007 | 3/4   | 50  | 250 | 035 | 2.00  |
| 4101-010 | 1     | 10  | 100 | 035 | 10.03 |
| 4101-012 | 1-1/4 | 10  | 100 | 035 | 15.46 |
| 4101-015 | 1-1/2 | 5   | 50  | 035 | 20.14 |
| 4101-020 | 2     | 5   | 25  | 035 | 32.56 |

### Tee - Reducing

#### Socket x Socket x Socket



NSF® Certified Lead Free

|                       |               |    |     |     |       |
|-----------------------|---------------|----|-----|-----|-------|
| 4101-074              | 1/2X1/2X3/4   | 10 | 100 | 035 | 3.72  |
| 4101-094              | 3/4X1/2X1/2   | 50 | 250 | 035 | 1.99  |
| 4101-095              | 3/4X1/2X3/4   | 25 | 250 | 035 | 2.72  |
| 4101-101              | 3/4X3/4X1/2   | 50 | 250 | 035 | 2.07  |
| 4101-102 <sup>1</sup> | 3/4X3/4X1     | 10 | 100 | 035 | 22.22 |
| 4101-120 <sup>1</sup> | 1X1/2X1/2     | 10 | 100 | 035 | 23.95 |
| 4101-121 <sup>1</sup> | 1X1/2X3/4     | 10 | 100 | 035 | 24.60 |
| 4101-122 <sup>1</sup> | 1X1/2X1       | 10 | 100 | 035 | 18.75 |
| 4101-124 <sup>1</sup> | 1X3/4X1/2     | 10 | 100 | 035 | 22.36 |
| 4101-125              | 1X3/4X3/4     | 10 | 100 | 035 | 12.22 |
| 4101-126 <sup>1</sup> | 1X3/4X1       | 10 | 100 | 035 | 17.89 |
| 4101-130              | 1X1X1/2       | 10 | 100 | 035 | 11.44 |
| 4101-131              | 1X1X3/4       | 10 | 100 | 035 | 10.92 |
| 4101-138 <sup>1</sup> | 1-1/4X1/2X1/2 | 10 | 80  | 035 | 27.92 |
| 4101-139 <sup>1</sup> | 1-1/4X1/2X3/4 | 10 | 80  | 035 | 27.92 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

### Tee - Reducing (continued)

#### Socket x Socket x Socket

|                       |                   |    |     |     |       |
|-----------------------|-------------------|----|-----|-----|-------|
| 4101-142 <sup>1</sup> | 1-1/4X1/2X1-1/4   | 10 | 80  | 035 | 27.92 |
| 4101-146 <sup>1</sup> | 1-1/4X3/4X1/2     | 10 | 80  | 035 | 27.92 |
| 4101-147 <sup>1</sup> | 1-1/4X3/4X3/4     | 10 | 80  | 035 | 24.94 |
| 4101-148 <sup>1</sup> | 1-1/4X3/4X1       | 10 | 80  | 035 | 27.03 |
| 4101-149 <sup>1</sup> | 1-1/4X3/4X1-1/4   | 10 | 80  | 035 | 24.84 |
| 4101-156 <sup>1</sup> | 1-1/4X1X1/2       | 10 | 80  | 035 | 26.40 |
| 4101-157 <sup>1</sup> | 1-1/4X1X3/4       | 10 | 80  | 035 | 25.27 |
| 4101-158 <sup>1</sup> | 1-1/4X1X1         | 10 | 100 | 035 | 25.95 |
| 4101-159 <sup>1</sup> | 1-1/4X1X1-1/4     | 10 | 80  | 035 | 29.11 |
| 4101-166              | 1-1/4X1-1/4X1/2   | 10 | 100 | 035 | 27.92 |
| 4101-168              | 1-1/4X1-1/4X1     | 10 | 100 | 035 | 26.26 |
| 4101-167              | 1-1/4X1-1/4X3/4   | 10 | 100 | 035 | 24.84 |
| 4101-169 <sup>1</sup> | 1-1/4X1-1/4X1-1/2 | 5  | 40  | 035 | 27.92 |
| 4101-173 <sup>1</sup> | 1-1/2X1/2X1/2     | 5  | 40  | 035 | 33.82 |
| 4101-174 <sup>1</sup> | 1-1/2X1/2X3/4     | 5  | 40  | 035 | 33.82 |
| 4101-175 <sup>1</sup> | 1-1/2X1/2X1       | 5  | 40  | 035 | 33.82 |
| 4101-176 <sup>1</sup> | 1-1/2X1/2X1-1/4   | 5  | 40  | 035 | 33.82 |
| 4101-177 <sup>1</sup> | 1-1/2X1/2X1-1/2   | 5  | 40  | 035 | 33.82 |
| 4101-182 <sup>1</sup> | 1-1/2X3/4X1/2     | 5  | 40  | 035 | 33.82 |
| 4101-184 <sup>1</sup> | 1-1/2X3/4X3/4     | 5  | 40  | 035 | 33.82 |
| 4101-185 <sup>1</sup> | 1-1/2X3/4X1       | 5  | 40  | 035 | 33.82 |
| 4101-186 <sup>1</sup> | 1-1/2X3/4X1-1/4   | 5  | 40  | 035 | 33.82 |
| 4101-188 <sup>1</sup> | 1-1/2X3/4X1-1/2   | 5  | 40  | 035 | 33.82 |
| 4101-193 <sup>1</sup> | 1-1/2X1X1/2       | 5  | 40  | 035 | 33.82 |
| 4101-194 <sup>1</sup> | 1-1/2X1X3/4       | 5  | 40  | 035 | 33.82 |
| 4101-195 <sup>1</sup> | 1-1/2X1X1         | 10 | 100 | 035 | 33.82 |
| 4101-196 <sup>1</sup> | 1-1/2X1X1-1/4     | 5  | 40  | 035 | 33.82 |
| 4101-197 <sup>1</sup> | 1-1/2X1X1-1/2     | 5  | 40  | 035 | 33.82 |
| 4101-199 <sup>1</sup> | 1-1/2X1-1/4X1/2   | 5  | 40  | 035 | 33.82 |
| 4101-201 <sup>1</sup> | 1-1/2X1-1/4X3/4   | 5  | 40  | 035 | 33.82 |
| 4101-202 <sup>1</sup> | 1-1/2X1-1/4X1     | 5  | 40  | 035 | 33.82 |



**CTS CPVC Product**  
**EverTUFF® CPVC CTS Products**

| Part Number | Size | Std<br>Pk | Mstr<br>Ctn | Prod<br>Code | MSRP |
|-------------|------|-----------|-------------|--------------|------|
|-------------|------|-----------|-------------|--------------|------|

**Tee - Reducing (continued)**

**Socket x Socket x Socket**

|                       |                   |    |     |     |       |
|-----------------------|-------------------|----|-----|-----|-------|
| 4101-203 <sup>1</sup> | 1-1/2X1-1/4X1-1/4 | 5  | 40  | 035 | 33.82 |
| 4101-204 <sup>1</sup> | 1-1/2X1-1/4X1-1/2 | 5  | 40  | 035 | 33.82 |
| 4101-209              | 1-1/2X1-1/2X1/2   | 10 | 50  | 035 | 30.05 |
| 4101-210              | 1-1/2X1-1/2X3/4   | 10 | 100 | 035 | 25.05 |
| 4101-211              | 1-1/2X1-1/2X1     | 5  | 50  | 035 | 22.94 |
| 4101-212 <sup>1</sup> | 1-1/2X1-1/2X1-1/4 | 5  | 50  | 035 | 33.82 |
| 4101-213 <sup>1</sup> | 1-1/2X1-1/2X2     | 5  | 0   | 035 | 33.82 |
| 4101-216 <sup>1</sup> | 2X1/2X1/2         | 5  | 0   | 035 | 42.34 |
| 4101-217 <sup>1</sup> | 2X1/2X3/4         | 5  | 0   | 035 | 42.34 |
| 4101-218 <sup>1</sup> | 2X1/2X1           | 5  | 0   | 035 | 42.34 |
| 4101-219 <sup>1</sup> | 2X1/2X1-1/4       | 5  | 0   | 035 | 42.34 |
| 4101-220 <sup>1</sup> | 2X1/2X1-1/2       | 5  | 0   | 035 | 42.34 |
| 4101-221 <sup>1</sup> | 2X1/2X2           | 5  | 0   | 035 | 42.34 |
| 4101-222 <sup>1</sup> | 2X3/4X1/2         | 5  | 0   | 035 | 42.34 |
| 4101-223 <sup>1</sup> | 2X3/4X3/4         | 5  | 0   | 035 | 42.34 |
| 4101-224 <sup>1</sup> | 2X3/4X1           | 5  | 0   | 035 | 42.34 |
| 4101-225 <sup>1</sup> | 2X3/4X1-1/4       | 5  | 0   | 035 | 42.34 |
| 4101-226 <sup>1</sup> | 2X3/4X1-1/2       | 5  | 0   | 035 | 42.34 |
| 4101-227 <sup>1</sup> | 2X3/4X2           | 5  | 0   | 035 | 42.34 |
| 4101-228 <sup>1</sup> | 2X1X1/2           | 5  | 0   | 035 | 42.34 |
| 4101-229 <sup>1</sup> | 2X1X3/4           | 5  | 0   | 035 | 42.34 |
| 4101-230 <sup>1</sup> | 2X1X1             | 5  | 0   | 035 | 42.34 |
| 4101-231 <sup>1</sup> | 2X1X1-1/4         | 5  | 0   | 035 | 42.34 |
| 4101-232 <sup>1</sup> | 2X1X1-1/2         | 5  | 0   | 035 | 42.34 |
| 4101-233 <sup>1</sup> | 2X1X2             | 5  | 0   | 035 | 42.34 |
| 4101-234 <sup>1</sup> | 2X1-1/4X1/2       | 5  | 0   | 035 | 42.34 |
| 4101-235 <sup>1</sup> | 2X1-1/4X3/4       | 5  | 0   | 035 | 42.34 |
| 4101-236 <sup>1</sup> | 2X1-1/4X1         | 5  | 0   | 035 | 42.34 |
| 4101-237 <sup>1</sup> | 2X1-1/2X1/2       | 5  | 0   | 035 | 42.34 |
| 4101-238 <sup>1</sup> | 2X1-1/2X3/4       | 5  | 0   | 035 | 42.34 |
| 4101-239 <sup>1</sup> | 2X1-1/2X1         | 5  | 0   | 035 | 42.34 |
| 4101-240 <sup>1</sup> | 2X1-1/2X1-1/4     | 5  | 0   | 035 | 42.34 |
| 4101-241 <sup>1</sup> | 2X1-1/2X1-1/2     | 5  | 0   | 035 | 42.34 |
| 4101-242 <sup>1</sup> | 2X1-1/4X1-1/4     | 5  | 0   | 035 | 42.34 |
| 4101-243 <sup>1</sup> | 2X1-1/4X1-1/2     | 5  | 0   | 035 | 42.34 |
| 4101-244 <sup>1</sup> | 2X1-1/4X2         | 5  | 0   | 035 | 42.34 |
| 4101-247              | 2X2X1/2           | 10 | 30  | 035 | 37.98 |
| 4101-248              | 2X2X3/4           | 5  | 25  | 035 | 32.66 |
| 4101-249              | 2X2X1             | 5  | 25  | 035 | 32.66 |
| 4101-250 <sup>1</sup> | 2X2X1-1/4         | 5  | 25  | 035 | 36.81 |
| 4101-251              | 2X2X1-1/2         | 5  | 25  | 035 | 36.81 |
| 4101-257 <sup>1</sup> | 2X1-1/2X2         | 5  | 0   | 035 | 36.81 |

<sup>1</sup> Outlet sized with bushing.

**Drop Ear Tee - CPVC Fitting with Bracket**

**Socket x Socket x Socket**

NSF® Certified Lead Free

|            |     |    |     |     |      |
|------------|-----|----|-----|-----|------|
| DE4101-005 | 1/2 | 25 | 150 | 035 | 3.80 |
|------------|-----|----|-----|-----|------|



| Part Number | Size | Std<br>Pk | Mstr<br>Ctn | Prod<br>Code | MSRP |
|-------------|------|-----------|-------------|--------------|------|
|-------------|------|-----------|-------------|--------------|------|

**90° EII**

**Socket x Socket**



NSF® Certified Lead Free

|          |       |     |      |     |       |
|----------|-------|-----|------|-----|-------|
| 4106-005 | 1/2   | 100 | 1000 | 035 | .83   |
| 4106-007 | 3/4   | 50  | 500  | 035 | 1.37  |
| 4106-010 | 1     | 10  | 100  | 035 | 4.00  |
| 4106-012 | 1-1/4 | 10  | 100  | 035 | 7.99  |
| 4106-015 | 1-1/2 | 10  | 100  | 035 | 14.40 |
| 4106-020 | 2     | 5   | 100  | 035 | 27.64 |

**90° EII - Reducing**

**Socket x Socket**



NSF® Certified Lead Free

|                       |             |    |     |     |       |
|-----------------------|-------------|----|-----|-----|-------|
| 4106-101              | 3/4X1/2     | 50 | 250 | 035 | 2.89  |
| 4106-130 <sup>1</sup> | 1X1/2       | 25 | 200 | 035 | 10.93 |
| 4106-131 <sup>1</sup> | 1X3/4       | 25 | 200 | 035 | 10.94 |
| 4106-167 <sup>1</sup> | 1-1/4X3/4   | 10 | 80  | 035 | 18.18 |
| 4106-168 <sup>1</sup> | 1-1/4X1     | 10 | 80  | 035 | 17.34 |
| 4106-209 <sup>1</sup> | 1-1/2X1/2   | 10 | 0   | 035 | 29.44 |
| 4106-210 <sup>1</sup> | 1-1/2X3/4   | 10 | 0   | 035 | 29.44 |
| 4106-211 <sup>1</sup> | 1-1/2X1     | 10 | 0   | 035 | 29.04 |
| 4106-212 <sup>1</sup> | 1-1/2X1-1/4 | 10 | 0   | 035 | 29.04 |
| 4106-247 <sup>1</sup> | 2X1/2       | 5  | 30  | 035 | 60.43 |
| 4106-248 <sup>1</sup> | 2X3/4       | 5  | 30  | 035 | 59.05 |
| 4106-249 <sup>1</sup> | 2X1         | 5  | 30  | 035 | 58.40 |
| 4106-250 <sup>1</sup> | 2X1-1/4     | 5  | 30  | 035 | 58.36 |
| 4106-251 <sup>1</sup> | 2X1-1/2     | 5  | 30  | 035 | 58.36 |

<sup>1</sup> Outlet sized with bushing.

**90° EII - Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**



NSF® Certified Lead Free

|            |     |    |     |     |      |
|------------|-----|----|-----|-----|------|
| 4107-005SR | 1/2 | 50 | 300 | 035 | 9.28 |
|------------|-----|----|-----|-----|------|

**Drop Ear 90° EII - CPVC Zinc Reinforced(One Piece Unit)**

**Socket x SR Fipt - Zinc Collar**



NSF® Certified Lead Free

|               |     |    |     |     |       |
|---------------|-----|----|-----|-----|-------|
| DEZ4107-005SR | 1/2 | 10 | 150 | 035 | 19.44 |
|---------------|-----|----|-----|-----|-------|

**Drop Ear 90° EII - CPVC Fitting with Bracket**

**Socket x Socket**



NSF® Certified Lead Free

|            |     |    |     |     |      |
|------------|-----|----|-----|-----|------|
| DE4106-005 | 1/2 | 25 | 150 | 035 | 2.52 |
|------------|-----|----|-----|-----|------|

CTS CPVC Product  
**EverTUFF® CPVC CTS Products**



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Drop Ear 90° EII - Special Reinforced CPVC Fitting with Bracket**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead Free

|              |     |    |     |     |      |
|--------------|-----|----|-----|-----|------|
| DE4107-005SR | 1/2 | 10 | 200 | 035 | 9.57 |
|--------------|-----|----|-----|-----|------|



**Drop Ear Tee & EII Bracket ONLY**

**For 4101-005 and 4106-005**

|         |     |   |     |     |      |
|---------|-----|---|-----|-----|------|
| DES-005 | 1/2 | 1 | 800 | 035 | 1.89 |
|---------|-----|---|-----|-----|------|



**Drop Ear SR EII Bracket ONLY**

**For 4107-005SR**

|         |     |     |   |     |      |
|---------|-----|-----|---|-----|------|
| DET-005 | 1/2 | 400 | 0 | 035 | 1.89 |
|---------|-----|-----|---|-----|------|



**Drop Ear EII - CPVC One Piece**

**Socket x Socket**

NSF® Certified Lead Free

|             |     |    |     |     |      |
|-------------|-----|----|-----|-----|------|
| DE4106-005C | 1/2 | 50 | 250 | 035 | 2.48 |
|-------------|-----|----|-----|-----|------|



**Drop Ear EII - CPVC One Piece with Gasket**

**Socket x Fipt**

NSF® Certified Lead Free

|              |     |    |     |     |      |
|--------------|-----|----|-----|-----|------|
| DE4107-005CG | 1/2 | 50 | 250 | 035 | 4.21 |
|--------------|-----|----|-----|-----|------|



**Drop Ear EII - Stainless Steel Thread**

**Socket x SS Fipt**

NSF® Certified Lead Free

|              |     |     |   |     |       |
|--------------|-----|-----|---|-----|-------|
| DE4107-005SS | 1/2 | 100 | 0 | 036 | 19.94 |
|--------------|-----|-----|---|-----|-------|



**Drop Ear EII - Stainless Steel Thread/CPVC Body**

**Socket x SS Fipt**

NSF® Certified Lead Free

|               |     |     |   |     |       |
|---------------|-----|-----|---|-----|-------|
| DE4107-005CSS | 1/2 | 100 | 0 | 036 | 14.18 |
|---------------|-----|-----|---|-----|-------|



**90° Street EII**

**Spigot x Socket**

NSF® Certified Lead Free

|          |     |     |     |     |     |
|----------|-----|-----|-----|-----|-----|
| 4109-005 | 1/2 | 100 | 500 | 035 | .98 |
|----------|-----|-----|-----|-----|-----|



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**90° Street EII (continued)**

**Spigot x Socket**

|          |     |    |     |     |      |
|----------|-----|----|-----|-----|------|
| 4109-007 | 3/4 | 50 | 250 | 035 | 1.57 |
| 4109-010 | 1   | 50 | 100 | 035 | 7.21 |

**90° Stub Out EII**

**Socket x Closed End**

NSF® Certified Lead Free

|           |     |    |   |     |       |
|-----------|-----|----|---|-----|-------|
| S4106-005 | 1/2 | 50 | 0 | 035 | 14.11 |
|-----------|-----|----|---|-----|-------|



**45° EII**

**Socket x Socket**

NSF® Certified Lead Free

|          |       |     |     |     |       |
|----------|-------|-----|-----|-----|-------|
| 4117-005 | 1/2   | 100 | 500 | 035 | 1.05  |
| 4117-007 | 3/4   | 50  | 250 | 035 | 1.83  |
| 4117-010 | 1     | 10  | 100 | 035 | 4.64  |
| 4117-012 | 1-1/4 | 10  | 100 | 035 | 9.84  |
| 4117-015 | 1-1/2 | 10  | 100 | 035 | 14.26 |
| 4117-020 | 2     | 10  | 100 | 035 | 29.87 |



**45° Street EII**

**Spigot x Socket**

NSF® Certified Lead Free

|          |     |     |     |     |      |
|----------|-----|-----|-----|-----|------|
| 4127-005 | 1/2 | 100 | 500 | 035 | 2.24 |
| 4127-007 | 3/4 | 50  | 250 | 035 | 3.00 |
| 4127-010 | 1   | 50  | 250 | 035 | 8.63 |



**Coupling**

**Socket x Socket**

NSF® Certified Lead Free

|          |       |     |      |     |       |
|----------|-------|-----|------|-----|-------|
| 4129-005 | 1/2   | 100 | 1000 | 035 | .68   |
| 4129-007 | 3/4   | 50  | 500  | 035 | .91   |
| 4129-010 | 1     | 10  | 100  | 035 | 4.07  |
| 4129-012 | 1-1/4 | 10  | 100  | 035 | 5.26  |
| 4129-015 | 1-1/2 | 10  | 100  | 035 | 7.44  |
| 4129-020 | 2     | 10  | 50   | 035 | 14.17 |



**Coupling - Reducer**

**Socket x Socket**

NSF® Certified Lead Free

|          |         |    |     |     |      |
|----------|---------|----|-----|-----|------|
| 4129-101 | 3/4X1/2 | 50 | 250 | 035 | 1.45 |
| 4129-130 | 1X1/2   | 25 | 150 | 035 | 4.88 |
| 4129-131 | 1X3/4   | 25 | 150 | 035 | 4.88 |



Made in the U.S.A.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

Effective 06/26/2017 See MSRP-1 Sheet or Check Spears® On-line Catalog @ www.spearsmfg.com for Pricing



CTS CPVC Product  
**EverTUFF® CPVC CTS Products**

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Coupling - Reducer (continued)**

**Socket x Socket**

|                       |             |    |     |     |       |
|-----------------------|-------------|----|-----|-----|-------|
| 4129-166 <sup>1</sup> | 1-1/4X1/2   | 10 | 120 | 035 | 15.42 |
| 4129-167 <sup>1</sup> | 1-1/4X3/4   | 10 | 120 | 035 | 15.42 |
| 4129-168 <sup>1</sup> | 1-1/4X1     | 10 | 120 | 035 | 15.42 |
| 4129-209 <sup>1</sup> | 1-1/2X1/2   | 10 | 60  | 035 | 15.42 |
| 4129-210 <sup>1</sup> | 1-1/2X3/4   | 10 | 60  | 035 | 15.42 |
| 4129-211 <sup>1</sup> | 1-1/2X1     | 10 | 60  | 035 | 15.42 |
| 4129-212 <sup>1</sup> | 1-1/2X1-1/4 | 10 | 120 | 035 | 15.42 |
| 4129-247 <sup>1</sup> | 2X1/2       | 10 | 0   | 035 | 41.08 |
| 4129-248 <sup>1</sup> | 2X3/4       | 10 | 0   | 035 | 41.08 |
| 4129-249              | 2X1         | 10 | 0   | 035 | 41.08 |
| 4129-250 <sup>1</sup> | 2X1-1/4     | 10 | 0   | 035 | 41.08 |
| 4129-251 <sup>1</sup> | 2X1-1/2     | 10 | 0   | 035 | 41.08 |

<sup>1</sup> Outlet sized with bushing.

**GripLoc™ Coupling**

**WARNING: DO NOT INSERT FINGERS**  
**Grip Socket x Grip Socket - Uses No Solvent Cement**



NSF® Certified Lead Free

|            |     |    |    |     |       |
|------------|-----|----|----|-----|-------|
| GL4129-005 | 1/2 | 1  | 75 | 135 | 15.79 |
| GL4129-007 | 3/4 | 1  | 50 | 135 | 16.45 |
| GL4129-010 | 1   | 12 | 24 | 135 | 20.83 |

Note: The GripLoc™ is water tight, permanent and cannot be removed.

**Female Adapter - with Gasket**

**Socket x Thread**



For Cold Water Service Only - NSF® Certified Lead Free

|            |     |     |     |     |      |
|------------|-----|-----|-----|-----|------|
| 4135-005OR | 1/2 | 100 | 500 | 035 | 2.95 |
| 4135-007OR | 3/4 | 50  | 250 | 035 | 4.16 |
| 4135-010OR | 1   | 10  | 100 | 035 | 4.82 |

**Female Adapter - Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use NO Thread Sealant**



NSF® Certified Lead Free

|             |       |    |     |     |        |
|-------------|-------|----|-----|-----|--------|
| 4135-005BRG | 1/2   | 25 | 150 | 033 | 14.93  |
| 4135-007BRG | 3/4   | 25 | 150 | 033 | 19.77  |
| 4135-010BRG | 1     | 15 | 90  | 033 | 68.26  |
| 4135-012BRG | 1-1/4 | 15 | 60  | 033 | 114.43 |
| 4135-015BRG | 1-1/2 | 10 | 40  | 033 | 130.28 |
| 4135-020BRG | 2     | 8  | 32  | 033 | 203.66 |

**Female Adapter - Reducing Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use NO Thread Sealant**



NSF® Certified Lead Free

|             |         |    |     |     |       |
|-------------|---------|----|-----|-----|-------|
| 4135-101BRG | 3/4X1/2 | 25 | 150 | 033 | 29.18 |
| 4135-130BRG | 1X1/2   | 50 | 0   | 033 | 49.49 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Female Adapter - CPVC Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**



NSF® Certified Lead Free

|            |     |    |     |     |       |
|------------|-----|----|-----|-----|-------|
| 4135-005SR | 1/2 | 25 | 200 | 036 | 7.97  |
| 4135-007SR | 3/4 | 25 | 300 | 036 | 8.76  |
| 4135-010SR | 1   | 5  | 100 | 036 | 11.11 |

**Female Adapter - CPVC Reducing Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**



NSF® Certified Lead Free

|            |       |    |     |     |       |
|------------|-------|----|-----|-----|-------|
| 4135-131SR | 1X3/4 | 25 | 150 | 036 | 15.47 |
|------------|-------|----|-----|-----|-------|

**Female Adapter - Stainless Steel Thread Transition**

**Socket x SS Fipt**



NSF® Certified Lead Free

|            |       |    |     |     |        |
|------------|-------|----|-----|-----|--------|
| 4135-005SS | 1/2   | 25 | 150 | 036 | 9.95   |
| 4135-007SS | 3/4   | 25 | 100 | 036 | 14.27  |
| 4135-010SS | 1     | 25 | 50  | 036 | 23.69  |
| 4135-012SS | 1-1/4 | 16 | 0   | 036 | 54.56  |
| 4135-015SS | 1-1/2 | 16 | 0   | 036 | 91.55  |
| 4135-020SS | 2     | 8  | 0   | 036 | 135.33 |

**Male Adapter**

**Mipt x Socket**



For Cold Water Service Only - NSF® Certified Lead Free

|          |       |     |      |     |       |
|----------|-------|-----|------|-----|-------|
| 4136-005 | 1/2   | 100 | 1000 | 035 | .87   |
| 4136-007 | 3/4   | 50  | 500  | 035 | 1.47  |
| 4136-010 | 1     | 10  | 100  | 035 | 6.98  |
| 4136-012 | 1-1/4 | 10  | 100  | 035 | 10.80 |
| 4136-015 | 1-1/2 | 10  | 100  | 035 | 13.33 |
| 4136-020 | 2     | 10  | 100  | 035 | 21.97 |

**Male Adapter - Reducing**

**Mipt x Socket**



For Cold Water Service Only - NSF® Certified Lead Free

|          |         |    |     |     |      |
|----------|---------|----|-----|-----|------|
| 4136-074 | 1/2X3/4 | 50 | 250 | 035 | 3.56 |
| 4136-101 | 3/4X1/2 | 50 | 250 | 035 | 3.56 |

**Male Adapter - Spigot**

**Mipt x Spigot**



For Cold Water Service Only - NSF® Certified Lead Free

|          |     |    |     |     |      |
|----------|-----|----|-----|-----|------|
| 4161-005 | 1/2 | 50 | 700 | 035 | 2.81 |
|----------|-----|----|-----|-----|------|

**CTS CPVC Product**  
**EverTUFF® CPVC CTS Products**



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Male Adapter - Internal Stainless Steel Reinforced**

**R Mipt x Socket - Stainless Steel Sleeve**



NSF® Certified Lead Free

|           |       |    |     |     |       |
|-----------|-------|----|-----|-----|-------|
| 4136-005R | 1/2   | 25 | 300 | 036 | 10.22 |
| 4136-007R | 3/4   | 25 | 300 | 036 | 11.36 |
| 4136-010R | 1     | 10 | 120 | 036 | 16.93 |
| 4136-012R | 1-1/4 | 20 | 120 | 036 | 51.96 |

**Male Adapter - Transition with CPVC Lined Brass Thread**

**Brass Mipt x Socket**



NSF® Certified Lead Free

|            |       |    |     |     |        |
|------------|-------|----|-----|-----|--------|
| 4136-005BR | 1/2   | 60 | 360 | 033 | 17.91  |
| 4136-007BR | 3/4   | 40 | 160 | 033 | 23.72  |
| 4136-010BR | 1     | 10 | 60  | 033 | 81.92  |
| 4136-012BR | 1-1/4 | 10 | 60  | 033 | 137.32 |
| 4136-015BR | 1-1/2 | 10 | 40  | 033 | 156.34 |
| 4136-020BR | 2     | 8  | 32  | 033 | 244.38 |

**Male Adapter - Transition with Stainless Steel Thread**

**Socket x SS Mipt**



NSF® Certified Lead Free

|            |       |    |     |     |        |
|------------|-------|----|-----|-----|--------|
| 4136-005SS | 1/2   | 25 | 150 | 036 | 9.96   |
| 4136-007SS | 3/4   | 25 | 100 | 036 | 15.76  |
| 4136-010SS | 1     | 25 | 50  | 036 | 26.67  |
| 4136-012SS | 1-1/4 | 16 | 0   | 036 | 53.43  |
| 4136-015SS | 1-1/2 | 16 | 0   | 036 | 91.55  |
| 4136-020SS | 2     | 8  | 0   | 036 | 100.71 |

**Reducer Bushing**

**Spigot x Socket**



NSF® Certified Lead Free

|          |             |    |     |     |       |
|----------|-------------|----|-----|-----|-------|
| 4137-101 | 3/4X1/2     | 10 | 500 | 035 | 1.04  |
| 4137-130 | 1X1/2       | 10 | 100 | 035 | 3.40  |
| 4137-131 | 1X3/4       | 10 | 100 | 035 | 3.40  |
| 4137-166 | 1-1/4X1/2   | 10 | 100 | 035 | 4.40  |
| 4137-167 | 1-1/4X3/4   | 10 | 100 | 035 | 4.40  |
| 4137-168 | 1-1/4X1     | 10 | 100 | 035 | 4.40  |
| 4137-209 | 1-1/2X1/2   | 10 | 100 | 035 | 5.54  |
| 4137-210 | 1-1/2X3/4   | 10 | 100 | 035 | 5.54  |
| 4137-211 | 1-1/2X1     | 10 | 100 | 035 | 5.81  |
| 4137-212 | 1-1/2X1-1/4 | 10 | 100 | 035 | 6.04  |
| 4137-247 | 2X1/2       | 10 | 50  | 035 | 12.59 |
| 4137-248 | 2X3/4       | 10 | 50  | 035 | 12.59 |
| 4137-249 | 2X1         | 10 | 60  | 035 | 12.59 |
| 4137-250 | 2X1-1/4     | 10 | 50  | 035 | 12.59 |
| 4137-251 | 2X1-1/2     | 10 | 100 | 035 | 12.59 |

Made in the U.S.A.

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Transition Bushing**

**IPS Spigot x CTS Socket**



NSF® Certified Lead Free

|          |       |    |     |     |      |
|----------|-------|----|-----|-----|------|
| 4140-005 | 1/2   | 10 | 600 | 035 | 4.39 |
| 4140-007 | 3/4   | 10 | 100 | 035 | 4.59 |
| 4140-010 | 1     | 10 | 100 | 035 | 5.07 |
| 4140-012 | 1-1/4 | 10 | 100 | 035 | 6.27 |
| 4140-015 | 1-1/2 | 10 | 100 | 035 | 7.91 |
| 4140-020 | 2     | 10 | 50  | 035 | 8.63 |

**Transition Coupling**

**IPS Socket x CTS Socket**



NSF® Certified Lead Free

|          |     |    |     |     |      |
|----------|-----|----|-----|-----|------|
| 4141-007 | 3/4 | 25 | 300 | 035 | 3.14 |
| 4141-010 | 1   | 10 | 150 | 035 | 5.94 |

**Cap**

**Socket**



NSF® Certified Lead Free

|          |       |     |     |     |       |
|----------|-------|-----|-----|-----|-------|
| 4147-005 | 1/2   | 100 | 500 | 035 | .75   |
| 4147-007 | 3/4   | 50  | 250 | 035 | .95   |
| 4147-010 | 1     | 10  | 100 | 035 | 3.47  |
| 4147-012 | 1-1/4 | 10  | 100 | 035 | 4.78  |
| 4147-015 | 1-1/2 | 10  | 100 | 035 | 7.36  |
| 4147-020 | 2     | 10  | 50  | 035 | 14.85 |

**GripLoc™ Cap**

**WARNING: DO NOT INSERT FINGERS  
Grip Socket - Uses No Solvent Cement**



NSF® Certified Lead Free

|            |     |    |     |     |       |
|------------|-----|----|-----|-----|-------|
| GL4147-005 | 1/2 | 25 | 200 | 135 | 15.36 |
| GL4147-007 | 3/4 | 25 | 150 | 135 | 16.31 |
| GL4147-010 | 1   | 10 | 50  | 135 | 18.17 |

Note: The GripLoc™ is water tight, permanent and cannot be removed.

**Union**

**Socket with EPDM O-ring Seal**



100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

|          |       |    |     |     |       |
|----------|-------|----|-----|-----|-------|
| 4197-005 | 1/2   | 25 | 150 | 035 | 8.00  |
| 4197-007 | 3/4   | 12 | 48  | 035 | 12.68 |
| 4197-010 | 1     | 36 | 0   | 035 | 20.79 |
| 4197-012 | 1-1/4 | 12 | 48  | 035 | 40.58 |
| 4197-015 | 1-1/2 | 12 | 0   | 035 | 43.12 |
| 4197-020 | 2     | 6  | 36  | 035 | 67.77 |



**CTS CPVC Product**  
**EverTUFF® CPVC CTS Products**

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Union - Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**



100 psi Maximum Internal Pressure @ 180°F (82°C) - NSF® Certified Lead Free

|            |     |    |     |     |       |
|------------|-----|----|-----|-----|-------|
| 4199-005SR | 1/2 | 20 | 120 | 036 | 14.59 |
| 4199-007SR | 3/4 | 10 | 60  | 036 | 25.04 |
| 4199-010SR | 1   | 10 | 40  | 036 | 41.58 |

**Union - Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use No Thread Sealant**



100 psi Maximum Internal Pressure @ 180°F (82°C) - NSF® Certified Lead Free

|             |     |    |     |     |       |
|-------------|-----|----|-----|-----|-------|
| 4199-005BRG | 1/2 | 20 | 120 | 033 | 24.00 |
| 4199-007BRG | 3/4 | 10 | 60  | 033 | 36.18 |
| 4199-010BRG | 1   | 10 | 40  | 033 | 62.37 |

**Transition Compression Adapter**

**Comp w/Gasket x CPVC Spigot**



NSF® Certified Lead Free

|         |     |    |     |     |      |
|---------|-----|----|-----|-----|------|
| TCA-005 | 1/2 | 25 | 200 | 035 | 2.97 |
| TCA-007 | 3/4 | 25 | 100 | 035 | 3.52 |

**Transition Union - Brass Compression**

**Brass Comp x CPVC Spigot**



NSF® Certified Lead Free

|         |     |     |   |     |       |
|---------|-----|-----|---|-----|-------|
| TUC-005 | 1/2 | 150 | 0 | 036 | 19.94 |
| TUC-007 | 3/4 | 75  | 0 | 036 | 33.33 |

**Transition Union - Brass Male Thread**

**Brass Mipt x CPVC Spigot**



NSF® Certified Lead Free

|         |     |     |   |     |       |
|---------|-----|-----|---|-----|-------|
| TUM-005 | 1/2 | 150 | 0 | 036 | 18.52 |
| TUM-007 | 3/4 | 75  | 0 | 036 | 33.75 |

**Transition Union - Brass Female Thread**

**Brass Fipt x CPVC Spigot**



NSF® Certified Lead Free

|         |     |     |   |     |       |
|---------|-----|-----|---|-----|-------|
| TUF-005 | 1/2 | 150 | 0 | 036 | 16.66 |
| TUF-007 | 3/4 | 75  | 0 | 036 | 33.68 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**CPVC-PEX Transition Spigot Adapters**

**Spigot x PEX Barb-Crimp Style**



CPVC Spigot is also (Socket) NSF® Certified Lead Free

|         |           |    |     |     |       |
|---------|-----------|----|-----|-----|-------|
| TPC-005 | 1/2       | 25 | 150 | 036 | 24.74 |
| TPC-007 | 3/4 (1/2) | 25 | 100 | 036 | 27.89 |
| TPC-010 | 1 (3/4)   | 25 | 50  | 036 | 38.74 |

ASTM F1807 Standard PEX Connector, Stainless Steel

**CPVC-PEX Transition Socket Adapters**

**Socket x PEX Barb-Crimp Style**



CPVC Socket is also (Spigot) NSF® Certified Lead Free

|           |           |    |     |     |       |
|-----------|-----------|----|-----|-----|-------|
| TPC-005-S | 1/2 (3/4) | 25 | 150 | 036 | 24.74 |
| TPC-007-S | 3/4 (1)   | 25 | 100 | 036 | 27.89 |
| TPC-010-S | 1 (1-1/4) | 50 | 300 | 036 | 38.74 |

ASTM F1807 Standard PEX Connector, Stainless Steel

**Water Hammer Arrester**

**Spigot**



NSF® Certified Lead Free

|         |     |    |     |     |       |
|---------|-----|----|-----|-----|-------|
| WHA-005 | 1/2 | 25 | 100 | 035 | 20.12 |
|---------|-----|----|-----|-----|-------|

| Part Number | Size | Travel - T | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|------------|--------|----------|-----------|------|
|-------------|------|------------|--------|----------|-----------|------|

**Expansion Joint/Repair Couplings - Socket x Spigot**

**CPVC With EPDM O-Rings**

NSF Certified Lead Free

|           |     |   |    |   |     |       |
|-----------|-----|---|----|---|-----|-------|
| CTS118-07 | 3/4 | 3 | 30 | 0 | 027 | 15.51 |
| CTS118-10 | 1   | 4 | 24 | 0 | 027 | 17.60 |

**Unit Must Be Thrust Blocked**  
**T = Repair Coupling Travel**



**Expansion Joint/Repair Couplings - Socket x Socket**

**CPVC With EPDM O-Rings**

NSF® Certified Lead Free

|           |     |   |    |   |     |       |
|-----------|-----|---|----|---|-----|-------|
| CTS119-07 | 3/4 | 3 | 30 | 0 | 027 | 15.51 |
| CTS119-10 | 1   | 4 | 24 | 0 | 027 | 17.60 |

**Unit Must Be Thrust Blocked**  
**T = Repair Coupling Travel**



**CTS CPVC Product**  
**EverTUFF® CPVC CTS Products**



| Part Number | Size | Std PK | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Quarter Turn Angle Supply Stop**

**Socket x NPT**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having 1/2"  
 Female NPT Thread Inlet - NSF® Certified Lead Free

|          |     |    |     |     |       |
|----------|-----|----|-----|-----|-------|
| 7722-005 | 1/2 | 50 | 400 | 217 | 11.27 |
|----------|-----|----|-----|-----|-------|



**Quarter Turn Angle Supply Stop**

**SR Fipt x NPT**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having 1/2"  
 Female NPT Thread Inlet - NSF® Certified Lead Free

|            |     |    |     |     |       |
|------------|-----|----|-----|-----|-------|
| 7721-005SR | 1/2 | 50 | 400 | 217 | 12.81 |
|------------|-----|----|-----|-----|-------|



**Quarter Turn Angle Supply Stop**

**SR Fipt x Comp Thread**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having  
 Female 3/8" Compression Thread Inlet - NSF® Certified Lead Free

|            |         |    |     |     |       |
|------------|---------|----|-----|-----|-------|
| 7721-073SR | 1/2X3/8 | 50 | 400 | 217 | 12.81 |
|------------|---------|----|-----|-----|-------|



**Quarter Turn Angle Supply Stop**

**Socket x Comp Thread**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having 1/4",  
 3/8" or 1/2" Female Compression Thread Inlet - NSF® Certified  
 Lead Free

|            |         |    |   |     |       |
|------------|---------|----|---|-----|-------|
| 7722CM-072 | 1/2X1/4 | 72 | 0 | 217 | 11.27 |
| 7722CM-073 | 1/2X3/8 | 72 | 0 | 217 | 11.27 |
| 7722CM-005 | 1/2     | 72 | 0 | 217 | 11.27 |



**Quarter Turn Straight Supply Stop**

**Socket x Comp Thread**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having  
 Female 3/8" or 1/2" Compression Thread Inlet - NSF® Certified  
 Lead Free

|            |         |    |   |     |       |
|------------|---------|----|---|-----|-------|
| 7422CM-073 | 1/2X3/8 | 72 | 0 | 217 | 11.27 |
| 7422CM-005 | 1/2     | 72 | 0 | 217 | 11.27 |



| Part Number | Size | Std PK | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Quarter Turn Straight Supply Stop**

**Socket x NPT**

100 psi @ 180°F (82°C)  
 Male Thread for Connection to Flexible Supply Line having  
 Female 1/2" NPT Thread Inlet - NSF® Certified Lead Free

|          |     |    |   |     |       |
|----------|-----|----|---|-----|-------|
| 7422-005 | 1/2 | 72 | 0 | 217 | 11.27 |
|----------|-----|----|---|-----|-------|



**Ball Valve - Commercial CTS**

**Socket with EPDM O-ring Seal**

100 psi Maximum Internal Pressure @ 180°F (82°C)  
 NSF® Certified Lead Free

|          |       |    |     |     |        |
|----------|-------|----|-----|-----|--------|
| 1922-005 | 1/2   | 25 | 200 | 217 | 19.11  |
| 1922-007 | 3/4   | 24 | 0   | 217 | 27.71  |
| 1922-010 | 1     | 25 | 0   | 217 | 35.52  |
| 1922-012 | 1-1/4 | 8  | 0   | 217 | 60.49  |
| 1922-015 | 1-1/2 | 6  | 0   | 217 | 84.35  |
| 1922-020 | 2     | 4  | 0   | 217 | 107.44 |



**Ball Valve - Residential CTS**

**Socket x Socket**

100 psi Maximum Internal Pressure @ 180°F (82°C)  
 NSF® Certified Lead Free

|           |       |    |    |     |       |
|-----------|-------|----|----|-----|-------|
| 1922R-005 | 1/2   | 72 | 0  | 217 | 11.07 |
| 1922R-007 | 3/4   | 36 | 0  | 217 | 15.76 |
| 1922R-010 | 1     | 24 | 0  | 217 | 27.42 |
| 1922R-012 | 1-1/4 | 8  | 32 | 217 | 55.65 |
| 1922R-015 | 1-1/2 | 6  | 0  | 217 | 65.46 |
| 1922R-020 | 2     | 4  | 16 | 217 | 85.53 |



**Stop Valve - Red Handle**

**Socket x Socket**

NSF® Certified Lead Free

|          |     |    |   |     |       |
|----------|-----|----|---|-----|-------|
| 8422-005 | 1/2 | 36 | 0 | 217 | 13.45 |
| 8422-007 | 3/4 | 36 | 0 | 217 | 13.45 |



**Stop Valve - Clear Handle**

**Socket x Socket**

NSF® Certified Lead Free

|            |     |    |   |     |       |
|------------|-----|----|---|-----|-------|
| 8422CH-005 | 1/2 | 36 | 0 | 217 | 13.45 |
| 8422CH-007 | 3/4 | 36 | 0 | 217 | 13.45 |





**CTS CPVC Product**  
**EverTUFF® CPVC CTS Products**

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Stop & Waste Valve**

**Socket x Socket**



NSF® Certified Lead Free

|           |     |    |   |     |       |
|-----------|-----|----|---|-----|-------|
| 8422W-005 | 1/2 | 36 | 0 | 217 | 14.11 |
| 8422W-007 | 3/4 | 36 | 0 | 217 | 14.11 |

**Boiler Drain Valve**

**Socket x MHT**



NSF® Certified Lead Free

|          |     |    |   |     |       |
|----------|-----|----|---|-----|-------|
| 82MH-005 | 1/2 | 36 | 0 | 217 | 14.11 |
| 82MH-007 | 3/4 | 36 | 0 | 217 | 14.11 |

**Pipe - CPVC CTS SDR 11**

**10' Lengths, Priced Per Foot**



NSF® Certified Lead Free

|         |       |     |   |     |       |
|---------|-------|-----|---|-----|-------|
| CTS-005 | 1/2   | 500 | 0 | 034 | 1.03  |
| CTS-007 | 3/4   | 250 | 0 | 034 | 1.85  |
| CTS-010 | 1     | 150 | 0 | 034 | 3.80  |
| CTS-012 | 1-1/4 | 100 | 0 | 034 | 5.63  |
| CTS-015 | 1-1/2 | 100 | 0 | 034 | 7.47  |
| CTS-020 | 2     | 50  | 0 | 034 | 12.64 |

• Pipe sold in bag quantities only - no broken bags • No return on Pipe • Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges. • See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

**Pipe - CPVC CTS SDR 11**

**20' Lengths, Priced Per Foot**



NSF® Certified Lead Free

|            |       |      |   |     |       |
|------------|-------|------|---|-----|-------|
| CTS-005-20 | 1/2   | 1000 | 0 | 034 | 1.03  |
| CTS-007-20 | 3/4   | 500  | 0 | 034 | 1.85  |
| CTS-010-20 | 1     | 300  | 0 | 034 | 3.80  |
| CTS-012-20 | 1-1/4 | 200  | 0 | 034 | 5.63  |
| CTS-015-20 | 1-1/2 | 200  | 0 | 034 | 7.47  |
| CTS-020-20 | 2     | 100  | 0 | 034 | 12.64 |

**Pipe - CPVC CTS Coiled SDR 11**

**100 ft. Coil, Priced Per Foot**



NSF® Certified Lead Free

|             |     |     |   |     |      |
|-------------|-----|-----|---|-----|------|
| CTS-005-100 | 1/2 | 100 | 0 | 034 | 1.21 |
|-------------|-----|-----|---|-----|------|

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Pipe - CPVC CTS Coiled SDR 11 (continued)**

**100 ft. Coil, Priced Per Foot**

|             |     |     |   |     |      |
|-------------|-----|-----|---|-----|------|
| CTS-007-100 | 3/4 | 100 | 0 | 034 | 2.20 |
| CTS-010-100 | 1   | 100 | 0 | 034 | 4.33 |

**CPVC CTS COILED PIPE WEIGHTS:**

CTS-005-100 Weight per Foot .090 lbs; per Coil Weight 9 lbs.  
CTS-007-100 Weight per Foot .149 lbs; per Coil Weight 14.9 lbs.  
CTS-010-100 Weight per Foot .239 lbs; per Coil Weight 23.9 lbs.

**WARNING: Banded coils will expand when opened. Exercise caution to avoid injury during banding removal.**

**CTS Tubing Straps**

**Std Pk Bag of 25 For Anchoring CTS Pipe**



Priced Each - Sold in Full Bag Quantity Only

|      |     |    |     |     |     |
|------|-----|----|-----|-----|-----|
| 556A | 1/2 | 25 | 500 | 299 | .40 |
| 556B | 3/4 | 25 | 500 | 299 | .41 |

**CTS Tube Talon with Nail**

**Std Pk Bag Quantities as Specified. For Anchoring CTS Pipe**



Priced Each - Sold in Full Bag Quantity Only

|      |     |     |      |     |      |
|------|-----|-----|------|-----|------|
| 555A | 1/2 | 100 | 1000 | 299 | 1.15 |
| 555B | 3/4 | 100 | 1000 | 299 | 1.75 |
| 555C | 1   | 50  | 500  | 299 | 4.92 |

**Solvent Cement -EverTUFF® CTS One Step**

NSF® Certified Lead Free



|          |          |    |   |     |        |
|----------|----------|----|---|-----|--------|
| CTS5-005 | 1/4 Pint | 24 | 0 | 701 | 9.48   |
| CTS5-010 | 1/2 Pint | 24 | 0 | 701 | 15.09  |
| CTS5-020 | Pint     | 12 | 0 | 701 | 24.45  |
| CTS5-030 | Quart    | 12 | 0 | 701 | 42.55  |
| CTS5-040 | Gallon   | 6  | 0 | 701 | 145.57 |

**Cap Daubers**



|        |                   |    |     |     |      |
|--------|-------------------|----|-----|-----|------|
| DHP-38 | 3/8" for 1/2 Pint | 50 | 400 | 710 | 1.29 |
| DHP-50 | 1/2" for 1/2 Pint | 50 | 400 | 710 | 1.29 |
| DHP-75 | 3/4" for 1/2 Pint | 50 | 0   | 710 | 1.38 |
| DP-50  | 1/2" for Pint     | 50 | 0   | 710 | 1.29 |
| DP-75  | 3/4" for Pint     | 50 | 0   | 710 | 1.38 |
| DP-125 | 1-1/4" for Pint   | 50 | 0   | 710 | 1.66 |
| DQ-50  | 1/2" for Quart    | 50 | 0   | 710 | 1.29 |
| DQ-75  | 3/4" for Quart    | 50 | 0   | 710 | 1.29 |
| DQ-125 | 1-1/4" for Quart  | 50 | 0   | 710 | 1.66 |

3/8" for pipe to 3/4" • 1/2" for pipe to 1" • 3/4" for pipe to 1-1/2" • 1-1/4" for pipe 1-1/2" to 3"



CTS CPVC Product  
**EverTUFF® CPVC CTS Products**



| Part Number | Size | Std<br>Pk | Mstr<br>Ctn | Prod<br>Code | MSRP |
|-------------|------|-----------|-------------|--------------|------|
|-------------|------|-----------|-------------|--------------|------|

**Can-Mate Daubers**

**Adjustable Plastic Applicator with Telescoping Stem for use with Standard 1/2 Pint, Pint and Quart Cans**



|  |        |    |   |     |      |
|--|--------|----|---|-----|------|
| CM-50  | 1/2"   | 50 | 0 | 710 | 5.54 |
| CM-75  | 3/4"   | 50 | 0 | 710 | 5.54 |
| CM-150   | 1-1/4" | 50 | 0 | 710 | 5.54 |
| 1/2" for pipe to 1" • 3/4" for pipe to 1-1/2" • 1-1/4" for pipe 1-1/2" to 3" |        |    |   |     |      |

**Deburring Tool**

**Cone Type for pipe from 1/2" through 2"**



|       |                 |   |   |     |        |
|-------|-----------------|---|---|-----|--------|
| DEB-2 | 1/2" to 2" Pipe | 1 | 6 | 710 | 102.85 |
|-------|-----------------|---|---|-----|--------|