



Double Containment Product Access Tees & Closure Fittings

Access Tees


DC Access Tee CPVC Sch 80 x CPVC Sch 80 (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCAT-C030-C060	3X6	1	4	470	1784.69
DCAT-C040-C080	4X8	1	2	470	4532.61
DCAT-C060-C100	6X10	1	0	470	4847.29
DCAT-C080-C120	8X12	1	0	470	7386.62

DC Access Tee CPVC Sch 80 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCAT-C005-G020	1/2X2	1	10	470	325.32
DCAT-C007-G030	3/4X3	1	5	470	684.76
DCAT-C010-G030	1X3	1	5	470	692.02
DCAT-C015-G040	1-1/2X4	1	3	470	1144.64
DCAT-C020-G040	2X4	1	6	470	1153.22
DCAT-C030-G060	3X6	1	4	470	1649.07
DCAT-C040-G080	4X8	1	2	470	2946.18

Closure Fittings



A Closure Fitting is a special coupling configuration for joining both Carrier and Containment piping in situations where opposing runs of Carrier and Containment system must meet. Closure Fittings are frequently used at the end of a system where the final Termination Fitting must connect to a fixed point in the system. Spears® offers a complete range of Solvent Cement Closure Fittings that form a permanent solvent cement joint, plus special Union Closure Fittings in limited sizes that provide an easily-installed union to join these opposing Containment piping runs. See Double Containment Design & Installation Guide for proper installation.

Solvent Cement Closure Fittings consist of a male component and a female component. An internal O-ring on each component serves as a "cement-wiper" during installation to assure a proper joint. A "One-step" type cement, such as Spears® CPVC 24 for both PVC & CPVC, should be used to facilitate rapid assembly. See Double Containment Design & Installation Guide for proper installation.

Union Closure Fittings consist of a male component and female component with Union Nut and O-ring seal. Each component is installed on the carrier pipe incorporating a double O-ring seal on the carrier pipe with cemented retainers. Union Closure Fitting allows for easy access to carrier pipe after installation and also provides a small amount of expansion and contraction. See Double Containment Design & Installation Guide and product-enclosed instructions for proper installation.

Closure Fittings

Centralizers are used inside the Containment piping system, but not inside fittings installed on Carrier pipe and must be ordered separately according to same Carrier x Containment size and pipe schedule selected.

DC Solvent Cement Closure Fitting PVC Sch 40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-A030	3	1	10	470	548.00
DCCF-A040	4	1	5	470	561.47
DCCF-A060	6	1	2	470	584.33
DCCF-A080	8	1	0	470	806.02
DCCF-A100	10	1	2	470	889.14
DCCF-A120	12	1	2	470	1404.54

DC Solvent Cement Closure Fitting PVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-B020	2	1	10	470	547.52
DCCF-B030	3	1	10	470	556.89
DCCF-B040	4	1	5	470	573.82
DCCF-B060	6	1	2	470	607.78
DCCF-B080	8	1	3	470	805.77
DCCF-B100	10	1	2	470	1069.33
DCCF-B120	12	1	0	470	1714.17

DC Solvent Cement Closure Fitting CPVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-C020	2	1	10	470	555.83
DCCF-C030	3	1	10	470	579.01
DCCF-C040	4	1	5	470	604.33
DCCF-C060	6	1	2	470	736.61
DCCF-C080	8	1	3	470	990.93
DCCF-C100	10	1	2	470	1844.71
DCCF-C120	12	1	0	470	2926.78

DC Solvent Cement Closure Fitting PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-G030	3	1	10	470	611.48
DCCF-G040	4	1	5	470	635.29
DCCF-G060	6	1	2	470	753.53
DCCF-G080	8	1	6	470	1119.74

DC Union Closure Fittings PVC Clear - EPDM Seals

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCUC-030	3	1	0	471	166.20
DCUC-040	4	1	0	471	213.85
DCUC-060	6	1	0	471	267.51

Maximum 100 psi Short Term Hydrostatic Test Only.
50 psi Working Pressure @ 73° F (23° C)

DC Union Closure Fittings PVC Clear - FKM Seals

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCUC2-040	4	1	0	471	274.44
DCUC2-060	6	1	0	471	376.89