



Double Containment Product
Isolation Couplers & Termination Fittings

Isolation Couplers

DC Isolation Coupler CPVC Sch 80 x CPVC Sch 80 (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCDB-C015-C040	1-1/2X4	1	4	470	279.83
DCDB-C020-C040	2X4	1	4	470	313.31
DCDB-C030-C060	3X6	1	4	470	406.29
DCDB-C040-C080	4X8	1	4	470	414.37
DCDB-C060-C100	6X10	1	0	470	692.71

DC Isolation Coupler CPVC Sch 80 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCDB-C005-G020	1/2X2	1	5	470	117.26
DCDB-C007-G030	3/4X3	1	5	470	129.05
DCDB-C010-G030	1X3	1	5	470	268.12
DCDB-C015-G040	1-1/2X4	1	4	470	366.66
DCDB-C020-G040	2X4	1	4	470	400.94
DCDB-C030-G060	3X6	1	5	470	426.08

Termination Fittings



DC Termination Fittings are a special configuration for starting or stopping the containment portion of a system. Termination Fittings consist of a reducer coupling to accept the Containment pipe that is pre-fabricated to an internal extender coupling for connection to existing Carrier system. See *Double Containment Design & Installation Guide* for proper installation.

Centralizers are used inside the Containment piping system, but not inside fittings, installed on Carrier pipe and must be ordered separately according to same Carrier x Containment size and pipe schedule selected.

DC Termination Fitting PVC Sch 40 x PVC Sch 40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-A005-A020	1/2X2	8	0	470	120.85
DCTM-A007-A030	3/4X3	7	0	470	127.16
DCTM-A010-A030	1X3	9	0	470	133.18
DCTM-A015-A040	1-1/2X4	4	0	470	143.76
DCTM-A020-A040	2X4	5	0	470	150.93
DCTM-A030-A060	3X6	1	2	470	205.91
DCTM-A040-A080	4X8	1	3	470	268.58
DCTM-A060-A100	6X10	1	2	470	508.51
DCTM-A080-A120	8X12	1	2	470	822.57

DC Termination Fitting PVC Sch 40 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-A005-G020	1/2X2	8	0	470	157.28

DC Termination Fitting PVC Sch 40 x PVC Sch 40 Clear (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-A007-G030	3/4X3	7	0	470	257.38
DCTM-A010-G030	1X3	1	9	470	258.31
DCTM-A015-G040	1-1/2X4	1	4	470	324.40
DCTM-A020-G040	2X4	1	4	470	331.66
DCTM-A030-G060	3X6	1	2	470	514.58
DCTM-A040-G080	4X8	1	3	470	821.57

DC Termination Fitting PVC Sch 80 x PVC Sch 40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-B005-A020	1/2X2	8	0	470	132.57
DCTM-B007-A030	3/4X3	9	0	470	148.08
DCTM-B010-A030	1X3	8	0	470	148.52
DCTM-B015-A040	1-1/2X4	4	0	470	169.38
DCTM-B020-A040	2X4	5	0	470	177.06
DCTM-B030-A060	3X6	1	4	470	276.46
DCTM-B040-A080	4X8	1	3	470	353.67
DCTM-B060-A100	6X10	1	0	470	673.38
DCTM-B080-A120	8X12	1	3	470	999.63

DC Termination Fitting PVC Sch 80 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-B005-G020	1/2X2	9	0	470	173.81
DCTM-B007-G030	3/4X3	10	0	470	277.19
DCTM-B010-G030	1X3	8	0	470	277.63
DCTM-B015-G040	1-1/2X4	4	0	470	353.59
DCTM-B020-G040	2X4	5	0	470	360.69
DCTM-B030-G060	3X6	1	2	470	590.94
DCTM-B040-G080	4X8	1	3	470	1037.35

DC Termination Fitting PVC Sch 80 x PVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-B005-B020	1/2X2	10	0	470	150.39
DCTM-B007-B030	3/4X3	8	0	470	187.36
DCTM-B010-B030	1X3	8	0	470	187.80
DCTM-B015-B040	1-1/2X4	4	0	470	214.94
DCTM-B020-B040	2X4	4	0	470	222.61
DCTM-B030-B060	3X6	1	2	470	361.61
DCTM-B040-B080	4X8	1	2	470	449.88
DCTM-B060-B100	6X10	1	2	470	1028.05
DCTM-B080-B120	8X12	1	3	470	1239.29

DC Termination Fitting CPVC Sch 80 x PVC Sch 40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-C005-A020	1/2X2	8	0	470	133.40
DCTM-C007-A030	3/4X3	1	8	470	149.77
DCTM-C010-A030	1X3	8	0	470	156.35
DCTM-C015-A040	1-1/2X4	4	0	470	188.29
DCTM-C020-A040	2X4	3	0	470	201.60
DCTM-C030-A060	3X6	1	2	470	323.15
DCTM-C040-A080	4X8	1	3	470	419.96
DCTM-C060-A100	6X10	1	0	470	850.62
DCTM-C080-A120	8X12	1	3	470	1797.08

Double Containment Product
Termination Fittings & Centralizers



Termination Fittings

DC Termination Fitting CPVC Sch 80 x Sch 80 Gray

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-C005-B020	1/2X2	8	0	470	151.23
DCTM-C007-B030	3/4X3	8	0	470	189.05
DCTM-C010-B030	1X3	8	0	470	195.60
DCTM-C015-B040	1-1/2X4	4	0	470	233.83
DCTM-C020-B040	2X4	1	4	470	247.15
DCTM-C030-B060	3X6	1	2	470	408.19
DCTM-C040-B080	4X8	1	3	470	516.15
DCTM-C060-B100	6X10	1	2	470	1206.40
DCTM-C080-B120	8X12	1	3	470	2036.58


DC Termination Fitting CPVC Sch 80 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-C005-G020	1/2X2	8	0	470	180.48
DCTM-C007-G030	3/4X3	10	0	470	298.04
DCTM-C010-G030	1X3	9	0	470	309.60
DCTM-C015-G040	1-1/2X4	10	0	470	406.25
DCTM-C020-G040	2X4	3	0	470	419.57
DCTM-C030-G060	3X6	1	15	470	710.09
DCTM-C040-G080	4X8	1	3	470	1075.16

DC Termination Fitting CPVC Sch 80 x CPVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCTM-C005-C020	1/2X2	9	0	470	226.56
DCTM-C007-C030	3/4X3	8	0	470	231.52
DCTM-C010-C030	1X3	4	0	470	238.06
DCTM-C015-C040	1-1/2X4	4	0	470	301.33
DCTM-C020-C040	2X4	4	0	470	314.61
DCTM-C030-C060	3X6	1	3	470	569.87
DCTM-C040-C080	4X8	1	2	470	1018.76
DCTM-C060-C100	6X10	1	2	470	1550.53
DCTM-C080-C120	8X12	1	3	470	2492.92

Centralizers



Centralizers are a simple slip-on design that are positioned and held in place by a few wraps of clean-room adhesive on each side. Centralizers hold the Carrier piping centrally located within the Containment piping and are designed with an annular space for routing of leak detection cable, if used. See *Double Containment Design & Installation Guide* for proper installation. The following Spacing Chart can be used as a guide for determining the quantity of Centralizers needed, based on temperature and Carrier pipe size and schedule selected.

Centralizers

RECOMMENDED MINIMUM CENTRALIZER SUPPORT SPACING (ft.) *

Carrier Size (in.)	PVC SCHEDULE 40 CARRIER Temperature °F				
	60°	80°	100°	120°	140°
1/2	4-1/2	4-1/2	4	2-1/2	2-1/2
3/4	5	4-1/2	4	2-1/2	2-1/2
1	5-1/2	5	4-1/2	3	2-1/2
1-1/2	6	5-1/2	5	3-1/2	3
2	6	5-1/2	5	3-1/2	3
3	7	7	6	4	3-1/2
4	7-1/2	7	6-1/2	4-1/2	4
6	8-1/2	8	7-1/2	5	4-1/2
8	9	8-1/2	8	5	4-1/2
10	10	9	8-1/2	5-1/2	5
12	11-1/2	10-1/2	9-1/2	6-1/2	5-1/2

Carrier Size (in.)	PVC SCHEDULE 80 CARRIER Temperature °F				
	60°	80°	100°	120°	140°
1/2	5	4-1/2	4-1/2	3	2-1/2
3/4	5-1/2	5	4-1/2	3	2-1/2
1	6	5-1/2	5	3-1/2	3
1-1/2	6-1/2	6	5-1/2	3-1/2	3-1/2
2	7	6-1/2	6	4	3-1/2
3	8	7-1/2	7	4-1/2	4
4	9	8-1/2	7-1/2	5	4-1/2
6	10	9-1/2	9	6	5
8	11	10-1/2	9-1/2	6-1/2	5-1/2
10	12	11	10	7	6
12	5-1/2	13	12	10-1/2	7-1/2

Carrier Size (in.)	CPVC SCHEDULE 80 CARRIER Temperature °F					
	73°	100°	120°	140°	160°	180°
1/2	5-1/2	5	4-1/2	4-1/2	3	2-1/2
3/4	5-1/2	5-1/2	5	4-1/2	3	2-1/2
1	6	6	5-1/2	5	3-1/2	2
1-1/2	7	6-1/2	6	5-1/2	3-1/2	3-1/2
2	7	7	6-1/2	6	4	3-1/2
3	8	8	7-1/2	7	4-1/2	4
4	9	8-1/2	8	7-1/2	5	4-1/2
6	10	9-1/2	9	8	5-1/2	5
8	11	10-1/2	10	9	6	5-1/2
10	11-1/2	11	10-1/2	9-1/2	6-1/2	6
12	12-1/2	12	11-1/2	10-1/2	7-1/2	6-1/2

Note: Specified minimum spacing can also be used for system support according to the secondary Containment pipe size and schedule used. Where practical, system support should correspond to internal carrier support (centralizers) to minimize concentrated point loads.

Note: Data furnished is based on raw material manufacturer's information. This information can be considered a reliable recommendation, but not a guarantee. Actual service conditions and system parameters should be evaluated by qualified personnel.

DC Centralizer IPS O.D. x Sch 40 White I.D.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Carrier x Containment					
DCCT-H005-A020	1/2X2	55	330	470	13.93