



FlameGuard® CPVC Fire Sprinkler Piping Products

FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Pipe - FlameGuard® CPVC Fire Sprinkler Plain End

SDR 13.5 10' Lengths



Price Per Foot

CP-007-10	3/4	260	0	071	2.04
CP-010-10	1	170	0	071	3.15
CP-012-10	1-1/4	90	0	071	4.93
CP-015-10	1-1/2	70	0	071	6.81
CP-020-10	2	50	0	071	10.18
CP-025-10	2-1/2	40	0	071	15.54
CP-030-10	3	30	0	071	23.61

Pipe - FlameGuard® CPVC Fire Sprinkler Plain End

SDR 13.5, 15' Lengths



Price Per Foot

CP-007	3/4	390	0	071	2.04
CP-010	1	255	0	071	3.15
CP-012	1-1/4	135	0	071	4.93
CP-015	1-1/2	105	0	071	6.81
CP-020	2	75	0	071	10.18
CP-025	2-1/2	60	0	071	15.54
CP-030	3	45	0	071	23.61

Tee



Socket x Socket x Socket

4201-007	3/4	20	220	070	4.18
4201-010	1	15	120	070	8.46
4201-012	1-1/4	10	0	070	12.64
4201-015	1-1/2	10	0	070	18.60
4201-020	2	10	0	070	27.46
4201-025	2-1/2	10	0	070	44.74
4201-030	3	5	0	070	70.11

GripLoc™ Tee



**WARNING: DO NOT INSERT FINGERS
EPDM Gasket**

Uses No Solvent Cement - NSF® Certified Lead Free
175 psi (1.21 Mpa) @ 150° F (66°C)

GL4201-007	3/4	15	0	134	39.60
GL4201-010	1	1	15	134	44.95

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Reducing Tee



Socket x Socket x Socket

4201-102	3/4X1	20	0	070	7.15
4201-125	1X3/4X3/4	15	150	070	7.15
4201-126	1X3/4X1	15	0	070	7.15
4201-131	1X3/4	20	0	070	7.15
4201-157	1-1/4X1X3/4	15	0	070	13.19
4201-158	1-1/4X1X1	15	0	070	13.19
4201-159	1-1/4X1X1-1/4	15	0	070	13.19
4201-167	1-1/4X3/4	15	0	070	13.19
4201-168	1-1/4X1	15	0	070	13.19
4201-169	1-1/4X1-1/2	10	0	070	15.93
4201-201	1-1/2X1-1/4X3/4	10	0	070	15.93
4201-202	1-1/2X1-1/4X1	10	0	070	15.93
4201-210	1-1/2X3/4	15	0	070	15.93
4201-211	1-1/2X1	10	0	070	15.93
4201-212	1-1/2X1-1/4	10	0	070	15.93
4201-213	1-1/2X2	10	0	070	25.27
4201-248	2X3/4	10	0	070	25.27
4201-249	2X1	10	0	070	25.27
4201-250	2X1-1/4	10	0	070	25.27
4201-251	2X1-1/2	10	0	070	25.27
4201-289	2-1/2X1	10	0	070	34.75
4201-290	2-1/2X1-1/4	10	0	070	34.75
4201-291	2-1/2X1-1/2	10	0	070	34.75
4201-292	2-1/2X2	10	0	070	34.75
4201-335	3X1	5	0	070	40.11
4201-336 ¹	3X1-1/4	5	0	070	40.11
4201-337	3X1-1/2	5	0	070	40.11
4201-338	3X2	5	0	070	40.11
4201-339	3X2-1/2	6	0	070	40.11

¹ Outlet sized with Bushing

GripLoc™ Extension Tee

**Socket x Socket x GripLoc™
WARNING: DO NOT INSERT FINGERS
EPDM Gasket**



Uses No Solvent Cement - NSF® Certified Lead Free
175 psi (1.21 Mpa) @ 150° F (66°C)

GLS4201-010	1	1	15	134	23.68
-------------	---	---	----	-----	-------

**SofTorque™ SR Sprinkler Head Tee - Gasket
Sealed Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar With
Elastomer Seal - Use NO Thread Sealant**



NSF® Certified Lead Free

4202-101GSR	3/4X1/2	50	0	076	15.48
4202-124GSR	1X3/4X1/2	50	0	076	16.72
4202-130GSR	1X1/2	20	0	076	16.72

FlameGuard® CPVC Fire Sprinkler Piping Products



FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

TorqueSafe™ Sprinkler Head Tee - Gasket Sealed Brass Thread Insert Style

Socket x Socket x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant



4202-101 G	3/4X1/2	50	0	076	15.48
4202-124 G	1X3/4X1/2	50	0	076	16.72
4202-130 G	1X1/2	50	0	076	16.72
4202-131 G	1X3/4	50	0	076	18.11
4202-166 G	1-1/4X1/2	15	0	076	27.87
4202-209 G	1-1/2X1/2	10	0	076	36.72
4202-247 G	2X1/2	10	0	076	51.78

FIPT With Elastomer Seal - Use NO Thread Sealant.
Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head Tee - Brass Thread Insert Style

Socket x Socket x Fipt



4202-101	3/4X1/2	50	0	076	15.48
4202-124	1X3/4X1/2	50	0	076	16.72
4202-130	1X1/2	50	0	076	16.72
4202-010	1	10	40	076	42.99
4202-156	1-1/4X1X1/2	15	0	076	27.87
4202-166	1-1/4X1/2	15	0	076	27.87
4202-199	1-1/2X1-1/4X1/2	10	0	076	36.72
4202-209	1-1/2X1/2	10	0	076	36.72
4202-237	2X1-1/2X1/2	10	0	076	51.78
4202-247	2X1/2	10	0	076	51.78

Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head Tee - Special Reinforced Plastic Thread Style

Socket x Socket x SR Fipt - Stainless Steel Collar




NSF® Certified Lead-Free

4202-010SR	1	15	0	076	22.84
4202-101SR	3/4X1/2	50	0	076	8.24
4202-124SR	1X3/4X1/2	50	0	076	8.91
4202-130SR	1X1/2	50	0	076	8.91
4202-131SR	1X3/4	15	0	076	18.11
4202-156SR	1-1/4X1X1/2	15	0	076	14.84
4202-166SR	1-1/4X1/2	15	0	076	14.84
4202-168SR	1-1/4X1	15	0	076	31.89
4202-199SR	1-1/2X1-1/4X1/2	10	0	076	19.53
4202-209SR	1-1/2X1/2	25	0	076	19.53
4202-211SR	1-1/2X1-1/2X1	10	0	076	19.53
4202-237SR	2X1-1/2X1/2	10	0	076	27.56
4202-247SR	2X1/2	10	0	076	27.56
4202-287SR	2-1/2X1/2	10	0	076	37.77

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

SofTorque™ SR Sprinkler Head Tee - Gasket Sealed Special Reinforced Plastic Thread Style
Socket x SR Fipt x Socket - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant



NSF® Certified Lead Free

4203-122GSR	1X1/2X1	50	0	076	16.72
-------------	---------	----	---	-----	-------

TorqueSafe™ Sprinkler Head Tee - Gasket Sealed Brass Thread Insert Style

Socket x Gasket Fipt x Socket With Elastomer Seal - Use NO Thread Sealant



4203-122 G	1X1/2X1	50	0	076	27.46
------------	---------	----	---	-----	-------

FIPT With Elastomer Seal - Use NO Thread Sealant
Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head Tee - Brass Thread Insert Style

Socket x Fipt x Socket



4203-122	1X1/2X1	50	0	076	27.46
----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head Tee - Special Reinforced Plastic Thread Style

Socket x SR Fipt x Socket - Stainless Steel Collar



NSF® Certified Lead-Free

4203-122SR	1X1/2X1	50	0	076	9.57
------------	---------	----	---	-----	------

Street Tee

Spigot x Socket x Socket



4244-007	3/4	15	105	070	7.44
4244-010	1	15	0	070	9.94
4244-012	1-1/4	10	0	070	18.05
4244-015	1-1/2	10	0	070	21.85
4244-020	2	10	0	070	32.29

90° El

Socket x Socket



4206-007	3/4	30	300	070	3.08
4206-010	1	20	200	070	6.84
4206-012	1-1/4	10	100	070	8.74
4206-015	1-1/2	10	0	070	12.20
4206-020	2	25	0	070	15.08
4206-025	2-1/2	5	0	070	29.12
4206-030	3	5	0	070	39.71



FlameGuard® CPVC Fire Sprinkler Piping Products

FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

90° EII - Sweep

Socket x Socket



4206-010S	1	30	0	070	12.64
-----------	---	----	---	-----	-------

GripLoc™ 90° EII

WARNING: DO NOT INSERT FINGERS
EPDM Gasket



Uses No Solvent Cement - NSF® Certified Lead Free
175 psi (1.21 Mpa) @ 150° F (66°C)

GL4206-007	3/4	20	0	134	25.06
GL4206-010	1	1	20	134	28.63

90° Reducing EII

Socket x Socket



4206-131	1X3/4	20	240	070	6.06
4206-168	1-1/4X1	15	0	070	25.74

SofTorque™ SR 90° Sprinkler Head Elbow - Gasket Sealed Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant



NSF® Certified Lead-Free

4207-101GSR	3/4X1/2	20	140	076	5.43
4207-130GSR	1X1/2	20	80	076	7.66
4207-166GSR	1-1/4X1/2	15	60	076	9.73

TorqueSafe™ 90° Sprinkler Head Elbow - Gasket Sealed Brass Thread Insert Style

Socket x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant



4207-101 G	3/4X1/2	20	120	076	10.23
4207-130 G	1X1/2	15	90	076	14.38
4207-166 G	1-1/4X1/2	10	60	076	20.02

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head 90° EII - Brass Thread Insert Style

Socket x Fipt



4207-101	3/4X1/2	20	120	076	10.23
4207-130	1X1/2	15	90	076	14.38

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Sprinkler Head 90° EII - Brass Thread Insert Style (continued)

Socket x Fipt

4207-131	1X3/4	25	0	076	17.40
4207-166	1-1/4X1/2	10	60	076	20.02

Not intended to convey or dispense water for human consumption through drinking or cooking

Sprinkler Head 90° EII - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4207-101SR	3/4X1/2	20	180	076	5.43
4207-130SR	1X1/2	10	150	076	7.66
4207-131SR	1X3/4	50	0	076	9.26
4207-166SR	1-1/4X1/2	25	0	076	9.73

90° Street EII

Spigot x Socket



4209-007	3/4	50	0	070	6.68
4209-010	1	50	0	070	9.87
4209-012	1-1/4	25	0	070	16.25
4209-015	1-1/2	10	0	070	19.79
4209-020	2	25	0	070	29.14

Side Outlet EII

Socket x Socket x Socket



4213-007	3/4	50	0	070	10.02
4213-010	1	25	0	070	13.66

22-1/2° EII

Socket x Socket



4216-007	3/4	20	360	070	4.99
4216-010	1	20	240	070	6.45
4216-012	1-1/4	20	0	070	8.73
4216-015	1-1/2	20	0	070	11.99
4216-020	2	20	0	070	14.84
4216-025	2-1/2	5	0	070	30.48
4216-030	3	5	0	070	38.64

22-1/2° Street EII

Spigot x Socket



4242-007	3/4	50	0	070	5.24
4242-010	1	50	0	070	6.75
4242-012	1-1/4	20	0	070	9.18
4242-015	1-1/2	25	0	070	12.60

FlameGuard® Product
FlameGuard® CPVC Fire Sprinkler Piping Products



FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

22-1/2° Street Ell (continued)

Spigot x Socket

4242-020	2	20	0	070	15.60
4242-025	2-1/2	5	0	070	21.87
4242-030	3	5	0	070	31.33

45° Ell

Socket x Socket

4217-007	3/4	20	360	070	4.18
4217-010	1	15	240	070	4.96
4217-012	1-1/4	10	120	070	7.26
4217-015	1-1/2	10	0	070	10.00
4217-020	2	10	0	070	12.58
4217-025	2-1/2	5	0	070	22.41
4217-030	3	5	0	070	32.41

45° Street Ell

Spigot x Socket

4227-010	1	50	0	070	4.96
4227-012	1-1/4	25	0	070	7.26
4227-015	1-1/2	25	0	070	8.99
4227-020	2	20	0	070	12.58

Cross

Socket x Socket x Socket x Socket

4220-007	3/4	20	0	070	6.59
4220-010	1	15	0	070	8.23
4220-012	1-1/4	10	0	070	11.46
4220-015	1-1/2	10	0	070	15.65
4220-020	2	8	0	070	25.49
4220-025	2-1/2	5	0	070	56.03
4220-030	3	5	0	070	82.18

Reducing Cross

Socket x Socket x Socket x Socket

4220-131	1X3/4	20	0	070	8.89
4220-167	1-1/4X3/4	25	0	070	13.73
4220-210	1-1/2X3/4	15	0	070	19.16
4220-248	2X3/4	10	0	070	25.14
4220-289	2-1/2X1	15	0	070	35.44

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Coupling

Socket x Socket

4229-007	3/4	25	500	070	3.00
4229-010	1	25	250	070	3.84
4229-012	1-1/4	10	160	070	5.77
4229-015	1-1/2	10	100	070	8.23
4229-020	2	20	0	070	11.09
4229-025	2-1/2	10	0	070	16.89
4229-030	3	5	0	070	21.98

Reducer Coupling

Socket x Socket

4229-131	1X3/4	15	270	070	3.84
4229-167	1-1/4X3/4	25	0	070	5.97
4229-168	1-1/4X1	10	140	070	5.77
4229-210	1-1/2X3/4	25	0	070	8.89
4229-211	1-1/2X1	10	70	070	8.64
4229-212	1-1/2X1-1/4	10	120	070	8.23
4229-248	2X3/4	10	80	070	11.59
4229-249	2X1	25	0	070	11.59
4229-250	2X1-1/4	10	60	070	11.29
4229-251	2X1-1/2	10	100	070	11.09
4229-291	2-1/2X1-1/2	10	0	070	17.07
4229-292	2-1/2X2	10	0	070	17.51
4229-337	3X1-1/2	5	0	070	44.12
4229-339	3X2-1/2	10	0	070	51.98

GripLoc™ Coupling

**WARNING: DO NOT INSERT FINGERS
EPDM Gasket**

Uses No Solvent Cement - NSF® Certified Lead Free

175 psi (1.21 Mpa) @ 150° F (66°C)

GL4229-007	3/4	1	36	134	25.00
GL4229-010	1	1	20	134	26.84
GL4229-020	2	1	10	134	28.53

Grooved Coupling Adapter

Groove x Socket

4233-012	1-1/4	10	40	076	115.49
4233-015	1-1/2	10	40	076	122.41
4233-020	2	8	32	076	141.77
4233-025	2-1/2	5	0	076	181.85
4233-030	3	5	0	076	202.16

Not intended to convey or dispense water for human consumption through drinking or cooking



FlameGuard® CPVC Fire Sprinkler Piping Products

FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

QuickTorque™ SR Female Sprinkler Head Adapter - Gasket Sealed Special Reinforced Metal Thread Style

Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant

NSF® Certified Lead Free

4235-101GMR	3/4X1/2	50	0	076	10.89
4235-130GMR	1X1/2	50	0	076	12.11



SofTorque™ SR Female Sprinkler Head Adapter - Gasket Sealed Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant

NSF® Certified Lead-Free

4235-101GSR	3/4X1/2	50	0	076	10.89
4235-130GSR	1X1/2	50	0	076	11.60



TorqueSafe™ Female Sprinkler Head Adapter - Gasket Sealed Brass Thread Insert Style

Socket x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

4235-101 G	3/4X1/2	50	0	076	13.31
4235-130GS	1X1/2	50	0	076	14.12
4235-131 G	1X3/4	50	0	076	20.29



FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

GripLoc™ TorqueSafe™ Female Sprinkler Head Adapter - Gasket Sealed Brass Thread Insert Style

WARNING: DO NOT INSERT FINGERS EPDM Gasket

Uses No Solvent Cement or Thread Sealant

GL4235-101 G	3/4X1/2	25	0	134	22.40
GL4235-130 G	1X1/2	25	0	132	24.98

FIPT With Elastomer Seal - Use NO Thread Sealant

Not intended to convey or dispense water for human consumption through drinking or cooking Uses No Solvent Cement 175 psi (1.21 Mpa) @ 150° F (66°C)



Female Adapter - Brass Thread Insert Style

Socket x Fipt

4235-007	3/4	15	90	076	20.41
4235-010	1	15	90	076	35.82
4235-012	1-1/4	15	60	076	58.40



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Brass Thread Insert Style (continued)

Socket x Fipt

4235-015	1-1/2	10	40	076	77.91
4235-020	2	8	32	076	97.64

Not intended to convey or dispense water for human consumption through drinking or cooking

Female Sprinkler Head Adapter - Brass Thread Insert Style

Socket x Fipt

4235-101	3/4X1/2	50	0	076	12.35
4235-130	1X1/2	50	0	076	13.05
4235-131	1X3/4	50	0	076	18.81

Not intended to convey or dispense water for human consumption through drinking or cooking



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4235-101SR	3/4X1/2	50	200	076	5.92
4235-130SR	1X1/2	50	0	076	6.33
4235-131SR	1X3/4	50	0	076	10.02



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Socket Body Wrench Flats

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

W4235-101SR	3/4X1/2	50	0	076	6.75
W4235-130SR	1X1/2	50	0	076	7.22



Female Sprinkler Head Adapter - Brass Thread Insert Style with Long Body

Socket x Fipt

L4235-130	1X1/2	50	0	076	16.87
-----------	-------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking



Female Sprinkler Head Adapter - Brass Thread Insert Style with Positioning Ring

Socket x Fipt

R4235-101	3/4X1/2	50	0	076	11.16
-----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Positioning Ring

Socket x SR Fipt - Stainless Steel Collar

R4235-101SR	3/4X1/2	25	300	076	6.68
-------------	---------	----	-----	-----	------





FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4235-007SR	3/4	25	300	076	9.68
4235-010SR	1	25	200	076	17.03
4235-012SR	1-1/4	10	60	076	27.73



Transition Male Adapter with Brass Thread

Mipt x Socket

NSF® Certified Lead-Free

4236-007	3/4	40	160	076	45.94
4236-010	1	10	60	076	70.23
4236-012	1-1/4	10	40	076	83.99
4236-015	1-1/2	10	40	076	152.43
4236-020	2	8	32	076	202.84



TorqueSafe™ Female Spigot Sprinkler Head Adapters - Gasket Sealed Brass Thread Insert Style

Spigot x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

4238-101 G	3/4X1/2	50	200	076	11.16
4238-130 G	1X1/2	50	0	076	11.91

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking



SofTorque™ Reducer Bushing - Gasket Sealed Plastic Thread Style

Spigot x Fipt - With Elastomer Seal - Use NO Thread Sealant

4238-130GSR	1X1/2	50	300	076	13.45
-------------	-------	----	-----	-----	-------



TorqueSafe™ Bushing - Gasket Sealed Brass Thread Insert Style

Spigot x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

4238-130BR G	1X1/2	50	200	076	15.41
--------------	-------	----	-----	-----	-------

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking



Bushing - with Brass Thread Insert

Spigot x Fipt

4238-130BR	1X1/2	50	200	076	15.41
------------	-------	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Bushing - with Brass Thread Insert (continued)

Spigot x Fipt

Not intended to convey or dispense water for human consumption through drinking or cooking

Spigot Female Sprinkler Head Adapters - Brass Thread Insert Style

Spigot x Fipt

4238-101	3/4X1/2	50	200	076	11.16
4238-130	1X1/2	50	0	076	11.91

Not intended to convey or dispense water for human consumption through drinking or cooking

SofTorque™ Spigot Female Adapter - Gasket Sealed Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant

NSF® Certified Lead Free

4278-101GSR	3/4X1/2	50	0	076	10.17
4278-130GSR	1X1/2	50	0	076	18.11

Spigot Female Adapter - Brass Thread Insert Style

Spigot x Fipt

4278-007	3/4	25	150	076	19.09
4278-010	1	15	90	076	34.01

Not intended to convey or dispense water for human consumption through drinking or cooking

Spigot Female Adapter - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4278-007SR	3/4	25	300	076	10.17
4278-010SR	1	50	0	076	18.11

Replacement Gaskets for all TorqueSafe™ Gasket Sealed Head Adapters

Pack of 25 EPDM Gaskets

For Use in 1/2" or 3/4" Gasket Sealed Threads

RGSK-005	1/2	1	100	299	12.39
RGSK-007	3/4	1	100	299	17.31



Spigot Female Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4238-101SR	3/4X1/2	50	400	076	5.92
4238-130SR	1X1/2	50	0	076	6.41





FlameGuard® CPVC Fire Sprinkler Piping Products

FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	L - Max	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	---------	--------	----------	-----------	------

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar TRAVEL = 1-9/16"



NSF® Certified Lead-Free

42001SR	3/4X1/2	8-1/4	12	0	076	15.11
42011SR	1X1/2	8-3/8	12	0	076	15.11

L-Max = Maximum Adjustable Length

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar TRAVEL = 1-5/8"



NSF® Certified Lead-Free

42004SR	3/4X1/2	8-1/4	12	0	076	15.11
42014SR	1X1/2	8-1/4	12	0	076	15.11

L-Max = Maximum Adjustable Length

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Reducer Bushing - Flush Style

Spigot x Socket



4237-131	1X3/4	50	700	070	2.33
4237-167	1-1/4X3/4	25	200	070	3.66
4237-168	1-1/4X1	25	350	070	3.66
4237-210	1-1/2X3/4	25	125	070	4.12
4237-211	1-1/2X1	25	150	070	4.12
4237-212	1-1/2X1-1/4	25	300	070	4.12
4237-248	2X3/4	10	150	070	6.04
4237-249	2X1	10	160	070	6.04
4237-250	2X1-1/4	10	160	070	6.04
4237-251	2X1-1/2	10	160	070	6.04
4237-290	2-1/2X1-1/4	10	40	070	10.46
4237-291	2-1/2X1-1/2	10	40	070	10.46
4237-292	2-1/2X2	15	0	070	10.46
4237-338	3X2	10	0	070	15.65
4237-339	3X2-1/2	10	0	070	15.65

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Transition Bushing

IPS Spigot x CTS Socket



4240-101	3/4X1/2	50	300	070	10.54
4240-130	1X1/2	50	300	070	8.29

Cap

Socket



4247-007	3/4	25	400	070	1.81
4247-010	1	25	450	070	2.62
4247-012	1-1/4	10	60	070	4.12
4247-015	1-1/2	10	160	070	5.73
4247-020	2	10	60	070	8.72
4247-025	2-1/2	5	40	070	12.36
4247-030	3	5	0	070	20.22

GripLoc™ Cap

WARNING: DO NOT INSERT FINGERS EPDM Gasket



Uses No Solvent Cement - NSF® Certified Lead Free
175 psi (1.21 Mpa) @ 150° F (66°C)

GL4247-007	3/4	1	25	134	22.27
GL4247-010	1	1	50	134	23.91

Test Plug - O-ring Sealed

Mipt - For Pressure Testing Only. NOT for use with TorqueSafe™ or Z4235 Series Adapters



FTP-005	1/2	50	400	079	1.87
---------	-----	----	-----	-----	------

DO NOT use with Tape or Paste thread sealants

Test Plug Replacement O-ring

Buna-N, For O-ring Sealed Test Plug Only



Pack of 100

BPB-116	116	1	10	891	4.15
---------	-----	---	----	-----	------

For Use With FTP-005 Test Plug

Test Plug for TorqueSafe™ & SofTorque™ Gasket Sealed Head Adapters

Mipt - For Pressure Testing Only. Use ONLY with Gasket Sealed Adapters



FTP-005GS	1/2	50	400	079	1.87
-----------	-----	----	-----	-----	------

FlameGuard® Product
FlameGuard® CPVC Fire Sprinkler Piping Products



FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Test Plug - White PVC

Mipt - For Pressure Testing Only



4250-005	1/2	50	400	070	1.97
Requires use of a thread sealant					

Flange - One Piece

Socket - 4 Bolt Holes - 175 psi (1.21 Mpa) @ 150° F (66°C)



4251-007	3/4	25	0	070	6.48
4251-010	1	15	0	070	8.61
4251-012	1-1/4	15	0	070	11.09
4251-015	1-1/2	15	0	070	12.85
4251-020	2	10	0	070	19.65
4251-025	2-1/2	10	0	070	33.25

Blind Flange

4 Bolt Holes - 175 psi (1.21 Mpa) @ 150° F (66°C)



4253-007	3/4	25	0	070	6.48
4253-010	1	15	0	070	9.22
4253-012	1-1/4	15	0	070	11.78
4253-015	1-1/2	15	0	070	13.23
4253-020	2	10	0	070	21.67
4253-025	2-1/2	10	0	070	34.84
4253-030	3	10	0	070	38.26

Flange - Van Stone Style

Socket - 4 Bolt Holes - 175 psi (1.21 Mpa) @ 150° F (66°C)



4254-030	3	10	0	070	40.86
----------	---	----	---	-----	-------

Flange - Van Stone Style

Spigot - 4 Bolt Holes - 175 psi (1.21 Mpa) @ 150° F (66°C)



4256-007	3/4	25	0	070	6.68
4256-010	1	15	0	070	9.43
4256-012	1-1/4	15	0	070	12.06
4256-015	1-1/2	15	0	070	13.54
4256-020	2	10	0	070	22.08
4256-025	2-1/2	10	0	070	35.32
4256-030	3	10	0	070	41.21

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union

Socket x Socket



175 psi (1.21 Mpa) @ 150° F (66°C)

4257-007	3/4	10	80	070	8.36
4257-010	1	10	40	070	15.15
4257-012	1-1/4	5	20	070	19.83
4257-015	1-1/2	5	0	070	23.51
4257-020	2	5	0	070	38.62

Transition Union - Metal Thread Insert Style

Socket x Fipt



175 psi (1.21 Mpa) @ 150° F (66°C)

4259-010BR	1	10	0	076	52.64
4259-012BR	1-1/4	5	20	076	77.19
4259-015BR	1-1/2	5	0	076	109.68
4259-020BR	2	5	0	076	161.75

Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------

Short Repair Couplings

Spigot x Socket



175 psi (1.21 Mpa) @ 150° F (66°C)

SH118-07CO	3/4	2	30	0	025	15.81
SH118-10CO	1	2-1/8	35	0	025	25.64

**Unit Must Be Thrust Blocked
T = Repair Coupling Travel**

GripLoc™ Repair Coupling

**WARNING: DO NOT INSERT FINGERS
EPDM Gasket**



Uses No Solvent Cement - NSF® Certified Lead Free

175 psi (1.21 Mpa) @ 150° F (66°C)

SG118-07CO	3/4	2-15/16	1	25	134	41.84
SG118-10CO	1	2-15/16	1	25	134	47.37



FlameGuard® CPVC Fire Sprinkler Piping Products

FlameGuard® CPVC Fire Sprinkler Piping Products

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------

GripLoc™ Repair Coupling (continued)

WARNING: DO NOT INSERT FINGERS

EPDM Gasket

Unit Must Be Thrust Blocked
T = Repair Coupling Travel

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------



Blue 75™ Thread Sealant

SB75-005	1/4 Pint	24	0	895	12.20
SB75-010	1/2 Pint	24	0	895	19.43
SB75-020	Pint	12	0	895	31.42
SB75-030	Quart	12	0	895	56.46



FS-5 One-Step Cement

FS5-020	Pint	12	0	703	31.31
FS5-030	Quart	12	0	703	57.43



Empty Cans

With Cap/Lid - order Daubers separately

MT-654	Pint	12	0	710	5.79
MT-651	Quart	12	0	710	7.52
MT-653	Quart	12	0	710	8.80

¹ 1-3/4 Screw Neck
² TT Paint Type

Brush

For Pint and Quart Cans

KD-110	4-1/2" Length	25	0	710	10.09
KD-112	5-1/2" length	25	0	710	10.09

1" Brush w/1-3/4" Screw Cap, for pipe size 3/4" - 2"



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Roller - Small Cap



Fits 1-3/4" Neck Quart Cans (MT-651).
Replaceable cover. For pipe size 3" to 6".

6020	4" length	24	0	710	15.72
------	-----------	----	---	-----	-------

Roller Replacement Covers



Fits Rollers with Heavy Handles #5520,
#6020 & #6520. Sold as Pack of 2, full pack only.

5520-1	Fits 5520 & 6020 Roller	1	75	710	14.24
--------	-------------------------	---	----	-----	-------



Cap Dauber

DP-75	3/4" for Pint	50	0	710	1.38
DP-125	1-1/4" for Pint	50	0	710	1.66
DQ-125	1-1/4" for Quart	50	0	710	1.66

* 3/4" Diameter fits Pint Cans, for pipe size 3/4"
** 1-1/2" Diameter fits Pint Cans, for pipe size 1-1/2"
***1-1/2" Diameter fits Quart Cans, for pipe size 1-1/2"

Can-Mate Dauber



Adjustable Plastic Applicator with
Telescoping Stem for use with Standard
Pint and Quart Cans.

CM-75	3/4"	50	0	710	5.54
CM-150	1-1/4"	50	0	710	5.54

3/4" Diameter fits Pint or Quart Cans, for pipe sizes 3/4" - 1-1/4"
1-1/4" Diameter fits Pint or Quart Cans, for pipe sizes 1-1/2" - 3"

Deburring Tool



Cone Type for pipe 1/2" - 2"

DEB-2	1/2" to 2" Pipe	1	6	710	102.85
-------	-----------------	---	---	-----	--------