



**Spears® Sprinkler Head Adapter Removal Kit & CPVC Riser Drain Valves For NFPA 13D Installations Only**

**Spears® Sprinkler Head Adapter Removal Kit**

Occasionally a Sprinkler Head Adapter may need to be removed for relocation, extension or repair. Kit includes Cutter, Deburring Tool and Wrench. Cutter provides easy cutting of pipe from the inside (using a power drill) to remove adapters without disturbing ceiling or side wall. Deburring Tool allows removal of burrs in cut pipe. Wrench is designed to hold Spears® TorqueSafe™ Head Adapter brass insert from rotating to aid in sprinkler head removal from adapter, if required.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Complete Kit**

**Inside Pipe Cutter, Deburring Tool and Wrench**



SHRK-005	3/4" & 1" Pipe	1	15	299	627.29
----------	----------------	---	----	-----	--------

**Inside Pipe Cutter Only**



GSC-005	3/4" & 1" Pipe	80	0	299	368.62
---------	----------------	----	---	-----	--------

**Deburring Tool Only**



GSB-005	3/4" & 1" Pipe	25	0	299	425.28
---------	----------------	----	---	-----	--------

**Wrench Only**



GSW-005	For 1/2	1	50	299	152.98
---------	---------	---	----	-----	--------

**CPVC Riser Drain Valves For NFPA 13D Installations Only**

**FlameGuard® CPVC Drain & Check Valves For NFPA 13D Applications Only**

Application: FlameGuard® CPVC Orange Check Valves and PVC/CPVC True Union Drain Valves are for use in configuring CPVC Fire Sprinkler System connection to water supply (riser/drain assembly) in NFPA 13D installations only. These valves are not UL Listed and NOT for use in any other locations within the fire sprinkler system.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**True Union Industrial Drain Valve With Locking Handle**



**Socket x Socket**

CPVC Gray Valve with CPVC Orange End Connector

1822-007CFG	3/4	1	18	077	91.58
1822-010CFG	1	1	12	077	109.03
1822-012CFG	1-1/4	1	8	077	173.33
1822-015CFG	1-1/2	1	8	077	183.06
1822-020CFG	2	1	4	077	244.82

Not UL Listed

**True Union Standard Drain Valves**



**Socket x Socket**

PVC Gray Valve with CPVC Orange End Connector

3622-007FG	3/4	1	18	077	52.12
3622-010FG	1	1	12	077	62.07

Not UL Listed

**Compact 2000 Drain Valve**



**Socket x Socket**

6622-007CO	3/4	10	80	077	35.77
6622-010CO	1	10	0	077	44.72

Not UL Listed

**CPVC Swing Check Valves**



**Socket x Socket**

S1520-10CO	1	20	0	077	35.59
S1520-12CO	1-1/4	12	0	077	39.77
S1520-15CO	1-1/2	12	0	077	44.72



**CPVC Riser Drain Valves For NFPA 13D Installations Only**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**CPVC Swing Check Valves** (continued)

**Socket x Socket**

Not UL Listed
---------------

**CPVC Special Reinforced Thread Inlet Swing Check Valves**



**SR Fipt x Socket**

S1520-10FSRSCO	<b>1</b>	20	0	077	38.54
S1520-12FSRSCO	<b>1-1/4</b>	12	0	077	44.49
S1520-15FSRSCO	<b>1-1/2</b>	12	0	077	52.79

Not UL Listed
---------------

**General Installation Information:** Socket end connections should be installed using Spears® FS-5 One-Step Cement for use with Spears® CPVC Fire Sprinkler Products. Threaded connections should be made using Spears® **BLUE 75™** Thread Sealant tested for compatibility with CPVC materials. PVC True Union Drain Valves are to be installed with system connection to Valve CPVC End Connector. Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down.