




EverTUFF® TURF™ PVC Repair Couplings



EverTUFF® TURF™ PVC Features

- Injection molded from Specially Balanced PVC Material in Distinct Blue color
- Full Class 315 Pressure Rating
- NSF® Certified for Potable Water Use

GripLoc™ Compression Couplings

- Uses NO Solvent Cement
- EPDM Sealed Gripper Ring
- Provides Quick, Permanent Connection for Repairs or Extensions


Expansion Repair Couplings

- Multi-function Telescoping Design
- Double O-ring Seal in EPDM
- Regular and Short configurations
- Socket x Socket Configuration for Pipe Repair or Use as a Short-Stroke Expansion Joint
- Spigot x Socket Configuration for Replacing Damged Fittings
- Both Configurations can be Easily Modified for Opposite Use

Versatile Repair Capability

Spears® GripLoc™ Compression Couplings use NO solvent cement which provides for immediate repairs of damaged components or system extensions. O-ring sealed stainless steel Gripper Ring forms leak-tight, reliable connections. Spears® Repair Couplings™ provide a variety of system repair and alteration solutions. Use Socket x Socket configurations for quick pipe damage repair - can also be used as a short-stroke expansion joint to compensate for thermal expansion & contraction. Spigot x Socket configurations are excellent for lateral and riser add-ons, damaged fitting replacement, or for installing valves in existing piping systems. Order the wrong configuration? Simply cut coupling from Socket shaft end to function as a spigot or add a coupling to Spigot shaft end for Socket connections.

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------




EverTUFF® TURF™ PVC Repair Coupling - Spigot x Socket

EPDM O-rings

Can be used as a short-stroke Expansion Joint

S118-10T	1	4	15	0	031	12.79
S118-12T	1-1/4	4	25	0	031	24.11
S118-15T	1-1/2	4	25	0	031	26.24
S118-20T	2	4	12	0	031	40.60
S118-25T	2-1/2	6	5	0	031	58.89
S118-30T	3	6	4	0	031	73.58
S118-40T	4	6	2	0	031	128.77
S118-60T	6	6	1	0	031	315.08

Unit Must Be Thrust Blocked
T= Repair Coupling Travel



EverTUFF® TURF™ PVC Repair Coupling - Socket x Socket


EPDM O-rings

Can be used as a short-stroke Expansion Joint

S119-10T	1	4	20	0	031	12.79
S119-12T	1-1/4	4	10	0	031	24.11
S119-15T	1-1/2	4	16	0	031	26.24
S119-20T	2	4	10	0	031	40.60
S119-25T	2-1/2	6	5	0	031	58.89
S119-30T	3	6	4	0	031	73.58
S119-40T	4	6	2	0	031	128.77
S119-60T	6	6	1	0	031	315.08

Unit Must Be Thrust Blocked
T= Repair Coupling Travel

EverTUFF® TURF™ PVC Short Repair Couplings



EverTUFF® TURF™ PVC Repair Coupling - Short, Spigot x Socket

EPDM O-ring

SH118-10T	1	2	35	0	031	12.79
SH118-12T	1-1/4	2-1/2	25	0	031	24.11
SH118-15T	1-1/2	2-3/4	32	0	031	26.24
SH118-20T	2	3-1/4	15	0	031	40.60

Unit Must Be Thrust Blocked
T= Repair Coupling Travel