




Irrigation & Turf Product
EverTUFF® TURF™ Repair & GripLoc™ Fittings

EverTUFF® TURF™ PVC Short Repair Couplings

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------



EverTUFF® TURF™ PVC Repair Coupling
 - Short, Socket x Socket


EPDM O-ring

SH119-10T	1	2	30	0	031	12.79
SH119-12T	1-1/4	2-1/2	20	0	031	24.11
SH119-15T	1-1/2	2-3/4	21	0	031	26.24
SH119-20T	2	3-1/4	12	0	031	40.60

Unit Must Be Thrust Blocked
T= Repair Coupling Travel

EverTUFF® TURF™ PVC GripLoc™ Compression Couplings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------



EverTUFF® GripLoc™ Compression Coupling

WARNING: DO NOT INSERT FINGERS
For Cold Water Only - EPDM O-rings
Pressure Rated 1" - 2" = 235 psi, 3" & Up = 150 psi
When using over rated pressure up to 315 psi MUST BE RESTRAINED

Hand Tighten ONLY - No Nut Wrenches Required

S112-10T	1	1	20	131	44.40
S112-12T	1-1/4	1	10	131	48.40
S112-15T	1-1/2	1	16	131	56.58
S112-20T	2	1	9	131	66.68
S112-30T	3	1	4	131	114.48
S112-40T	4	1	4	131	129.40