

Lab Specialty Product
Lab Ball Valves & Needle Valves



Lab Ball Valves



Socket/Threaded Valve Only

Pressure Rating @ 73°F (23°C),
 Water
 1/8" - 3/8" 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings
 Apply
 Rated for Vacuum Service



Valve & Adapters

Valve & Adapters includes:
 1 - Threaded 1/4" Valve
 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
 2 - EPDM or FKM O-rings (AS568-013 size)
 1 - End Connector Wrench
 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters - OR -
 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

Lab Valve - PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 28.54	1539-002A 29.83	1	25	218
1/4X3/8T	1529-002 28.54	1539-002 29.83	1	25	218

Valve only Threaded Ends

1/4	1521-002 22.80	1531-002 25.39	50	200	218
3/8	1521-003 32.05	1531-003 35.54	50	200	218

Valve Only Female x Male Thread Ends

1/8	152FM-001 28.54	153FM-001 29.83	25	200	218
1/4	152FM-002 28.54	153FM-002 29.83	25	200	218

Lab Valve - PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve only Socket Ends

1/4	1522-002 22.80	1532-002 25.80	50	200	218
3/8	1522-003 32.05	1532-003 35.54	50	200	218

Lab Valve - CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 34.25	1539-002CA 34.92	1	25	219
1/4X3/8T	1529-002C 34.25	1539-002C 34.92	1	25	219

Valve only Threaded Ends

1/4	1521-002C 27.42	1531-002C 30.15	50	200	219
3/8	1521-003C 38.46	1531-003C 36.04	50	200	219

Valve Only Female x Male Thread Ends

1/8	152FM-001C 34.25	---	25	200	219
1/4	152FM-002C 34.25	---	25	200	219

Valve only Socket Ends

1/4	1522-002C 27.42	1532-002C 32.63	50	200	219
3/8	1522-003C 38.46	1532-003C 42.69	50	200	219

Needle Valves



Pressure Rating @ 73°F
 (23°C), Water
 PVC or CPVC 235 psi
 PP 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 PP = 180°F (82°C)
 Solid PTFE Stem Seals
 No Elastomer or Lubricants used
 Valves include Panel Mounting Nut

PVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Prod Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002 78.97	5592-002 78.97	---	1	18	218
3/8	5591-003 78.97	5592-003 78.97	5591-003SR 72.03	1	18	218
1/2	5591-005 87.65	5592-005 87.65	5591-005SR 90.01	1	18	218

Angle Pattern

1/4	5691-002 78.97	5692-002 78.97	---	1	18	218
-----	-------------------	-------------------	-----	---	----	-----