




Low Extractable Technical
Low Extractable Technical Information

Reducer Coupling

Socket x Socket



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
829-101BL	3/4X1/2	1- 13/32	1- 13/32	1- 3/16	7/32	.06
829-131BL	1X3/4	2- 13/32	1- 23/32	1- 13/32	1/4	.09
829-168BL	1-1/4X1	2- 23/32	2- 3/32	1- 23/32	3/8	.16
829-210BL	1-1/2X3/4	3	2-13/32	1-13/32	5/8	.19
829-211BL	1-1/2X1	2- 7/8	2- 11/32	1- 15/16	3/8	.24
829-212BL	1-1/2X1-1/4	2- 13/16	2- 3/8	2- 3/32	5/32	.21
829-249BL	2X1	3- 1/8	2- 7/8	1- 23/32	17/32	.31
829-251BL	2X1-1/2	3- 7/32	2- 27/32	2- 11/32	7/32	.29
829-338BL	3X2	4	4- 5/32	2- 27/32	11/16	.68
829-420BL	4X2	4- 5/8	5- 9/32	2- 7/8	13/16	1.19
829-422BL	4X3	4- 5/8	5- 1/4	4- 1/8	1/2	1.25
829-532BL	6X4	6- 5/8	7- 5/8	5- 5/16	1- 7/16	3.22


Threaded Connections

Use only quality grade PTFE tape as a thread sealant for Spears® low-extractable applications. **Warning:** Some pipe joint compounds or PTFE pastes may contain substances that could cause stress cracking to plastics and increase the potential for system contamination. 1 to 2 full turns beyond finger tight is generally all that is required to make a sound plastic threaded connection. Unnecessary overtightening will cause damage to both pipe and fitting.



Special Reinforced Female Adapter

Socket x SR Fipt



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
835-005SRBL	1/2	1-23/32	1- 5/32	1- 3/16	3/32	.05
835-007SRBL	3/4	1- 7/8	1- 13/32	1- 3/8	1/8	.08
835-010SRBL	1	2- 5/32	1- 23/32	1- 23/32	3/32	.13
835-012SRBL	1-1/4	2- 5/16	2- 1/8	2- 1/16	3/16	.18
835-015SRBL	1-1/2	2- 7/16	2- 13/32	2- 7/16	7/32	.26
835-020SRBL	2	2- 11/16	3	3- 3/32	9/32	.42
835-030SRBL	3	3- 1/2	4- 1/4	4- 9/32	7/32	1.03
835-040SRBL	4	3- 31/32	5- 7/32	5- 7/32	1/4	1.28