




Low Extractable Technical
Low Extractable Technical Information

Union


Socket x Socket EPDM O-ring Seals
 235 psi Maximum Internal Pressure Rating @ 73°
 F (23°C)



Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
897-005BL	1/2	2- 3/32	1- 9/32	11/32	1- 31/32	.14
897-007BL	3/4	2- 3/8	1- 17/32	11/32	2- 1/2	.25
897-010BL	1	2- 9/16	1- 27/32	3/8	2- 7/8	.35
897-012BL	1-1/4	2- 7/8	2- 7/32	3/8	3- 5/16	.49
897-015BL	1-1/2	3- 3/32	2- 9/16	15/32	3- 9/16	.59
897-020BL	2	3- 5/8	3- 1/32	9/16	4- 3/16	.95
8097-030BL	3	4- 1/4	4- 3/16	1/2	6- 5/32	2.11
8097-040BL	4	5- 1/8	5- 1/4	5/8	7- 3/4	3.72

Union

Socket x Socket FKM O-ring Seals
 235 psi Maximum Internal Pressure Rating @ 73°
 F (23°C)



Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
857-005BL	1/2	2- 3/32	1- 9/32	11/32	1- 31/32	.14
857-007BL	3/4	2- 3/8	1- 17/32	11/32	2- 1/2	.25
857-010BL	1	2- 9/16	1- 27/32	3/8	2- 7/8	.36
857-012BL	1-1/4	2- 7/8	2- 7/32	3/8	3- 5/16	.50
857-015BL	1-1/2	3- 3/32	2- 9/16	15/32	3- 9/16	.60
857-020BL	2	3- 5/8	3- 1/32	9/16	4- 3/16	.96
8057-030BL	3	4- 1/4	4- 3/16	1/2	6- 5/32	2.11
8057-040BL	4	5- 1/8	5- 1/4	5/8	7- 3/4	3.73