



CTS CPVC Pipe - USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

CTS CPVC Pipe SDR 11 - CTS MARINE

10 Ft Length



Priced per foot
NSF® Certified Lead Free

| | | | | | |
|------------|-------|-----|---|-----|-------|
| CG-CTS-005 | 1/2 | 500 | 0 | 176 | 1.36 |
| CG-CTS-007 | 3/4 | 250 | 0 | 176 | 2.43 |
| CG-CTS-010 | 1 | 150 | 0 | 176 | 5.00 |
| CG-CTS-012 | 1-1/4 | 100 | 0 | 176 | 7.41 |
| CG-CTS-015 | 1-1/2 | 100 | 0 | 176 | 9.83 |
| CG-CTS-020 | 2 | 50 | 0 | 176 | 16.63 |

CTS CPVC Pipe SDR 11 - CTS MARINE

20 FT Lengths



Priced per foot
NSF® Certified Lead Free

| | | | | | |
|---------------|-------|------|---|-----|-------|
| CG-CTS-005-20 | 1/2 | 1000 | 0 | 176 | 1.36 |
| CG-CTS-007-20 | 3/4 | 500 | 0 | 176 | 2.43 |
| CG-CTS-010-20 | 1 | 300 | 0 | 176 | 5.00 |
| CG-CTS-012-20 | 1-1/4 | 200 | 0 | 176 | 7.41 |
| CG-CTS-015-20 | 1-1/2 | 200 | 0 | 176 | 9.83 |
| CG-CTS-020-20 | 2 | 100 | 0 | 176 | 16.63 |

Pipe - CPVC CTS Coiled SDR 11 - CTS MARINE

100 ft. Coil, Priced Per Foot



NSF® Certified Lead Free

| | | | | | |
|----------------|-----|-----|---|-----|------|
| CG-CTS-005-100 | 1/2 | 100 | 0 | 176 | 1.59 |
| CG-CTS-007-100 | 3/4 | 100 | 0 | 176 | 3.04 |
| CG-CTS-010-100 | 1 | 100 | 0 | 176 | 6.25 |

CPVC CTS COILED PIPE WEIGHTS:
 CTS-005-100 Weight per Foot .090 lbs; per Coil Weight 9 lbs.
 CTS-007-100 Weight per Foot .149 lbs; per Coil Weight 14.9 lbs.
 CTS-010-100 Weight per Foot .239 lbs; per Coil Weight 23.9 lbs.
WARNING: Banded coils will expand when opened. Exercise caution to avoid injury during banding removal.

CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Tee -CTS MARINE

Socket x Socket x Socket



NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|-----|-----|-------|
| CG-4101-005 | 1/2 | 100 | 500 | 173 | 1.41 |
| CG-4101-007 | 3/4 | 50 | 250 | 173 | 2.63 |
| CG-4101-010 | 1 | 10 | 100 | 173 | 13.20 |
| CG-4101-012 | 1-1/4 | 10 | 100 | 173 | 20.35 |
| CG-4101-015 | 1-1/2 | 5 | 50 | 173 | 26.51 |
| CG-4101-020 | 2 | 5 | 25 | 173 | 42.84 |

Tee - Reducing - CTS MARINE

Socket x Socket x Socket



NSF® Certified Lead Free

| | | | | | |
|--------------------------|-------------------|----|-----|-----|-------|
| CG-4101-074 | 1/2X1/2X3/4 | 10 | 100 | 173 | 4.89 |
| CG-4101-094 | 3/4X1/2X1/2 | 50 | 250 | 173 | 2.62 |
| CG-4101-095 | 3/4X1/2X3/4 | 25 | 250 | 173 | 3.58 |
| CG-4101-101 | 3/4X3/4X1/2 | 50 | 250 | 173 | 2.73 |
| CG-4101-102 ¹ | 3/4X3/4X1 | 10 | 100 | 173 | 29.24 |
| CG-4101-120 ¹ | 1X1/2X1/2 | 10 | 100 | 173 | 31.52 |
| CG-4101-121 ¹ | 1X1/2X3/4 | 10 | 100 | 173 | 32.37 |
| CG-4101-122 ¹ | 1X1/2X1 | 10 | 100 | 173 | 24.67 |
| CG-4101-124 ¹ | 1X3/4X1/2 | 10 | 100 | 173 | 29.42 |
| CG-4101-125 | 1X3/4X3/4 | 10 | 100 | 173 | 16.08 |
| CG-4101-126 ¹ | 1X3/4X1 | 10 | 100 | 173 | 23.54 |
| CG-4101-130 | 1X1X1/2 | 10 | 100 | 173 | 15.05 |
| CG-4101-131 | 1X1X3/4 | 10 | 100 | 173 | 14.37 |
| CG-4101-138 ¹ | 1-1/4X1/2X1/2 | 10 | 80 | 173 | 36.74 |
| CG-4101-139 ¹ | 1-1/4X1/2X3/4 | 10 | 80 | 173 | 36.74 |
| CG-4101-142 ¹ | 1-1/4X1/2X1-1/4 | 10 | 80 | 173 | 36.74 |
| CG-4101-146 ¹ | 1-1/4X3/4X1/2 | 10 | 80 | 173 | 36.74 |
| CG-4101-147 ¹ | 1-1/4X3/4X3/4 | 10 | 80 | 173 | 32.82 |
| CG-4101-148 ¹ | 1-1/4X3/4X1 | 10 | 80 | 173 | 35.57 |
| CG-4101-149 ¹ | 1-1/4X3/4X1-1/4 | 10 | 80 | 173 | 32.68 |
| CG-4101-156 ¹ | 1-1/4X1X1/2 | 10 | 80 | 173 | 34.74 |
| CG-4101-157 ¹ | 1-1/4X1X3/4 | 10 | 80 | 173 | 33.25 |
| CG-4101-158 ¹ | 1-1/4X1X1 | 10 | 100 | 173 | 34.15 |
| CG-4101-159 ¹ | 1-1/4X1X1-1/4 | 10 | 80 | 173 | 38.31 |
| CG-4101-166 | 1-1/4X1/2 | 10 | 100 | 173 | 36.74 |
| CG-4101-167 | 1-1/4X3/4 | 10 | 100 | 173 | 32.68 |
| CG-4101-168 | 1-1/4X1-1/4X1 | 10 | 100 | 173 | 34.56 |
| CG-4101-169 | 1-1/4X1-1/4X1-1/2 | 5 | 40 | 173 | 36.74 |
| CG-4101-173 ¹ | 1-1/2X1/2X1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-174 ¹ | 1-1/2X1/2X3/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-175 ¹ | 1-1/2X1/2X1 | 5 | 40 | 173 | 44.51 |
| CG-4101-176 ¹ | 1-1/2X1/2X1-1/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-177 ¹ | 1-1/2X1/2X1-1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-182 ¹ | 1-1/2X3/4X1/2 | 5 | 40 | 173 | 44.51 |



Marine & Offshore Products
CTS CPVC Fittings & Valves - ABS & USCG Approved

CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|--|-------------------|--------|----------|-----------|-------|
| Tee - Reducing - CTS MARINE (continued) | | | | | |
| Socket x Socket x Socket | | | | | |
| CG-4101-184 ¹ | 1-1/2X3/4X3/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-185 ¹ | 1-1/2X3/4X1 | 5 | 40 | 173 | 44.51 |
| CG-4101-186 ¹ | 1-1/2X3/4X1-1/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-188 ¹⁴ | 1-1/2X3/4X1-1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-193 ¹ | 1-1/2X1X1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-194 ¹ | 1-1/2X1X3/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-195 ¹ | 1-1/2X1X1 | 10 | 100 | 173 | 44.51 |
| CG-4101-196 ¹ | 1-1/2X1X1-1/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-197 ¹ | 1-1/2X1X1-1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-199 ¹ | 1-1/2X1-1/4X1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-201 ¹ | 1-1/2X1-1/4X3/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-202 ¹ | 1-1/2X1-1/4X1 | 5 | 40 | 173 | 44.51 |
| CG-4101-203 ¹ | 1-1/2X1-1/4X1-1/4 | 5 | 40 | 173 | 44.51 |
| CG-4101-204 ¹ | 1-1/2X1-1/4X1-1/2 | 5 | 40 | 173 | 44.51 |
| CG-4101-209 | 1-1/2X1-1/2X1/2 | 10 | 50 | 173 | 39.54 |
| CG-4101-210 | 1-1/2X3/4 | 10 | 100 | 173 | 32.96 |
| CG-4101-211 | 1-1/2X1 | 5 | 50 | 173 | 30.19 |
| CG-4101-212 ¹ | 1-1/2X1-1/2X1-1/4 | 5 | 50 | 173 | 44.51 |
| CG-4101-213 ¹ | 1-1/2X1-1/2X2 | 5 | 0 | 173 | 44.51 |
| CG-4101-216 ¹ | 2X1/2X1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-217 ¹ | 2X1/2X3/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-218 ¹ | 2X1/2X1 | 5 | 0 | 173 | 55.72 |
| CG-4101-219 ¹ | 2X1/2X1-1/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-220 ¹ | 2X1/2X1-1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-221 ¹ | 2X1/2X2 | 5 | 0 | 173 | 55.72 |
| CG-4101-222 ¹ | 2X3/4X1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-223 ¹ | 2X3/4X3/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-224 ¹ | 2X3/4X1 | 5 | 0 | 173 | 55.72 |
| CG-4101-225 ¹ | 2X3/4X1-1/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-226 ¹ | 2X3/4X1-1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-227 ¹ | 2X3/4X2 | 5 | 0 | 173 | 55.72 |
| CG-4101-228 ¹ | 2X1X1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-229 ¹ | 2X1X3/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-230 ¹ | 2X1X1 | 5 | 0 | 173 | 55.72 |
| CG-4101-231 ¹ | 2X1X1-1/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-232 ¹ | 2X1X1-1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-233 ¹ | 2X1X2 | 5 | 0 | 173 | 55.72 |
| CG-4101-234 ¹ | 2X1-1/4X1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-235 ¹ | 2X1-1/4X3/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-236 ¹ | 2X1-1/4X1 | 5 | 0 | 173 | 55.72 |
| CG-4101-237 ¹ | 2X1-1/2X1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-238 ¹ | 2X1-1/2X3/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-239 ¹ | 2X1-1/2X1 | 5 | 0 | 173 | 55.72 |
| CG-4101-240 ¹ | 2X1-1/2X1-1/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-241 ¹ | 2X1-1/2X1-1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-242 ¹ | 2X1-1/4X1-1/4 | 5 | 0 | 173 | 55.72 |
| CG-4101-243 ¹ | 2X1-1/4X1-1/2 | 5 | 0 | 173 | 55.72 |
| CG-4101-244 ¹ | 2X1-1/4X2 | 5 | 0 | 173 | 55.72 |
| CG-4101-247 | 2X1/2 | 10 | 30 | 173 | 49.98 |
| CG-4101-248 | 2X3/4 | 5 | 25 | 173 | 42.98 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Tee - Reducing - CTS MARINE (continued)

Socket x Socket x Socket

| | | | | | |
|--------------------------|-----------|---|----|-----|-------|
| CG-4101-249 | 2X1 | 5 | 25 | 173 | 42.98 |
| CG-4101-250 ¹ | 2X2X1-1/4 | 5 | 25 | 173 | 48.43 |
| CG-4101-251 ¹ | 2X2X1-1/2 | 5 | 25 | 173 | 48.43 |
| CG-4101-257 ¹ | 2X1-1/2X2 | 5 | 0 | 173 | 48.43 |

¹ Outlet sized with bushing.



90° EII - CTS MARINE

Socket x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|------|-----|-------|
| CG-4106-005 | 1/2 | 100 | 1000 | 173 | 1.09 |
| CG-4106-007 | 3/4 | 50 | 500 | 173 | 1.80 |
| CG-4106-010 | 1 | 10 | 100 | 173 | 5.26 |
| CG-4106-012 | 1-1/4 | 10 | 100 | 173 | 10.52 |
| CG-4106-015 | 1-1/2 | 10 | 100 | 173 | 18.95 |
| CG-4106-020 | 2 | 5 | 100 | 173 | 36.37 |



90° EII - Reducing - CTS MARINE

Socket x Socket

NSF® Certified Lead Free

| | | | | | |
|--------------------------|-------------|----|-----|-----|-------|
| CG-4106-101 | 3/4X1/2 | 50 | 250 | 173 | 3.80 |
| CG-4106-130 ¹ | 1X1/2 | 25 | 200 | 173 | 14.38 |
| CG-4106-131 ¹ | 1X3/4 | 25 | 200 | 173 | 14.40 |
| CG-4106-167 ¹ | 1/4X3/4 | 10 | 80 | 173 | 23.93 |
| CG-4106-168 ¹ | 1-1/4X1 | 10 | 80 | 173 | 22.82 |
| CG-4106-209 ¹ | 1-1/2X1/2 | 10 | 0 | 173 | 38.74 |
| CG-4106-210 ¹ | 1-1/2X3/4 | 10 | 0 | 173 | 38.74 |
| CG-4106-211 ¹ | 1-1/2X1 | 10 | 0 | 173 | 38.21 |
| CG-4106-212 ¹ | 1-1/2X1-1/4 | 10 | 0 | 173 | 38.21 |
| CG-4106-247 ¹ | 2X1/2 | 5 | 30 | 173 | 79.52 |
| CG-4106-248 ¹ | 2X3/4 | 5 | 30 | 173 | 77.69 |
| CG-4106-249 ¹ | 2X1 | 5 | 30 | 173 | 76.84 |
| CG-4106-250 ¹ | 2X1-1/4 | 5 | 30 | 173 | 76.79 |
| CG-4106-251 ¹ | 2X1-1/2 | 5 | 30 | 173 | 76.79 |

¹ Outlet sized with bushing



90° EII - Special Reinforced - CTS MARINE

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|-------|
| CG-4107-005SR | 1/2 | 50 | 300 | 173 | 12.21 |
|---------------|-----|----|-----|-----|-------|

Drop Ear 90° EII - CPVC Fitting with Bracket - CTS MARINE

Socket x Socket

NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|------|
| CG-DE4106-005 | 1/2 | 25 | 150 | 173 | 3.32 |
|---------------|-----|----|-----|-----|------|



Marine & Offshore Products
CTS CPVC Fittings & Valves - ABS & USCG Approved



CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Drop Ear 90° EII - Special Reinforced CPVC Fitting with Bracket - CTS MARINE

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

| | | | | | |
|-----------------|-----|----|-----|-----|-------|
| CG-DE4107-005SR | 1/2 | 10 | 200 | 173 | 12.59 |
|-----------------|-----|----|-----|-----|-------|



Drop Ear EII Bracket ONLY - CTS MARINE

For 4107-005SR

| | | | | | |
|------------|-----|-----|---|-----|------|
| CG-DET-005 | 1/2 | 400 | 0 | 173 | 2.48 |
|------------|-----|-----|---|-----|------|



Drop Ear EII - Stainless Steel Thread - CTS MARINE

Drop Ear EII - Stainless Steel Thread

NSF® Certified Lead Free

| | | | | | |
|-----------------|-----|-----|---|-----|-------|
| CG-DE4107-005SS | 1/2 | 100 | 0 | 173 | 26.24 |
|-----------------|-----|-----|---|-----|-------|



Drop Ear EII - Stainless Steel Thread/CPVC Body - CTS MARINE

Socket x SS Fipt

NSF® Certified Lead Free

| | | | | | |
|-----------------|-----|-----|---|-----|-------|
| CG-DE4107005CSS | 1/2 | 100 | 0 | 173 | 18.66 |
|-----------------|-----|-----|---|-----|-------|



90° Street EII - CTS MARINE

Spigot x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-----|-----|-----|-----|------|
| CG-4109-005 | 1/2 | 100 | 500 | 173 | 1.29 |
| CG-4109-007 | 3/4 | 50 | 250 | 173 | 2.06 |
| CG-4109-010 | 1 | 50 | 100 | 173 | 9.48 |



90° Stub Out EII - CTS MARINE

Socket x Closed End

NSF® Certified Lead Free

| | | | | | |
|--------------|-----|----|---|-----|-------|
| CG-S4106-005 | 1/2 | 50 | 0 | 173 | 18.57 |
|--------------|-----|----|---|-----|-------|



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

45° EII - CTS MARINE

Socket x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|-----|-----|-------|
| CG-4117-005 | 1/2 | 100 | 500 | 173 | 1.38 |
| CG-4117-007 | 3/4 | 50 | 250 | 173 | 2.41 |
| CG-4117-010 | 1 | 10 | 100 | 173 | 6.11 |
| CG-4117-012 | 1-1/4 | 10 | 100 | 173 | 12.95 |
| CG-4117-015 | 1-1/2 | 10 | 100 | 173 | 18.77 |
| CG-4117-020 | 2 | 10 | 100 | 173 | 39.31 |



45° Street EII - CTS MARINE

Spigot x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-----|-----|-----|-----|-------|
| CG-4127-005 | 1/2 | 100 | 500 | 173 | 2.95 |
| CG-4127-007 | 3/4 | 50 | 250 | 173 | 3.95 |
| CG-4127-010 | 1 | 50 | 250 | 173 | 11.36 |



Coupling - CTS MARINE

Socket x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|------|-----|-------|
| CG-4129-005 | 1/2 | 100 | 1000 | 173 | .89 |
| CG-4129-007 | 3/4 | 50 | 500 | 173 | 1.20 |
| CG-4129-010 | 1 | 10 | 100 | 173 | 5.36 |
| CG-4129-012 | 1-1/4 | 10 | 100 | 173 | 6.93 |
| CG-4129-015 | 1-1/2 | 10 | 100 | 173 | 9.79 |
| CG-4129-020 | 2 | 10 | 50 | 173 | 18.64 |



GripLoc™ Coupling - CTS MARINE

WARNING: DO NOT INSERT FINGERS
Grip Socket x Grip Socket -

Uses No Solvent Cement. NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|----|-----|-------|
| CG-GL4129-005 | 1/2 | 1 | 75 | 173 | 20.78 |
| CG-GL4129-007 | 3/4 | 1 | 50 | 173 | 21.64 |
| CG-GL4129-010 | 1 | 12 | 24 | 173 | 27.41 |

Gripper is 410 Stainless Steel



Female Adapter with O-ring Gasket - CTS MARINE

Socket x Thread

For Cold Water Service Only - NSF® Certified Lead Free

| | | | | | |
|---------------|-----|-----|-----|-----|------|
| CG-4135-005OR | 1/2 | 100 | 500 | 173 | 3.88 |
| CG-4135-007OR | 3/4 | 50 | 250 | 173 | 5.47 |
| CG-4135-010OR | 1 | 10 | 100 | 173 | 6.35 |





Marine & Offshore Products
CTS CPVC Fittings & Valves - ABS & USCG Approved

CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Female Adapter - Special Reinforced - CTS MARINE

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|-------|
| CG-4135-005SR | 1/2 | 25 | 200 | 173 | 10.48 |
| CG-4135-007SR | 3/4 | 25 | 300 | 173 | 11.53 |
| CG-4135-010SR | 1 | 5 | 100 | 173 | 14.62 |



Female Adapter - Reducing Special Reinforced - CTS MARINE

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

| | | | | | |
|---------------|-------|----|-----|-----|-------|
| CG-4135-131SR | 1X3/4 | 25 | 150 | 173 | 20.36 |
|---------------|-------|----|-----|-----|-------|



Female Adapter - Stainless Steel Thread Transition - CTS MARINE

Socket x SS Fipt

NSF® Certified Lead Free

| | | | | | |
|---------------|-------|----|-----|-----|--------|
| CG-4135-005SS | 1/2 | 25 | 150 | 173 | 13.09 |
| CG-4135-007SS | 3/4 | 25 | 150 | 173 | 18.78 |
| CG-4135-010SS | 1 | 25 | 100 | 173 | 31.17 |
| CG-4135-012SS | 1-1/4 | 16 | 0 | 173 | 71.79 |
| CG-4135-015SS | 1-1/2 | 16 | 0 | 173 | 120.46 |
| CG-4135-020SS | 2 | 8 | 0 | 173 | 178.06 |



Male Adapter - CTS MARINE

Mipt x Socket

For Cold Water Service Only - NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|------|-----|-------|
| CG-4136-005 | 1/2 | 100 | 1000 | 173 | 1.15 |
| CG-4136-007 | 3/4 | 50 | 500 | 173 | 1.94 |
| CG-4136-010 | 1 | 10 | 100 | 173 | 9.19 |
| CG-4136-012 | 1-1/4 | 10 | 100 | 173 | 14.21 |
| CG-4136-015 | 1-1/2 | 10 | 100 | 173 | 17.54 |
| CG-4136-020 | 2 | 10 | 100 | 173 | 28.91 |



Male Adapter - Spigot - CTS Marine

Mipt xx Spigot

For Cold Water Service Only - NSF® Certified Lead Free

| | | | | | |
|-------------|-----|----|-----|-----|------|
| CG-4161-005 | 1/2 | 50 | 700 | 173 | 3.69 |
|-------------|-----|----|-----|-----|------|



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Male Adapter - Internal Stainless Steel Reinforced - CTS MARINE

R Mipt x Socket - Stainless Steel Sleeve

NSF® Certified Lead Free

| | | | | | |
|--------------|-----|----|-----|-----|-------|
| CG-4136-005R | 1/2 | 25 | 300 | 173 | 13.45 |
| CG-4136-007R | 3/4 | 25 | 300 | 173 | 14.95 |
| CG-4136-010R | 1 | 10 | 120 | 173 | 22.27 |



Male Adapter - Transition with Stainless Steel Thread - CTS MARINE

Socket x SS Mipt

NSF® Certified Lead Free

| | | | | | |
|---------------|-------|----|-----|-----|--------|
| CG-4136-005SS | 1/2 | 25 | 150 | 173 | 13.11 |
| CG-4136-007SS | 3/4 | 25 | 150 | 173 | 20.74 |
| CG-4136-010SS | 1 | 25 | 0 | 173 | 35.09 |
| CG-4136-012SS | 1-1/4 | 16 | 0 | 173 | 70.31 |
| CG-4136-015SS | 1-1/2 | 16 | 0 | 173 | 120.46 |
| CG-4136-020SS | 2 | 8 | 0 | 173 | 132.52 |



Reducer Bushing - CTS MARINE

Spigot x Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------------|----|-----|-----|-------|
| CG-4137-101 | 3/4X1/2 | 10 | 500 | 173 | 1.37 |
| CG-4137-130 | 1X1/2 | 10 | 100 | 173 | 4.47 |
| CG-4137-131 | 1X3/4 | 10 | 100 | 173 | 4.47 |
| CG-4137-166 | 1-1/4X1/2 | 10 | 100 | 173 | 5.79 |
| CG-4137-167 | 1-1/4X3/4 | 10 | 100 | 173 | 5.79 |
| CG-4137-168 | 1-1/4X1 | 10 | 100 | 173 | 5.79 |
| CG-4137-209 | 1-1/2X1/2 | 10 | 100 | 173 | 7.29 |
| CG-4137-210 | 1-1/2X3/4 | 10 | 100 | 173 | 7.29 |
| CG-4137-211 | 1-1/2X1 | 10 | 100 | 173 | 7.64 |
| CG-4137-212 | 1-1/2X1-1/4 | 10 | 100 | 173 | 7.95 |
| CG-4137-247 | 2X1/2 | 10 | 50 | 173 | 16.57 |
| CG-4137-248 | 2X3/4 | 10 | 50 | 173 | 16.57 |
| CG-4137-249 | 2X1 | 10 | 60 | 173 | 16.57 |
| CG-4137-250 | 2X1-1/4 | 10 | 50 | 173 | 16.57 |
| CG-4137-251 | 2X1-1/2 | 10 | 100 | 173 | 16.57 |



Transition Bushing - CTS MARINE

IPS Spigot x CTS Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------|----|-----|-----|-------|
| CG-4140-005 | 1/2 | 10 | 600 | 173 | 5.78 |
| CG-4140-007 | 3/4 | 10 | 100 | 173 | 6.04 |
| CG-4140-010 | 1 | 10 | 100 | 173 | 6.67 |
| CG-4140-015 | 1-1/2 | 10 | 100 | 173 | 10.41 |
| CG-4140-012 | 1-1/4 | 10 | 100 | 173 | 8.25 |
| CG-4140-020 | 2 | 10 | 50 | 173 | 11.36 |



Marine & Offshore Products
CTS CPVC Fittings & Valves - ABS & USCG Approved



CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Transition Coupling - CTS MARINE

IPS Socket x CTS Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-----|----|-----|-----|------|
| CG-4141-007 | 3/4 | 25 | 300 | 173 | 4.14 |
|-------------|-----|----|-----|-----|------|



Cap - CTS MARINE

Socket

NSF® Certified Lead Free

| | | | | | |
|-------------|-------|-----|-----|-----|-------|
| CG-4147-005 | 1/2 | 100 | 500 | 173 | .99 |
| CG-4147-007 | 3/4 | 50 | 250 | 173 | 1.25 |
| CG-4147-010 | 1 | 10 | 100 | 173 | 4.57 |
| CG-4147-012 | 1-1/4 | 10 | 100 | 173 | 6.29 |
| CG-4147-015 | 1-1/2 | 10 | 100 | 173 | 9.68 |
| CG-4147-020 | 2 | 10 | 50 | 173 | 19.54 |



GripLoc™ Cap - CTS MARINE

**WARNING: DO NOT INSERT FINGERS
Grip Socket**

Uses No Solvent Cement. NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|-------|
| CG-GL4147-005 | 1/2 | 25 | 200 | 173 | 20.21 |
| CG-GL4147-007 | 3/4 | 25 | 150 | 173 | 21.46 |
| CG-GL4147-010 | 1 | 10 | 50 | 173 | 23.91 |

Gripper is 410 Stainless Steel



Union - CTS MARINE

Socket with EPDM O-ring Seal

100 psi Maximum Internal Pressure @ 180°F (82°C) - NSF® Certified Lead Free

| | | | | | |
|-------------|-------|----|-----|-----|-------|
| CG-4197-005 | 1/2 | 25 | 150 | 173 | 10.53 |
| CG-4197-007 | 3/4 | 12 | 48 | 173 | 16.68 |
| CG-4197-010 | 1 | 36 | 0 | 173 | 27.36 |
| CG-4197-012 | 1-1/4 | 12 | 48 | 173 | 53.40 |
| CG-4197-015 | 1-1/2 | 12 | 0 | 173 | 56.74 |
| CG-4197-020 | 2 | 6 | 36 | 173 | 89.17 |



Union - Special Reinforced - CTS MARINE

Socket x SR Fipt - EPDM O-ring Seal, Stainless Steel Collar

100 psi Maximum Internal Pressure @ 180°F (82°C) - NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|-------|
| CG-4199-005SR | 1/2 | 20 | 120 | 173 | 19.20 |
| CG-4199-007SR | 3/4 | 10 | 60 | 173 | 32.95 |



| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Union - Special Reinforced - CTS MARINE (continued)

Socket x SR Fipt - EPDM O-ring Seal, Stainless Steel Collar

| | | | | | |
|---------------|---|----|----|-----|-------|
| CG-4199-010SR | 1 | 10 | 40 | 173 | 54.72 |
|---------------|---|----|----|-----|-------|

CPVC-PEX Transition Spigot Adapters - CTS MARINE

Spigot x PEX Barb-Crimp Style

CPVC Spigot is also (Socket)
NSF® Certified Lead Free

| | | | | | |
|------------|-----------|----|-----|-----|-------|
| CG-TPC-005 | 1/2 | 25 | 150 | 173 | 32.56 |
| CG-TPC-007 | 3/4 (1/2) | 25 | 100 | 173 | 36.69 |
| CG-TPC-010 | 1(3/4) | 25 | 50 | 173 | 50.98 |

ASTM F1807 PEX Connector, Stainless Steel



CPVC-PEX Transition Socket Adapters - CTS MARINE

Socket x PEX Barb-Crimp Style

CPVC Socket is also (Spigot)
NSF® Certified Lead Free

| | | | | | |
|--------------|-----------|----|-----|-----|-------|
| CG-TPC-005-S | 1/2 (3/4) | 25 | 150 | 173 | 32.56 |
| CG-TPC-007-S | 3/4(1) | 25 | 100 | 173 | 36.69 |
| CG-TPC-010-S | 1(1-1/4) | 50 | 300 | 173 | 50.98 |

ASTM F1807 PEX Connector, Stainless Steel



Water Hammer Arrester - CTS MARINE

Spigot

NSF® Certified Lead Free

| | | | | | |
|------------|-----|----|-----|-----|-------|
| CG-WHA-005 | 1/2 | 25 | 100 | 173 | 26.47 |
|------------|-----|----|-----|-----|-------|



Quarter Turn Angle Supply Stop - Socket - CTS MARINE

Socket x NPT

100 psi @ 180°F (82°C)

Male Thread for Connection to Flexible Supply Line having 1/2" Female NPT Thread Inlet - NSF® Certified Lead Free

| | | | | | |
|-------------|-----|----|-----|-----|-------|
| CG-7722-005 | 1/2 | 50 | 400 | 173 | 14.83 |
|-------------|-----|----|-----|-----|-------|



Quarter Turn Angle Supply Stop - Special Reinforced - CTS MARINE

SR Fipt x NPT

100 psi @ 180°F (82°C)

Male Thread for Connection to Flexible Supply Line having 1/2" Female NPT Thread Inlet - NSF® Certified Lead Free

| | | | | | |
|---------------|-----|----|-----|-----|-------|
| CG-7721-005SR | 1/2 | 50 | 400 | 179 | 16.85 |
|---------------|-----|----|-----|-----|-------|





CTS CPVC Fittings & Valves - ABS & USCG Approved

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|



Ball Valve - Commercial - CTS MARINE-

Socket with EPDM O-ring Seal

100 psi Maximum Internal Pressure @ 180°F (82°C)
NSF® Certified Lead Free

| | | | | | |
|-------------|--------------|----|-----|-----|--------|
| CG-1922-005 | 1/2 | 25 | 200 | 179 | 25.15 |
| CG-1922-007 | 3/4 | 24 | 0 | 179 | 36.46 |
| CG-1922-010 | 1 | 25 | 0 | 179 | 46.74 |
| CG-1922-012 | 1-1/4 | 8 | 0 | 179 | 79.59 |
| CG-1922-015 | 1-1/2 | 6 | 0 | 179 | 110.99 |
| CG-1922-020 | 2 | 4 | 0 | 179 | 141.37 |

CTS CPVC Solvent Cement - ABS & USCG Approved



CTS-5 Solvent Cement - Yellow -CTS MARINE

One-Step (requires no primer)

| | | | | | |
|----------|---------------|----|---|-----|--------|
| CTS5-020 | Pint | 12 | 0 | 701 | 25.74 |
| CTS5-030 | Quart | 12 | 0 | 701 | 44.79 |
| CTS5-040 | Gallon | 6 | 0 | 701 | 153.23 |