

Metric Fittings Product

Class 10/12 PVC & CPVC Metric Fittings & Class 150 Flanges & PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray)



Class 10/12 PVC & CPVC Metric Fittings & Class 150 Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with PN/10/16 Drilling PVC Ring*

(continued)

ASTM Socket x DIN PN 10/16 Drilling

* Hubs fit 3" or 4" ASTM IPS Pipe. Rings are manufactured to DIN 8063-4 PN 10 and PN 16 bolt patterns.



Flange Van Stone Style with PN 10/16 Drilling CPVC Ring

ASTM Socket x DIN PN 10/16 Drilling

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

854-030CDIN	3	10	0	090	125.45
854-040CDIN	4	5	0	090	169.41

* Hubs fit 3" or 4" ASTM IPS Pipe. Rings are manufactured to DIN 8063-4 PN 10 and PN 16 bolt patterns.

PVC Flange* Van Stone Style

ASTM Spigot x DIN PN 10/16 Drilling

150 psi

856-030DIN	3"/80 nom.	10	0	080	60.47
856-040DIN	4"/110 nom.	5	0	080	76.52

* Spigots fit 3" or 4" ASTM IPS fitting sockets. Rings are manufactured to DIN 8063-4 PN 10 and PN 16 bolt patterns.

PVC Flange* Van Stone Style

Metric Socket x Multi Pattern Ring

150 psi

6254-160	160 d	5	0	190	119.39
6254-200	200 d	2	0	190	194.40
6254-225	225 d	2	0	190	194.40
6254-280	280 d	2	0	191	251.69

* Hubs are manufactured to fit 160mm - 225mm and 280 mm O.D. Pipe. Rings are manufactured to accept bolt patterns for ANSI Class 150, B.S. 4504 PN10, B.S. 4504 PN16 (except 225mm), B.S. 10 Table D (except 280mm) and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray)

PVC White Tee

ASTM Socket x FBSP



SCH 40

302-007	3/4	50	0	195	1.92
302-010	1	50	0	195	3.55
302-131	1X3/4	50	0	195	3.55

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

PVC White Tee (continued)

ASTM Socket x FBSP

302-211	1-1/2X1	25	0	195	7.36
302-249	2X1	10	0	195	9.26



PVC White 90° Ell

ASTM Socket x FBSP

SCH 40

307-007	3/4	50	0	195	1.07
307-010	1	50	0	195	2.01
307-131	1X3/4	50	0	195	3.08
307-211	1-1/2X1	25	0	195	7.45

HDPE Black 90° Street Ell

MBSP X FBSP

N.P.R.

M312-010	1	50	0	195	4.29
----------	---	----	---	-----	------



PVC White Riser Extension

MBSP X FBSP

SCH 40

334-007	3/4	50	400	195	2.31
334-010	1	50	0	195	2.88



PVC White Female Adapter

ASTM Socket x FBSP

SCH 40

335-010	1	50	0	195	1.24
335-012	1-1/4	25	0	195	1.92
335-015	1-1/2	25	0	195	2.19
335-020	2	10	0	195	2.95



PVC White Male Adapter

MBSP x ASTM Socket

SCH 40

336-005	1/2	50	300	195	.67
336-007	3/4	50	400	195	.75
336-010	1	50	300	195	1.35
336-012	1-1/4	25	200	195	1.64
336-015	1-1/2	25	0	195	2.19
336-020	2	25	0	195	2.88
336-030	3	10	0	195	12.44
336-131	1X3/4	50	400	195	4.14





Metric Fittings Product
PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray) & PVC Transition Unions

PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

PVC White Female Adapter

ASTM Spigot x FBSP

SCH 40

378-010	1	50	0	195	1.89
378-015	1-1/2	20	0	195	3.06
378-020	2	20	0	195	4.48



PVC Gray Tee

Socket x Socket x FBSP

SCH 40

302-010G	1	50	0	196	3.97
302-012G	1-1/4	25	0	196	6.29
302-211G	1-1/2X1	25	0	196	8.16
302-249G	2X1	10	0	196	10.28



PVC Gray Female Adapter

ASTM Socket x FBSP

SCH 40

335-010G	1	50	0	196	1.39
335-012G	1-1/4	25	0	196	2.12
335-015G	1-1/2	25	0	196	2.47
335-020G	2	10	0	196	3.31
335-025G	2-1/2	5	0	196	8.33



PVC Gray Male Adapter

MBSP x ASTM Socket

SCH 40

336-010G	1	50	300	196	1.48
336-012G	1-1/4	25	200	196	1.80
336-015G	1-1/2	25	0	196	2.47
336-020G	2	25	0	196	3.19
336-025G	2-1/2	5	0	196	9.44
336-030G	3	10	0	196	13.84
336-040G	4	5	0	196	17.63



PVC Gray Female Adapter

ASTM Spigot x FBSP

378-010G	1	50	0	196	1.99
378-015G	1-1/2	25	0	196	3.40
378-020G	2	20	0	196	5.00



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

PVC Gray Take-Off Adapter

Spigot x MBSP

SCH 40

361-005G	1/2	50	300	196	1.19
361-007G	3/4	50	400	196	1.35
361-010G	1	50	0	196	2.34
361-012G	1-1/4	25	100	196	2.88
361-015G	1-1/2	25	0	196	3.85
361-020G	2	25	0	196	4.75



PVC Gray Reducing Take-Off Adapter

Spigot/Socket x MBSP

SCH 40

361-168G	1-1/4X1X1	25	100	196	2.88
361-212G	1-1/2X1-1/4X1-1/4	25	0	196	3.85
361-251G	2X1-1/2X1-1/2	25	0	196	4.75



PVC Transition Unions

Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	12.84
8657-025	25 d X 3/4	10	60	197	16.36
8657-032	32 d X 1	10	40	197	18.66
8657-040	40 d X 1-1/4	10	0	197	37.06
8657-050	50 d X 1-1/2	10	0	197	41.97
8657-063	63 d X 2	5	0	197	56.93
8657-090	90 d X 3	5	0	197	105.96
8657-110	110 d X 4	4	0	197	147.59



Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	15.69
8658-025	25 d X 3/4	20	80	197	21.93
8658-032	32 d X 1	15	90	197	29.18
8658-040	40 d X 1-1/4	10	0	197	55.71
8658-050	50 d X 1-1/2	10	0	197	68.96
8658-063	63 d X 2	5	0	197	106.09
8658-090	90 d X 3	5	0	197	250.44
8658-110	110 d X 4	4	0	197	287.82

