



Metric Fittings Product
PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray) & PVC Transition Unions

PVC ASTM Schedule 40 Socket x BSP Adapter Fittings (White & Gray)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

PVC White Female Adapter

ASTM Spigot x FBSP



SCH 40

378-010	1	50	0	195	1.71
378-015	1-1/2	20	0	195	2.76
378-020	2	20	0	195	4.05

PVC Gray Tee

Socket x Socket x Fipt



SCH 40

302-010G	1	50	0	196	3.58
302-012G	1-1/4	25	0	196	5.68
302-211G	1-1/2X1	25	0	196	7.36
302-249G	2X1	10	0	196	9.28

PVC Gray Female Adapter

ASTM Socket x FBSP



SCH 40

335-010G	1	50	0	196	1.25
335-012G	1-1/4	25	0	196	1.91
335-015G	1-1/2	25	0	196	2.23
335-020G	2	10	0	196	2.98
335-025G	2-1/2	5	0	196	7.51

PVC Gray Male Adapter

MBSP x ASTM Socket



SCH 40

336-010G	1	50	300	196	1.34
336-012G	1-1/4	25	200	196	1.62
336-015G	1-1/2	25	0	196	2.23
336-020G	2	25	0	196	2.88
336-025G	2-1/2	5	0	196	8.52
336-030G	3	10	0	196	12.49
336-040G	4	5	0	196	15.91

PVC Gray Female Adapter

ASTM Spigot x FBSP



378-010G	1	50	0	196	1.80
378-015G	1-1/2	25	0	196	3.07
378-020G	2	20	0	196	4.51

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

PVC Gray Take-Off Adapter

Spigot x MBSP



SCH 40

361-005G	1/2	50	300	196	1.07
361-007G	3/4	50	400	196	1.22
361-010G	1	50	0	196	2.11
361-012G	1-1/4	25	100	196	2.60
361-015G	1-1/2	25	0	196	3.48
361-020G	2	25	0	196	4.28

PVC Gray Reducing Take-Off Adapter

Spigot/Socket x MBSP



SCH 40

361-168G	1-1/4X1X1	25	100	196	2.60
361-212G	1-1/2X1-1/4X1-1/4	25	0	196	3.48
361-251G	2X1-1/2X1-1/2	25	0	196	4.28

PVC Transition Unions

Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	11.59
8657-025	25 d X 3/4	10	60	197	14.76
8657-032	32 d X 1	10	40	197	16.84
8657-040	40 d X 1-1/4	10	0	197	33.45
8657-050	50 d X 1-1/2	10	0	197	37.88
8657-063	63 d X 2	5	0	197	51.38
8657-090	90 d X 3	5	0	197	95.63
8657-110	110 d X 4	4	0	197	133.20

Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	14.16
8658-025	25 d X 3/4	20	80	197	19.79
8658-032	32 d X 1	15	90	197	26.33
8658-040	40 d X 1-1/4	10	0	197	50.27
8658-050	50 d X 1-1/2	10	0	197	62.23
8658-063	63 d X 2	5	0	197	95.75
8658-090	90 d X 3	5	0	197	226.02
8658-110	110 d X 4	4	0	197	259.76

Metric Fittings Product
PVC Transition Unions



PVC Transition Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition DIN to ASTM/EPDM

DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8697-020	20 d X 1/2	20	240	197	11.44
8697-025	25 d X 3/4	10	60	197	14.58
8697-032	32d X 1	15	90	197	16.67
8697-040	40 d X 1-1/4	10	0	197	33.05
8697-050	50 d X 1-1/2	10	0	197	37.42
8697-063	63 d X 2	5	0	197	50.75
8697-090	90 d X 3	5	0	197	94.44
8697-110	110 d X 4	4	0	197	130.61

Union - Transition DIN to ASTM/EPDM

DIN (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8698-020	20 d X 1/2	20	160	197	13.96
8698-025	25 d X 3/4	20	80	197	19.54
8698-032	32 d X 1	15	90	197	25.99
8698-040	40 d X 1-1/4	10	0	197	49.41
8698-050	50 d X 1-1/2	10	0	197	61.45
8698-063	63 d X 2	5	0	197	94.57
8698-090	90 d X 3	5	0	197	223.19
8698-110	110 d X 4	4	0	197	256.26

Union -Transition JIS to ASTM/FKM

JIS (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8257-016	16 DN X 1/2	20	160	197	11.59
8257-020	20 DN X 3/4	10	60	197	14.76
8257-025	25 DN X1	15	90	197	16.84
8257-030	30 DN X 1-1/4	10	0	197	33.45
8257-040	40 DN X 1-1/2	10	0	197	37.88
8257-050	50 DN X 2	5	0	197	51.38
8257-075	75 DN X 3	5	0	197	95.63
8257-100	100 DN X 4	4	0	197	133.20

Union -Transition JIS to ASTM/FKM

JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8258-016	16 DN X 1/2	20	160	197	14.16
8258-020	20 DN X 3/4	20	80	197	19.79
8258-025	25 DN X 1	15	90	197	26.33
8258-030	30 DN X 1-1/4	10	0	197	50.27
8258-040	40 DN X 1-1/2	10	0	197	62.23

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union -Transition JIS to ASTM/FKM (continued)

JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal

8258-050	50 DN X 2	5	0	197	95.75
8258-075	75 DN X 3	5	0	197	226.02
8258-100	100 DN X 4	4	0	197	259.76

Union -Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	11.44
8297-020	20 DN X 3/4	20	80	197	14.58
8297-025	25 DN X 1	15	90	197	16.67
8297-030	30 DN X 1-1/4	10	0	197	33.05
8297-040	40 DN X 1-1/2	10	0	197	37.42
8297-050	50 DN X 2	5	0	197	50.75
8297-075	75 DN X 3	5	0	197	94.44
8297-100	100 DN X 4	4	0	197	130.61

Union -Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8298-016	16 DN X 1/2	20	160	197	13.96
8298-020	20 DN X 3/4	20	80	197	19.54
8298-025	25 DN X 1	15	90	197	25.99
8298-030	30 DN X 1-1/4	10	0	197	49.41
8298-040	40 DN X 1-1/2	10	0	197	61.45
8298-050	50 DN X 2	5	0	197	94.57
8298-075	75 DN X 3	5	0	197	223.19
8298-100	100 DN X 4	4	0	197	256.26

Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8359-005	1/2	20	160	197	14.16
8359-007	3/4	20	80	197	19.79
8359-010	1	15	90	197	26.33
8359-012	1-1/4	10	0	197	50.27
8359-015	1-1/2	10	0	197	62.23
8359-020	2	5	0	197	95.75
8359-030	3	5	0	197	226.02
8359-040	4	4	0	197	259.76

Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	13.49
8358-007	3/4	20	80	197	18.85



Metric Fittings Product

PVC Transition Unions & True Union Ball Valves (Regular Style)

PVC Transition Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition BSP to ASTM/FKM (continued)

BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal

8358-010	1	15	90	197	25.09
8358-012	1-1/4	10	0	197	47.87
8358-015	1-1/2	10	0	197	59.27
8358-020	2	5	0	197	91.20
8358-030	3	5	0	197	231.33
8358-040	4	4	0	197	271.85

Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8399-005	1/2	10	60	197	13.96
8399-007	3/4	20	80	197	19.54
8399-010	1	15	90	197	25.99
8399-012	1-1/4	10	0	197	49.65
8399-015	1-1/2	10	0	197	61.45
8399-020	2	5	0	197	94.57
8399-030	3	5	0	197	223.19
8399-040	4	4	0	197	256.26

Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	13.29
8398-007	3/4	10	60	197	18.61
8398-010	1	10	40	197	24.78
8398-012	1-1/4	5	20	197	47.28
8398-015	1-1/2	5	0	197	58.53
8398-020	2	5	0	197	94.03
8398-030	3	5	0	197	228.46
8398-040	4	4	0	197	267.20

True Union Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water

2-1/2" - 4" PN 10
PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Pressure Deratings Apply
Rated for Vacuum Service
PTFE Seats

PVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

DIN Socket EPDM

2324-025	75MM	1	0	238	340.84
----------	------	---	---	-----	--------

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

PVC True Union Ball Valve (Regular Style) (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

DIN Socket EPDM

2324-030	90MM	1	0	238	449.38
2324-040	110MM	1	0	238	759.25

PVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

DIN Socket FKM

2334-025	75MM	1	0	238	461.84
2334-030	90MM	1	0	238	499.32
2334-040	110MM	1	0	238	843.60

PVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

BSP Threaded EPDM

2325-025	2-1/2	1	0	238	340.84
2325-030	3	1	0	238	449.38
2325-040	4	1	0	238	759.25

PVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

BSP Threaded FKM

2335-025	2-1/2	1	0	238	461.84
2335-030	3	1	0	238	499.32
2335-040	4	1	0	238	843.60

CPVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

DIN Socket EPDM

2324-025C	75MM	1	0	239	570.54
2324-030C	90MM	1	0	239	667.11
2324-040C	110MM	1	0	239	1208.81

CPVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

DIN Socket FKM

2334-025C	75MM	1	0	239	633.91
2334-030C	90MM	1	0	239	741.25
2334-040C	110MM	1	0	239	1343.13

CPVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

BSP Threaded EPDM

2325-025C	2-1/2	1	0	239	570.68
2325-030C	3	1	0	239	667.11
2325-040C	4	1	0	239	1208.81

CPVC True Union Ball Valve (Regular Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

BSP Threaded FKM

2335-025C	2-1/2	1	0	239	633.91
2335-030C	3	1	0	239	741.25
2335-040C	4	1	0	239	1343.13