

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Reducer Bushing

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Reducer Bushing (T.T.) Flush Style

Mipt x Fipt



839-041C	1/4X1/8	25	500	090	22.45
839-052C	3/8X1/4	50	450	090	22.45
839-072C	1/2X1/4	50	300	090	22.45
839-073C	1/2X3/8	50	300	090	22.45
839-098C	3/4X1/4	50	300	090	24.76
839-099C	3/4X3/8	50	300	090	24.76
839-101C	3/4X1/2	50	300	090	10.65
839-128C	1X1/4	25	150	090	26.74
839-129C	1X3/8	50	300	090	26.74
839-130C	1X1/2	50	300	090	17.94
839-131C	1X3/4	50	700	090	17.94
839-166C	1-1/4X1/2	25	150	090	35.63
839-167C	1-1/4X3/4	25	150	090	35.63
839-168C	1-1/4X1	25	300	090	35.36
839-209C	1-1/2X1/2	25	300	090	42.92
839-210C	1-1/2X3/4	25	300	090	42.92
839-211C	1-1/2X1	25	300	090	42.92
839-212C	1-1/2X1-1/4	25	300	090	42.58
839-247C	2X1/2	10	60	090	47.45
839-248C	2X3/4	10	60	090	47.45
839-249C	2X1	10	60	090	47.45
839-250C	2X1-1/4	10	60	090	47.45
839-251C	2X1-1/2	10	60	090	42.58
839-292C	2-1/2X2	10	40	090	114.09
839-337C	3X1-1/2	10	0	090	153.49
839-338C	3X2	10	0	090	153.49
839-339C	3X2-1/2	10	0	090	153.49
839-420C	4X2	6	0	090	263.75
839-422C	4X3	6	0	090	263.75
839-530C	6X3	5	0	090	952.13
839-532C	6X4	5	0	090	952.13

Reducer Bushing - Special Reinforced Reducing Flush Style

Mipt x SR Fipt - Stainless Steel Collar



839-209CSR	1-1/2X1/2	25	300	096	25.78
839-210CSR	1-1/2X3/4	25	300	096	25.78
839-247CSR	2X1/2	10	60	096	28.49
839-248CSR	2X3/4	10	60	096	28.49
839-249CSR	2X1	10	120	096	28.49
839-420CSR	4X2	6	0	096	158.23

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Cap

Socket



847-002C	1/4	25	450	090	12.81
847-003C	3/8	25	450	090	12.81
847-005C	1/2	25	150	090	11.59
847-007C	3/4	25	300	090	16.52
847-010C	1	15	90	090	29.22
847-012C	1-1/4	10	60	090	31.97
847-015C	1-1/2	10	60	090	31.97
847-020C	2	10	80	090	33.72
847-025C	2-1/2	5	40	090	113.51
847-030C	3	5	0	090	124.41
847-040C	4	5	0	090	126.47
847-050CF	5	1	6	097	238.51
847-060C	6	4	0	090	418.48
847-080C	8	3	0	090	1269.96
847-100CF	10	1	5	097	1060.99
847-120CF	12	1	4	097	1162.82
847-140CF	14	1	2	097	3566.78
847-160CF	16	1	2	097	5245.84
847-180CF	18	1	0	097	6467.74
847-200CF	20	1	0	097	8706.36
847-240CF	24	1	0	097	16615.75

Cap

Fipt



848-002C	1/4	25	450	090	14.99
848-003C	3/8	25	450	090	14.99
848-005C	1/2	25	150	090	12.87
848-007C	3/4	25	300	090	21.31
848-010C	1	15	90	090	29.84
848-012C	1-1/4	10	60	090	53.21
848-015C	1-1/2	10	120	090	54.52
848-020C	2	10	80	090	78.53
848-025C	2-1/2	5	40	090	181.71
848-030C	3	5	0	090	238.38
848-040C	4	5	0	090	346.28
848-060CF	6	1	4	097	489.92
848-080CF	8	1	0	097	531.60
848-100CF	10	1	2	097	2761.68
848-120CF	12	1	0	097	1890.72

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar



848-002CSR	1/4	25	500	096	8.23
848-003CSR	3/8	25	450	096	8.23



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap - Special Reinforced (continued)					
SR Fipt - Stainless Steel Collar					
848-005CSR	1/2	50	300	096	7.36
848-007CSR	3/4	25	300	096	12.83
848-030CSR	3	5	0	096	143.22

Plugs

Plug

Spigot



849-005C	1/2	50	300	090	14.76
849-007C	3/4	50	300	090	18.20
849-010C	1	50	200	090	20.55
849-012C	1-1/4	25	100	090	26.19
849-015C	1-1/2	10	120	090	28.75
849-020C	2	10	120	090	38.51
849-025CF ⁴	2-1/2	1	8	097	45.67
849-030CF ⁴	3	1	4	097	105.02
849-040CF ⁴	4	1	4	097	129.60
849-060CF ⁴	6	1	6	097	160.89
849-080CF ⁴	8	1	6	097	432.17
849-100CF ⁴	10	1	2	097	859.85
849-120CF ⁴	12	1	0	097	1666.53

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt



850-002C	1/4	50	900	090	12.05
850-003C	3/8	50	450	090	12.05
850-005C	1/2	50	500	090	10.47
850-007C	3/4	50	300	090	13.26
850-010C	1	25	175	090	21.82
850-012C	1-1/4	25	150	090	24.80
850-015C	1-1/2	25	150	090	27.34
850-020C	2	10	120	090	37.22
850-025C	2-1/2	5	30	090	63.18
850-030C	3	5	40	090	67.65
850-040C	4	5	0	090	120.05
850-060C	6	6	0	090	168.59
850-060CF ⁴	6	1	2	097	435.32
850-080C	8	6	0	090	299.58
850-080CF ⁴	8	1	2	097	835.84
850-100CF ⁴	10	1	3	097	1206.41
850-120CF ⁴	12	1	0	097	1840.17

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	19.14
875-007C	3/4	25	0	090	19.77
875-010C	1	20	0	090	33.31
875-012C	1-1/4	20	0	090	50.45
875-015C	1-1/2	20	0	090	54.23
875-020C	2	10	0	090	132.79
875-025C	2-1/2	6	0	090	423.13
875-030C	3	5	0	090	654.76
875-040C	4	4	0	090	692.24
875-060C	6	3	0	090	947.44
875-080C	8	1	0	090	1618.02
875-080CF ²	8	1	0	097	1415.19
875-100CF ²	10	1	0	097	2431.12
875-120CF ²	12	1	0	097	3386.20
875-140CF ²	14	1	0	097	11772.94
875-160CF ²	16	1	0	097	14767.12
875-180CF ²	18	1	0	097	21428.80
875-200CF ²	20	1	0	097	24888.44
875-240CF ²	24	1	0	097	31799.86

² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C ¹	3/4X1/2	25	0	090	28.26
875-130C ¹	1X1/2	20	0	090	46.57
875-131C ¹	1X3/4	20	0	090	46.57
875-166C ¹	1-1/4X1/2	20	0	090	84.88
875-167C ¹	1-1/4X3/4	20	0	090	84.88
875-168C ¹	1-1/4X1	20	0	090	84.88
875-209C ¹	1-1/2X1/2	20	0	090	93.11
875-210C ¹	1-1/2X3/4	20	0	090	93.11
875-211C ¹	1-1/2X1	20	0	090	93.11
875-212C ¹	1-1/2X1-1/4	20	0	090	93.11
875-247C ¹	2X1/2	10	0	090	184.23
875-248C ¹	2X3/4	10	0	090	184.23