



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**

**Reducer Bushing**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Reducer Bushing Flush Style (continued)</b>					
<b>Spigot x Fipt</b>					
838-251C	2X1-1/2	10	120	090	57.02
838-287C	2-1/2X1/2	10	0	090	91.22
838-288C	2-1/2X3/4	10	40	090	91.22
838-289C	2-1/2X1	10	40	090	91.22
838-290C	2-1/2X1-1/4	10	0	090	91.22
838-291C	2-1/2X1-1/2	10	40	090	90.60
838-292C	2-1/2X2	10	40	090	90.60
838-334C	3X3/4	10	0	090	241.38
838-335C	3X1	10	0	090	241.38
838-336C	3X1-1/4	10	0	090	211.16
838-337C	3X1-1/2	10	0	090	211.16
838-338C	3X2	10	0	090	201.96
838-339C	3X2-1/2	10	0	090	203.60
838-420C	4X2	6	0	090	411.54
838-421C	4X2-1/2	6	0	090	411.54
838-422C	4X3	6	0	090	411.54
838-528C	6X2	5	0	090	829.71
838-530C	6X3	5	0	090	829.71
838-532C	6X4	5	0	090	829.71



**Reducer Bushing - Special Reinforced**

**Spigot x SR Fipt - Stainless Steel Collar**

838-128CSR	1X1/4	25	150	096	14.12
838-207CSR	1-1/2X1/4	25	200	096	23.87
838-209CSR	1-1/2X1/2	10	120	096	24.88
838-210CSR	1-1/2X3/4	10	120	096	24.88
838-247CSR	2X1/2	10	80	096	34.19
838-248CSR	2X3/4	10	80	096	34.19
838-249CSR	2X1	10	120	096	34.19
838-334CSR	3X3/4	10	0	096	144.80
838-335CSR	3X1	10	0	096	144.80
838-336CSR	3X1-1/4	10	0	096	144.80
838-337CSR	3X1-1/2	10	0	096	144.80
838-528CSR	6X2	5	0	096	497.81
838-530CSR	6X3	5	0	096	497.81
838-532CSR	6X4	5	0	096	527.48



**Reducer Bushing (T.T.) Flush Style**

**Mipt x Fipt**

839-041C	1/4X1/8	25	500	090	21.33
839-052C	3/8X1/4	50	450	090	21.33
839-072C	1/2X1/4	50	300	090	21.33
839-073C	1/2X3/8	50	300	090	21.33
839-098C	3/4X1/4	50	300	090	23.52
839-099C	3/4X3/8	50	300	090	23.52
839-101C	3/4X1/2	50	300	090	10.12
839-128C	1X1/4	25	150	090	25.40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Reducer Bushing (T.T.) Flush Style (continued)**

**Mipt x Fipt**

839-129C	1X3/8	50	300	090	25.40
839-130C	1X1/2	50	300	090	17.04
839-131C	1X3/4	50	700	090	17.04
839-166C	1-1/4X1/2	25	150	090	33.85
839-167C	1-1/4X3/4	25	150	090	33.85
839-168C	1-1/4X1	25	300	090	33.59
839-209C	1-1/2X1/2	25	300	090	40.77
839-210C	1-1/2X3/4	25	300	090	40.77
839-211C	1-1/2X1	25	300	090	40.77
839-212C	1-1/2X1-1/4	25	300	090	40.45
839-247C	2X1/2	10	60	090	45.08
839-248C	2X3/4	10	60	090	45.08
839-249C	2X1	10	60	090	45.08
839-250C	2X1-1/4	10	60	090	45.08
839-251C	2X1-1/2	10	60	090	40.45
839-292C	2-1/2X2	10	40	090	108.39
839-337C	3X1-1/2	10	0	090	145.82
839-338C	3X2	10	0	090	145.82
839-339C	3X2-1/2	10	0	090	145.82
839-420C	4X2	6	0	090	250.56
839-422C	4X3	6	0	090	250.56
839-530C	6X3	5	0	090	904.52
839-532C	6X4	5	0	090	904.52

**Reducer Bushing - Special Reinforced Reducing Flush Style**

**Mipt x SR Fipt - Stainless Steel Collar**

839-209CSR	1-1/2X1/2	25	300	096	24.49
839-210CSR	1-1/2X3/4	25	300	096	24.49
839-247CSR	2X1/2	10	60	096	27.07
839-248CSR	2X3/4	10	60	096	27.07
839-249CSR	2X1	10	120	096	27.07
839-420CSR	4X2	6	0	096	150.32

**Caps**

**Cap**

**Socket**

847-002C	1/4	25	450	090	12.17
847-003C	3/8	25	450	090	12.17
847-005C	1/2	25	150	090	11.01
847-007C	3/4	25	300	090	15.69
847-010C	1	15	90	090	27.76
847-012C	1-1/4	10	60	090	30.37
847-015C	1-1/2	10	60	090	30.37
847-020C	2	10	80	090	32.03
847-025C	2-1/2	5	40	090	107.83
847-030C	3	5	0	090	118.19
847-040C	4	5	0	090	120.15
847-050CF	5	1	6	097	226.58

**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**



**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap (continued)</b>					
<b>Socket</b>					
847-060C	6	4	0	090	397.56
847-080C	8	3	0	090	1206.46
847-100CF	10	1	5	097	1007.94
847-120CF	12	1	4	097	1104.68
847-140CF	14	1	2	097	3388.44
847-160CF	16	1	2	097	4983.55
847-180CF	18	1	0	097	6144.35
847-200CF	20	1	0	097	8271.04
847-240CF	24	1	0	097	15784.96

**Cap**

**Fipt**

848-002C	1/4	25	450	090	14.24
848-003C	3/8	25	450	090	14.24
848-005C	1/2	25	150	090	12.23
848-007C	3/4	25	300	090	20.24
848-010C	1	15	90	090	28.35
848-012C	1-1/4	10	60	090	50.55
848-015C	1-1/2	10	120	090	51.79
848-020C	2	10	80	090	74.60
848-025C	2-1/2	5	40	090	172.62
848-030C	3	5	0	090	226.46
848-040C	4	5	0	090	328.97
848-060CF	6	1	4	097	465.42
848-080CF	8	1	0	097	505.02

**Cap - Special Reinforced**

**SR Fipt - Stainless Steel Collar**

848-002CSR	1/4	25	500	096	7.82
848-003CSR	3/8	25	450	096	7.82
848-005CSR	1/2	50	300	096	6.99
848-007CSR	3/4	25	300	096	12.19
848-030CSR	3	5	0	096	136.06

**Plugs**

**Plug**

**Spigot**

849-005C	1/2	50	300	090	14.02
849-007C	3/4	50	300	090	17.29
849-010C	1	50	200	090	19.52
849-012C	1-1/4	25	100	090	24.88
849-015C	1-1/2	10	120	090	27.31
849-020C	2	10	120	090	36.58

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Plug (continued)**

**Spigot**

849-025CF <sup>4</sup>	2-1/2	1	8	097	43.39
849-030CF <sup>4</sup>	3	1	4	097	99.77
849-040CF <sup>4</sup>	4	1	4	097	123.12
849-060CF <sup>4</sup>	6	1	6	097	152.85
849-080CF <sup>4</sup>	8	1	6	097	410.56
849-100CF <sup>4</sup>	10	1	2	097	816.86
849-120CF <sup>4</sup>	12	1	0	097	1583.20

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Plug**

**Mipt**

850-002C	1/4	50	900	090	11.45
850-003C	3/8	50	450	090	11.45
850-005C	1/2	50	500	090	9.95
850-007C	3/4	50	300	090	12.60
850-010C	1	25	175	090	20.73
850-012C	1-1/4	25	150	090	23.56
850-015C	1-1/2	25	150	090	25.97
850-020C	2	10	120	090	35.36
850-025C	2-1/2	5	30	090	60.02
850-030C	3	5	40	090	64.27
850-040C	4	5	0	090	114.05
850-060C	6	6	0	090	160.16
850-060CF <sup>4</sup>	6	1	2	097	413.55
850-080C	8	4	0	090	284.60
850-080CF <sup>4</sup>	8	1	2	097	794.05
850-100CF <sup>4</sup>	10	1	3	097	1146.09
850-120CF <sup>4</sup>	12	1	0	097	1748.16

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	18.18
875-007C	3/4	25	0	090	18.78
875-010C	1	20	0	090	31.64
875-012C	1-1/4	20	0	090	47.93
875-015C	1-1/2	20	0	090	51.52
875-020C	2	10	0	090	126.15
875-025C	2-1/2	6	0	090	401.97
875-030C	3	5	0	090	622.02
875-040C	4	4	0	090	657.63