



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**

**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap - Special Reinforced (continued)</b>					
<b>SR Fipt - Stainless Steel Collar</b>					
848-005CSR	1/2	50	300	096	7.36
848-007CSR	3/4	25	300	096	12.83
848-030CSR	3	5	0	096	143.22

**Plugs**

**Plug**

**Spigot**



849-005C	1/2	50	300	090	14.76
849-007C	3/4	50	300	090	18.20
849-010C	1	50	200	090	20.55
849-012C	1-1/4	25	100	090	26.19
849-015C	1-1/2	10	120	090	28.75
849-020C	2	10	120	090	38.51
849-025CF <sup>4</sup>	2-1/2	1	8	097	45.67
849-030CF <sup>4</sup>	3	1	4	097	105.02
849-040CF <sup>4</sup>	4	1	4	097	129.60
849-060CF <sup>4</sup>	6	1	6	097	160.89
849-080CF <sup>4</sup>	8	1	6	097	432.17
849-100CF <sup>4</sup>	10	1	2	097	859.85
849-120CF <sup>4</sup>	12	1	0	097	1666.53

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Plug**

**Mipt**



850-002C	1/4	50	900	090	12.05
850-003C	3/8	50	450	090	12.05
850-005C	1/2	50	500	090	10.47
850-007C	3/4	50	300	090	13.26
850-010C	1	25	175	090	21.82
850-012C	1-1/4	25	150	090	24.80
850-015C	1-1/2	25	150	090	27.34
850-020C	2	10	120	090	37.22
850-025C	2-1/2	5	30	090	63.18
850-030C	3	5	40	090	67.65
850-040C	4	5	0	090	120.05
850-060C	6	6	0	090	168.59
850-060CF <sup>4</sup>	6	1	2	097	435.32
850-080C	8	6	0	090	299.58
850-080CF <sup>4</sup>	8	1	2	097	835.84
850-100CF <sup>4</sup>	10	1	3	097	1206.41
850-120CF <sup>4</sup>	12	1	0	097	1840.17

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	19.14
875-007C	3/4	25	0	090	19.77
875-010C	1	20	0	090	33.31
875-012C	1-1/4	20	0	090	50.45
875-015C	1-1/2	20	0	090	54.23
875-020C	2	10	0	090	132.79
875-025C	2-1/2	6	0	090	423.13
875-030C	3	5	0	090	654.76
875-040C	4	4	0	090	692.24
875-060C	6	3	0	090	947.44
875-080C	8	1	0	090	1618.02
875-080CF <sup>2</sup>	8	1	0	097	1415.19
875-100CF <sup>2</sup>	10	1	0	097	2431.12
875-120CF <sup>2</sup>	12	1	0	097	3386.20
875-140CF <sup>2</sup>	14	1	0	097	11772.94
875-160CF <sup>2</sup>	16	1	0	097	14767.12
875-180CF <sup>2</sup>	18	1	0	097	21428.80
875-200CF <sup>2</sup>	20	1	0	097	24888.44
875-240CF <sup>2</sup>	24	1	0	097	31799.86

<sup>2</sup> Fiberglass reinforced

**Wye - Reducing**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C <sup>1</sup>	3/4X1/2	25	0	090	28.26
875-130C <sup>1</sup>	1X1/2	20	0	090	46.57
875-131C <sup>1</sup>	1X3/4	20	0	090	46.57
875-166C <sup>1</sup>	1-1/4X1/2	20	0	090	84.88
875-167C <sup>1</sup>	1-1/4X3/4	20	0	090	84.88
875-168C <sup>1</sup>	1-1/4X1	20	0	090	84.88
875-209C <sup>1</sup>	1-1/2X1/2	20	0	090	93.11
875-210C <sup>1</sup>	1-1/2X3/4	20	0	090	93.11
875-211C <sup>1</sup>	1-1/2X1	20	0	090	93.11
875-212C <sup>1</sup>	1-1/2X1-1/4	20	0	090	93.11
875-247C <sup>1</sup>	2X1/2	10	0	090	184.23
875-248C <sup>1</sup>	2X3/4	10	0	090	184.23