



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**

**Caps**

| Part Number            | Size | Std Pk | Mstr Ctn | Prod Code | MSRP     |
|------------------------|------|--------|----------|-----------|----------|
| <b>Cap (continued)</b> |      |        |          |           |          |
| <b>Socket</b>          |      |        |          |           |          |
| 847-060C               | 6    | 4      | 0        | 090       | 377.68   |
| 847-080C               | 8    | 3      | 0        | 090       | 1146.14  |
| 847-100CF              | 10   | 1      | 5        | 097       | 957.54   |
| 847-120CF              | 12   | 1      | 4        | 097       | 1049.45  |
| 847-140CF              | 14   | 1      | 2        | 097       | 3219.02  |
| 847-160CF              | 16   | 1      | 2        | 097       | 4734.37  |
| 847-180CF              | 18   | 1      | 0        | 097       | 5837.13  |
| 847-200CF              | 20   | 1      | 0        | 097       | 7857.49  |
| 847-240CF              | 24   | 1      | 0        | 097       | 14995.71 |

**Cap**

**Fipt**

|           |       |    |     |     |        |
|-----------|-------|----|-----|-----|--------|
| 848-002C  | 1/4   | 25 | 450 | 090 | 13.53  |
| 848-003C  | 3/8   | 25 | 450 | 090 | 13.53  |
| 848-005C  | 1/2   | 25 | 150 | 090 | 11.62  |
| 848-007C  | 3/4   | 25 | 300 | 090 | 19.23  |
| 848-010C  | 1     | 15 | 90  | 090 | 26.93  |
| 848-012C  | 1-1/4 | 10 | 60  | 090 | 48.02  |
| 848-015C  | 1-1/2 | 10 | 120 | 090 | 49.20  |
| 848-020C  | 2     | 10 | 80  | 090 | 70.87  |
| 848-025C  | 2-1/2 | 5  | 40  | 090 | 163.99 |
| 848-030C  | 3     | 5  | 0   | 090 | 215.14 |
| 848-040C  | 4     | 5  | 0   | 090 | 312.52 |
| 848-060CF | 6     | 1  | 4   | 097 | 442.15 |
| 848-080CF | 8     | 1  | 0   | 097 | 479.77 |

**Cap - Special Reinforced**

**SR Fipt - Stainless Steel Collar**

|            |     |    |     |     |        |
|------------|-----|----|-----|-----|--------|
| 848-002CSR | 1/4 | 25 | 500 | 096 | 7.43   |
| 848-003CSR | 3/8 | 25 | 450 | 096 | 7.43   |
| 848-005CSR | 1/2 | 50 | 300 | 096 | 6.64   |
| 848-007CSR | 3/4 | 25 | 300 | 096 | 11.58  |
| 848-030CSR | 3   | 5  | 0   | 096 | 129.26 |

**Plugs**

**Plug**

**Spigot**

|          |       |    |     |     |       |
|----------|-------|----|-----|-----|-------|
| 849-005C | 1/2   | 50 | 300 | 090 | 13.32 |
| 849-007C | 3/4   | 50 | 300 | 090 | 16.43 |
| 849-010C | 1     | 50 | 200 | 090 | 18.54 |
| 849-012C | 1-1/4 | 25 | 100 | 090 | 23.64 |
| 849-015C | 1-1/2 | 10 | 120 | 090 | 25.94 |
| 849-020C | 2     | 10 | 120 | 090 | 34.75 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

**Plug (continued)**

**Spigot**

|                        |       |   |   |     |         |
|------------------------|-------|---|---|-----|---------|
| 849-025CF <sup>4</sup> | 2-1/2 | 1 | 8 | 097 | 41.22   |
| 849-030CF <sup>4</sup> | 3     | 1 | 4 | 097 | 94.78   |
| 849-040CF <sup>4</sup> | 4     | 1 | 4 | 097 | 116.96  |
| 849-060CF <sup>4</sup> | 6     | 1 | 6 | 097 | 145.21  |
| 849-080CF <sup>4</sup> | 8     | 1 | 6 | 097 | 390.03  |
| 849-100CF <sup>4</sup> | 10    | 1 | 2 | 097 | 776.02  |
| 849-120CF <sup>4</sup> | 12    | 1 | 0 | 097 | 1504.04 |

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Plug**

**Mipt**

|                        |       |    |     |     |         |
|------------------------|-------|----|-----|-----|---------|
| 850-002C               | 1/4   | 50 | 900 | 090 | 10.88   |
| 850-003C               | 3/8   | 50 | 450 | 090 | 10.88   |
| 850-005C               | 1/2   | 50 | 500 | 090 | 9.45    |
| 850-007C               | 3/4   | 50 | 300 | 090 | 11.97   |
| 850-010C               | 1     | 25 | 175 | 090 | 19.69   |
| 850-012C               | 1-1/4 | 25 | 150 | 090 | 22.38   |
| 850-015C               | 1-1/2 | 25 | 150 | 090 | 24.67   |
| 850-020C               | 2     | 10 | 120 | 090 | 33.59   |
| 850-025C               | 2-1/2 | 5  | 30  | 090 | 57.02   |
| 850-030C               | 3     | 5  | 40  | 090 | 61.06   |
| 850-040C               | 4     | 5  | 0   | 090 | 108.35  |
| 850-060C               | 6     | 6  | 0   | 090 | 152.15  |
| 850-060CF <sup>4</sup> | 6     | 1  | 2   | 097 | 392.87  |
| 850-080C               | 8     | 4  | 0   | 090 | 270.37  |
| 850-080CF <sup>4</sup> | 8     | 1  | 2   | 097 | 754.35  |
| 850-100CF <sup>4</sup> | 10    | 1  | 3   | 097 | 1088.79 |
| 850-120CF <sup>4</sup> | 12    | 1  | 0   | 097 | 1660.75 |

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

|          |       |    |     |     |        |
|----------|-------|----|-----|-----|--------|
| 875-005C | 1/2   | 25 | 100 | 090 | 17.27  |
| 875-007C | 3/4   | 25 | 0   | 090 | 17.84  |
| 875-010C | 1     | 20 | 0   | 090 | 30.06  |
| 875-012C | 1-1/4 | 20 | 0   | 090 | 45.53  |
| 875-015C | 1-1/2 | 20 | 0   | 090 | 48.94  |
| 875-020C | 2     | 10 | 0   | 090 | 119.84 |
| 875-025C | 2-1/2 | 6  | 0   | 090 | 381.87 |
| 875-030C | 3     | 5  | 0   | 090 | 590.92 |
| 875-040C | 4     | 4  | 0   | 090 | 624.75 |