

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Socket					
847-060C	6	4	0	090	397.56
847-080C	8	3	0	090	1206.46
847-100CF	10	1	5	097	1007.94
847-120CF	12	1	4	097	1104.68
847-140CF	14	1	2	097	3388.44
847-160CF	16	1	2	097	4983.55
847-180CF	18	1	0	097	6144.35
847-200CF	20	1	0	097	8271.04
847-240CF	24	1	0	097	15784.96



Cap

Fipt

848-002C	1/4	25	450	090	14.24
848-003C	3/8	25	450	090	14.24
848-005C	1/2	25	150	090	12.23
848-007C	3/4	25	300	090	20.24
848-010C	1	15	90	090	28.35
848-012C	1-1/4	10	60	090	50.55
848-015C	1-1/2	10	120	090	51.79
848-020C	2	10	80	090	74.60
848-025C	2-1/2	5	40	090	172.62
848-030C	3	5	0	090	226.46
848-040C	4	5	0	090	328.97
848-060CF	6	1	4	097	465.42
848-080CF	8	1	0	097	505.02



Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	7.82
848-003CSR	3/8	25	450	096	7.82
848-005CSR	1/2	50	300	096	6.99
848-007CSR	3/4	25	300	096	12.19
848-030CSR	3	5	0	096	136.06

Plugs

Plug

Spigot

849-005C	1/2	50	300	090	14.02
849-007C	3/4	50	300	090	17.29
849-010C	1	50	200	090	19.52
849-012C	1-1/4	25	100	090	24.88
849-015C	1-1/2	10	120	090	27.31
849-020C	2	10	120	090	36.58



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug (continued)

Spigot

849-025CF ⁴	2-1/2	1	8	097	43.39
849-030CF ⁴	3	1	4	097	99.77
849-040CF ⁴	4	1	4	097	123.12
849-060CF ⁴	6	1	6	097	152.85
849-080CF ⁴	8	1	6	097	410.56
849-100CF ⁴	10	1	2	097	816.86
849-120CF ⁴	12	1	0	097	1583.20

⁴ Plug fabricated using Cap and pipe spigot.



Plug

Mipt

850-002C	1/4	50	900	090	11.45
850-003C	3/8	50	450	090	11.45
850-005C	1/2	50	500	090	9.95
850-007C	3/4	50	300	090	12.60
850-010C	1	25	175	090	20.73
850-012C	1-1/4	25	150	090	23.56
850-015C	1-1/2	25	150	090	25.97
850-020C	2	10	120	090	35.36
850-025C	2-1/2	5	30	090	60.02
850-030C	3	5	40	090	64.27
850-040C	4	5	0	090	114.05
850-060C	6	6	0	090	160.16
850-060CF ⁴	6	1	2	097	413.55
850-080C	8	6	0	090	284.60
850-080CF ⁴	8	1	2	097	794.05
850-100CF ⁴	10	1	3	097	1146.09
850-120CF ⁴	12	1	0	097	1748.16

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)



875-005C	1/2	25	100	090	18.18
875-007C	3/4	25	0	090	18.78
875-010C	1	20	0	090	31.64
875-012C	1-1/4	20	0	090	47.93
875-015C	1-1/2	20	0	090	51.52
875-020C	2	10	0	090	126.15
875-025C	2-1/2	6	0	090	401.97
875-030C	3	5	0	090	622.02
875-040C	4	4	0	090	657.63