



Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002C	1/4	25	150	101	56.37
8170-003C	3/8	25	150	101	56.37
8170-005C	1/2	25	0	101	56.37
8170-007C	3/4	25	0	101	67.06
8170-010C	1	25	0	101	75.27
8170-012C	1-1/4	20	0	101	96.00
8170-015C	1-1/2	20	0	101	104.54
8170-020C	2	15	0	101	147.57
8170-025C	2-1/2	4	0	101	216.88
8170-030C	3	4	0	101	258.16
8170-040C	4	2	0	101	430.23
8170-060C	6	1	0	101	1183.16
8170-080C	8	1	0	101	2629.05



Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002C	1/4	25	150	101	64.12
8170E-003C	3/8	25	150	101	64.12
8170E-005C	1/2	25	0	101	64.12
8170E-007C	3/4	25	0	101	71.96
8170E-010C	1	25	0	101	83.56
8170E-012C	1-1/4	20	0	101	105.74
8170E-015C	1-1/2	20	0	101	110.95
8170E-020C	2	15	0	101	159.96
8170E-025C	2-1/2	4	0	101	227.20
8170E-030C	3	4	0	101	270.51
8170E-040C	4	2	0	101	449.02
8170E-060C	6	1	0	101	1232.45
8170E-080C	8	1	0	101	2705.91



Tank Adapters, CPVC New Style Standard with FKM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002C	1/4	25	150	101	84.06
8170V-003C	3/8	25	150	101	84.06
8170V-005C	1/2	25	0	101	84.06
8170V-007C	3/4	25	0	101	96.71
8170V-010C	1	25	0	101	111.95
8170V-012C	1-1/4	20	0	101	137.55
8170V-015C	1-1/2	20	0	101	143.39
8170V-020C	2	15	0	101	217.08
8170V-025C	2-1/2	4	0	101	312.45



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

(continued)

Socket x Socket

8170V-030C	3	4	0	101	371.98
8170V-040C	4	2	0	101	823.91
8170V-060C	6	1	0	101	2070.59
8170V-080C	8	1	0	101	4843.64

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002C	1/4	25	150	101	56.37
8171-003C	3/8	25	200	101	56.37
8171-005C	1/2	25	0	101	56.37
8171-007C	3/4	25	0	101	67.06
8171-010C	1	25	0	101	75.27
8171-012C	1-1/4	20	0	101	96.00
8171-015C	1-1/2	20	0	101	104.54
8171-020C	2	15	0	101	147.57
8171-025C	2-1/2	4	0	101	216.88
8171-030C	3	4	0	101	258.16
8171-040C	4	2	0	101	430.23
8171-060C	6	1	0	101	1183.16



Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002C	1/4	25	150	101	64.12
8171E-003C	3/8	25	200	101	64.12
8171E-005C	1/2	25	0	101	64.12
8171E-007C	3/4	25	0	101	71.96
8171E-010C	1	25	0	101	83.56
8171E-012C	1-1/4	20	0	101	105.74
8171E-015C	1-1/2	20	0	101	110.95
8171E-020C	2	15	0	101	159.96
8171E-025C	2-1/2	4	0	101	227.20
8171E-030C	3	4	0	101	270.51
8171E-040C	4	2	0	101	449.02
8171E-060C	6	1	0	101	1232.44



Tank Adapters, CPVC New Style Standard with FKM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002C	1/4	25	150	101	84.06
8171V-003C	3/8	25	200	101	84.06
8171V-005C	1/2	25	0	101	84.06
8171V-007C	3/4	25	0	101	96.71
8171V-010C	1	25	0	101	111.95
8171V-012C	1-1/4	20	0	101	137.55



Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

(continued)

Socket x Fipt

8171V-015C	1-1/2	20	0	101	143.39
8171V-020C	2	15	0	101	217.08
8171V-025C	2-1/2	4	0	101	312.49
8171V-030C	3	4	0	101	371.98
8171V-040C	4	2	0	101	823.91
8171V-060C	6	1	0	101	2070.59

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	58.08
8171-003CSR	3/8	25	200	101	58.08
8171-005CSR	1/2	25	0	101	58.08
8171-007CSR	3/4	25	0	101	69.52
8171-010CSR	1	25	0	101	78.64
8171-012CSR	1-1/4	20	0	101	101.44
8171-015CSR	1-1/2	20	0	101	113.88
8171-020CSR	2	15	0	101	157.48
8171-025CSR	2-1/2	4	0	101	239.56
8171-030CSR	3	4	0	101	285.13
8171-040CSR	4	2	0	101	458.24
8171-060CSR	6	1	0	101	1210.26

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	65.83
8171E-003CSR	3/8	25	200	101	65.83
8171E-005CSR	1/2	25	0	101	65.83
8171E-007CSR	3/4	25	0	101	74.40
8171E-010CSR	1	25	0	101	88.96
8171E-012CSR	1-1/4	20	0	101	111.18
8171E-015CSR	1-1/2	20	0	101	120.28
8171E-020CSR	2	15	0	101	170.04
8171E-025CSR	2-1/2	4	0	101	249.88
8171E-030CSR	3	4	0	101	297.47
8171E-040CSR	4	2	0	101	476.96
8171E-060CSR	6	2	0	101	1259.58

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	85.77
8171V-003CSR	3/8	25	200	101	85.77

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-005CSR	1/2	25	0	101	85.77
8171V-007CSR	3/4	25	0	101	99.15
8171V-010CSR	1	25	0	101	115.34
8171V-012CSR	1-1/4	20	0	101	142.98
8171V-015CSR	1-1/2	20	0	101	152.68
8171V-020CSR	2	15	0	101	227.36
8171V-025CSR	2-1/2	4	0	101	335.04
8171V-030CSR	3	4	0	101	398.95
8171V-040CSR	4	2	0	101	851.85
8171V-060CSR	6	2	0	101	2103.19

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002C	1/4	25	150	101	75.27
8172-003C	3/8	25	200	101	75.27
8172-005C	1/2	25	0	101	75.27
8172-007C	3/4	25	0	101	86.91
8172-010C	1	25	0	101	95.07
8172-012C	1-1/4	20	0	101	134.22
8172-015C	1-1/2	20	0	101	146.71
8172-020C	2	15	0	101	182.85
8172-025C	2-1/2	4	0	101	257.32
8172-030C	3	4	0	101	306.32
8172-040C	4	2	0	101	483.99
8172-060C	6	1	0	101	1344.49

Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002C	1/4	25	150	101	78.23
8172E-003C	3/8	25	200	101	78.23
8172E-005C	1/2	25	0	101	78.23
8172E-007C	3/4	25	0	101	92.23
8172E-010C	1	25	0	101	99.38
8172E-012C	1-1/4	20	0	101	139.62
8172E-015C	1-1/2	20	0	101	159.34
8172E-020C	2	15	0	101	196.93
8172E-025C	2-1/2	4	0	101	289.51
8172E-030C	3	4	0	101	344.69
8172E-040C	4	2	0	101	573.88
8172E-060C	6	1	0	101	1364.80



Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002C	1/4	25	150	101	121.05
8172V-003C	3/8	25	200	101	121.05
8172V-005C	1/2	25	0	101	121.05
8172V-007C	3/4	25	0	101	136.45
8172V-010C	1	25	0	101	157.02
8172V-012C	1-1/4	20	0	101	192.61
8172V-015C	1-1/2	20	0	101	199.29
8172V-020C	2	15	0	101	310.46
8172V-025C	2-1/2	4	0	101	440.57
8172V-030C	3	4	0	101	524.44
8172V-040C	4	2	0	101	1379.15
8172V-060C	6	1	0	101	2527.80



Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	76.94
8172-003CSR	3/8	25	200	101	76.94
8172-005CSR	1/2	25	0	101	76.94
8172-007CSR	3/4	25	0	101	89.35
8172-010CSR	1	25	0	101	98.45
8172-012CSR	1-1/4	20	0	101	139.66
8172-015CSR	1-1/2	20	0	101	156.03
8172-020CSR	2	15	0	101	192.92
8172-025CSR	2-1/2	4	0	101	279.98
8172-030CSR	3	4	0	101	333.32
8172-040CSR	4	2	0	101	511.95
8172-060CSR	6	2	0	101	1371.59



Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	79.96
8172E-003CSR	3/8	25	200	101	79.96
8172E-005CSR	1/2	25	0	101	79.96
8172E-007CSR	3/4	25	0	101	94.67
8172E-010CSR	1	25	0	101	102.78
8172E-012CSR	1-1/4	20	0	101	145.07
8172E-015CSR	1-1/2	20	0	101	168.65
8172E-020CSR	2	15	0	101	207.00
8172E-025CSR	2-1/2	4	0	101	312.27
8172E-030CSR	3	4	0	101	371.76
8172E-040CSR	4	2	0	101	601.83



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with EPDM Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172E-060CSR	6	2	0	101	1391.88
--------------	---	---	---	-----	---------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	122.77
8172V-003CSR	3/8	25	200	101	122.77
8172V-005CSR	1/2	25	0	101	122.77
8172V-007CSR	3/4	25	0	101	138.89
8172V-010CSR	1	25	0	101	160.41
8172V-012CSR	1-1/4	20	0	101	198.05
8172V-015CSR	1-1/2	20	0	101	208.58
8172V-020CSR	2	15	0	101	320.57
8172V-025CSR	2-1/2	4	0	101	463.20
8172V-030CSR	3	4	0	101	551.43
8172V-040CSR	4	2	0	101	1407.11
8172V-060CSR	6	2	0	101	2554.93



Tank Adapter, CPVC Self Aligning with Neoprene Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010C	1	5	0	101	246.46
8172SA-020C	2	4	0	101	371.98
8172SA-030C	3	2	0	101	579.62



Tank Adapter, CPVC Self Aligning with EPDM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010C	1	5	0	101	259.11
8172ESA-020C	2	4	0	101	392.40
8172ESA-030C	3	2	0	101	610.32



Tank Adapter, CPVC Self Aligning with FKM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010C	1	5	0	101	512.12
8172VSA-020C	2	4	0	101	775.17
8172VSA-030C	3	2	0	101	1204.40



Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter, CPVC Old Style with Neoprene Gasket

Socket x Fipt



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871-005C	1/2	25	0	101	56.37
871-007C	3/4	25	0	101	67.06
871-010C	1	25	0	101	75.27
871-012C	1-1/4	20	0	101	96.00
871-015C	1-1/2	20	0	101	104.54
871-020C	2	15	0	101	147.57
871-030C	3	4	0	101	258.16
871-040C	4	2	0	101	430.23

Tank Adapter, CPVC Old Style with Neoprene Gasket

Fipt x Fipt



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872-005C	1/2	25	0	101	75.27
872-007C	3/4	25	0	101	86.91
872-010C	1	25	0	101	95.07
872-012C	1-1/4	20	0	101	134.22
872-015C	1-1/2	20	0	101	146.71
872-020C	2	15	0	101	182.85
872-030C	3	4	0	101	306.32
872-040C	4	2	0	101	483.99

Tank Adapter Gasket Only - Neoprene (New Style)

3N-002	1/4	100	0	299	3.16
3N-003	3/8	50	0	299	3.16
3N-005	1/2	10	0	299	3.16
3N-007	3/4	10	0	299	3.39
3N-010	1	10	0	299	3.60
3N-012	1-1/4	10	0	299	4.98
3N-015	1-1/2	10	0	299	5.84
3N-020	2	10	0	299	7.65
3N-025	2-1/2	10	0	299	7.98
3N-030	3	10	0	299	8.34
3N-040	4	50	0	299	23.03
2N-060	6	10	0	299	28.78
3N-080	8	10	0	299	131.96

Tank Adapter Gasket Only - EPDM (New Style)

3E-002	1/4	10	0	299	1.96
3E-003	3/8	10	0	299	2.24

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter Gasket Only - EPDM (New Style) (continued)

3E-005	1/2	10	0	299	3.00
3E-007	3/4	10	0	299	3.17
3E-010	1	10	0	299	4.58
3E-012	1-1/4	10	0	299	9.63
3E-015	1-1/2	10	0	299	9.89
3E-020	2	10	0	299	11.33
3E-025	2-1/2	10	0	299	16.04
3E-030	3	10	0	299	17.25
3E-040	4	10	0	299	25.98
2E-060	6	10	0	299	46.92
3E-080	8	10	0	299	124.02

Tank Adapter Gasket Only - FKM (New Style)

3V-002	1/4	10	0	299	11.98
3V-003	3/8	10	0	299	15.23
3V-005	1/2	10	0	299	19.38
3V-007	3/4	10	0	299	21.48
3V-010	1	10	0	299	23.46
3V-012	1-1/4	10	0	299	43.91
3V-015	1-1/2	10	0	299	47.12
3V-020	2	10	0	299	60.72
3V-025	2-1/2	10	0	299	73.99
3V-030	3	10	0	299	133.44
3V-040	4	10	0	299	166.18
2V-060	6	10	0	299	586.61
3V-080	8	10	0	299	944.09

Tank Adapter Gasket Only - Neoprene (Old Style)

2N-005	1/2	10	0	299	3.16
2N-007	3/4	10	0	299	3.39
2N-010	1	10	0	299	3.60
2N-015	1-1/4 OR 1-1/2	10	0	299	5.84
2N-020	2	10	0	299	7.65
2N-030	3	10	0	299	8.34
2N-040	4	10	0	299	23.03

Tank Adapter Gasket Only - EPDM (Old Style)

2E-005	1/2	10	0	299	3.67
2E-007	3/4	10	0	299	3.79
2E-010	1	10	0	299	6.58
2E-015	1-1/4 OR 1-1/2	10	0	299	9.89
2E-020	2	10	0	299	11.33
2E-030	3	10	0	299	17.25
2E-040	4	10	0	299	25.98



Schedule 80 CPVC Product
Tank Adapters & Pipe Flanges

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter Wrench Sets (New Style)

Body Wrench & Nut Wrench



TAW-002	1/4	1	25	299	25.53
TAW-003	3/8	1	25	299	25.53
TAW-005	1/2	1	25	299	25.53
TAW-007	3/4	1	25	299	26.03
TAW-010	1	1	25	299	27.07
TAW-012	1-1/4	1	20	299	30.54
TAW-015	1-1/2	1	20	299	33.12
TAW-020	2	1	10	299	37.73
TAW-025	2-1/2	1	10	299	41.74
TAW-030	3	1	10	299	46.01
TAW-040	4	1	10	299	49.28

Tank Adapter Individual Body Wrench (New Style)

TAW1-002	1/4	500	0	299	14.33
TAW1-003	3/8	400	0	299	14.33
TAW1-005	1/2	250	0	299	14.33
TAW1-007	3/4	220	0	299	14.60
TAW1-010	1	200	0	299	15.20
TAW1-012	1-1/4	300	0	299	17.22
TAW1-015	1-1/2	150	0	299	18.54
TAW1-020	2	100	0	299	20.13
TAW1-025	2-1/2	80	0	299	21.03
TAW1-030	3	74	0	299	26.37
TAW1-040	4	35	0	299	27.13

Tank Adapter Individual Nut Wrench (New Style)

TAW2-002	1/4	300	0	299	14.33
TAW2-003	3/8	250	0	299	14.33
TAW2-005	1/2	200	0	299	14.33
TAW2-007	3/4	160	0	299	14.60
TAW2-010	1	110	0	299	15.20
TAW2-012	1-1/4	200	0	299	17.22
TAW2-015	1-1/2	120	0	299	18.54
TAW2-020	2	100	0	299	20.13
TAW2-025	2-1/2	50	0	299	21.03
TAW2-030	3	40	0	299	26.37
TAW2-040	4	35	0	299	27.13

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange One Piece

Socket



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

851-005C	1/2	25	0	090	31.34
851-007C	3/4	25	0	090	32.06
851-010C	1	15	0	090	35.01
851-012C	1-1/4	15	0	090	42.74
851-015C	1-1/2	20	0	090	47.43
851-020C	2	10	0	090	57.42
851-025C	2-1/2	10	0	090	118.98
851-030C	3	10	0	090	124.41
851-040C	4	5	0	090	168.09
851-050C	5	5	0	090	308.05
851-060C	6	5	0	090	286.35
851-080C	8	2	0	090	860.59
851-100C	10	2	0	091	1072.58
851-100CF	10	1	2	097	1858.75
851-120C	12	2	0	091	1506.61
851-120CF	12	1	0	097	2789.04

Flange One Piece

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005C	1/2	25	0	090	43.82
852-007C	3/4	25	0	090	53.13
852-010C	1	15	0	090	57.98
852-012C	1-1/4	15	0	090	80.46
852-015C	1-1/2	20	0	090	85.18
852-020C	2	10	0	090	86.74
852-025C	2-1/2	10	0	090	140.80
852-030C	3	10	0	090	139.71
852-040C	4	5	0	090	217.19
852-060CF	6	1	8	097	324.49
852-080CF	8	1	2	097	803.79

Flange - Special Reinforced One Piece Threaded

SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	24.08
852-007CSR	3/4	25	0	096	29.22
852-010CSR	1	15	0	096	31.97
852-012CSR	1-1/4	15	0	096	44.24
852-015CSR	1-1/2	15	0	096	46.91
852-020CSR	2	10	0	096	48.04
852-025CSR	2-1/2	10	0	096	77.29
852-030CSR	3	10	0	096	76.69