



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings & Tank Adapters**

**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union (Old Style) - Socket/Special Reinforced Fipt/EPDM**

(continued)

**Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar**

899-007CSR	3/4	10	40	096	29.55
899-010CSR	1	10	40	096	40.92
899-012CSR	1-1/4	5	20	096	77.52
899-015CSR	1-1/2	5	0	096	84.31
899-020CSR	2	5	0	096	88.78
899-030CSR	3	5	0	096	247.32
899-040CSR	4	4	0	096	290.45

**Tank Adapters**

**Tank Adapters, CPVC New Style Standard with Neoprene Gaskets**

**Socket x Socket**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002C	1/4	25	150	101	50.87
8170-003C	3/8	25	150	101	50.87
8170-005C	1/2	25	0	101	50.87
8170-007C	3/4	25	0	101	60.52
8170-010C	1	25	0	101	67.93
8170-012C	1-1/4	20	0	101	86.64
8170-015C	1-1/2	20	0	101	94.34
8170-020C	2	15	0	101	133.18
8170-025C	2-1/2	4	0	101	195.74
8170-030C	3	4	0	101	232.99
8170-040C	4	2	0	101	388.28
8170-060C	6	1	0	101	1067.80
8170-080C	8	1	0	101	2372.72

**Tank Adapters, CPVC New Style Standard with EPDM Gaskets**

**Socket x Socket**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002C	1/4	25	150	101	57.86
8170E-003C	3/8	25	150	101	57.86
8170E-005C	1/2	25	0	101	57.86
8170E-007C	3/4	25	0	101	64.94
8170E-010C	1	25	0	101	75.41
8170E-012C	1-1/4	20	0	101	95.43
8170E-015C	1-1/2	20	0	101	100.13
8170E-020C	2	15	0	101	144.36
8170E-025C	2-1/2	4	0	101	205.05
8170E-030C	3	4	0	101	244.13
8170E-040C	4	2	0	101	405.24
8170E-060C	6	1	0	101	1112.29
8170E-080C	8	1	0	101	2442.08

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tank Adapters, CPVC New Style Standard with FKM Gaskets**

**Socket x Socket**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002C	1/4	25	150	101	75.87
8170V-003C	3/8	25	150	101	75.87
8170V-005C	1/2	25	0	101	75.87
8170V-007C	3/4	25	0	101	87.28
8170V-010C	1	25	0	101	101.03
8170V-012C	1-1/4	20	0	101	124.14
8170V-015C	1-1/2	20	0	101	129.41
8170V-020C	2	15	0	101	195.92
8170V-025C	2-1/2	4	0	101	281.99
8170V-030C	3	4	0	101	335.71
8170V-040C	4	2	0	101	743.57
8170V-060C	6	1	0	101	1868.71
8170V-080C	8	1	0	101	4371.39

**Tank Adapters, CPVC New Style Standard with Neoprene Gaskets**

**Socket x Fipt**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002C	1/4	25	150	101	50.87
8171-003C	3/8	25	200	101	50.87
8171-005C	1/2	25	0	101	50.87
8171-007C	3/4	25	0	101	60.52
8171-010C	1	25	0	101	67.93
8171-012C	1-1/4	20	0	101	86.64
8171-015C	1-1/2	20	0	101	94.34
8171-020C	2	15	0	101	133.18
8171-025C	2-1/2	4	0	101	195.74
8171-030C	3	4	0	101	232.99
8171-040C	4	2	0	101	388.28
8171-060C	6	1	0	101	1067.80

**Tank Adapters, CPVC New Style Standard with EPDM Gaskets**

**Socket x Fipt**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002C	1/4	25	150	101	57.86
8171E-003C	3/8	25	200	101	57.86
8171E-005C	1/2	25	0	101	57.86
8171E-007C	3/4	25	0	101	64.94
8171E-010C	1	25	0	101	75.41
8171E-012C	1-1/4	20	0	101	95.43
8171E-015C	1-1/2	20	0	101	100.13
8171E-020C	2	15	0	101	144.36
8171E-025C	2-1/2	4	0	101	205.05
8171E-030C	3	4	0	101	244.13
8171E-040C	4	2	0	101	405.24
8171E-060C	6	1	0	101	1112.28

# Tank Adapters



## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, CPVC New Style Standard with FKM Gaskets

#### Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002C	1/4	25	150	101	75.87
8171V-003C	3/8	25	200	101	75.87
8171V-005C	1/2	25	0	101	75.87
8171V-007C	3/4	25	0	101	87.28
8171V-010C	1	25	0	101	101.03
8171V-012C	1-1/4	20	0	101	124.14
8171V-015C	1-1/2	20	0	101	129.41
8171V-020C	2	15	0	101	195.92
8171V-025C	2-1/2	4	0	101	282.03
8171V-030C	3	4	0	101	335.71
8171V-040C	4	2	0	101	743.57
8171V-060C	6	1	0	101	1868.71



### Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

#### Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	52.42
8171-003CSR	3/8	25	200	101	52.42
8171-005CSR	1/2	25	0	101	52.42
8171-007CSR	3/4	25	0	101	62.74
8171-010CSR	1	25	0	101	70.97
8171-012CSR	1-1/4	20	0	101	91.55
8171-015CSR	1-1/2	20	0	101	102.78
8171-020CSR	2	15	0	101	142.13
8171-025CSR	2-1/2	4	0	101	216.20
8171-030CSR	3	4	0	101	257.33
8171-040CSR	4	2	0	101	413.56
8171-060CSR	6	1	0	101	1092.26



### Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

#### Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	59.41
8171E-003CSR	3/8	25	200	101	59.41
8171E-005CSR	1/2	25	0	101	59.41
8171E-007CSR	3/4	25	0	101	67.15
8171E-010CSR	1	25	0	101	80.28
8171E-012CSR	1-1/4	20	0	101	100.34
8171E-015CSR	1-1/2	20	0	101	108.56
8171E-020CSR	2	15	0	101	153.46
8171E-025CSR	2-1/2	4	0	101	225.52
8171E-030CSR	3	4	0	101	268.47
8171E-040CSR	4	2	0	101	430.45



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets (continued)

#### Socket x SR Fipt - Stainless Steel Collar

8171E-060CSR	6	2	0	101	1136.77
--------------	---	---	---	-----	---------

### Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

#### Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	77.41
8171V-003CSR	3/8	25	200	101	77.41
8171V-005CSR	1/2	25	0	101	77.41
8171V-007CSR	3/4	25	0	101	89.48
8171V-010CSR	1	25	0	101	104.09
8171V-012CSR	1-1/4	20	0	101	129.04
8171V-015CSR	1-1/2	20	0	101	137.80
8171V-020CSR	2	15	0	101	205.19
8171V-025CSR	2-1/2	4	0	101	302.38
8171V-030CSR	3	4	0	101	360.05
8171V-040CSR	4	2	0	101	768.80
8171V-060CSR	6	2	0	101	1898.13



### Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

#### Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002C	1/4	25	150	101	67.93
8172-003C	3/8	25	200	101	67.93
8172-005C	1/2	25	0	101	67.93
8172-007C	3/4	25	0	101	78.43
8172-010C	1	25	0	101	85.80
8172-012C	1-1/4	20	0	101	121.13
8172-015C	1-1/2	20	0	101	132.40
8172-020C	2	15	0	101	165.02
8172-025C	2-1/2	4	0	101	232.23
8172-030C	3	4	0	101	276.45
8172-040C	4	2	0	101	436.80
8172-060C	6	1	0	101	1213.41



### Tank Adapters, CPVC New Style Standard with EPDM Gaskets

#### Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002C	1/4	25	150	101	70.60
8172E-003C	3/8	25	200	101	70.60
8172E-005C	1/2	25	0	101	70.60
8172E-007C	3/4	25	0	101	83.24
8172E-010C	1	25	0	101	89.69
8172E-012C	1-1/4	20	0	101	126.01
8172E-015C	1-1/2	20	0	101	143.80
8172E-020C	2	15	0	101	177.73
8172E-025C	2-1/2	4	0	101	261.28





## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

## Tank Adapters, CPVC New Style Standard with EPDM Gaskets

(continued)

## Fipt x Fipt

8172E-030C	3	4	0	101	311.09
8172E-040C	4	2	0	101	517.93
8172E-060C	6	1	0	101	1231.73

## Tank Adapters, CPVC New Style Standard with FKM Gaskets

## Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002C	1/4	25	150	101	109.25
8172V-003C	3/8	25	200	101	109.25
8172V-005C	1/2	25	0	101	109.25
8172V-007C	3/4	25	0	101	123.15
8172V-010C	1	25	0	101	141.71
8172V-012C	1-1/4	20	0	101	173.83
8172V-015C	1-1/2	20	0	101	179.86
8172V-020C	2	15	0	101	280.19
8172V-025C	2-1/2	4	0	101	397.61
8172V-030C	3	4	0	101	473.31
8172V-040C	4	2	0	101	1244.68
8172V-060C	6	1	0	101	2281.34

## Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

## Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	69.44
8172-003CSR	3/8	25	200	101	69.44
8172-005CSR	1/2	25	0	101	69.44
8172-007CSR	3/4	25	0	101	80.64
8172-010CSR	1	25	0	101	88.85
8172-012CSR	1-1/4	20	0	101	126.05
8172-015CSR	1-1/2	20	0	101	140.82
8172-020CSR	2	15	0	101	174.11
8172-025CSR	2-1/2	4	0	101	252.68
8172-030CSR	3	4	0	101	300.82
8172-040CSR	4	2	0	101	462.03
8172-060CSR	6	2	0	101	1237.86

## Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

## Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	72.16
8172E-003CSR	3/8	25	200	101	72.16
8172E-005CSR	1/2	25	0	101	72.16
8172E-007CSR	3/4	25	0	101	85.44
8172E-010CSR	1	25	0	101	92.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

## Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with EPDM Gaskets (continued)

## Fipt x SR Fipt - Stainless Steel Collar

8172E-012CSR	1-1/4	20	0	101	130.93
8172E-015CSR	1-1/2	20	0	101	152.21
8172E-020CSR	2	15	0	101	186.82
8172E-025CSR	2-1/2	4	0	101	281.83
8172E-030CSR	3	4	0	101	335.51
8172E-040CSR	4	2	0	101	543.15
8172E-060CSR	6	2	0	101	1256.18

## Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

## Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	110.80
8172V-003CSR	3/8	25	200	101	110.80
8172V-005CSR	1/2	25	0	101	110.80
8172V-007CSR	3/4	25	0	101	125.35
8172V-010CSR	1	25	0	101	144.77
8172V-012CSR	1-1/4	20	0	101	178.74
8172V-015CSR	1-1/2	20	0	101	188.24
8172V-020CSR	2	15	0	101	289.31
8172V-025CSR	2-1/2	4	0	101	418.04
8172V-030CSR	3	4	0	101	497.67
8172V-040CSR	4	2	0	101	1269.91
8172V-060CSR	6	2	0	101	2305.82

## Tank Adapter, CPVC Self Aligning with Neoprene Gasket

## Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010C	1	5	0	101	222.43
8172SA-020C	2	4	0	101	335.71
8172SA-030C	3	2	0	101	523.11

## Tank Adapter, CPVC Self Aligning with EPDM Gasket

## Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010C	1	5	0	101	233.84
8172ESA-020C	2	4	0	101	354.14
8172ESA-030C	3	2	0	101	550.81

## Tank Adapter, CPVC Self Aligning with FKM Gasket

## Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010C	1	5	0	101	462.18
8172VSA-020C	2	4	0	101	699.59
8172VSA-030C	3	2	0	101	1086.97

# Tank Adapters



## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapter, CPVC Old Style with Neoprene Gasket

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871-005C	1/2	25	0	101	50.87
871-007C	3/4	25	0	101	60.52
871-010C	1	25	0	101	67.93
871-012C	1-1/4	20	0	101	86.64
871-015C	1-1/2	20	0	101	94.34
871-020C	2	15	0	101	133.18
871-030C	3	4	0	101	232.99
871-040C	4	2	0	101	388.28



### Tank Adapter, CPVC Old Style with Neoprene Gasket

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872-005C	1/2	25	0	101	67.93
872-007C	3/4	25	0	101	78.43
872-010C	1	25	0	101	85.80
872-012C	1-1/4	20	0	101	121.13
872-015C	1-1/2	20	0	101	132.40
872-020C	2	15	0	101	165.02
872-030C	3	4	0	101	276.45
872-040C	4	2	0	101	436.80



### Tank Adapter Gasket Only - Neoprene (New Style)

3N-002	1/4	100	0	299	2.85
3N-003	3/8	50	0	299	2.85
3N-005	1/2	10	0	299	2.85
3N-007	3/4	10	0	299	3.06
3N-010	1	10	0	299	3.25
3N-012	1-1/4	10	0	299	4.49
3N-015	1-1/2	10	0	299	5.27
3N-020	2	10	0	299	6.91
3N-025	2-1/2	10	0	299	7.20
3N-030	3	10	0	299	7.52
3N-040	4	50	0	299	20.79
2N-060	6	10	0	299	25.97
3N-080	8	10	0	299	119.09



### Tank Adapter Gasket Only - EPDM (New Style)

3E-002	1/4	10	0	299	1.77
3E-003	3/8	10	0	299	2.02



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapter Gasket Only - EPDM (New Style) (continued)

3E-005	1/2	10	0	299	2.71
3E-007	3/4	10	0	299	2.86
3E-010	1	10	0	299	4.13
3E-012	1-1/4	10	0	299	8.69
3E-015	1-1/2	10	0	299	8.93
3E-020	2	10	0	299	10.22
3E-025	2-1/2	10	0	299	14.48
3E-030	3	10	0	299	15.57
3E-040	4	10	0	299	23.45
2E-060	6	10	0	299	42.34
3E-080	8	10	0	299	111.93



### Tank Adapter Gasket Only - FKM (New Style)

3V-002	1/4	10	0	299	16.79
3V-003	3/8	10	0	299	25.03
3V-005	1/2	10	0	299	26.19
3V-007	3/4	10	0	299	29.89
3V-010	1	10	0	299	37.95
3V-012	1-1/4	10	0	299	107.45
3V-015	1-1/2	10	0	299	118.11
3V-020	2	10	0	299	121.26
3V-025	2-1/2	10	0	299	147.96
3V-030	3	10	0	299	236.38
3V-040	4	10	0	299	299.12
2V-060	6	10	0	299	529.42
3V-080	8	10	0	299	1888.17



### Tank Adapter Gasket Only - Neoprene (Old Style)

2N-005	1/2	10	0	299	2.85
2N-007	3/4	10	0	299	3.06
2N-010	1	10	0	299	3.25
2N-015	1-1/4 OR 1-1/2	10	0	299	5.27
2N-020	2	10	0	299	6.91
2N-030	3	10	0	299	7.52
2N-040	4	10	0	299	20.79



### Tank Adapter Gasket Only - EPDM (Old Style)

2E-005	1/2	10	0	299	3.32
2E-007	3/4	10	0	299	3.42
2E-010	1	10	0	299	5.94
2E-015	1-1/4 OR 1-1/2	10	0	299	8.93
2E-020	2	10	0	299	10.22
2E-030	3	10	0	299	15.57
2E-040	4	10	0	299	23.45



Schedule 80 CPVC Product  
**Tank Adapters & Pipe Flanges**

**Tank Adapters**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tank Adapter Wrench Sets (New Style)**

**Body Wrench & Nut Wrench**



TAW-002	1/4	1	25	299	23.04
TAW-003	3/8	1	25	299	23.04
TAW-005	1/2	1	25	299	23.04
TAW-007	3/4	1	25	299	23.49
TAW-010	1	1	25	299	24.43
TAW-012	1-1/4	1	20	299	27.56
TAW-015	1-1/2	1	20	299	29.89
TAW-020	2	1	10	299	34.05
TAW-025	2-1/2	1	10	299	37.67
TAW-030	3	1	10	299	41.52
TAW-040	4	1	10	299	44.48

**Tank Adapter Individual Body Wrench (New Style)**

TAW1-002	1/4	500	0	299	12.93
TAW1-003	3/8	400	0	299	12.93
TAW1-005	1/2	250	0	299	12.93
TAW1-007	3/4	220	0	299	13.18
TAW1-010	1	200	0	299	13.72
TAW1-012	1-1/4	300	0	299	15.54
TAW1-015	1-1/2	150	0	299	16.73
TAW1-020	2	100	0	299	18.16
TAW1-025	2-1/2	80	0	299	18.98
TAW1-030	3	74	0	299	23.80
TAW1-040	4	35	0	299	24.48

**Tank Adapter Individual Nut Wrench (New Style)**

TAW2-002	1/4	300	0	299	12.93
TAW2-003	3/8	250	0	299	12.93
TAW2-005	1/2	200	0	299	12.93
TAW2-007	3/4	160	0	299	13.18
TAW2-010	1	110	0	299	13.72
TAW2-012	1-1/4	200	0	299	15.54
TAW2-015	1-1/2	120	0	299	16.73
TAW2-020	2	100	0	299	18.16
TAW2-025	2-1/2	50	0	299	18.98
TAW2-030	3	40	0	299	23.80
TAW2-040	4	35	0	299	24.48

**Pipe Flanges**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Flange One Piece**

**Socket**



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

851-005C	1/2	25	0	090	28.28
851-007C	3/4	25	0	090	28.94
851-010C	1	15	0	090	31.60
851-012C	1-1/4	15	0	090	38.57
851-015C	1-1/2	20	0	090	42.81
851-020C	2	10	0	090	51.82
851-025C	2-1/2	10	0	090	107.38
851-030C	3	10	0	090	112.28
851-040C	4	5	0	090	151.71
851-050C	5	5	0	090	278.02
851-060C	6	5	0	090	258.43
851-080C	8	2	0	090	776.68
851-100C	10	2	0	091	968.00
851-120C	12	2	0	091	1359.72

**Flange One Piece**

**Fipt**



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005C	1/2	25	0	090	39.55
852-007C	3/4	25	0	090	47.95
852-010C	1	15	0	090	52.33
852-012C	1-1/4	15	0	090	72.62
852-015C	1-1/2	20	0	090	76.87
852-020C	2	10	0	090	78.28
852-025C	2-1/2	10	0	090	127.07
852-030C	3	10	0	090	126.08
852-040C	4	5	0	090	196.01

**Flange - Special Reinforced One Piece Threaded**

**SR Fipt - Stainless Steel Collar**



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	21.74
852-007CSR	3/4	25	0	096	26.37
852-010CSR	1	15	0	096	28.85
852-012CSR	1-1/4	15	0	096	39.93
852-015CSR	1-1/2	15	0	096	42.33
852-020CSR	2	10	0	096	43.36
852-025CSR	2-1/2	10	0	096	69.76
852-030CSR	3	10	0	096	69.22
852-040CSR	4	5	0	096	129.71