



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	736.78
876-420CF ²	4X2	1	2	097	926.87
876-421CF ²	4X2-1/2	1	2	097	980.86
876-422CF ²	4X3	1	2	097	1056.03
876-528CF ²	6X2	1	3	097	1576.34
876-529CF ²	6X2-1/2	1	2	097	1595.97
876-530CF ²	6X3	1	2	097	1621.94
876-532CF ²	6X4	1	0	097	1801.21
876-578CF ²	8X2	1	2	097	2693.88
876-579CF ²	8X2-1/2	1	2	097	2733.69
876-580CF ²	8X3	1	2	097	2755.34
876-582CF ²	8X4	1	0	097	2966.31
876-585CF ²	8X6	1	0	097	3127.14
876-621CF ²	10X2	1	0	097	3247.88
876-622CF ²	10X2-1/2	1	0	097	3315.61
876-623CF ²	10X3	1	0	097	3374.47
876-624CF ²	10X4	1	0	097	3452.49
876-626CF ²	10X6	1	0	097	3696.63
876-628CF ²	10X8	1	0	097	3882.66
876-661CF ²	12X2	1	0	097	3496.76
876-662CF ²	12X2-1/2	1	0	097	3664.41
876-663CF ²	12X3	1	0	097	3729.06
876-666CF ²	12X6	1	0	097	4231.11
876-668CF ²	12X8	1	0	097	4800.39
876-664CF ²	12X4	1	0	097	3865.62
876-670CF ²	12X10	1	0	097	5226.89

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	43.32
857-003C	3/8	25	150	090	43.32
8057-005C	1/2	20	120	090	28.82
8057-007C	3/4	20	80	090	30.11
8057-010C	1	15	90	090	36.14
8057-012C	1-1/4	10	0	090	73.12
8057-015C	1-1/2	10	0	090	74.45
8057-020C	2	5	0	090	123.41
8057-025C	2-1/2	5	0	090	202.40
8057-030C	3	5	0	090	256.15

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/FKM (continued)

Socket x Socket with FKM O-ring Seal

8057-040C	4	4	0	090	327.25
8057-060C	6	1	0	090	727.23

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	42.79
897-003C	3/8	25	150	090	42.79
8097-005C	1/2	20	120	090	28.73
8097-007C	3/4	20	80	090	29.75
8097-010C	1	15	90	090	35.64
8097-012C	1-1/4	10	0	090	72.18
8097-015C	1-1/2	10	0	090	73.55
8097-020C	2	5	0	090	121.89
8097-025C	2-1/2	5	0	090	201.87
8097-030C	3	5	0	090	252.99
8097-040C	4	4	0	090	323.54
8097-060C	6	1	0	090	718.97

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	32.81
8059-007C	3/4	20	80	090	57.25
8059-010C	1	15	90	090	79.02
8059-012C	1-1/4	10	0	090	134.10
8059-015C	1-1/2	10	0	090	150.52
8059-020C	2	5	0	090	170.16
8059-025C	2-1/2	5	0	090	276.25
8059-030C	3	5	0	090	326.75
8059-040C	4	4	0	090	377.84
8059-060C	6	1	0	090	839.65

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	32.00
8099-007C	3/4	20	80	090	56.58
8099-010C	1	15	90	090	78.04
8099-012C	1-1/4	10	0	090	148.65
8099-015C	1-1/2	10	0	090	148.65
8099-020C	2	5	0	090	168.05
8099-025C	2-1/2	5	0	090	240.73
8099-030C	3	5	0	090	322.74
8099-040C	4	4	0	090	372.29
8099-060C	6	1	0	090	827.35

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Spigot/FKM

Socket x Spigot with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005C	1/2	20	160	090	28.82
8056-007C	3/4	20	160	090	30.11
8056-010C	1	15	90	090	36.14
8056-012C	1-1/4	10	0	090	73.12
8056-015C	1-1/2	10	0	090	74.45
8056-020C	2	5	0	090	123.41
8056-025C	2-1/2	5	0	090	225.49
8056-030C	3	5	0	090	256.15
8056-040C	4	4	0	090	327.25
8056-060C	6	1	0	090	727.23

Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005C	1/2	20	160	090	28.73
8096-007C	3/4	20	80	090	29.75
8096-010C	1	15	90	090	35.64
8096-012C	1-1/4	10	0	090	72.18
8096-015C	1-1/2	10	0	090	73.55
8096-020C	2	5	0	090	121.89
8096-025C	2-1/2	5	0	090	201.87
8096-030C	3	5	0	090	252.99
8096-040C	4	4	0	090	323.54
8096-060C	6	1	0	090	718.97

Union 2000 - Special Reinforced Fipt/Spigot/FKM

SR Fipt x Spigot with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005CSR	1/2	20	160	096	37.93
8055-007CSR	3/4	20	160	096	39.92
8055-010CSR	1	15	90	096	50.88
8055-012CSR	1-1/4	10	0	096	81.78
8055-015CSR	1-1/2	10	0	096	93.61
8055-020CSR	2	5	0	096	143.82
8055-025CSR	2-1/2	5	0	096	271.46
8055-030CSR	3	5	0	096	286.85
8055-040CSR	4	4	0	096	370.54
8055-060CSR	6	1	0	096	806.52

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/Spigot/EPDM

SR Fipt x Spigot with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005CSR	1/2	20	120	096	37.58
8095-007CSR	3/4	20	160	096	38.88
8095-010CSR	1	15	90	096	49.86
8095-012CSR	1-1/4	10	0	096	76.58
8095-015CSR	1-1/2	10	0	096	86.98
8095-020CSR	2	5	0	096	131.26
8095-025CSR	2-1/2	5	0	096	260.51
8095-030CSR	3	5	0	096	280.83
8095-040CSR	4	4	0	096	354.38
8095-060CSR	6	1	0	096	773.35

Union 2000 - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002C	1/4	25	150	090	48.71
858-003C	3/8	25	150	090	48.71
8058-005C	1/2	20	120	090	30.87
8058-007C	3/4	20	80	090	54.56
8058-010C	1	15	90	090	75.23
8058-012C	1-1/4	10	0	090	143.35
8058-015C	1-1/2	10	0	090	143.35
8058-020C	2	5	0	090	162.03
8058-025C	2-1/2	5	0	090	261.04
8058-030C	3	5	0	090	495.32
8058-040C	4	4	0	090	532.44
8058-060C	6	1	0	090	1183.23

Union 2000 - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002C	1/4	25	150	090	48.13
898-003C	3/8	25	100	090	48.13
8098-005C	1/2	20	120	090	30.48
8098-007C	3/4	20	80	090	53.88
8098-010C	1	15	90	090	74.31
8098-012C	1-1/4	10	0	090	141.68
8098-015C	1-1/2	10	0	090	141.68
8098-020C	2	5	0	090	160.06
8098-025C	2-1/2	5	0	090	225.49
8098-030C	3	5	0	090	448.64
8098-040C	4	4	0	090	522.31
8098-060C	6	1	0	090	1160.66



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	16.98
8059-007CSR	3/4	20	160	096	29.95
8059-010CSR	1	15	90	096	41.26
8059-012CSR	1-1/4	10	0	096	78.67
8059-015CSR	1-1/2	10	0	096	85.52
8059-020CSR	2	5	0	096	89.03
8059-025CSR	2-1/2	5	0	096	154.16
8059-030CSR	3	5	0	096	250.46
8059-040CSR	4	4	0	096	292.21
8059-060CSR	6	1	0	096	649.42

Union 2000 - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	16.64
8099-007CSR	3/4	20	160	096	29.55
8099-010CSR	1	15	90	096	40.92
8099-012CSR	1-1/4	10	0	096	77.52
8099-015CSR	1-1/2	10	0	096	84.31
8099-020CSR	2	5	0	096	88.78
8099-025CSR	2-1/2	5	0	096	152.27
8099-030CSR	3	5	0	096	247.32
8099-040CSR	4	4	0	096	290.45
8099-060CSR	6	1	0	096	645.47

Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	17.42
8058-007CSR	3/4	20	80	096	30.37
8058-010CSR	1	15	90	096	41.74
8058-012CSR	1-1/4	10	0	096	78.67
8058-015CSR	1-1/2	10	0	096	85.85
8058-020CSR	2	5	0	096	90.46
8058-025CSR	2-1/2	5	0	096	156.61
8058-030CSR	3	5	0	096	255.63
8058-040CSR	4	4	0	096	299.48
8058-060CSR	6	1	0	096	674.45

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/EPDM

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	16.84
8098-007CSR	3/4	20	80	096	30.09
8098-010CSR	1	15	90	096	41.26
8098-012CSR	1-1/4	10	0	096	77.91
8098-015CSR	1-1/2	10	0	096	85.19
8098-020CSR	2	5	0	096	89.57
8098-025CSR	2-1/2	5	0	096	154.79
8098-030CSR	3	5	0	096	251.67
8098-040CSR	4	4	0	096	291.36
8098-060CSR	6	1	0	096	647.46

Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005C	1/2	15	90	090	28.82
857-007C	3/4	10	60	090	30.11
857-010C	1	10	40	090	36.14
857-012C	1-1/4	5	20	090	73.12
857-015C	1-1/2	5	0	090	74.45
857-020C	2	5	0	090	123.41
857-025C	2-1/2	5	0	090	202.40
857-030C	3	5	0	090	256.15
857-040C	4	4	0	090	327.25

Union (Old Style) - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005C	1/2	15	90	090	28.73
897-007C	3/4	10	60	090	29.75
897-010C	1	10	40	090	35.64
897-012C	1-1/4	5	20	090	72.18
897-015C	1-1/2	5	0	090	73.55
897-020C	2	5	0	090	121.89
897-025C	2-1/2	5	0	090	201.87
897-030C	3	5	0	090	252.99
897-040C	4	4	0	090	323.54

Union (Old Style) - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005C	1/2	15	90	090	32.81
859-007C	3/4	10	40	090	57.25
859-010C	1	10	40	090	79.02

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Socket/Fipt/FKM (continued)

Socket x Fipt with FKM O-ring Seal

859-012C	1-1/4	5	20	090	150.52
859-015C	1-1/2	5	0	090	150.52
859-020C	2	5	0	090	170.16
859-025C	2-1/2	5	0	090	276.25
859-030C	3	5	0	090	326.75
859-040C	4	4	0	090	377.84



Union (Old Style) - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005C	1/2	15	90	090	32.00
899-007C	3/4	10	60	090	56.58
899-010C	1	10	40	090	78.04
899-012C	1-1/4	5	20	090	148.65
899-015C	1-1/2	5	0	090	148.65
899-020C	2	5	0	090	168.05
899-025C	2-1/2	5	0	090	240.73
899-030C	3	5	0	090	322.74
899-040C	4	4	0	090	372.29

Union - Socket/Brass Fipt/FKM

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005CBR	1/2	10	60	096	107.83
859-007CBR	3/4	10	20	096	153.86
859-010CBR	1	10	0	096	171.37
859-012CBR	1-1/4	5	0	096	287.27
859-015CBR	1-1/2	5	0	096	326.45
859-020CBR	2	5	0	096	368.96

Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005CBR	1/2	10	60	096	111.84
899-007CBR	3/4	10	40	096	151.25
899-010CBR	1	10	0	096	169.26
899-012CBR	1-1/4	5	20	096	283.64
899-015CBR	1-1/2	5	0	096	322.28
899-020CBR	2	5	0	096	364.43

Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005C	1/2	15	90	090	30.87
858-007C	3/4	10	60	090	54.56
858-010C	1	10	40	090	75.23
858-012C	1-1/4	5	20	090	143.35
858-015C	1-1/2	5	0	090	143.35
858-020C	2	5	0	090	162.03
858-025C	2-1/2	5	0	090	261.04
858-030C	3	5	0	090	495.32
858-040C	4	4	0	090	532.44

Union (Old Style) - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005C	1/2	15	90	090	30.48
898-007C	3/4	10	60	090	53.88
898-010C	1	10	40	090	74.31
898-012C	1-1/4	5	20	090	141.68
898-015C	1-1/2	5	0	090	141.68
898-020C	2	5	0	090	160.06
898-025C	2-1/2	5	0	090	225.49
898-030C	3	5	0	090	448.64
898-040C	4	4	0	090	522.31

Union (Old Style) - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	26.72
859-003CSR	3/8	25	100	096	26.72
859-005CSR	1/2	10	60	096	16.98
859-007CSR	3/4	10	60	096	29.95
859-010CSR	1	10	40	096	41.26
859-012CSR	1-1/4	5	20	096	78.67
859-015CSR	1-1/2	5	0	096	85.52
859-020CSR	2	5	0	096	89.03
859-030CSR	3	5	0	096	250.46
859-040CSR	4	4	0	096	292.21

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	26.54
899-003CSR	3/8	25	100	096	26.54
899-005CSR	1/2	10	60	096	16.64



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings & Tank Adapters

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM

(continued)

Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar

899-007CSR	3/4	10	40	096	29.55
899-010CSR	1	10	40	096	40.92
899-012CSR	1-1/4	5	20	096	77.52
899-015CSR	1-1/2	5	0	096	84.31
899-020CSR	2	5	0	096	88.78
899-030CSR	3	5	0	096	247.32
899-040CSR	4	4	0	096	290.45

Tank Adapters

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002C	1/4	25	150	101	50.87
8170-003C	3/8	25	150	101	50.87
8170-005C	1/2	25	0	101	50.87
8170-007C	3/4	25	0	101	60.52
8170-010C	1	25	0	101	67.93
8170-012C	1-1/4	20	0	101	86.64
8170-015C	1-1/2	20	0	101	94.34
8170-020C	2	15	0	101	133.18
8170-025C	2-1/2	4	0	101	195.74
8170-030C	3	4	0	101	232.99
8170-040C	4	2	0	101	388.28
8170-060C	6	1	0	101	1067.80
8170-080C	8	1	0	101	2372.72

Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002C	1/4	25	150	101	57.86
8170E-003C	3/8	25	150	101	57.86
8170E-005C	1/2	25	0	101	57.86
8170E-007C	3/4	25	0	101	64.94
8170E-010C	1	25	0	101	75.41
8170E-012C	1-1/4	20	0	101	95.43
8170E-015C	1-1/2	20	0	101	100.13
8170E-020C	2	15	0	101	144.36
8170E-025C	2-1/2	4	0	101	205.05
8170E-030C	3	4	0	101	244.13
8170E-040C	4	2	0	101	405.24
8170E-060C	6	1	0	101	1112.29
8170E-080C	8	1	0	101	2442.08

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002C	1/4	25	150	101	75.87
8170V-003C	3/8	25	150	101	75.87
8170V-005C	1/2	25	0	101	75.87
8170V-007C	3/4	25	0	101	87.28
8170V-010C	1	25	0	101	101.03
8170V-012C	1-1/4	20	0	101	124.14
8170V-015C	1-1/2	20	0	101	129.41
8170V-020C	2	15	0	101	195.92
8170V-025C	2-1/2	4	0	101	281.99
8170V-030C	3	4	0	101	335.71
8170V-040C	4	2	0	101	743.57
8170V-060C	6	1	0	101	1868.71
8170V-080C	8	1	0	101	4371.39

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002C	1/4	25	150	101	50.87
8171-003C	3/8	25	200	101	50.87
8171-005C	1/2	25	0	101	50.87
8171-007C	3/4	25	0	101	60.52
8171-010C	1	25	0	101	67.93
8171-012C	1-1/4	20	0	101	86.64
8171-015C	1-1/2	20	0	101	94.34
8171-020C	2	15	0	101	133.18
8171-025C	2-1/2	4	0	101	195.74
8171-030C	3	4	0	101	232.99
8171-040C	4	2	0	101	388.28
8171-060C	6	1	0	101	1067.80

Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002C	1/4	25	150	101	57.86
8171E-003C	3/8	25	200	101	57.86
8171E-005C	1/2	25	0	101	57.86
8171E-007C	3/4	25	0	101	64.94
8171E-010C	1	25	0	101	75.41
8171E-012C	1-1/4	20	0	101	95.43
8171E-015C	1-1/2	20	0	101	100.13
8171E-020C	2	15	0	101	144.36
8171E-025C	2-1/2	4	0	101	205.05
8171E-030C	3	4	0	101	244.13
8171E-040C	4	2	0	101	405.24
8171E-060C	6	1	0	101	1112.28