

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing

Socket x Socket x Socket x Socket



Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	775.56
876-420CF ²	4X2	1	2	097	975.65
876-421CF ²	4X2-1/2	1	2	097	1032.48
876-422CF ²	4X3	1	2	097	1111.61
876-528CF ²	6X2	1	3	097	1659.31
876-529CF ²	6X2-1/2	1	2	097	1679.97
876-530CF ²	6X3	1	2	097	1707.31
876-532CF ²	6X4	1	0	097	1896.01
876-578CF ²	8X2	1	2	097	2835.66
876-579CF ²	8X2-1/2	1	2	097	2877.57
876-580CF ²	8X3	1	2	097	2900.36
876-582CF ²	8X4	1	0	097	3122.43
876-585CF ²	8X6	1	0	097	3291.73
876-621CF ²	10X2	1	0	097	3418.82
876-622CF ²	10X2-1/2	1	0	097	3490.12
876-623CF ²	10X3	1	0	097	3552.07
876-624CF ²	10X4	1	0	097	3634.20
876-626CF ²	10X6	1	0	097	3891.19
876-628CF ²	10X8	1	0	097	4087.01
876-661CF ²	12X2	1	0	097	3680.80
876-662CF ²	12X2-1/2	1	0	097	3857.27
876-663CF ²	12X3	1	0	097	3925.33
876-664CF ²	12X4	1	0	097	4069.07
876-666CF ²	12X6	1	0	097	4453.80
876-668CF ²	12X8	1	0	097	5053.04
876-670CF ²	12X10	1	0	097	5501.99

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	45.60
857-003C	3/8	25	150	090	45.60
8057-005C	1/2	20	120	090	30.34
8057-007C	3/4	20	80	090	31.69
8057-010C	1	15	90	090	38.04
8057-012C	1-1/4	10	0	090	76.97
8057-015C	1-1/2	10	0	090	78.37
8057-020C	2	5	0	090	129.91
8057-025C	2-1/2	5	0	090	213.05

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/FKM (continued)

Socket x Socket with FKM O-ring Seal

8057-030C	3	5	0	090	269.63
8057-040C	4	4	0	090	344.47
8057-060C	6	1	0	090	765.51

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	45.04
897-003C	3/8	25	150	090	45.04
8097-005C	1/2	20	120	090	30.24
8097-007C	3/4	20	80	090	31.32
8097-010C	1	15	90	090	37.52
8097-012C	1-1/4	10	0	090	75.98
8097-015C	1-1/2	10	0	090	77.42
8097-020C	2	5	0	090	128.31
8097-025C	2-1/2	5	0	090	212.49
8097-030C	3	5	0	090	266.31
8097-040C	4	4	0	090	340.57
8097-060C	6	1	0	090	756.81

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	34.54
8059-007C	3/4	20	80	090	60.26
8059-010C	1	15	90	090	83.18
8059-012C	1-1/4	10	0	090	141.16
8059-015C	1-1/2	10	0	090	158.44
8059-020C	2	5	0	090	179.12
8059-025C	2-1/2	5	0	090	290.79
8059-030C	3	5	0	090	343.95
8059-040C	4	4	0	090	397.73
8059-060C	6	1	0	090	883.84

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	33.68
8099-007C	3/4	20	80	090	59.56
8099-010C	1	15	90	090	82.15
8099-012C	1-1/4	10	0	090	156.47
8099-015C	1-1/2	10	0	090	156.47
8099-020C	2	5	0	090	176.89
8099-025C	2-1/2	5	0	090	253.40
8099-030C	3	5	0	090	339.73
8099-040C	4	4	0	090	391.88
8099-060C	6	1	0	090	870.89



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Spigot/FKM

Socket x Spigot with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005C	1/2	20	160	090	30.34
8056-007C	3/4	20	160	090	31.69
8056-010C	1	15	90	090	38.04
8056-012C	1-1/4	10	0	090	76.97
8056-015C	1-1/2	10	0	090	78.37
8056-020C	2	5	0	090	129.91
8056-025C	2-1/2	5	0	090	237.36
8056-030C	3	5	0	090	269.63
8056-040C	4	4	0	090	344.47
8056-060C	6	1	0	090	765.51

Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005C	1/2	20	160	090	30.24
8096-007C	3/4	20	80	090	31.32
8096-010C	1	15	90	090	37.52
8096-012C	1-1/4	10	0	090	75.98
8096-015C	1-1/2	10	0	090	77.42
8096-020C	2	5	0	090	128.31
8096-025C	2-1/2	5	0	090	212.49
8096-030C	3	5	0	090	266.31
8096-040C	4	4	0	090	340.57
8096-060C	6	1	0	090	756.81

Union 2000 - Special Reinforced Fipt/Spigot/FKM

SR Fipt x Spigot with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005CSR	1/2	20	160	096	39.93
8055-007CSR	3/4	20	160	096	42.02
8055-010CSR	1	15	90	096	53.56
8055-012CSR	1-1/4	10	0	096	86.08
8055-015CSR	1-1/2	10	0	096	98.54
8055-020CSR	2	5	0	096	151.39
8055-025CSR	2-1/2	5	0	096	285.75
8055-030CSR	3	5	0	096	301.95
8055-040CSR	4	4	0	096	390.04
8055-060CSR	6	1	0	096	848.97

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/Spigot/EPDM

SR Fipt x Spigot with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005CSR	1/2	20	120	096	39.56
8095-007CSR	3/4	20	160	096	40.93
8095-010CSR	1	15	90	096	52.48
8095-012CSR	1-1/4	10	0	096	80.61
8095-015CSR	1-1/2	10	0	096	91.56
8095-020CSR	2	5	0	096	138.17
8095-025CSR	2-1/2	5	0	096	274.22
8095-030CSR	3	5	0	096	295.61
8095-040CSR	4	4	0	096	373.03
8095-060CSR	6	1	0	096	814.05

Union 2000 - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002C	1/4	25	150	090	51.27
858-003C	3/8	25	150	090	51.27
8058-005C	1/2	20	120	090	32.49
8058-007C	3/4	20	80	090	57.43
8058-010C	1	15	90	090	79.19
8058-012C	1-1/4	10	0	090	150.89
8058-015C	1-1/2	10	0	090	150.89
8058-020C	2	5	0	090	170.56
8058-025C	2-1/2	5	0	090	274.78
8058-030C	3	5	0	090	521.39
8058-040C	4	4	0	090	560.46
8058-060C	6	1	0	090	1245.51

Union 2000 - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002C	1/4	25	150	090	50.66
898-003C	3/8	25	100	090	50.66
8098-005C	1/2	20	120	090	32.08
8098-007C	3/4	20	80	090	56.72
8098-010C	1	15	90	090	78.22
8098-012C	1-1/4	10	0	090	149.14
8098-015C	1-1/2	10	0	090	149.14
8098-020C	2	5	0	090	168.48
8098-025C	2-1/2	5	0	090	237.36
8098-030C	3	5	0	090	472.25
8098-040C	4	4	0	090	549.80
8098-060C	6	1	0	090	1221.75

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	17.87
8059-007CSR	3/4	20	160	096	31.53
8059-010CSR	1	15	90	096	43.43
8059-012CSR	1-1/4	10	0	096	82.81
8059-015CSR	1-1/2	10	0	096	90.02
8059-020CSR	2	5	0	096	93.72
8059-025CSR	2-1/2	5	0	096	162.27
8059-030CSR	3	5	0	096	263.64
8059-040CSR	4	4	0	096	307.59
8059-060CSR	6	1	0	096	683.60

Union 2000 - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	17.52
8099-007CSR	3/4	20	160	096	31.11
8099-010CSR	1	15	90	096	43.07
8099-012CSR	1-1/4	10	0	096	81.60
8099-015CSR	1-1/2	10	0	096	88.75
8099-020CSR	2	5	0	096	93.45
8099-025CSR	2-1/2	5	0	096	160.28
8099-030CSR	3	5	0	096	260.34
8099-040CSR	4	4	0	096	305.74
8099-060CSR	6	1	0	096	679.44

Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	18.34
8058-007CSR	3/4	20	80	096	31.97
8058-010CSR	1	15	90	096	43.94
8058-012CSR	1-1/4	10	0	096	82.81
8058-015CSR	1-1/2	10	0	096	90.37
8058-020CSR	2	5	0	096	95.22
8058-025CSR	2-1/2	5	0	096	164.85
8058-030CSR	3	5	0	096	269.08
8058-040CSR	4	4	0	096	315.24
8058-060CSR	6	1	0	096	709.95

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/EPDM

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	17.73
8098-007CSR	3/4	20	80	096	31.67
8098-010CSR	1	15	90	096	43.43
8098-012CSR	1-1/4	10	0	096	82.01
8098-015CSR	1-1/2	10	0	096	89.67
8098-020CSR	2	5	0	096	94.28
8098-025CSR	2-1/2	5	0	096	162.94
8098-030CSR	3	5	0	096	264.92
8098-040CSR	4	4	0	096	306.69
8098-060CSR	6	1	0	096	681.54

Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005C	1/2	15	90	090	30.34
857-007C	3/4	10	60	090	31.69
857-010C	1	10	40	090	38.04
857-012C	1-1/4	5	20	090	76.97
857-015C	1-1/2	5	0	090	78.37
857-020C	2	5	0	090	129.91
857-025C	2-1/2	5	0	090	213.05
857-030C	3	5	0	090	269.63
857-040C	4	4	0	090	344.47

Union (Old Style) - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005C	1/2	15	90	090	30.24
897-007C	3/4	10	60	090	31.32
897-010C	1	10	40	090	37.52
897-012C	1-1/4	5	20	090	75.98
897-015C	1-1/2	5	0	090	77.42
897-020C	2	5	0	090	128.31
897-025C	2-1/2	5	0	090	212.49
897-030C	3	5	0	090	266.31
897-040C	4	4	0	090	340.57

Union (Old Style) - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005C	1/2	15	90	090	34.54
859-007C	3/4	10	40	090	60.26
859-010C	1	10	40	090	83.18



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Union (Old Style) - Socket/Fipt/FKM (continued)					
Socket x Fipt with FKM O-ring Seal					
859-012C	1-1/4	5	20	090	158.44
859-015C	1-1/2	5	0	090	158.44
859-020C	2	5	0	090	179.12
859-025C	2-1/2	5	0	090	290.79
859-030C	3	5	0	090	343.95
859-040C	4	4	0	090	397.73

Union (Old Style) - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005C	1/2	15	90	090	33.68
899-007C	3/4	10	60	090	59.56
899-010C	1	10	40	090	82.15
899-012C	1-1/4	5	20	090	156.47
899-015C	1-1/2	5	0	090	156.47
899-020C	2	5	0	090	176.89
899-025C	2-1/2	5	0	090	253.40
899-030C	3	5	0	090	339.73
899-040C	4	4	0	090	391.88

Union - Socket/Brass Fipt/FKM

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005CBR	1/2	10	60	096	113.51
859-007CBR	3/4	10	20	096	161.96
859-010CBR	1	10	0	096	180.39
859-012CBR	1-1/4	5	0	096	302.39
859-015CBR	1-1/2	5	0	096	343.63
859-020CBR	2	5	0	096	388.38

Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005CBR	1/2	10	60	096	117.73
899-007CBR	3/4	10	40	096	159.21
899-010CBR	1	10	0	096	178.17
899-012CBR	1-1/4	5	20	096	298.57
899-015CBR	1-1/2	5	0	096	339.24
899-020CBR	2	5	0	096	383.61

Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005C	1/2	15	90	090	32.49
858-007C	3/4	10	60	090	57.43
858-010C	1	10	40	090	79.19
858-012C	1-1/4	5	20	090	150.89
858-015C	1-1/2	5	0	090	150.89
858-020C	2	5	0	090	170.56
858-025C	2-1/2	5	0	090	274.78
858-030C	3	5	0	090	521.39
858-040C	4	4	0	090	560.46

Union (Old Style) - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005C	1/2	15	90	090	32.08
898-007C	3/4	10	60	090	56.72
898-010C	1	10	40	090	78.22
898-012C	1-1/4	5	20	090	149.14
898-015C	1-1/2	5	0	090	149.14
898-020C	2	5	0	090	168.48
898-025C	2-1/2	5	0	090	237.36
898-030C	3	5	0	090	472.25
898-040C	4	4	0	090	549.80

Union (Old Style) - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	28.13
859-003CSR	3/8	25	100	096	28.13
859-005CSR	1/2	10	60	096	17.87
859-007CSR	3/4	10	60	096	31.53
859-010CSR	1	10	40	096	43.43
859-012CSR	1-1/4	5	20	096	82.81
859-015CSR	1-1/2	5	0	096	90.02
859-020CSR	2	5	0	096	93.72
859-030CSR	3	5	0	096	263.64
859-040CSR	4	4	0	096	307.59

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	27.94
899-003CSR	3/8	25	100	096	27.94
899-005CSR	1/2	10	60	096	17.52

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings & Tank Adapters



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Union (Old Style) - Socket/Special Reinforced Fipt/EPDM					
(continued)					
Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar					
899-007CSR	3/4	10	40	096	31.11
899-010CSR	1	10	40	096	43.07
899-012CSR	1-1/4	5	20	096	81.60
899-015CSR	1-1/2	5	0	096	88.75
899-020CSR	2	5	0	096	93.45
899-030CSR	3	5	0	096	260.34
899-040CSR	4	4	0	096	305.74

Tank Adapters

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8170-002C	1/4	25	150	101	53.55
8170-003C	3/8	25	150	101	53.55
8170-005C	1/2	25	0	101	53.55
8170-007C	3/4	25	0	101	63.71
8170-010C	1	25	0	101	71.51
8170-012C	1-1/4	20	0	101	91.20
8170-015C	1-1/2	20	0	101	99.31
8170-020C	2	15	0	101	140.19
8170-025C	2-1/2	4	0	101	206.04
8170-030C	3	4	0	101	245.25
8170-040C	4	2	0	101	408.72
8170-060C	6	1	0	101	1124.00
8170-080C	8	1	0	101	2497.60

Tank Adapters, CPVC New Style Standard with EPDM Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8170E-002C	1/4	25	150	101	60.91
8170E-003C	3/8	25	150	101	60.91
8170E-005C	1/2	25	0	101	60.91
8170E-007C	3/4	25	0	101	68.36
8170E-010C	1	25	0	101	79.38
8170E-012C	1-1/4	20	0	101	100.45
8170E-015C	1-1/2	20	0	101	105.40
8170E-020C	2	15	0	101	151.96
8170E-025C	2-1/2	4	0	101	215.84
8170E-030C	3	4	0	101	256.98
8170E-040C	4	2	0	101	426.57
8170E-060C	6	1	0	101	1170.83
8170E-080C	8	1	0	101	2570.61

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8170V-002C	1/4	25	150	101	79.86
8170V-003C	3/8	25	150	101	79.86
8170V-005C	1/2	25	0	101	79.86
8170V-007C	3/4	25	0	101	91.87
8170V-010C	1	25	0	101	106.35
8170V-012C	1-1/4	20	0	101	130.67
8170V-015C	1-1/2	20	0	101	136.22
8170V-020C	2	15	0	101	206.23
8170V-025C	2-1/2	4	0	101	296.83
8170V-030C	3	4	0	101	353.38
8170V-040C	4	2	0	101	782.71
8170V-060C	6	1	0	101	1967.06
8170V-080C	8	1	0	101	4601.46

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets



Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171-002C	1/4	25	150	101	53.55
8171-003C	3/8	25	200	101	53.55
8171-005C	1/2	25	0	101	53.55
8171-007C	3/4	25	0	101	63.71
8171-010C	1	25	0	101	71.51
8171-012C	1-1/4	20	0	101	91.20
8171-015C	1-1/2	20	0	101	99.31
8171-020C	2	15	0	101	140.19
8171-025C	2-1/2	4	0	101	206.04
8171-030C	3	4	0	101	245.25
8171-040C	4	2	0	101	408.72
8171-060C	6	1	0	101	1124.00

Tank Adapters, CPVC New Style Standard with EPDM Gaskets



Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171E-002C	1/4	25	150	101	60.91
8171E-003C	3/8	25	200	101	60.91
8171E-005C	1/2	25	0	101	60.91
8171E-007C	3/4	25	0	101	68.36
8171E-010C	1	25	0	101	79.38
8171E-012C	1-1/4	20	0	101	100.45
8171E-015C	1-1/2	20	0	101	105.40
8171E-020C	2	15	0	101	151.96
8171E-025C	2-1/2	4	0	101	215.84
8171E-030C	3	4	0	101	256.98
8171E-040C	4	2	0	101	426.57
8171E-060C	6	1	0	101	1170.82