



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Socket					
847-060C	6	4	0	090	377.68
847-080C	8	3	0	090	1146.14
847-100CF	10	1	5	097	957.54
847-120CF	12	1	4	097	1049.45
847-140CF	14	1	2	097	3219.02
847-160CF	16	1	2	097	4734.37
847-180CF	18	1	0	097	5837.13
847-200CF	20	1	0	097	7857.49
847-240CF	24	1	0	097	14995.71

Cap

Fipt

848-002C	1/4	25	450	090	13.53
848-003C	3/8	25	450	090	13.53
848-005C	1/2	25	150	090	11.62
848-007C	3/4	25	300	090	19.23
848-010C	1	15	90	090	26.93
848-012C	1-1/4	10	60	090	48.02
848-015C	1-1/2	10	120	090	49.20
848-020C	2	10	80	090	70.87
848-025C	2-1/2	5	40	090	163.99
848-030C	3	5	0	090	215.14
848-040C	4	5	0	090	312.52
848-060CF	6	1	4	097	442.15
848-080CF	8	1	0	097	479.77

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	7.43
848-003CSR	3/8	25	450	096	7.43
848-005CSR	1/2	50	300	096	6.64
848-007CSR	3/4	25	300	096	11.58
848-030CSR	3	5	0	096	129.26

Plugs

Plug

Spigot

849-005C	1/2	50	300	090	13.32
849-007C	3/4	50	300	090	16.43
849-010C	1	50	200	090	18.54
849-012C	1-1/4	25	100	090	23.64
849-015C	1-1/2	10	120	090	25.94
849-020C	2	10	120	090	34.75

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug (continued)

Spigot

849-025CF ⁴	2-1/2	1	8	097	41.22
849-030CF ⁴	3	1	4	097	94.78
849-040CF ⁴	4	1	4	097	116.96
849-060CF ⁴	6	1	6	097	145.21
849-080CF ⁴	8	1	6	097	390.03
849-100CF ⁴	10	1	2	097	776.02
849-120CF ⁴	12	1	0	097	1504.04

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt

850-002C	1/4	50	900	090	10.88
850-003C	3/8	50	450	090	10.88
850-005C	1/2	50	500	090	9.45
850-007C	3/4	50	300	090	11.97
850-010C	1	25	175	090	19.69
850-012C	1-1/4	25	150	090	22.38
850-015C	1-1/2	25	150	090	24.67
850-020C	2	10	120	090	33.59
850-025C	2-1/2	5	30	090	57.02
850-030C	3	5	40	090	61.06
850-040C	4	5	0	090	108.35
850-060C	6	6	0	090	152.15
850-060CF ⁴	6	1	2	097	392.87
850-080C	8	4	0	090	270.37
850-080CF ⁴	8	1	2	097	754.35
850-100CF ⁴	10	1	3	097	1088.79
850-120CF ⁴	12	1	0	097	1660.75

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	17.27
875-007C	3/4	25	0	090	17.84
875-010C	1	20	0	090	30.06
875-012C	1-1/4	20	0	090	45.53
875-015C	1-1/2	20	0	090	48.94
875-020C	2	10	0	090	119.84
875-025C	2-1/2	6	0	090	381.87
875-030C	3	5	0	090	590.92
875-040C	4	4	0	090	624.75

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

875-060C	6	3	0	090	855.07
875-080C	8	1	0	090	1460.26
875-080CF ²	8	1	0	097	1277.21
875-100CF ²	10	1	0	097	2194.08
875-120CF ²	12	1	0	097	3056.05
875-140CF ²	14	1	0	097	10625.08
875-160CF ²	16	1	0	097	13327.32
875-180CF ²	18	1	0	097	19339.49

¹ Sized with Bushing
² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C ¹	3/4X1/2	25	0	090	25.51
875-130C ¹	1X1/2	20	0	090	42.03
875-131C ¹	1X3/4	20	0	090	42.03
875-166C ¹	1-1/4X1/2	20	0	090	76.61
875-167C ¹	1-1/4X3/4	20	0	090	76.61
875-168C ¹	1-1/4X1	20	0	090	76.61
875-209C ¹	1-1/2X1/2	20	0	090	84.03
875-210C ¹	1-1/2X3/4	20	0	090	84.03
875-211C ¹	1-1/2X1	20	0	090	84.03
875-212C ¹	1-1/2X1-1/4	20	0	090	84.03
875-247C ¹	2X1/2	10	0	090	166.27
875-248C ¹	2X3/4	10	0	090	166.27
875-249C ¹	2X1	10	0	090	166.27
875-250C ¹	2X1-1/4	10	0	090	166.27
875-251C ¹	2X1-1/2	10	0	090	166.27
875-335C ¹	3X1	5	0	090	683.95
875-336C ¹	3X1-1/4	5	0	090	683.95
875-337C ¹	3X1-1/2	5	0	090	683.95
875-338C ¹	3X2	4	0	090	683.95
875-339C ¹	3X2-1/2	5	0	090	683.95
875-420C	4X2	4	0	090	691.61
875-422C ¹	4X3	4	0	090	691.61
875-528C ¹	6X2	5	0	090	876.00
875-528CF ²	6X2	1	3	097	687.29
875-530C ¹	6X3	5	0	090	875.83
875-530CF ²	6X3	1	2	097	764.15
875-532C	6X4	5	0	090	668.77
875-578C ¹	8X2	1	0	090	2316.54
875-578CF ²	8X2	1	2	097	923.91
875-579CF ²	8X2-1/2	1	2	097	968.36
875-580C ¹	8X3	2	0	090	2316.54

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-580CF ²	8X3	1	2	097	946.88
875-582C	8X4	2	0	090	2316.54
875-582CF ²	8X4	1	2	097	972.48
875-585C ¹	8X6	1	0	090	2122.94
875-585CF ²	8X6	1	0	097	1350.87
875-621CF ²	10X2	1	0	097	1029.24
875-623CF ²	10X3	1	0	097	1095.72
875-624CF ²	10X4	1	0	097	1339.03
875-626C	10X6	1	0	091	2393.13
875-626CF ²	10X6	1	0	097	1520.38
875-628C	10X8	1	0	091	2519.71
875-628CF ²	10X8	1	0	097	1790.38
875-661CF ²	12X2	1	0	097	1698.16
875-663CF ²	12X3	1	0	097	1784.05
875-664CF ²	12X4	1	0	097	2035.09
875-666CF ²	12X6	1	0	097	2117.04
875-668CF ²	12X8	1	0	097	2234.54
875-670CF ²	12X10	1	0	097	2751.15
875-694CF ²	14X4	1	0	097	4555.11
875-696CF ²	14X6	1	0	097	5003.17
875-698CF ²	14X8	1	0	097	5412.15
875-700CF	14X10	1	0	097	6307.81
875-702CF ²	14X12	1	0	097	6593.25
875-754CF ²	16X4	1	0	097	5731.66
875-756CF ²	16X6	1	0	097	6035.16
875-758CF ²	16X8	1	0	097	7007.73
875-760CF ²	16X10	1	0	097	7875.69
875-762CF ²	16X12	1	0	097	8541.56
875-764CF ²	16X14	1	0	097	10745.01
875-784CF ²	18X4	1	0	097	7662.35
875-786CF ²	18X6	1	0	097	8223.53
875-788CF ²	18X8	1	0	097	9129.23
875-790CF ²	18X10	1	0	097	10064.67
875-792CF ²	18X12	1	0	097	11068.66
875-794CF ²	18X14	1	0	097	14093.60
875-796CF ²	18X16	1	0	097	15694.45

¹ Sized with Bushing
² Fiberglass reinforced

Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum internal Pressure Rating @ 73°F (23°C)

876-020CF ²	2	1	4	097	497.38
876-030CF ²	3	1	4	097	634.41
876-040CF ²	4	1	2	097	1087.77
876-060CF ²	6	1	0	097	1896.52
876-080CF ²	8	1	0	097	3401.32
876-100CF ²	10	1	0	097	3691.18
876-120CF ²	12	1	0	097	5530.32

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.





Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	736.78
876-420CF ²	4X2	1	2	097	926.87
876-421CF ²	4X2-1/2	1	2	097	980.86
876-422CF ²	4X3	1	2	097	1056.03
876-528CF ²	6X2	1	3	097	1576.34
876-529CF ²	6X2-1/2	1	2	097	1595.97
876-530CF ²	6X3	1	2	097	1621.94
876-532CF ²	6X4	1	0	097	1801.21
876-578CF ²	8X2	1	2	097	2693.88
876-579CF ²	8X2-1/2	1	2	097	2733.69
876-580CF ²	8X3	1	2	097	2755.34
876-582CF ²	8X4	1	0	097	2966.31
876-585CF ²	8X6	1	0	097	3127.14
876-621CF ²	10X2	1	0	097	3247.88
876-622CF ²	10X2-1/2	1	0	097	3315.61
876-623CF ²	10X3	1	0	097	3374.47
876-624CF ²	10X4	1	0	097	3452.49
876-626CF ²	10X6	1	0	097	3696.63
876-628CF ²	10X8	1	0	097	3882.66
876-661CF ²	12X2	1	0	097	3496.76
876-662CF ²	12X2-1/2	1	0	097	3664.41
876-663CF ²	12X3	1	0	097	3729.06
876-666CF ²	12X6	1	0	097	4231.11
876-668CF ²	12X8	1	0	097	4800.39
876-664CF ²	12X4	1	0	097	3865.62
876-670CF ²	12X10	1	0	097	5226.89

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	43.32
857-003C	3/8	25	150	090	43.32
8057-005C	1/2	20	120	090	28.82
8057-007C	3/4	20	80	090	30.11
8057-010C	1	15	90	090	36.14
8057-012C	1-1/4	10	0	090	73.12
8057-015C	1-1/2	10	0	090	74.45
8057-020C	2	5	0	090	123.41
8057-025C	2-1/2	5	0	090	202.40
8057-030C	3	5	0	090	256.15

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/FKM (continued)

Socket x Socket with FKM O-ring Seal

8057-040C	4	4	0	090	327.25
8057-060C	6	1	0	090	727.23

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	42.79
897-003C	3/8	25	150	090	42.79
8097-005C	1/2	20	120	090	28.73
8097-007C	3/4	20	80	090	29.75
8097-010C	1	15	90	090	35.64
8097-012C	1-1/4	10	0	090	72.18
8097-015C	1-1/2	10	0	090	73.55
8097-020C	2	5	0	090	121.89
8097-025C	2-1/2	5	0	090	201.87
8097-030C	3	5	0	090	252.99
8097-040C	4	4	0	090	323.54
8097-060C	6	1	0	090	718.97

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	32.81
8059-007C	3/4	20	80	090	57.25
8059-010C	1	15	90	090	79.02
8059-012C	1-1/4	10	0	090	134.10
8059-015C	1-1/2	10	0	090	150.52
8059-020C	2	5	0	090	170.16
8059-025C	2-1/2	5	0	090	276.25
8059-030C	3	5	0	090	326.75
8059-040C	4	4	0	090	377.84
8059-060C	6	1	0	090	839.65

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	32.00
8099-007C	3/4	20	80	090	56.58
8099-010C	1	15	90	090	78.04
8099-012C	1-1/4	10	0	090	148.65
8099-015C	1-1/2	10	0	090	148.65
8099-020C	2	5	0	090	168.05
8099-025C	2-1/2	5	0	090	240.73
8099-030C	3	5	0	090	322.74
8099-040C	4	4	0	090	372.29
8099-060C	6	1	0	090	827.35