



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**

**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap - Special Reinforced (continued)</b>					
<b>SR Fipt - Stainless Steel Collar</b>					
848-005CSR	1/2	50	300	096	7.36
848-007CSR	3/4	25	300	096	12.83
848-030CSR	3	5	0	096	143.22

**Plugs**

**Plug**

**Spigot**



849-005C	1/2	50	300	090	14.76
849-007C	3/4	50	300	090	18.20
849-010C	1	50	200	090	20.55
849-012C	1-1/4	25	100	090	26.19
849-015C	1-1/2	10	120	090	28.75
849-020C	2	10	120	090	38.51
849-025CF <sup>4</sup>	2-1/2	1	8	097	45.67
849-030CF <sup>4</sup>	3	1	4	097	105.02
849-040CF <sup>4</sup>	4	1	4	097	129.60
849-060CF <sup>4</sup>	6	1	6	097	160.89
849-080CF <sup>4</sup>	8	1	6	097	432.17
849-100CF <sup>4</sup>	10	1	2	097	859.85
849-120CF <sup>4</sup>	12	1	0	097	1666.53

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Plug**

**Mipt**



850-002C	1/4	50	900	090	12.05
850-003C	3/8	50	450	090	12.05
850-005C	1/2	50	500	090	10.47
850-007C	3/4	50	300	090	13.26
850-010C	1	25	175	090	21.82
850-012C	1-1/4	25	150	090	24.80
850-015C	1-1/2	25	150	090	27.34
850-020C	2	10	120	090	37.22
850-025C	2-1/2	5	30	090	63.18
850-030C	3	5	40	090	67.65
850-040C	4	5	0	090	120.05
850-060C	6	6	0	090	168.59
850-060CF <sup>4</sup>	6	1	2	097	435.32
850-080C	8	6	0	090	299.58
850-080CF <sup>4</sup>	8	1	2	097	835.84
850-100CF <sup>4</sup>	10	1	3	097	1206.41
850-120CF <sup>4</sup>	12	1	0	097	1840.17

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	19.14
875-007C	3/4	25	0	090	19.77
875-010C	1	20	0	090	33.31
875-012C	1-1/4	20	0	090	50.45
875-015C	1-1/2	20	0	090	54.23
875-020C	2	10	0	090	132.79
875-025C	2-1/2	6	0	090	423.13
875-030C	3	5	0	090	654.76
875-040C	4	4	0	090	692.24
875-060C	6	3	0	090	947.44
875-080C	8	1	0	090	1618.02
875-080CF <sup>2</sup>	8	1	0	097	1415.19
875-100CF <sup>2</sup>	10	1	0	097	2431.12
875-120CF <sup>2</sup>	12	1	0	097	3386.20
875-140CF <sup>2</sup>	14	1	0	097	11772.94
875-160CF <sup>2</sup>	16	1	0	097	14767.12
875-180CF <sup>2</sup>	18	1	0	097	21428.80
875-200CF <sup>2</sup>	20	1	0	097	24888.44
875-240CF <sup>2</sup>	24	1	0	097	31799.86

<sup>2</sup> Fiberglass reinforced

**Wye - Reducing**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C <sup>1</sup>	3/4X1/2	25	0	090	28.26
875-130C <sup>1</sup>	1X1/2	20	0	090	46.57
875-131C <sup>1</sup>	1X3/4	20	0	090	46.57
875-166C <sup>1</sup>	1-1/4X1/2	20	0	090	84.88
875-167C <sup>1</sup>	1-1/4X3/4	20	0	090	84.88
875-168C <sup>1</sup>	1-1/4X1	20	0	090	84.88
875-209C <sup>1</sup>	1-1/2X1/2	20	0	090	93.11
875-210C <sup>1</sup>	1-1/2X3/4	20	0	090	93.11
875-211C <sup>1</sup>	1-1/2X1	20	0	090	93.11
875-212C <sup>1</sup>	1-1/2X1-1/4	20	0	090	93.11
875-247C <sup>1</sup>	2X1/2	10	0	090	184.23
875-248C <sup>1</sup>	2X3/4	10	0	090	184.23

Schedule 80 CPVC Product  
**CPVC Schedule 80 Fittings**



**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Wye - Reducing (continued)</b>					
<b>Socket x Socket x Socket</b>					
875-249C <sup>1</sup>	2X1	10	0	090	184.23
875-250C <sup>1</sup>	2X1-1/4	10	0	090	184.23
875-251C <sup>1</sup>	2X1-1/2	10	0	090	184.23
875-335C <sup>1</sup>	3X1	5	0	090	757.84
875-336C <sup>1</sup>	3X1-1/4	5	0	090	757.84
875-337C <sup>1</sup>	3X1-1/2	5	0	090	757.84
875-338C <sup>1</sup>	3X2	4	0	090	757.84
875-339C <sup>1</sup>	3X2-1/2	5	0	090	757.84
875-420C	4X2	4	0	090	766.33
875-422C	4X3	4	0	090	766.33
875-528C <sup>1</sup>	6X2	5	0	090	970.64
875-528CF <sup>2</sup>	6X2	1	3	097	761.54
875-530C <sup>1</sup>	6X3	5	0	090	970.45
875-530CF <sup>2</sup>	6X3	1	2	097	846.71
875-532C	6X4	5	0	090	741.02
875-578C <sup>1</sup>	8X2	2	0	090	2566.80
875-578CF <sup>2</sup>	8X2	1	2	097	1023.73
875-579CF <sup>2</sup>	8X2-1/2	1	2	097	1072.98
875-580C <sup>1</sup>	8X3	2	0	090	2566.80
875-580CF <sup>2</sup>	8X3	1	2	097	1049.18
875-582C	8X4	2	0	090	2566.80
875-582CF <sup>2</sup>	8X4	1	2	097	1077.54
875-585C <sup>1</sup>	8X6	1	0	090	2352.28
875-585CF <sup>2</sup>	8X6	1	0	097	1496.81
875-621CF <sup>2</sup>	10X2	1	0	097	1140.43
875-623CF <sup>2</sup>	10X3	1	0	097	1214.09
875-624CF <sup>2</sup>	10X4	1	0	097	1483.69
875-626C	10X6	1	0	091	2651.66
875-626CF <sup>2</sup>	10X6	1	0	097	1684.63
875-628C	10X8	1	0	091	2791.93
875-628CF <sup>2</sup>	10X8	1	0	097	1983.80
875-661CF <sup>2</sup>	12X2	1	0	097	1881.62
875-663CF <sup>2</sup>	12X3	1	0	097	1976.79
875-664CF <sup>2</sup>	12X4	1	0	097	2254.95
875-666CF <sup>2</sup>	12X6	1	0	097	2345.75
875-668CF <sup>2</sup>	12X8	1	0	097	2475.95
875-670CF <sup>2</sup>	12X10	1	0	097	3048.37
875-694CF <sup>2</sup>	14X4	1	0	097	5047.21
875-696CF <sup>2</sup>	14X6	1	0	097	5543.67
875-698CF <sup>2</sup>	14X8	1	0	097	5996.84
875-700CF <sup>2</sup>	14X10	1	0	097	6989.26
875-702CF <sup>2</sup>	14X12	1	0	097	7305.54
875-754CF <sup>2</sup>	16X4	1	0	097	6350.87
875-756CF <sup>2</sup>	16X6	1	0	097	6687.16
875-758CF <sup>2</sup>	16X8	1	0	097	7764.80
875-760CF <sup>2</sup>	16X10	1	0	097	8726.53
875-762CF <sup>2</sup>	16X12	1	0	097	9464.34
875-764CF <sup>2</sup>	16X14	1	0	097	11905.83
875-784CF <sup>2</sup>	18X4	1	0	097	8490.14
875-786CF <sup>2</sup>	18X6	1	0	097	9111.95
875-788CF <sup>2</sup>	18X8	1	0	097	10115.49

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye - Reducing (continued)**

**Socket x Socket x Socket**

875-790CF <sup>2</sup>	18X10	1	0	097	11151.99
875-792CF <sup>2</sup>	18X12	1	0	097	12264.44
875-794CF <sup>2</sup>	18X14	1	0	097	15616.18
875-796CF <sup>2</sup>	18X16	1	0	097	17389.97

<sup>1</sup> Sized with Bushing

<sup>2</sup> Fiberglass reinforced



**Double Wye**

**Socket x Socket x Socket x Socket**

100 psi Maximum internal Pressure Rating @ 73°F (23°C)

876-020CF <sup>2</sup>	2	1	4	097	551.12
876-030CF <sup>2</sup>	3	1	4	097	702.95
876-040CF <sup>2</sup>	4	1	2	097	1205.28
876-060CF <sup>2</sup>	6	1	0	097	2101.41
876-080CF <sup>2</sup>	8	1	0	097	3768.78
876-100CF <sup>2</sup>	10	1	0	097	4089.95
876-120CF <sup>2</sup>	12	1	0	097	6127.78

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.



**Double Wye - Reducing**

**Socket x Socket x Socket x Socket**

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	816.38
876-420CF <sup>2</sup>	4X2	1	2	097	1027.00
876-421CF <sup>2</sup>	4X2-1/2	1	2	097	1086.82
876-422CF <sup>2</sup>	4X3	1	2	097	1170.12
876-528CF <sup>2</sup>	6X2	1	3	097	1746.64
876-529CF <sup>2</sup>	6X2-1/2	1	2	097	1768.39
876-530CF <sup>2</sup>	6X3	1	2	097	1797.17
876-532CF <sup>2</sup>	6X4	1	0	097	1995.80
876-578CF <sup>2</sup>	8X2	1	2	097	2984.91
876-579CF <sup>2</sup>	8X2-1/2	1	2	097	3029.02
876-580CF <sup>2</sup>	8X3	1	2	097	3053.01
876-582CF <sup>2</sup>	8X4	1	0	097	3286.77
876-585CF <sup>2</sup>	8X6	1	0	097	3464.98
876-621CF <sup>2</sup>	10X2	1	0	097	3598.76
876-622CF <sup>2</sup>	10X2-1/2	1	0	097	3673.81
876-623CF <sup>2</sup>	10X3	1	0	097	3739.02
876-624CF <sup>2</sup>	10X4	1	0	097	3825.47
876-626CF <sup>2</sup>	10X6	1	0	097	4095.99
876-628CF <sup>2</sup>	10X8	1	0	097	4302.12
876-661CF <sup>2</sup>	12X2	1	0	097	3874.53
876-662CF <sup>2</sup>	12X2-1/2	1	0	097	4060.28
876-663CF <sup>2</sup>	12X3	1	0	097	4131.93
876-664CF <sup>2</sup>	12X4	1	0	097	4283.23
876-666CF <sup>2</sup>	12X6	1	0	097	4688.21
876-668CF <sup>2</sup>	12X8	1	0	097	5318.99



**Schedule 80 CPVC Product**  
**CPVC Schedule 80 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing (continued)**

**Socket x Socket x Socket x Socket**

876-670CF <sup>2</sup>	12X10	1	0	097	5791.57
------------------------	-------	---	---	-----	---------

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union 2000 - Socket/FKM**

**Socket x Socket with FKM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	48.00
857-003C	3/8	25	150	090	48.00
8057-005C	1/2	20	120	090	31.94
8057-007C	3/4	20	80	090	33.36
8057-010C	1	15	90	090	40.04
8057-012C	1-1/4	10	0	090	81.02
8057-015C	1-1/2	10	0	090	82.49
8057-020C	2	5	0	090	136.75
8057-025C	2-1/2	5	0	090	224.26
8057-030C	3	5	0	090	283.82
8057-040C	4	4	0	090	362.60
8057-060C	6	1	0	090	805.80

**Union 2000 - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	47.41
897-003C	3/8	25	150	090	47.41
8097-005C	1/2	20	120	090	31.83
8097-007C	3/4	20	80	090	32.97
8097-010C	1	15	90	090	39.49
8097-012C	1-1/4	10	0	090	79.98
8097-015C	1-1/2	10	0	090	81.49
8097-020C	2	5	0	090	135.06
8097-025C	2-1/2	5	0	090	223.67
8097-030C	3	5	0	090	280.33
8097-040C	4	4	0	090	358.49
8097-060C	6	1	0	090	796.64

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	36.36
8059-007C	3/4	20	80	090	63.43
8059-010C	1	15	90	090	87.56
8059-012C	1-1/4	10	0	090	148.59
8059-015C	1-1/2	10	0	090	166.78
8059-020C	2	5	0	090	188.55
8059-025C	2-1/2	5	0	090	306.09
8059-030C	3	5	0	090	362.05
8059-040C	4	4	0	090	418.66
8059-060C	6	1	0	090	930.36

**Union 2000 - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	35.45
8099-007C	3/4	20	80	090	62.69
8099-010C	1	15	90	090	86.47
8099-012C	1-1/4	10	0	090	164.71
8099-015C	1-1/2	10	0	090	164.71
8099-020C	2	5	0	090	186.20
8099-025C	2-1/2	5	0	090	266.74
8099-030C	3	5	0	090	357.61
8099-040C	4	4	0	090	412.51
8099-060C	6	1	0	090	916.73

**Union 2000 - Socket/Spigot/FKM**

**Socket x Spigot with FKM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005C	1/2	20	160	090	31.94
8056-007C	3/4	20	160	090	33.36
8056-010C	1	15	90	090	40.04
8056-012C	1-1/4	10	0	090	81.02
8056-015C	1-1/2	10	0	090	82.49
8056-020C	2	5	0	090	136.75
8056-025C	2-1/2	5	0	090	249.85
8056-030C	3	5	0	090	283.82
8056-040C	4	4	0	090	362.60
8056-060C	6	1	0	090	805.80