

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Socket					
847-060C	6	4	0	090	397.56
847-080C	8	3	0	090	1206.46
847-100CF	10	1	5	097	1007.94
847-120CF	12	1	4	097	1104.68
847-140CF	14	1	2	097	3388.44
847-160CF	16	1	2	097	4983.55
847-180CF	18	1	0	097	6144.35
847-200CF	20	1	0	097	8271.04
847-240CF	24	1	0	097	15784.96

Cap

Fipt

848-002C	1/4	25	450	090	14.24
848-003C	3/8	25	450	090	14.24
848-005C	1/2	25	150	090	12.23
848-007C	3/4	25	300	090	20.24
848-010C	1	15	90	090	28.35
848-012C	1-1/4	10	60	090	50.55
848-015C	1-1/2	10	120	090	51.79
848-020C	2	10	80	090	74.60
848-025C	2-1/2	5	40	090	172.62
848-030C	3	5	0	090	226.46
848-040C	4	5	0	090	328.97
848-060CF	6	1	4	097	465.42
848-080CF	8	1	0	097	505.02

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	7.82
848-003CSR	3/8	25	450	096	7.82
848-005CSR	1/2	50	300	096	6.99
848-007CSR	3/4	25	300	096	12.19
848-030CSR	3	5	0	096	136.06

Plugs

Plug

Spigot

849-005C	1/2	50	300	090	14.02
849-007C	3/4	50	300	090	17.29
849-010C	1	50	200	090	19.52
849-012C	1-1/4	25	100	090	24.88
849-015C	1-1/2	10	120	090	27.31
849-020C	2	10	120	090	36.58

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug (continued)

Spigot

849-025CF ⁴	2-1/2	1	8	097	43.39
849-030CF ⁴	3	1	4	097	99.77
849-040CF ⁴	4	1	4	097	123.12
849-060CF ⁴	6	1	6	097	152.85
849-080CF ⁴	8	1	6	097	410.56
849-100CF ⁴	10	1	2	097	816.86
849-120CF ⁴	12	1	0	097	1583.20

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt

850-002C	1/4	50	900	090	11.45
850-003C	3/8	50	450	090	11.45
850-005C	1/2	50	500	090	9.95
850-007C	3/4	50	300	090	12.60
850-010C	1	25	175	090	20.73
850-012C	1-1/4	25	150	090	23.56
850-015C	1-1/2	25	150	090	25.97
850-020C	2	10	120	090	35.36
850-025C	2-1/2	5	30	090	60.02
850-030C	3	5	40	090	64.27
850-040C	4	5	0	090	114.05
850-060C	6	6	0	090	160.16
850-060CF ⁴	6	1	2	097	413.55
850-080C	8	4	0	090	284.60
850-080CF ⁴	8	1	2	097	794.05
850-100CF ⁴	10	1	3	097	1146.09
850-120CF ⁴	12	1	0	097	1748.16

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	18.18
875-007C	3/4	25	0	090	18.78
875-010C	1	20	0	090	31.64
875-012C	1-1/4	20	0	090	47.93
875-015C	1-1/2	20	0	090	51.52
875-020C	2	10	0	090	126.15
875-025C	2-1/2	6	0	090	401.97
875-030C	3	5	0	090	622.02
875-040C	4	4	0	090	657.63



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye (continued)					
Socket x Socket x Socket					
875-060C	6	3	0	090	900.07
875-080C	8	1	0	090	1537.12
875-080CF ²	8	1	0	097	1344.43
875-100CF ²	10	1	0	097	2309.56
875-120CF ²	12	1	0	097	3216.89
875-140CF ²	14	1	0	097	11184.29
875-160CF ²	16	1	0	097	14028.76
875-180CF ²	18	1	0	097	20357.36

² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C ¹	3/4X1/2	25	0	090	26.85
875-130C ¹	1X1/2	20	0	090	44.24
875-131C ¹	1X3/4	20	0	090	44.24
875-166C ¹	1-1/4X1/2	20	0	090	80.64
875-167C ¹	1-1/4X3/4	20	0	090	80.64
875-168C ¹	1-1/4X1	20	0	090	80.64
875-209C ¹	1-1/2X1/2	20	0	090	88.45
875-210C ¹	1-1/2X3/4	20	0	090	88.45
875-211C ¹	1-1/2X1	20	0	090	88.45
875-212C ¹	1-1/2X1-1/4	20	0	090	88.45
875-247C ¹	2X1/2	10	0	090	175.02
875-248C ¹	2X3/4	10	0	090	175.02
875-249C ¹	2X1	10	0	090	175.02
875-250C ¹	2X1-1/4	10	0	090	175.02
875-251C ¹	2X1-1/2	10	0	090	175.02
875-335C ¹	3X1	5	0	090	719.95
875-336C ¹	3X1-1/4	5	0	090	719.95
875-337C ¹	3X1-1/2	5	0	090	719.95
875-338C ¹	3X2	4	0	090	719.95
875-339C ¹	3X2-1/2	5	0	090	719.95
875-420C	4X2	4	0	090	728.01
875-422C ¹	4X3	4	0	090	728.01
875-528C ¹	6X2	5	0	090	922.11
875-528CF ²	6X2	1	3	097	723.46
875-530C ¹	6X3	5	0	090	921.93
875-530CF ²	6X3	1	2	097	804.37
875-532C	6X4	5	0	090	703.97
875-578C ¹	8X2	2	0	090	2438.46
875-578CF ²	8X2	1	2	097	972.54
875-579CF ²	8X2-1/2	1	2	097	1019.33
875-580C ¹	8X3	2	0	090	2438.46

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-580CF ²	8X3	1	2	097	996.72
875-582C	8X4	2	0	090	2438.46
875-582CF ²	8X4	1	2	097	1023.66
875-585C ¹	8X6	1	0	090	2234.67
875-585CF ²	8X6	1	0	097	1421.97
875-621CF ²	10X2	1	0	097	1083.41
875-623CF ²	10X3	1	0	097	1153.39
875-624CF ²	10X4	1	0	097	1409.51
875-626C	10X6	1	0	091	2519.08
875-626CF ²	10X6	1	0	097	1600.40
875-628C	10X8	1	0	091	2652.33
875-628CF ²	10X8	1	0	097	1884.61
875-661CF ²	12X2	1	0	097	1787.54
875-663CF ²	12X3	1	0	097	1877.95
875-664CF ²	12X4	1	0	097	2142.20
875-666CF ²	12X6	1	0	097	2228.46
875-668CF ²	12X8	1	0	097	2352.15
875-670CF ²	12X10	1	0	097	2895.95
875-694CF ²	14X4	1	0	097	4794.85
875-696CF ²	14X6	1	0	097	5266.49
875-698CF ²	14X8	1	0	097	5697.00
875-700CF	14X10	1	0	097	6639.80
875-702CF ²	14X12	1	0	097	6940.26
875-754CF ²	16X4	1	0	097	6033.33
875-756CF ²	16X6	1	0	097	6352.80
875-758CF ²	16X8	1	0	097	7376.56
875-760CF ²	16X10	1	0	097	8290.20
875-762CF ²	16X12	1	0	097	8991.12
875-764CF ²	16X14	1	0	097	11310.54
875-784CF ²	18X4	1	0	097	8065.63
875-786CF ²	18X6	1	0	097	8656.35
875-788CF ²	18X8	1	0	097	9609.72
875-790CF ²	18X10	1	0	097	10594.39
875-792CF ²	18X12	1	0	097	11651.22
875-794CF ²	18X14	1	0	097	14835.37
875-796CF ²	18X16	1	0	097	16520.47

¹ Sized with Bushing
² Fiberglass reinforced

Double Wye

Socket x Socket x Socket x Socket



100 psi Maximum internal Pressure Rating @ 73°F (23°C)

876-020CF ²	2	1	4	097	523.56
876-030CF ²	3	1	4	097	667.80
876-040CF ²	4	1	2	097	1145.02
876-060CF ²	6	1	0	097	1996.34
876-080CF ²	8	1	0	097	3580.34
876-100CF ²	10	1	0	097	3885.45
876-120CF ²	12	1	0	097	5821.39

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Wyes					
Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/FKM (continued)

Socket x Socket with FKM O-ring Seal

8057-030C	3	5	0	090	269.63
8057-040C	4	4	0	090	344.47
8057-060C	6	1	0	090	765.51

Double Wye - Reducing

Socket x Socket x Socket x Socket



Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	775.56
876-420CF ²	4X2	1	2	097	975.65
876-421CF ²	4X2-1/2	1	2	097	1032.48
876-422CF ²	4X3	1	2	097	1111.61
876-528CF ²	6X2	1	3	097	1659.31
876-529CF ²	6X2-1/2	1	2	097	1679.97
876-530CF ²	6X3	1	2	097	1707.31
876-532CF ²	6X4	1	0	097	1896.01
876-578CF ²	8X2	1	2	097	2835.66
876-579CF ²	8X2-1/2	1	2	097	2877.57
876-580CF ²	8X3	1	2	097	2900.36
876-582CF ²	8X4	1	0	097	3122.43
876-585CF ²	8X6	1	0	097	3291.73
876-621CF ²	10X2	1	0	097	3418.82
876-622CF ²	10X2-1/2	1	0	097	3490.12
876-623CF ²	10X3	1	0	097	3552.07
876-624CF ²	10X4	1	0	097	3634.20
876-626CF ²	10X6	1	0	097	3891.19
876-628CF ²	10X8	1	0	097	4087.01
876-661CF ²	12X2	1	0	097	3680.80
876-662CF ²	12X2-1/2	1	0	097	3857.27
876-663CF ²	12X3	1	0	097	3925.33
876-664CF ²	12X4	1	0	097	4069.07
876-666CF ²	12X6	1	0	097	4453.80
876-668CF ²	12X8	1	0	097	5053.04
876-670CF ²	12X10	1	0	097	5501.99

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	45.60
857-003C	3/8	25	150	090	45.60
8057-005C	1/2	20	120	090	30.34
8057-007C	3/4	20	80	090	31.69
8057-010C	1	15	90	090	38.04
8057-012C	1-1/4	10	0	090	76.97
8057-015C	1-1/2	10	0	090	78.37
8057-020C	2	5	0	090	129.91
8057-025C	2-1/2	5	0	090	213.05



Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	45.04
897-003C	3/8	25	150	090	45.04
8097-005C	1/2	20	120	090	30.24
8097-007C	3/4	20	80	090	31.32
8097-010C	1	15	90	090	37.52
8097-012C	1-1/4	10	0	090	75.98
8097-015C	1-1/2	10	0	090	77.42
8097-020C	2	5	0	090	128.31
8097-025C	2-1/2	5	0	090	212.49
8097-030C	3	5	0	090	266.31
8097-040C	4	4	0	090	340.57
8097-060C	6	1	0	090	756.81



Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	34.54
8059-007C	3/4	20	80	090	60.26
8059-010C	1	15	90	090	83.18
8059-012C	1-1/4	10	0	090	141.16
8059-015C	1-1/2	10	0	090	158.44
8059-020C	2	5	0	090	179.12
8059-025C	2-1/2	5	0	090	290.79
8059-030C	3	5	0	090	343.95
8059-040C	4	4	0	090	397.73
8059-060C	6	1	0	090	883.84



Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	33.68
8099-007C	3/4	20	80	090	59.56
8099-010C	1	15	90	090	82.15
8099-012C	1-1/4	10	0	090	156.47
8099-015C	1-1/2	10	0	090	156.47
8099-020C	2	5	0	090	176.89
8099-025C	2-1/2	5	0	090	253.40
8099-030C	3	5	0	090	339.73
8099-040C	4	4	0	090	391.88
8099-060C	6	1	0	090	870.89

