

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Socket					
847-060C	6	4	0	090	397.56
847-080C	8	3	0	090	1206.46
847-100CF	10	1	5	097	1007.94
847-120CF	12	1	4	097	1104.68
847-140CF	14	1	2	097	3388.44
847-160CF	16	1	2	097	4983.55
847-180CF	18	1	0	097	6144.35
847-200CF	20	1	0	097	8271.04
847-240CF	24	1	0	097	15784.96

Cap

Fipt

848-002C	1/4	25	450	090	14.24
848-003C	3/8	25	450	090	14.24
848-005C	1/2	25	150	090	12.23
848-007C	3/4	25	300	090	20.24
848-010C	1	15	90	090	28.35
848-012C	1-1/4	10	60	090	50.55
848-015C	1-1/2	10	120	090	51.79
848-020C	2	10	80	090	74.60
848-025C	2-1/2	5	40	090	172.62
848-030C	3	5	0	090	226.46
848-040C	4	5	0	090	328.97
848-060CF	6	1	4	097	465.42
848-080CF	8	1	0	097	505.02

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	7.82
848-003CSR	3/8	25	450	096	7.82
848-005CSR	1/2	50	300	096	6.99
848-007CSR	3/4	25	300	096	12.19
848-030CSR	3	5	0	096	136.06

Plugs

Plug

Spigot

849-005C	1/2	50	300	090	14.02
849-007C	3/4	50	300	090	17.29
849-010C	1	50	200	090	19.52
849-012C	1-1/4	25	100	090	24.88
849-015C	1-1/2	10	120	090	27.31
849-020C	2	10	120	090	36.58

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug (continued)

Spigot

849-025CF ⁴	2-1/2	1	8	097	43.39
849-030CF ⁴	3	1	4	097	99.77
849-040CF ⁴	4	1	4	097	123.12
849-060CF ⁴	6	1	6	097	152.85
849-080CF ⁴	8	1	6	097	410.56
849-100CF ⁴	10	1	2	097	816.86
849-120CF ⁴	12	1	0	097	1583.20

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt

850-002C	1/4	50	900	090	11.45
850-003C	3/8	50	450	090	11.45
850-005C	1/2	50	500	090	9.95
850-007C	3/4	50	300	090	12.60
850-010C	1	25	175	090	20.73
850-012C	1-1/4	25	150	090	23.56
850-015C	1-1/2	25	150	090	25.97
850-020C	2	10	120	090	35.36
850-025C	2-1/2	5	30	090	60.02
850-030C	3	5	40	090	64.27
850-040C	4	5	0	090	114.05
850-060C	6	6	0	090	160.16
850-060CF ⁴	6	1	2	097	413.55
850-080C	8	4	0	090	284.60
850-080CF ⁴	8	1	2	097	794.05
850-100CF ⁴	10	1	3	097	1146.09
850-120CF ⁴	12	1	0	097	1748.16

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	18.18
875-007C	3/4	25	0	090	18.78
875-010C	1	20	0	090	31.64
875-012C	1-1/4	20	0	090	47.93
875-015C	1-1/2	20	0	090	51.52
875-020C	2	10	0	090	126.15
875-025C	2-1/2	6	0	090	401.97
875-030C	3	5	0	090	622.02
875-040C	4	4	0	090	657.63



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

875-060C	6	3	0	090	900.07
875-080C	8	1	0	090	1537.12
875-080CF ²	8	1	0	097	1344.43
875-100CF ²	10	1	0	097	2309.56
875-120CF ²	12	1	0	097	3216.89
875-140CF ²	14	1	0	097	11184.29
875-160CF ²	16	1	0	097	14028.76
875-180CF ²	18	1	0	097	20357.36

² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C ¹	3/4X1/2	25	0	090	26.85
875-130C ¹	1X1/2	20	0	090	44.24
875-131C ¹	1X3/4	20	0	090	44.24
875-166C ¹	1-1/4X1/2	20	0	090	80.64
875-167C ¹	1-1/4X3/4	20	0	090	80.64
875-168C ¹	1-1/4X1	20	0	090	80.64
875-209C ¹	1-1/2X1/2	20	0	090	88.45
875-210C ¹	1-1/2X3/4	20	0	090	88.45
875-211C ¹	1-1/2X1	20	0	090	88.45
875-212C ¹	1-1/2X1-1/4	20	0	090	88.45
875-247C ¹	2X1/2	10	0	090	175.02
875-248C ¹	2X3/4	10	0	090	175.02
875-249C ¹	2X1	10	0	090	175.02
875-250C ¹	2X1-1/4	10	0	090	175.02
875-251C ¹	2X1-1/2	10	0	090	175.02
875-335C ¹	3X1	5	0	090	719.95
875-336C ¹	3X1-1/4	5	0	090	719.95
875-337C ¹	3X1-1/2	5	0	090	719.95
875-338C ¹	3X2	4	0	090	719.95
875-339C ¹	3X2-1/2	5	0	090	719.95
875-420C	4X2	4	0	090	728.01
875-422C ¹	4X3	4	0	090	728.01
875-528C ¹	6X2	5	0	090	922.11
875-528CF ²	6X2	1	3	097	723.46
875-530C ¹	6X3	5	0	090	921.93
875-530CF ²	6X3	1	2	097	804.37
875-532C	6X4	5	0	090	703.97
875-578C ¹	8X2	2	0	090	2438.46
875-578CF ²	8X2	1	2	097	972.54
875-579CF ²	8X2-1/2	1	2	097	1019.33
875-580C ¹	8X3	2	0	090	2438.46

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-580CF ²	8X3	1	2	097	996.72
875-582C	8X4	2	0	090	2438.46
875-582CF ²	8X4	1	2	097	1023.66
875-585C ¹	8X6	1	0	090	2234.67
875-585CF ²	8X6	1	0	097	1421.97
875-621CF ²	10X2	1	0	097	1083.41
875-623CF ²	10X3	1	0	097	1153.39
875-624CF ²	10X4	1	0	097	1409.51
875-626C	10X6	1	0	091	2519.08
875-626CF ²	10X6	1	0	097	1600.40
875-628C	10X8	1	0	091	2652.33
875-628CF ²	10X8	1	0	097	1884.61
875-661CF ²	12X2	1	0	097	1787.54
875-663CF ²	12X3	1	0	097	1877.95
875-664CF ²	12X4	1	0	097	2142.20
875-666CF ²	12X6	1	0	097	2228.46
875-668CF ²	12X8	1	0	097	2352.15
875-670CF ²	12X10	1	0	097	2895.95
875-694CF ²	14X4	1	0	097	4794.85
875-696CF ²	14X6	1	0	097	5266.49
875-698CF ²	14X8	1	0	097	5697.00
875-700CF	14X10	1	0	097	6639.80
875-702CF ²	14X12	1	0	097	6940.26
875-754CF ²	16X4	1	0	097	6033.33
875-756CF ²	16X6	1	0	097	6352.80
875-758CF ²	16X8	1	0	097	7376.56
875-760CF ²	16X10	1	0	097	8290.20
875-762CF ²	16X12	1	0	097	8991.12
875-764CF ²	16X14	1	0	097	11310.54
875-784CF ²	18X4	1	0	097	8065.63
875-786CF ²	18X6	1	0	097	8656.35
875-788CF ²	18X8	1	0	097	9609.72
875-790CF ²	18X10	1	0	097	10594.39
875-792CF ²	18X12	1	0	097	11651.22
875-794CF ²	18X14	1	0	097	14835.37
875-796CF ²	18X16	1	0	097	16520.47

¹ Sized with Bushing

² Fiberglass reinforced

Double Wye

Socket x Socket x Socket x Socket



100 psi Maximum internal Pressure Rating @ 73°F (23°C)

876-020CF ²	2	1	4	097	523.56
876-030CF ²	3	1	4	097	667.80
876-040CF ²	4	1	2	097	1145.02
876-060CF ²	6	1	0	097	1996.34
876-080CF ²	8	1	0	097	3580.34
876-100CF ²	10	1	0	097	3885.45
876-120CF ²	12	1	0	097	5821.39

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing

Socket x Socket x Socket x Socket



Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	775.56
876-420CF ²	4X2	1	2	097	975.65
876-421CF ²	4X2-1/2	1	2	097	1032.48
876-422CF ²	4X3	1	2	097	1111.61
876-528CF ²	6X2	1	3	097	1659.31
876-529CF ²	6X2-1/2	1	2	097	1679.97
876-530CF ²	6X3	1	2	097	1707.31
876-532CF ²	6X4	1	0	097	1896.01
876-578CF ²	8X2	1	2	097	2835.66
876-579CF ²	8X2-1/2	1	2	097	2877.57
876-580CF ²	8X3	1	2	097	2900.36
876-582CF ²	8X4	1	0	097	3122.43
876-585CF ²	8X6	1	0	097	3291.73
876-621CF ²	10X2	1	0	097	3418.82
876-622CF ²	10X2-1/2	1	0	097	3490.12
876-623CF ²	10X3	1	0	097	3552.07
876-624CF ²	10X4	1	0	097	3634.20
876-626CF ²	10X6	1	0	097	3891.19
876-628CF ²	10X8	1	0	097	4087.01
876-661CF ²	12X2	1	0	097	3680.80
876-662CF ²	12X2-1/2	1	0	097	3857.27
876-663CF ²	12X3	1	0	097	3925.33
876-664CF ²	12X4	1	0	097	4069.07
876-666CF ²	12X6	1	0	097	4453.80
876-668CF ²	12X8	1	0	097	5053.04
876-670CF ²	12X10	1	0	097	5501.99

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	45.60
857-003C	3/8	25	150	090	45.60
8057-005C	1/2	20	120	090	30.34
8057-007C	3/4	20	80	090	31.69
8057-010C	1	15	90	090	38.04
8057-012C	1-1/4	10	0	090	76.97
8057-015C	1-1/2	10	0	090	78.37
8057-020C	2	5	0	090	129.91
8057-025C	2-1/2	5	0	090	213.05

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/FKM (continued)

Socket x Socket with FKM O-ring Seal

8057-030C	3	5	0	090	269.63
8057-040C	4	4	0	090	344.47
8057-060C	6	1	0	090	765.51

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	45.04
897-003C	3/8	25	150	090	45.04
8097-005C	1/2	20	120	090	30.24
8097-007C	3/4	20	80	090	31.32
8097-010C	1	15	90	090	37.52
8097-012C	1-1/4	10	0	090	75.98
8097-015C	1-1/2	10	0	090	77.42
8097-020C	2	5	0	090	128.31
8097-025C	2-1/2	5	0	090	212.49
8097-030C	3	5	0	090	266.31
8097-040C	4	4	0	090	340.57
8097-060C	6	1	0	090	756.81

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	34.54
8059-007C	3/4	20	80	090	60.26
8059-010C	1	15	90	090	83.18
8059-012C	1-1/4	10	0	090	141.16
8059-015C	1-1/2	10	0	090	158.44
8059-020C	2	5	0	090	179.12
8059-025C	2-1/2	5	0	090	290.79
8059-030C	3	5	0	090	343.95
8059-040C	4	4	0	090	397.73
8059-060C	6	1	0	090	883.84

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	33.68
8099-007C	3/4	20	80	090	59.56
8099-010C	1	15	90	090	82.15
8099-012C	1-1/4	10	0	090	156.47
8099-015C	1-1/2	10	0	090	156.47
8099-020C	2	5	0	090	176.89
8099-025C	2-1/2	5	0	090	253.40
8099-030C	3	5	0	090	339.73
8099-040C	4	4	0	090	391.88
8099-060C	6	1	0	090	870.89