



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Reducer Bushing**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Reducer Bushing (T.T.) Flush Style (continued)</b>					
<b>Mipt x Fipt</b>					
839-250	2X1-1/4	10	60	080	22.47
839-251	2X1-1/2	10	60	080	22.47
839-292	2-1/2X2	10	80	080	30.43
839-337	3X1-1/2	10	0	080	41.36
839-338	3X2	10	0	080	41.36
839-339	3X2-1/2	10	0	080	41.36
839-420	4X2	6	0	080	85.25
839-422	4X3	6	0	080	108.87
839-532	6X4	5	0	080	143.04



**Reducer Bushing - Special Reinforced**

**Mipt x SR Fipt - Stainless Steel Collar**

839-128SR	1X1/4	25	150	086	6.29
839-209SR	1-1/2X1/2	25	300	086	9.20
839-210SR	1-1/2X3/4	25	300	086	9.20
839-247SR	2X1/2	10	60	086	13.51
839-248SR	2X3/4	10	60	086	13.51
839-249SR	2X1	10	120	086	13.51
839-420SR	4X2	6	0	086	51.15

**Caps**

**Cap**

**Socket**



847-002	1/4	25	450	080	8.00
847-003	3/8	25	450	080	8.00
847-005	1/2	25	150	080	6.16
847-007	3/4	25	300	080	6.49
847-010	1	15	90	080	11.54
847-012	1-1/4	10	60	080	13.92
847-015	1-1/2	10	120	080	13.92
847-020	2	10	80	080	27.48
847-025	2-1/2	5	40	080	56.12
847-030	3	5	0	080	65.66
847-040	4	5	0	080	110.73
847-050F	5	1	6	083	140.62
847-060	6	4	0	080	275.45
847-080	8	3	0	080	353.66
847-100F	10	1	5	083	361.77
847-120F	12	1	4	083	542.94
847-140F	14	1	2	083	601.27
847-160F	16	1	2	083	778.95
847-180F	18	1	0	083	1137.24
847-200F	20	1	0	083	1524.52
847-240F	24	1	0	083	2836.26

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Cap**

**Fipt**



848-002	1/4	25	450	080	7.71
848-003	3/8	25	450	080	7.71
848-005	1/2	25	300	080	7.71
848-007	3/4	25	300	080	8.63
848-010	1	15	90	080	10.87
848-012	1-1/4	10	60	080	12.94
848-015	1-1/2	10	120	080	14.78
848-020	2	10	40	080	29.04
848-025	2-1/2	5	40	080	58.09
848-030	3	5	0	080	68.39
848-040	4	5	0	080	120.42
848-060F	6	1	4	083	200.91
848-080F	8	1	3	083	261.46
848-100F	10	1	2	084	472.23
848-120F	12	1	0	083	1007.73

**Cap - Special Reinforced**

**SR Fipt - Stainless Steel Collar**



848-002SR	1/4	25	500	086	4.24
848-003SR	3/8	25	450	086	4.24
848-005SR	1/2	50	300	086	4.64
848-007SR	3/4	25	300	086	5.95
848-030SR	3	5	0	086	36.67

**Plugs**

**Plug**

**Spigot**



849-005	1/2	50	300	080	5.76
849-007	3/4	50	300	080	6.41
849-010	1	50	200	080	7.23
849-012	1-1/4	25	100	080	9.23
849-015	1-1/2	10	120	080	10.13
849-020	2	10	120	080	13.40
849-025F <sup>4</sup>	2-1/2	1	4	083	31.37
849-030F <sup>4</sup>	3	1	4	083	37.83
849-040F <sup>4</sup>	4	1	4	083	82.75
849-060F <sup>4</sup>	6	1	6	083	230.08
849-080F <sup>4</sup>	8	1	6	083	299.58
849-100F <sup>4</sup>	10	1	2	083	487.15
849-120F <sup>4</sup>	12	1	0	083	902.43

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**



**Plugs**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Plug**

**Mipt**



850-002	1/4	50	900	080	6.65
850-003	3/8	50	600	080	6.65
850-005	1/2	50	500	080	5.93
850-007	3/4	50	300	080	6.16
850-010	1	25	150	080	7.55
850-012	1-1/4	10	120	080	11.13
850-015	1-1/2	10	120	080	13.53
850-020	2	10	120	080	13.89
850-025	2-1/2	5	60	080	38.78
850-030	3	5	40	080	45.25
850-040	4	6	0	080	88.09
850-060	6	6	0	080	104.73
850-080	8	6	0	080	151.60
850-080F <sup>4</sup>	8	1	2	083	258.51
850-100F <sup>4</sup>	10	1	3	083	378.87
850-120F <sup>4</sup>	12	1	0	083	518.93

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)



875-005	1/2	25	100	080	14.40
875-007	3/4	25	0	080	15.14
875-010	1	20	0	080	24.22
875-012	1-1/4	20	0	080	37.14
875-015	1-1/2	20	0	080	37.14
875-020	2	10	0	080	106.55
875-025 <sup>1</sup>	2-1/2	6	0	080	263.20
875-030	3	5	0	080	342.51
875-040	4	4	0	080	424.39
875-050F <sup>2</sup>	5	1	2	083	663.91
875-060	6	2	0	080	579.64
875-080	8	1	0	080	1165.68
875-080F	8	1	0	083	898.20
875-100F <sup>2</sup>	10	1	0	083	1409.46
875-120F <sup>2</sup>	12	1	0	083	1791.48
875-140F <sup>2</sup>	14	1	0	083	2992.03
875-160F <sup>2</sup>	16	1	0	083	3930.40
875-180F <sup>2</sup>	18	1	0	083	4406.51

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye (continued)**

**Socket x Socket x Socket**

875-200F <sup>2</sup>	20	1	0	083	5886.25
875-240F <sup>2</sup>	24	1	0	083	7833.84

<sup>1</sup> Sized with Bushing

<sup>2</sup> Fiberglass reinforced

**Wye - Reducing**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 <sup>1</sup>	3/4X1/2	25	0	080	17.47
875-130 <sup>1</sup>	1X1/2	20	0	080	30.64
875-131 <sup>1</sup>	1X3/4	20	0	080	30.64
875-166 <sup>1</sup>	1-1/4X1/2	20	0	080	47.20
875-167 <sup>1</sup>	1-1/4X3/4	20	0	080	47.20
875-168 <sup>1</sup>	1-1/4X1	20	0	080	47.20
875-209 <sup>1</sup>	1-1/2X1/2	20	0	080	50.56
875-210 <sup>1</sup>	1-1/2X3/4	20	0	080	50.56
875-211 <sup>1</sup>	1-1/2X1	20	0	080	50.56
875-212 <sup>1</sup>	1-1/2X1-1/4	20	0	080	50.56
875-247 <sup>1</sup>	2X1/2	10	0	080	126.75
875-248 <sup>1</sup>	2X3/4	10	0	080	126.75
875-249 <sup>1</sup>	2X1	10	0	080	126.75
875-250 <sup>1</sup>	2X1-1/4	10	0	080	126.75
875-251 <sup>1</sup>	2X1-1/2	10	0	080	126.75
875-291 <sup>1</sup>	2-1/2X1-1/2	4	0	080	493.43
875-292 <sup>1</sup>	2-1/2X2-1/2X2	5	0	080	493.43
875-335 <sup>1</sup>	3X1	5	0	080	399.23
875-336 <sup>1</sup>	3X1-1/4	5	0	080	399.23
875-337 <sup>1</sup>	3X1-1/2	5	0	080	399.23
875-338 <sup>1</sup>	3X2	4	0	080	399.23
875-339 <sup>1</sup>	3X2-1/2	5	0	080	399.23
875-419 <sup>1</sup>	4X1-1/2	4	0	080	600.77
875-420	4X2	4	0	080	501.93
875-420F <sup>2</sup>	4X2	1	5	083	418.33
875-421 <sup>1</sup>	4X2-1/2	4	0	080	556.36
875-421F <sup>2</sup>	4X2-1/2	1	4	083	467.49
875-422 <sup>1</sup>	4X3	4	0	080	501.93
875-525 <sup>1</sup>	6X1	5	0	080	615.41
875-528 <sup>1</sup>	6X2	5	0	080	546.52
875-528F <sup>2</sup>	6X2	1	3	083	429.77
875-530 <sup>1</sup>	6X3	5	0	080	546.52
875-530F <sup>2</sup>	6X3	1	2	083	466.92
875-532	6X4	5	0	080	441.75
875-578 <sup>1</sup>	8X2	2	0	080	1524.89
875-578F <sup>2</sup>	8X2	1	2	083	695.33
875-579F <sup>2</sup>	8X2-1/2	1	2	083	710.92
875-580 <sup>1</sup>	8X3	2	0	080	1524.89
875-580F <sup>2</sup>	8X3	1	2	083	706.26