



Schedule 80 PVC Product
PVC Schedule 80 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap - Special Reinforced (continued)					
SR Fipt - Stainless Steel Collar					
848-005SR	1/2	50	300	086	5.14
848-007SR	3/4	25	300	086	6.59
848-030SR	3	5	0	086	40.63

Plugs

Plug

Spigot



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
849-005	1/2	50	300	080	6.38
849-007	3/4	50	300	080	7.11
849-010	1	50	200	080	8.01
849-012	1-1/4	25	100	080	10.23
849-015	1-1/2	10	120	080	11.22
849-020	2	10	120	080	14.85
849-025F ⁴	2-1/2	1	4	083	34.76
849-030F ⁴	3	1	4	083	41.92
849-040F ⁴	4	1	4	083	91.69
849-060F ⁴	6	1	6	083	254.94
849-080F ⁴	8	1	6	083	331.95
849-100F ⁴	10	1	2	083	539.78
849-120F ⁴	12	1	0	083	999.93

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
850-002	1/4	50	900	080	7.37
850-003	3/8	50	600	080	7.37
850-005	1/2	50	500	080	6.57
850-007	3/4	50	300	080	6.82
850-010	1	25	150	080	8.37
850-012	1-1/4	10	120	080	12.34
850-015	1-1/2	10	120	080	14.99
850-020	2	10	120	080	15.39
850-025	2-1/2	5	60	080	42.97
850-030	3	5	40	080	50.14
850-040	4	6	0	080	97.61
850-060	6	6	0	080	116.04
850-080	8	6	0	080	167.98
850-080F ⁴	8	1	2	083	286.44
850-100F ⁴	10	1	3	083	419.80
850-120F ⁴	12	1	0	083	574.99

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	15.96
875-007	3/4	25	0	080	16.78
875-010	1	20	0	080	26.83
875-012	1-1/4	20	0	080	41.15
875-015	1-1/2	20	0	080	41.15
875-020	2	10	0	080	118.06
875-025 ¹	2-1/2	6	0	080	291.63
875-030	3	5	0	080	379.52
875-040	4	4	0	080	470.24
875-050F ²	5	1	2	083	735.63
875-060	6	2	0	080	642.26
875-080	8	1	0	080	1291.61
875-080F	8	1	0	083	995.23
875-100F ²	10	1	0	083	1561.73
875-120F ²	12	1	0	083	1985.02
875-140F ²	14	1	0	083	3315.27
875-160F ²	16	1	0	083	4355.01
875-180F ²	18	1	0	083	4882.56
875-200F ²	20	1	0	083	6522.16
875-240F ²	24	1	0	083	8680.16

¹ Sized with Bushing
² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	19.36
875-130 ¹	1X1/2	20	0	080	33.95
875-131 ¹	1X3/4	20	0	080	33.95
875-166 ¹	1-1/4X1/2	20	0	080	52.29
875-167 ¹	1-1/4X3/4	20	0	080	52.29
875-168 ¹	1-1/4X1	20	0	080	52.29
875-209 ¹	1-1/2X1/2	20	0	080	56.02
875-210 ¹	1-1/2X3/4	20	0	080	56.02
875-211 ¹	1-1/2X1	20	0	080	56.02
875-212 ¹	1-1/2X1-1/4	20	0	080	56.02