



Schedule 80 PVC Product
PVC Schedule 80 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap - Special Reinforced (continued)					
SR Fipt - Stainless Steel Collar					
848-005SR	1/2	50	300	086	4.88
848-007SR	3/4	25	300	086	6.26
848-030SR	3	5	0	086	38.60

Plugs

Plug

Spigot



849-005	1/2	50	300	080	6.06
849-007	3/4	50	300	080	6.75
849-010	1	50	200	080	7.61
849-012	1-1/4	25	100	080	9.72
849-015	1-1/2	10	120	080	10.66
849-020	2	10	120	080	14.11
849-025F ⁴	2-1/2	1	4	083	33.02
849-030F ⁴	3	1	4	083	39.82
849-040F ⁴	4	1	4	083	87.11
849-060F ⁴	6	1	6	083	242.19
849-080F ⁴	8	1	6	083	315.35
849-100F ⁴	10	1	2	083	512.79
849-120F ⁴	12	1	0	083	949.93

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt



850-002	1/4	50	900	080	7.00
850-003	3/8	50	600	080	7.00
850-005	1/2	50	500	080	6.24
850-007	3/4	50	300	080	6.48
850-010	1	25	150	080	7.95
850-012	1-1/4	10	120	080	11.72
850-015	1-1/2	10	120	080	14.24
850-020	2	10	120	080	14.62
850-025	2-1/2	5	60	080	40.82
850-030	3	5	40	080	47.63
850-040	4	6	0	080	92.73
850-060	6	6	0	080	110.24
850-080	8	6	0	080	159.58
850-080F ⁴	8	1	2	083	272.12
850-100F ⁴	10	1	3	083	398.81
850-120F ⁴	12	1	0	083	546.24

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	15.16
875-007	3/4	25	0	080	15.94
875-010	1	20	0	080	25.49
875-012	1-1/4	20	0	080	39.09
875-015	1-1/2	20	0	080	39.09
875-020	2	10	0	080	112.16
875-025 ¹	2-1/2	6	0	080	277.05
875-030	3	5	0	080	360.54
875-040	4	4	0	080	446.73
875-050F ²	5	1	2	083	698.85
875-060	6	2	0	080	610.15
875-080	8	1	0	080	1227.03
875-080F	8	1	0	083	945.47
875-100F ²	10	1	0	083	1483.64
875-120F ²	12	1	0	083	1885.77
875-140F ²	14	1	0	083	3149.51
875-160F ²	16	1	0	083	4137.26
875-180F ²	18	1	0	083	4638.43
875-200F ²	20	1	0	083	6196.05
875-240F ²	24	1	0	083	8246.15

¹ Sized with Bushing

² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	18.39
875-130 ¹	1X1/2	20	0	080	32.25
875-131 ¹	1X3/4	20	0	080	32.25
875-166 ¹	1-1/4X1/2	20	0	080	49.68
875-167 ¹	1-1/4X3/4	20	0	080	49.68
875-168 ¹	1-1/4X1	20	0	080	49.68
875-209 ¹	1-1/2X1/2	20	0	080	53.22
875-210 ¹	1-1/2X3/4	20	0	080	53.22
875-211 ¹	1-1/2X1	20	0	080	53.22
875-212 ¹	1-1/2X1-1/4	20	0	080	53.22