

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Reducer Bushing**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Reducer Bushing (T.T.) Flush Style (continued)</b>					
<b>Mipt x Fipt</b>					
839-250	2X1-1/4	10	60	080	23.65
839-251	2X1-1/2	10	60	080	23.65
839-292	2-1/2X2	10	80	080	32.03
839-337	3X1-1/2	10	0	080	43.54
839-338	3X2	10	0	080	43.54
839-339	3X2-1/2	10	0	080	43.54
839-420	4X2	6	0	080	89.74
839-422	4X3	6	0	080	114.60
839-532	6X4	5	0	080	150.57



**Reducer Bushing - Special Reinforced**

**Mipt x SR Fipt - Stainless Steel Collar**

839-128SR	1X1/4	25	150	086	6.62
839-209SR	1-1/2X1/2	25	300	086	9.68
839-210SR	1-1/2X3/4	25	300	086	9.68
839-247SR	2X1/2	10	60	086	14.22
839-248SR	2X3/4	10	60	086	14.22
839-249SR	2X1	10	120	086	14.22
839-420SR	4X2	6	0	086	53.84

**Caps**



**Cap**

**Socket**

847-002	1/4	25	450	080	8.42
847-003	3/8	25	450	080	8.42
847-005	1/2	25	150	080	6.48
847-007	3/4	25	300	080	6.83
847-010	1	15	90	080	12.15
847-012	1-1/4	10	60	080	14.65
847-015	1-1/2	10	120	080	14.65
847-020	2	10	80	080	28.93
847-025	2-1/2	5	40	080	59.07
847-030	3	5	0	080	69.12
847-040	4	5	0	080	116.56
847-050F	5	1	6	083	148.02
847-060	6	4	0	080	289.95
847-080	8	3	0	080	372.27
847-100F	10	1	5	083	380.81
847-120F	12	1	4	083	571.52
847-140F	14	1	2	083	632.92
847-160F	16	1	2	083	819.95
847-180F	18	1	0	083	1197.09
847-200F	20	1	0	083	1604.76
847-240F	24	1	0	083	2985.54

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Cap**



**Fipt**

848-002	1/4	25	450	080	8.12
848-003	3/8	25	450	080	8.12
848-005	1/2	25	150	080	8.12
848-007	3/4	25	300	080	9.08
848-010	1	15	90	080	11.44
848-012	1-1/4	10	60	080	13.62
848-015	1-1/2	10	120	080	15.56
848-020	2	10	40	080	30.57
848-025	2-1/2	5	40	080	61.15
848-030	3	5	0	080	71.99
848-040	4	5	0	080	126.76
848-060F	6	1	4	083	211.48
848-080F	8	1	3	083	275.22
848-100F	10	1	2	084	497.08
848-120F	12	1	0	083	1060.77

**Cap - Special Reinforced**



**SR Fipt - Stainless Steel Collar**

848-002SR	1/4	25	500	086	4.46
848-003SR	3/8	25	450	086	4.46
848-005SR	1/2	50	300	086	4.88
848-007SR	3/4	25	300	086	6.26
848-030SR	3	5	0	086	38.60

**Plugs**

**Plug**



**Spigot**

849-005	1/2	50	300	080	6.06
849-007	3/4	50	300	080	6.75
849-010	1	50	200	080	7.61
849-012	1-1/4	25	100	080	9.72
849-015	1-1/2	10	120	080	10.66
849-020	2	10	120	080	14.11
849-025F <sup>4</sup>	2-1/2	1	4	083	33.02
849-030F <sup>4</sup>	3	1	4	083	39.82
849-040F <sup>4</sup>	4	1	4	083	87.11
849-060F <sup>4</sup>	6	1	6	083	242.19
849-080F <sup>4</sup>	8	1	6	083	315.35
849-100F <sup>4</sup>	10	1	2	083	512.79
849-120F <sup>4</sup>	12	1	0	083	949.93

<sup>4</sup> Plug fabricated using Cap and pipe spigot.



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Plugs**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Plug**

**Mipt**



850-002	1/4	50	900	080	7.00
850-003	3/8	50	600	080	7.00
850-005	1/2	50	500	080	6.24
850-007	3/4	50	300	080	6.48
850-010	1	25	150	080	7.95
850-012	1-1/4	10	120	080	11.72
850-015	1-1/2	10	120	080	14.24
850-020	2	10	120	080	14.62
850-025	2-1/2	5	60	080	40.82
850-030	3	5	40	080	47.63
850-040	4	6	0	080	92.73
850-060	6	6	0	080	110.24
850-080	8	6	0	080	159.58
850-080F <sup>4</sup>	8	1	2	083	272.12
850-100F <sup>4</sup>	10	1	3	083	398.81
850-120F <sup>4</sup>	12	1	0	083	546.24

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	15.16
875-007	3/4	25	0	080	15.94
875-010	1	20	0	080	25.49
875-012	1-1/4	20	0	080	39.09
875-015	1-1/2	20	0	080	39.09
875-020	2	10	0	080	112.16
875-025 <sup>1</sup>	2-1/2	6	0	080	277.05
875-030	3	5	0	080	360.54
875-040	4	4	0	080	446.73
875-050F <sup>2</sup>	5	1	2	083	698.85
875-060	6	2	0	080	610.15
875-080	8	1	0	080	1227.03
875-080F	8	1	0	083	945.47
875-100F <sup>2</sup>	10	1	0	083	1483.64
875-120F <sup>2</sup>	12	1	0	083	1885.77
875-140F <sup>2</sup>	14	1	0	083	3149.51
875-160F <sup>2</sup>	16	1	0	083	4137.26
875-180F <sup>2</sup>	18	1	0	083	4638.43

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye (continued)**

**Socket x Socket x Socket**

875-200F <sup>2</sup>	20	1	0	083	6196.05
875-240F <sup>2</sup>	24	1	0	083	8246.15

<sup>1</sup> Sized with Bushing  
<sup>2</sup> Fiberglass reinforced

**Wye - Reducing**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
 3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)  
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 <sup>1</sup>	3/4X1/2	25	0	080	18.39
875-130 <sup>1</sup>	1X1/2	20	0	080	32.25
875-131 <sup>1</sup>	1X3/4	20	0	080	32.25
875-166 <sup>1</sup>	1-1/4X1/2	20	0	080	49.68
875-167 <sup>1</sup>	1-1/4X3/4	20	0	080	49.68
875-168 <sup>1</sup>	1-1/4X1	20	0	080	49.68
875-209 <sup>1</sup>	1-1/2X1/2	20	0	080	53.22
875-210 <sup>1</sup>	1-1/2X3/4	20	0	080	53.22
875-211 <sup>1</sup>	1-1/2X1	20	0	080	53.22
875-212 <sup>1</sup>	1-1/2X1-1/4	20	0	080	53.22
875-247 <sup>1</sup>	2X1/2	10	0	080	133.42
875-248 <sup>1</sup>	2X3/4	10	0	080	133.42
875-249 <sup>1</sup>	2X1	10	0	080	133.42
875-250 <sup>1</sup>	2X1-1/4	10	0	080	133.42
875-251 <sup>1</sup>	2X1-1/2	10	0	080	133.42
875-291 <sup>1</sup>	2-1/2X1-1/2	4	0	080	519.40
875-292 <sup>1</sup>	2-1/2X2-1/2X2	5	0	080	519.40
875-335 <sup>1</sup>	3X1	5	0	080	420.24
875-336 <sup>1</sup>	3X1-1/4	5	0	080	420.24
875-337 <sup>1</sup>	3X1-1/2	5	0	080	420.24
875-338 <sup>1</sup>	3X2	4	0	080	420.24
875-339 <sup>1</sup>	3X2-1/2	5	0	080	420.24
875-419 <sup>1</sup>	4X1-1/2	4	0	080	632.39
875-420	4X2	4	0	080	528.35
875-420F <sup>2</sup>	4X2	1	5	083	440.35
875-421 <sup>1</sup>	4X2-1/2	4	0	080	585.64
875-421F <sup>2</sup>	4X2-1/2	1	4	083	492.09
875-422 <sup>1</sup>	4X3	4	0	080	528.35
875-525 <sup>1</sup>	6X1	5	0	080	647.80
875-528 <sup>1</sup>	6X2	5	0	080	575.28
875-528F <sup>2</sup>	6X2	1	3	083	452.39
875-530 <sup>1</sup>	6X3	5	0	080	575.28
875-530F <sup>2</sup>	6X3	1	2	083	491.49
875-532	6X4	5	0	080	465.00
875-578 <sup>1</sup>	8X2	2	0	080	1605.15
875-578F <sup>2</sup>	8X2	1	2	083	731.93
875-579F <sup>2</sup>	8X2-1/2	1	2	083	748.34
875-580 <sup>1</sup>	8X3	2	0	080	1605.15
875-580F <sup>2</sup>	8X3	1	2	083	743.43