

PVC Schedule 80 Fittings & Tank Adapters



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	12.04
8297-020	20 DN X 3/4	20	80	197	15.35
8297-025	25 DN X 1	15	90	197	17.55
8297-030	30 DN X 1-1/4	10	0	197	34.79
8297-040	40 DN X 1-1/2	10	0	197	39.39
8297-050	50 DN X 2	5	0	197	53.42
8297-075	75 DN X 3	5	0	197	99.41
8297-100	100 DN X 4	4	0	197	137.48

Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	14.20
8358-007	3/4	20	80	197	19.84
8358-010	1	15	90	197	26.41
8358-012	1-1/4	10	0	197	50.39
8358-015	1-1/2	10	0	197	62.39
8358-020	2	5	0	197	96.00
8358-030	3	5	0	197	243.51
8358-040	4	4	0	197	286.16

Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	13.99
8398-007	3/4	10	60	197	19.59
8398-010	1	10	40	197	26.08
8398-012	1-1/4	5	20	197	49.77
8398-015	1-1/2	5	0	197	61.61
8398-020	2	5	0	197	98.98
8398-030	3	5	0	197	240.48
8398-040	4	4	0	197	281.26

Tank Adapters

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Socket x Socket



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	38.05
8170-003	3/8	25	150	100	38.05

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

(continued)

Socket x Socket

8170-005	1/2	25	0	100	38.05
8170-007	3/4	25	0	100	43.38
8170-010	1	25	0	100	48.19
8170-012	1-1/4	20	0	100	58.06
8170-015	1-1/2	20	0	100	63.71
8170-020	2	15	0	100	94.43
8170-025	2-1/2	4	0	100	145.92
8170-030	3	4	0	100	173.71
8170-040	4	2	0	100	342.17
8170-060	6	1	0	100	664.18
8170-080	8	1	0	100	1473.95

Tank Adapters, PVC New Style Standard with EPDM Gaskets

Socket x Socket



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002	1/4	25	150	100	39.21
8170E-003	3/8	25	150	100	39.21
8170E-005	1/2	25	0	100	39.21
8170E-007	3/4	25	0	100	44.24
8170E-010	1	25	0	100	53.34
8170E-012	1-1/4	20	0	100	63.40
8170E-015	1-1/2	20	0	100	69.06
8170E-020	2	15	0	100	101.63
8170E-025	2-1/2	4	0	100	169.38
8170E-030	3	4	0	100	180.19
8170E-040	4	2	0	100	350.81
8170E-060	6	1	0	100	688.02
8170E-080	8	1	0	100	1528.61

Tank Adapters, PVC New Style Standard with FKM Gaskets

Socket x Socket



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002	1/4	25	150	100	64.65
8170V-003	3/8	25	150	100	64.65
8170V-005	1/2	25	0	100	64.65
8170V-007	3/4	25	0	100	70.88
8170V-010	1	25	0	100	84.87
8170V-012	1-1/4	20	0	100	89.49
8170V-015	1-1/2	20	0	100	98.57
8170V-020	2	15	0	100	161.73
8170V-025	2-1/2	4	0	100	243.78
8170V-030	3	4	0	100	290.22
8170V-040	4	2	0	100	725.99
8170V-060	6	1	0	100	1305.77
8170V-080	8	1	0	100	2430.73



Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171-002	1/4	25	150	100	38.05
8171-003	3/8	25	200	100	38.05
8171-005	1/2	25	0	100	38.05
8171-007	3/4	25	0	100	43.38
8171-010	1	25	0	100	48.19
8171-012	1-1/4	20	0	100	58.06
8171-015	1-1/2	20	0	100	63.71
8171-020	2	15	0	100	94.43
8171-025	2-1/2	4	0	100	145.92
8171-030	3	4	0	100	173.71
8171-040	4	2	0	100	342.17
8171-060	6	1	0	100	664.18



Tank Adapters, PVC New Style Standard with EPDM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171E-002	1/4	25	150	100	39.21
8171E-003	3/8	25	200	100	39.21
8171E-005	1/2	25	0	100	39.21
8171E-007	3/4	25	0	100	44.24
8171E-010	1	25	0	100	53.34
8171E-012	1-1/4	20	0	100	63.40
8171E-015	1-1/2	20	0	100	69.06
8171E-020	2	15	0	100	101.63
8171E-025	2-1/2	4	0	100	169.38
8171E-030	3	4	0	100	180.19
8171E-040	4	2	0	100	350.81
8171E-060	6	1	0	100	688.02



Tank Adapters, PVC New Style Standard with FKM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171V-002	1/4	25	150	100	64.65
8171V-003	3/8	25	200	100	64.65
8171V-005	1/2	25	0	100	64.65
8171V-007	3/4	25	0	100	70.88
8171V-010	1	25	0	100	84.87
8171V-012	1-1/4	20	0	100	89.49
8171V-015	1-1/2	20	0	100	98.57
8171V-020	2	15	0	100	161.73
8171V-025	2-1/2	4	0	100	243.78
8171V-030	3	4	0	100	290.22
8171V-040	4	2	0	100	725.99



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, PVC New Style Standard with FKM Gaskets

(continued)

Socket x Fipt

8171V-060	6	1	0	100	1305.77
-----------	---	---	---	-----	---------

Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171-002SR	1/4	25	150	100	39.42
8171-003SR	3/8	25	200	100	39.42
8171-005SR	1/2	25	0	100	39.42
8171-007SR	3/4	25	0	100	45.67
8171-010SR	1	25	0	100	51.43
8171-012SR	1-1/4	20	0	100	63.22
8171-015SR	1-1/2	20	0	100	72.57
8171-020SR	2	15	0	100	104.00
8171-025SR	2-1/2	4	0	100	167.45
8171-030SR	3	4	0	100	199.33
8171-040SR	4	2	0	100	368.71
8171-060SR	6	1	0	100	690.05



Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171E-002SR	1/4	25	150	100	40.81
8171E-003SR	3/8	25	200	100	40.81
8171E-005SR	1/2	25	0	100	40.81
8171E-007SR	3/4	25	0	100	46.54
8171E-010SR	1	25	0	100	56.58
8171E-012SR	1-1/4	20	0	100	68.55
8171E-015SR	1-1/2	20	0	100	77.91
8171E-020SR	2	15	0	100	111.20
8171E-025SR	2-1/2	4	0	100	172.88
8171E-030SR	3	4	0	100	205.83
8171E-040SR	4	2	0	100	377.38
8171E-060SR	6	1	0	100	713.78



Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
8171V-002SR	1/4	25	150	100	66.25
8171V-003SR	3/8	25	200	100	66.25
8171V-005SR	1/2	25	0	100	66.25
8171V-007SR	3/4	25	0	100	72.69
8171V-010SR	1	25	0	100	89.61
8171V-012SR	1-1/4	20	0	100	100.35
8171V-015SR	1-1/2	20	0	100	113.11
8171V-020SR	2	15	0	100	173.22
8171V-025SR	2-1/2	4	0	100	263.72



Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-030SR	3	4	0	100	313.93
8171V-040SR	4	2	0	100	754.25
8171V-060SR	6	1	0	100	1336.76

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002	1/4	25	150	100	51.11
8172-003	3/8	25	200	100	51.11
8172-005	1/2	25	0	100	51.11
8172-007	3/4	25	0	100	56.04
8172-010	1	25	0	100	61.29
8172-012	1-1/4	20	0	100	81.72
8172-015	1-1/2	20	0	100	89.07
8172-020	2	15	0	100	117.29
8172-025	2-1/2	4	0	100	171.69
8172-030	3	4	0	100	204.36
8172-040	4	2	0	100	382.95
8172-060	6	1	0	100	766.36



Tank Adapters, PVC New Style Standard with EPDM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002	1/4	25	150	100	52.61
8172E-003	3/8	25	200	100	52.61
8172E-005	1/2	25	0	100	52.61
8172E-007	3/4	25	0	100	57.14
8172E-010	1	25	0	100	67.87
8172E-012	1-1/4	20	0	100	89.23
8172E-015	1-1/2	20	0	100	96.49
8172E-020	2	15	0	100	126.24
8172E-025	2-1/2	4	0	100	178.08
8172E-030	3	4	0	100	212.03
8172E-040	4	2	0	100	392.71
8172E-060	6	1	0	100	793.89



Tank Adapters, PVC New Style Standard with FKM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002	1/4	25	150	100	79.06
8172V-003	3/8	25	200	100	79.06
8172V-005	1/2	25	0	100	79.06
8172V-007	3/4	25	0	100	84.25
8172V-010	1	25	0	100	96.23



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, PVC New Style Standard with FKM Gaskets

(continued)

Fipt x Fipt

8172V-012	1-1/4	20	0	100	109.21
8172V-015	1-1/2	20	0	100	124.64
8172V-020	2	15	0	100	184.68
8172V-025	2-1/2	4	0	100	263.79
8172V-030	3	4	0	100	314.12
8172V-040	4	2	0	100	765.57
8172V-060	6	1	0	100	1464.78

Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	52.71
8172-003SR	3/8	25	200	100	52.71
8172-005SR	1/2	25	0	100	52.71
8172-007SR	3/4	25	0	100	58.35
8172-010SR	1	25	0	100	64.54
8172-012SR	1-1/4	20	0	100	86.91
8172-015SR	1-1/2	20	0	100	97.94
8172-020SR	2	15	0	100	126.91
8172-025SR	2-1/2	4	0	100	193.21
8172-030SR	3	4	0	100	230.02
8172-040SR	4	2	0	100	409.49
8172-060SR	6	1	0	100	792.12



Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002SR	1/4	25	150	100	54.23
8172E-003SR	3/8	25	200	100	54.23
8172E-005SR	1/2	25	0	100	54.23
8172E-007SR	3/4	25	0	100	59.44
8172E-010SR	1	25	0	100	71.13
8172E-012SR	1-1/4	20	0	100	94.41
8172E-015SR	1-1/2	20	0	100	105.33
8172E-020SR	2	15	0	100	135.84
8172E-025SR	2-1/2	4	0	100	199.63
8172E-030SR	3	4	0	100	237.63
8172E-040SR	4	2	0	100	419.25
8172E-060SR	6	1	0	100	819.57



Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002SR	1/4	25	150	100	80.65
8172V-003SR	3/8	25	200	100	80.65
8172V-005SR	1/2	25	0	100	80.65





Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets (continued)					
Fipt x SR Fipt - Stainless Steel Collar					
8172V-007SR	3/4	25	0	100	86.59
8172V-010SR	1	25	0	100	99.48
8172V-012SR	1-1/4	20	0	100	114.36
8172V-015SR	1-1/2	20	0	100	133.49
8172V-020SR	2	15	0	100	194.31
8172V-025SR	2-1/2	4	0	100	285.31
8172V-030SR	3	4	0	100	339.75
8172V-040SR	4	2	0	100	792.12
8172V-060SR	6	2	0	100	1495.73

Tank Adapter, PVC Self Aligning with Neoprene Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010	1	5	0	100	163.82
8172SA-020	2	4	0	100	254.75
8172SA-030	3	2	0	100	385.45

Tank Adapter, PVC Self Aligning with EPDM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010	1	5	0	100	172.40
8172ESA-020	2	4	0	100	261.62
8172ESA-030	3	2	0	100	405.86

Tank Adapter, PVC Self Aligning with FKM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010	1	5	0	100	446.71
8172VSA-020	2	4	0	100	634.18
8172VSA-030	3	2	0	100	996.47

Tank Adapter, Spigot PVC with EPDM Gasket

Spigot

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8173E-005	1/2	25	150	100	39.21
8173E-007	3/4	25	100	100	44.24
8173E-010	1	25	0	100	53.34
8173E-015	1-1/2	20	0	100	69.06
8173E-020	2	12	0	100	101.63

Install with threaded end, gasket and one nut inside tank. Use thread sealant on internal nut.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter, PVC Old Style with Neoprene Gasket

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871-005	1/2	25	0	100	38.05
871-007	3/4	25	0	100	43.38
871-010	1	25	0	100	48.19
871-012	1-1/4	20	0	100	58.06
871-015	1-1/2	20	0	100	63.71
871-020	2	15	0	100	94.43
871-030	3	4	0	100	173.71
871-040	4	2	0	100	342.17

Tank Adapter, PVC Old Style with EPDM Gasket

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871E-005	1/2	25	0	100	39.21
871E-007	3/4	25	0	100	44.24
871E-010	1	25	0	100	53.34
871E-012	1-1/4	20	0	100	63.40
871E-015	1-1/2	20	0	100	69.06
871E-020	2	15	0	100	101.63
871E-030	3	4	0	100	180.19
871E-040	4	2	0	100	350.81

Tank Adapter, PVC Old Style with Neoprene Gasket

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872-005	1/2	25	0	100	51.11
872-007	3/4	25	0	100	56.04
872-010	1	25	0	100	61.29
872-012	1-1/4	20	0	100	81.72
872-015	1-1/2	20	0	100	89.07
872-020	2	15	0	100	117.29
872-030	3	4	0	100	204.36
872-040	4	2	0	100	382.95

Tank Adapter, PVC Old Style with EPDM Gasket

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872E-005	1/2	25	0	100	52.61
872E-007	3/4	25	0	100	57.14
872E-010	1	25	0	100	67.87
872E-012	1-1/4	20	0	100	89.23
872E-015	1-1/2	20	0	100	96.49
872E-020	2	15	0	100	126.24
872E-030	3	4	0	100	212.03

Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter, PVC Old Style with EPDM Gasket (continued)

Fipt x Fipt

872E-040	4	2	0	100	392.71
----------	---	---	---	-----	--------



Tank Adapter Gasket Only - Neoprene (Old Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
2N-005	1/2	10	0	299	3.00
2N-007	3/4	10	0	299	3.22
2N-010	1	10	0	299	3.42
2N-015	1-1/4 OR 1-1/2	10	0	299	5.55
2N-020	2	10	0	299	7.27
2N-030	3	10	0	299	7.92
2N-040	4	10	0	299	21.88



Tank Adapter Gasket Only - EPDM (Old Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
2E-005	1/2	10	0	299	3.49
2E-007	3/4	10	0	299	3.60
2E-010	1	10	0	299	6.25
2E-015	1-1/4 OR 1-1/2	10	0	299	9.40
2E-020	2	10	0	299	10.76
2E-030	3	10	0	299	16.39
2E-040	4	10	0	299	24.68



Tank Adapter Gasket Only - Neoprene (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
3N-002	1/4	100	0	299	3.00
3N-003	3/8	50	0	299	3.00
3N-005	1/2	10	0	299	3.00
3N-007	3/4	10	0	299	3.22
3N-010	1	10	0	299	3.42
3N-012	1-1/4	10	0	299	4.73
3N-015	1-1/2	10	0	299	5.55
3N-020	2	10	0	299	7.27
3N-025	2-1/2	10	0	299	7.58
3N-030	3	10	0	299	7.92
3N-040	4	50	0	299	21.88
2N-060	6	10	0	299	27.34
3N-080	8	10	0	299	125.36



Tank Adapter Gasket Only - EPDM (New Style)

3E-002	1/4	10	0	299	1.86
3E-003	3/8	10	0	299	2.13

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter Gasket Only - EPDM (New Style) (continued)

3E-005	1/2	10	0	299	2.85
3E-007	3/4	10	0	299	3.01
3E-010	1	10	0	299	4.35
3E-012	1-1/4	10	0	299	9.15
3E-015	1-1/2	10	0	299	9.40
3E-020	2	10	0	299	10.76
3E-025	2-1/2	10	0	299	15.24
3E-030	3	10	0	299	16.39
3E-040	4	10	0	299	24.68
2E-060	6	10	0	299	44.57
3E-080	8	10	0	299	117.82



Tank Adapter Gasket Only - FKM (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
3V-002	1/4	10	0	299	11.38
3V-003	3/8	10	0	299	14.46
3V-005	1/2	10	0	299	18.41
3V-007	3/4	10	0	299	20.41
3V-010	1	10	0	299	22.28
3V-012	1-1/4	10	0	299	41.71
3V-015	1-1/2	10	0	299	44.76
3V-020	2	10	0	299	57.68
3V-025	2-1/2	10	0	299	70.28
3V-030	3	10	0	299	126.76
3V-040	4	10	0	299	157.87
2V-060	6	10	0	299	557.28
3V-080	8	10	0	299	896.88



Tank Adapter Wrench Sets (New Style)

Body Wrench & Nut Wrench

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW-002	1/4	1	25	299	24.25
TAW-003	3/8	1	25	299	24.25
TAW-005	1/2	1	25	299	24.25
TAW-007	3/4	1	25	299	24.73
TAW-010	1	1	25	299	25.72
TAW-012	1-1/4	1	20	299	29.01
TAW-015	1-1/2	1	20	299	31.46
TAW-020	2	1	10	299	35.84
TAW-025	2-1/2	1	10	299	39.65
TAW-030	3	1	10	299	43.71
TAW-040	4	1	10	299	46.82



Tank Adapter Individual Body Wrench (New Style)

TAW1-002	1/4	500	0	299	13.61
TAW1-003	3/8	400	0	299	13.61
TAW1-005	1/2	250	0	299	13.61



Schedule 80 PVC Product Tank Adapters & Pipe Flanges

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW1-007	3/4	220	0	299	13.87
TAW1-010	1	200	0	299	14.44
TAW1-012	1-1/4	300	0	299	16.36
TAW1-015	1-1/2	150	0	299	17.61
TAW1-020	2	100	0	299	19.12
TAW1-025	2-1/2	80	0	299	19.98
TAW1-030	3	74	0	299	25.05
TAW1-040	4	35	0	299	25.77

Tank Adapter Individual Body Wrench (New Style) (continued)



Tank Adapter Individual Nut Wrench (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW2-002	1/4	300	0	299	13.61
TAW2-003	3/8	250	0	299	13.61
TAW2-005	1/2	200	0	299	13.61
TAW2-007	3/4	160	0	299	13.87
TAW2-010	1	110	0	299	14.44
TAW2-012	1-1/4	200	0	299	16.36
TAW2-015	1-1/2	120	0	299	17.61
TAW2-020	2	100	0	299	19.12
TAW2-025	2-1/2	50	0	299	19.98
TAW2-030	3	40	0	299	25.05
TAW2-040	4	35	0	299	25.77

Pipe Flanges

Flange Van Stone Style -PIP

Flange x PIP Socket



125 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
354-060F	6X6.140	1	4	320	140.71
354-080F	8X8.160	1	2	320	213.07
354-100F	10X10.200	1	2	320	299.59
354-120F	12X12.240	1	2	320	433.91
354-150F	14X15.300	1	0	320	1156.59
354-151F	16X15.300	1	0	320	1319.43
354-181F	18X18.701	1	0	320	2004.43
354-182F	18X18.360	1	0	320	2004.43
354-201F	20X22.047	1	0	320	3053.17
354-241F	24X24.803	1	0	320	4471.28

For more information, refer to 80, 100 & 125 psi PIP Fabrication Fittings.

PIP = Plastic Irrigation Pipe (dimensions are NOT the same as IPS dimensions)

Sizes 6" - 16" are furnished with Glass Filled PVC ring.
 Sizes 18" - 24" are furnished with steel ring.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange One Piece

Socket



1/2" - 16" 150 psi Maximum Internal Pressure Rating @73°F (23°C)

18" - 24" 50 psi Maximum Internal Pressure Rating @73°F (23°C)

851-005	1/2	25	0	080	20.06
851-007	3/4	25	0	080	21.44
851-010	1	15	0	080	23.87
851-012	1-1/4	15	0	080	24.60
851-015	1-1/2	20	0	080	25.13
851-020	2	10	0	080	33.45
851-025	2-1/2	10	0	080	51.63
851-030	3	10	0	080	57.02
851-040	4	5	0	080	72.20
851-050	5	5	0	080	113.52
851-060	6	5	0	080	113.52
851-080	8	2	0	080	203.14
851-100	10	2	0	081	278.81
851-100F	10	1	2	083	552.00
851-120	12	2	0	081	365.76
851-120F	12	1	0	083	670.32
851-140F	14	1	0	083	1232.85
851-160F	16	1	0	083	1691.96
851-180F	18	1	0	083	3579.17
851-200F	20	1	0	083	4382.95
851-240F	24	1	0	083	5821.07

Flange One Piece

Fipt



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005	1/2	25	0	080	24.01
852-007	3/4	25	0	080	28.14
852-010	1	15	0	080	30.80
852-012	1-1/4	15	0	080	42.47
852-015	1-1/2	20	0	080	46.35
852-020	2	10	0	080	47.40
852-025	2-1/2	10	0	080	108.99
852-030	3	10	0	080	112.18
852-040	4	5	0	080	210.77
852-060F	6	1	8	083	253.21
852-080F	8	1	2	083	635.48

Flange - Special Reinforced One Piece

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005SR	1/2	25	0	086	13.20
852-007SR	3/4	25	0	086	15.51