

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings & Tank Adapters**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Union - Transition DIN to ASTM/EPDM (continued)</b>					
<b>DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal</b>					
8697-025	25 d X 3/4	10	60	197	16.16
8697-032	32d X 1	15	90	197	18.47
8697-040	40 d X 1-1/4	10	0	197	36.62
8697-050	50 d X 1-1/2	10	0	197	41.46
8697-063	63 d X 2	5	0	197	56.23
8697-090	90 d X 3	5	0	197	104.64
8697-110	110 d X 4	4	0	197	144.72

**Union - Transition DIN to ASTM/FKM**

**DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	15.69
8658-025	25 d X 3/4	20	80	197	21.93
8658-032	32 d X 1	15	90	197	29.18
8658-040	40 d X 1-1/4	10	0	197	55.71
8658-050	50 d X 1-1/2	10	0	197	68.96
8658-063	63 d X 2	5	0	197	106.09
8658-090	90 d X 3	5	0	197	250.44
8658-110	110 d X 4	4	0	197	287.82

**Union - Transition DIN to ASTM/EPDM**

**DIN (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8698-020	20 d X 1/2	20	160	197	15.46
8698-025	25 d X 3/4	20	80	197	21.65
8698-032	32 d X 1	15	90	197	28.80
8698-040	40 d X 1-1/4	10	0	197	54.75
8698-050	50 d X 1-1/2	10	0	197	68.08
8698-063	63 d X 2	5	0	197	104.79
8698-090	90 d X 3	5	0	197	247.31
8698-110	110 d X 4	4	0	197	283.95

**Union-Transition JIS to ASTM/FKM**

**JIS (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8257-016	16 DN X 1/2	20	160	197	12.84
8257-020	20 DN X 3/4	10	60	197	16.36
8257-025	25 DN X 1	15	90	197	18.66
8257-030	30 DN X 1-1/4	10	0	197	37.06
8257-040	40 DN X 1-1/2	10	0	197	41.97
8257-050	50 DN X 2	5	0	197	56.93
8257-075	75 DN X 3	5	0	197	105.96
8257-100	100 DN X 4	4	0	197	147.59

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union -Transition JIS to ASTM/EPDM**

**JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	12.67
8297-020	20 DN X 3/4	20	80	197	16.16
8297-025	25 DN X 1	15	90	197	18.47
8297-030	30 DN X 1-1/4	10	0	197	36.62
8297-040	40 DN X 1-1/2	10	0	197	41.46
8297-050	50 DN X 2	5	0	197	56.23
8297-075	75 DN X 3	5	0	197	104.64
8297-100	100 DN X 4	4	0	197	144.72

**Union - Transition BSP to ASTM/FKM**

**BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	14.95
8358-007	3/4	20	80	197	20.88
8358-010	1	15	90	197	27.80
8358-012	1-1/4	10	0	197	53.04
8358-015	1-1/2	10	0	197	65.67
8358-020	2	5	0	197	101.05
8358-030	3	5	0	197	256.33
8358-040	4	4	0	197	301.22

**Union - Transition BSP to ASTM/EPDM**

**BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	14.73
8398-007	3/4	10	60	197	20.62
8398-010	1	10	40	197	27.45
8398-012	1-1/4	5	20	197	52.39
8398-015	1-1/2	5	0	197	64.85
8398-020	2	5	0	197	104.19
8398-030	3	5	0	197	253.14
8398-040	4	4	0	197	296.06

**Tank Adapters**

**Tank Adapters, PVC New Style Standard with Neoprene Gaskets**



**Socket x Socket**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	40.05
8170-003	3/8	25	150	100	40.05
8170-005	1/2	25	0	100	40.05
8170-007	3/4	25	0	100	45.66
8170-010	1	25	0	100	50.73



## Tank Adapters

## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Tank Adapters, PVC New Style Standard with Neoprene Gaskets</b>					
(continued)					
<b>Socket x Socket</b>					
8170-012	1-1/4	20	0	100	61.12
8170-015	1-1/2	20	0	100	67.06
8170-020	2	15	0	100	99.40
8170-025	2-1/2	4	0	100	153.60
8170-030	3	4	0	100	182.85
8170-040	4	2	0	100	360.18
8170-060	6	1	0	100	699.14
8170-080	8	1	0	100	1551.53

## Tank Adapters, PVC New Style Standard with EPDM Gaskets

## Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002	1/4	25	150	100	41.27
8170E-003	3/8	25	150	100	41.27
8170E-005	1/2	25	0	100	41.27
8170E-007	3/4	25	0	100	46.57
8170E-010	1	25	0	100	56.15
8170E-012	1-1/4	20	0	100	66.74
8170E-015	1-1/2	20	0	100	72.69
8170E-020	2	15	0	100	106.98
8170E-025	2-1/2	4	0	100	178.29
8170E-030	3	4	0	100	189.67
8170E-040	4	2	0	100	369.27
8170E-060	6	1	0	100	724.23
8170E-080	8	1	0	100	1609.06

## Tank Adapters, PVC New Style Standard with FKM Gaskets

## Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002	1/4	25	150	100	68.05
8170V-003	3/8	25	150	100	68.05
8170V-005	1/2	25	0	100	68.05
8170V-007	3/4	25	0	100	74.61
8170V-010	1	25	0	100	89.34
8170V-012	1-1/4	20	0	100	94.20
8170V-015	1-1/2	20	0	100	103.76
8170V-020	2	15	0	100	170.24
8170V-025	2-1/2	4	0	100	256.61
8170V-030	3	4	0	100	305.49
8170V-040	4	2	0	100	764.20
8170V-060	6	1	0	100	1374.49
8170V-080	8	1	0	100	2558.66

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

## Tank Adapters, PVC New Style Standard with Neoprene Gaskets

## Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002	1/4	25	150	100	40.05
8171-003	3/8	25	200	100	40.05
8171-005	1/2	25	0	100	40.05
8171-007	3/4	25	0	100	45.66
8171-010	1	25	0	100	50.73
8171-012	1-1/4	20	0	100	61.12
8171-015	1-1/2	20	0	100	67.06
8171-020	2	15	0	100	99.40
8171-025	2-1/2	4	0	100	153.60
8171-030	3	4	0	100	182.85
8171-040	4	2	0	100	360.18
8171-060	6	1	0	100	699.14

## Tank Adapters, PVC New Style Standard with EPDM Gaskets

## Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002	1/4	25	150	100	41.27
8171E-003	3/8	25	200	100	41.27
8171E-005	1/2	25	0	100	41.27
8171E-007	3/4	25	0	100	46.57
8171E-010	1	25	0	100	56.15
8171E-012	1-1/4	20	0	100	66.74
8171E-015	1-1/2	20	0	100	72.69
8171E-020	2	15	0	100	106.98
8171E-025	2-1/2	4	0	100	178.29
8171E-030	3	4	0	100	189.67
8171E-040	4	2	0	100	369.27
8171E-060	6	1	0	100	724.23

## Tank Adapters, PVC New Style Standard with FKM Gaskets

## Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002	1/4	25	150	100	68.05
8171V-003	3/8	25	200	100	68.05
8171V-005	1/2	25	0	100	68.05
8171V-007	3/4	25	0	100	74.61
8171V-010	1	25	0	100	89.34
8171V-012	1-1/4	20	0	100	94.20
8171V-015	1-1/2	20	0	100	103.76
8171V-020	2	15	0	100	170.24
8171V-025	2-1/2	4	0	100	256.61
8171V-030	3	4	0	100	305.49
8171V-040	4	2	0	100	764.20
8171V-060	6	1	0	100	1374.49

# Tank Adapters



## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002SR	1/4	25	150	100	41.49
8171-003SR	3/8	25	200	100	41.49
8171-005SR	1/2	25	0	100	41.49
8171-007SR	3/4	25	0	100	48.07
8171-010SR	1	25	0	100	54.14
8171-012SR	1-1/4	20	0	100	66.55
8171-015SR	1-1/2	20	0	100	76.39
8171-020SR	2	15	0	100	109.47
8171-025SR	2-1/2	4	0	100	176.26
8171-030SR	3	4	0	100	209.82
8171-040SR	4	2	0	100	388.12
8171-060SR	6	1	0	100	726.37



### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002SR	1/4	25	150	100	42.96
8171E-003SR	3/8	25	200	100	42.96
8171E-005SR	1/2	25	0	100	42.96
8171E-007SR	3/4	25	0	100	48.99
8171E-010SR	1	25	0	100	59.56
8171E-012SR	1-1/4	20	0	100	72.16
8171E-015SR	1-1/2	20	0	100	82.01
8171E-020SR	2	15	0	100	117.05
8171E-025SR	2-1/2	4	0	100	181.98
8171E-030SR	3	4	0	100	216.66
8171E-040SR	4	2	0	100	397.24
8171E-060SR	6	1	0	100	751.35



### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002SR	1/4	25	150	100	69.74
8171V-003SR	3/8	25	200	100	69.74
8171V-005SR	1/2	25	0	100	69.74
8171V-007SR	3/4	25	0	100	76.52
8171V-010SR	1	25	0	100	94.33
8171V-012SR	1-1/4	20	0	100	105.63
8171V-015SR	1-1/2	20	0	100	119.06
8171V-020SR	2	15	0	100	182.34
8171V-025SR	2-1/2	4	0	100	277.60
8171V-030SR	3	4	0	100	330.45
8171V-040SR	4	2	0	100	793.95



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-060SR	6	1	0	100	1407.12
-------------	---	---	---	-----	---------

### Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002	1/4	25	150	100	53.80
8172-003	3/8	25	200	100	53.80
8172-005	1/2	25	0	100	53.80
8172-007	3/4	25	0	100	58.99
8172-010	1	25	0	100	64.52
8172-012	1-1/4	20	0	100	86.02
8172-015	1-1/2	20	0	100	93.76
8172-020	2	15	0	100	123.46
8172-025	2-1/2	4	0	100	180.73
8172-030	3	4	0	100	215.12
8172-040	4	2	0	100	403.11
8172-060	6	1	0	100	806.69



### Tank Adapters, PVC New Style Standard with EPDM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002	1/4	25	150	100	55.38
8172E-003	3/8	25	200	100	55.38
8172E-005	1/2	25	0	100	55.38
8172E-007	3/4	25	0	100	60.15
8172E-010	1	25	0	100	71.44
8172E-012	1-1/4	20	0	100	93.93
8172E-015	1-1/2	20	0	100	101.57
8172E-020	2	15	0	100	132.88
8172E-025	2-1/2	4	0	100	187.45
8172E-030	3	4	0	100	223.19
8172E-040	4	2	0	100	413.38
8172E-060	6	1	0	100	835.67



### Tank Adapters, PVC New Style Standard with FKM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002	1/4	25	150	100	83.22
8172V-003	3/8	25	200	100	83.22
8172V-005	1/2	25	0	100	83.22
8172V-007	3/4	25	0	100	88.68
8172V-010	1	25	0	100	101.29
8172V-012	1-1/4	20	0	100	114.96
8172V-015	1-1/2	20	0	100	131.20
8172V-020	2	15	0	100	194.40
8172V-025	2-1/2	4	0	100	277.67







# Tank Adapters

## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, PVC New Style Standard with FKM Gaskets

(continued)

#### Fipt x Fipt

8172V-030	3	4	0	100	330.65
8172V-040	4	2	0	100	805.86
8172V-060	6	1	0	100	1541.87

### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

#### Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	55.48
8172-003SR	3/8	25	200	100	55.48
8172-005SR	1/2	25	0	100	55.48
8172-007SR	3/4	25	0	100	61.42
8172-010SR	1	25	0	100	67.94
8172-012SR	1-1/4	20	0	100	91.48
8172-015SR	1-1/2	20	0	100	103.09
8172-020SR	2	15	0	100	133.59
8172-025SR	2-1/2	4	0	100	203.38
8172-030SR	3	4	0	100	242.13
8172-040SR	4	2	0	100	431.04
8172-060SR	6	1	0	100	833.81



### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

#### Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002SR	1/4	25	150	100	57.08
8172E-003SR	3/8	25	200	100	57.08
8172E-005SR	1/2	25	0	100	57.08
8172E-007SR	3/4	25	0	100	62.57
8172E-010SR	1	25	0	100	74.87
8172E-012SR	1-1/4	20	0	100	99.38
8172E-015SR	1-1/2	20	0	100	110.87
8172E-020SR	2	15	0	100	142.99
8172E-025SR	2-1/2	4	0	100	210.14
8172E-030SR	3	4	0	100	250.14
8172E-040SR	4	2	0	100	441.32
8172E-060SR	6	1	0	100	862.71



### Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

#### Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002SR	1/4	25	150	100	84.89
8172V-003SR	3/8	25	200	100	84.89
8172V-005SR	1/2	25	0	100	84.89
8172V-007SR	3/4	25	0	100	91.15
8172V-010SR	1	25	0	100	104.72



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapters, PVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

#### Fipt x SR Fipt - Stainless Steel Collar

8172V-012SR	1-1/4	20	0	100	120.38
8172V-015SR	1-1/2	20	0	100	140.52
8172V-020SR	2	15	0	100	204.54
8172V-025SR	2-1/2	4	0	100	300.33
8172V-030SR	3	4	0	100	357.63
8172V-040SR	4	2	0	100	833.81
8172V-060SR	6	2	0	100	1574.45

### Tank Adapter, PVC Self Aligning with Neoprene Gasket

#### Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010	1	5	0	100	172.44
8172SA-020	2	4	0	100	268.16
8172SA-030	3	2	0	100	405.74



### Tank Adapter, PVC Self Aligning with EPDM Gasket

#### Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010	1	5	0	100	181.47
8172ESA-020	2	4	0	100	275.39
8172ESA-030	3	2	0	100	427.22



### Tank Adapter, PVC Self Aligning with FKM Gasket

#### Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010	1	5	0	100	470.22
8172VSA-020	2	4	0	100	667.56
8172VSA-030	3	2	0	100	1048.92



### Tank Adapter, Spigot PVC with EPDM Gasket

#### Spigot

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8173E-005	1/2	25	150	100	41.27
8173E-007	3/4	25	100	100	46.57
8173E-010	1	25	0	100	56.15
8173E-015	1-1/2	20	0	100	72.69
8173E-020	2	12	0	100	106.98



Install with threaded end, gasket and one nut inside tank. Use thread sealant on internal nut.

# Tank Adapters



## Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapter, PVC Old Style with Neoprene Gasket

#### Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871-005	1/2	25	0	100	40.05
871-007	3/4	25	0	100	45.66
871-010	1	25	0	100	50.73
871-012	1-1/4	20	0	100	61.12
871-015	1-1/2	20	0	100	67.06
871-020	2	15	0	100	99.40
871-030	3	4	0	100	182.85
871-040	4	2	0	100	360.18



### Tank Adapter, PVC Old Style with EPDM Gasket

#### Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871E-005	1/2	25	0	100	41.27
871E-007	3/4	25	0	100	46.57
871E-010	1	25	0	100	56.15
871E-012	1-1/4	20	0	100	66.74
871E-015	1-1/2	20	0	100	72.69
871E-020	2	15	0	100	106.98
871E-030	3	4	0	100	189.67
871E-040	4	2	0	100	369.27



### Tank Adapter, PVC Old Style with Neoprene Gasket

#### Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872-005	1/2	25	0	100	53.80
872-007	3/4	25	0	100	58.99
872-010	1	25	0	100	64.52
872-012	1-1/4	20	0	100	86.02
872-015	1-1/2	20	0	100	93.76
872-020	2	15	0	100	123.46
872-030	3	4	0	100	215.12
872-040	4	2	0	100	403.11



### Tank Adapter, PVC Old Style with EPDM Gasket

#### Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872E-005	1/2	25	0	100	55.38
872E-007	3/4	25	0	100	60.15
872E-010	1	25	0	100	71.44
872E-012	1-1/4	20	0	100	93.93
872E-015	1-1/2	20	0	100	101.57



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Tank Adapter, PVC Old Style with EPDM Gasket (continued)

#### Fipt x Fipt

872E-020	2	15	0	100	132.88
872E-030	3	4	0	100	223.19
872E-040	4	2	0	100	413.38



### Tank Adapter Gasket Only - Neoprene (Old Style)

2N-005	1/2	10	0	299	3.16
2N-007	3/4	10	0	299	3.39
2N-010	1	10	0	299	3.60
2N-015	1-1/4 OR 1-1/2	10	0	299	5.84
2N-020	2	10	0	299	7.65
2N-030	3	10	0	299	8.34
2N-040	4	10	0	299	23.03



### Tank Adapter Gasket Only - EPDM (Old Style)

2E-005	1/2	10	0	299	3.67
2E-007	3/4	10	0	299	3.79
2E-010	1	10	0	299	6.58
2E-015	1-1/4 OR 1-1/2	10	0	299	9.89
2E-020	2	10	0	299	11.33
2E-030	3	10	0	299	17.25
2E-040	4	10	0	299	25.98



### Tank Adapter Gasket Only - Neoprene (New Style)

3N-002	1/4	100	0	299	3.16
3N-003	3/8	50	0	299	3.16
3N-005	1/2	10	0	299	3.16
3N-007	3/4	10	0	299	3.39
3N-010	1	10	0	299	3.60
3N-012	1-1/4	10	0	299	4.98
3N-015	1-1/2	10	0	299	5.84
3N-020	2	10	0	299	7.65
3N-025	2-1/2	10	0	299	7.98
3N-030	3	10	0	299	8.34
3N-040	4	50	0	299	23.03
2N-060	6	10	0	299	28.78
3N-080	8	10	0	299	131.96



### Tank Adapter Gasket Only - EPDM (New Style)

3E-002	1/4	10	0	299	1.96
3E-003	3/8	10	0	299	2.24
3E-005	1/2	10	0	299	3.00



## Schedule 80 PVC Product Tank Adapters & Pipe Flanges

### Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Tank Adapter Gasket Only - EPDM (New Style) (continued)</b>					
3E-007	3/4	10	0	299	3.17
3E-010	1	10	0	299	4.58
3E-012	1-1/4	10	0	299	9.63
3E-015	1-1/2	10	0	299	9.89
3E-020	2	10	0	299	11.33
3E-025	2-1/2	10	0	299	16.04
3E-030	3	10	0	299	17.25
3E-040	4	10	0	299	25.98
2E-060	6	10	0	299	46.92
3E-080	8	10	0	299	124.02



### Tank Adapter Gasket Only - FKM (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
3V-002	1/4	10	0	299	11.98
3V-003	3/8	10	0	299	15.23
3V-005	1/2	10	0	299	19.38
3V-007	3/4	10	0	299	21.48
3V-010	1	10	0	299	23.46
3V-012	1-1/4	10	0	299	43.91
3V-015	1-1/2	10	0	299	47.12
3V-020	2	10	0	299	60.72
3V-025	2-1/2	10	0	299	73.99
3V-030	3	10	0	299	133.44
3V-040	4	10	0	299	166.18
2V-060	6	10	0	299	586.61
3V-080	8	10	0	299	944.09

### Tank Adapter Wrench Sets (New Style)

#### Body Wrench & Nut Wrench

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW-002	1/4	1	25	299	25.53
TAW-003	3/8	1	25	299	25.53
TAW-005	1/2	1	25	299	25.53
TAW-007	3/4	1	25	299	26.03
TAW-010	1	1	25	299	27.07
TAW-012	1-1/4	1	20	299	30.54
TAW-015	1-1/2	1	20	299	33.12
TAW-020	2	1	10	299	37.73
TAW-025	2-1/2	1	10	299	41.74
TAW-030	3	1	10	299	46.01
TAW-040	4	1	10	299	49.28



### Tank Adapter Individual Body Wrench (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW1-002	1/4	500	0	299	14.33
TAW1-003	3/8	400	0	299	14.33

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Tank Adapter Individual Body Wrench (New Style) (continued)</b>					
TAW1-005	1/2	250	0	299	14.33
TAW1-007	3/4	220	0	299	14.60
TAW1-010	1	200	0	299	15.20
TAW1-012	1-1/4	300	0	299	17.22
TAW1-015	1-1/2	150	0	299	18.54
TAW1-020	2	100	0	299	20.13
TAW1-025	2-1/2	80	0	299	21.03
TAW1-030	3	74	0	299	26.37
TAW1-040	4	35	0	299	27.13



### Tank Adapter Individual Nut Wrench (New Style)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
TAW2-002	1/4	300	0	299	14.33
TAW2-003	3/8	250	0	299	14.33
TAW2-005	1/2	200	0	299	14.33
TAW2-007	3/4	160	0	299	14.60
TAW2-010	1	110	0	299	15.20
TAW2-012	1-1/4	200	0	299	17.22
TAW2-015	1-1/2	120	0	299	18.54
TAW2-020	2	100	0	299	20.13
TAW2-025	2-1/2	50	0	299	21.03
TAW2-030	3	40	0	299	26.37
TAW2-040	4	35	0	299	27.13

### Pipe Flanges

#### Flange Van Stone Style -PIP

#### Flange x PIP Socket

125 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
354-060F	6X6.140	1	4	320	148.12
354-080F	8X8.160	1	2	320	224.28
354-100F	10X10.200	1	2	320	315.36
354-120F	12X12.240	1	2	320	456.75
354-150F	14X15.300	1	0	320	1217.46
354-151F	16X15.300	1	0	320	1388.87
354-181F	18X18.701	1	0	320	2109.93
354-182F	18X18.360	1	0	320	2109.93
354-201F	20X22.047	1	0	320	3213.86
354-241F	24X24.803	1	0	320	4706.61

For more information, refer to 80, 100 & 125 psi PIP Fabrication Fittings.

PIP = Plastic Irrigation Pipe (dimensions are NOT the same as IPS dimensions)

Sizes 6" - 16" are furnished with Glass Filled PVC ring.  
 Sizes 18" - 24" are furnished with steel ring.

