



Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing (continued)**

**Socket x Socket x Socket x Socket**

876-670F <sup>2</sup>	12X10	1	0	083	2413.38
-----------------------	-------	---	---	-----	---------

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union 2000 - Socket/FKM**

**Socket X Socket with FKM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002	1/4	25	150	080	25.39
857-003	3/8	25	150	080	25.39
8057-005	1/2	20	120	080	13.59
8057-007	3/4	20	80	080	17.26
8057-010	1	15	90	080	19.69
8057-012	1-1/4	10	0	080	39.13
8057-015	1-1/2	10	0	080	44.31
8057-020	2	5	0	080	60.06
8057-025	2-1/2	5	0	080	96.20
8057-030	3	5	0	080	111.84
8057-040	4	4	0	080	155.78
8057-060	6	1	0	080	346.22

**Union 2000 - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002	1/4	25	150	080	25.06
897-003	3/8	25	150	080	25.06
8097-005	1/2	20	120	080	13.39
8097-007	3/4	20	80	080	17.04
8097-010	1	15	90	080	19.51
8097-012	1-1/4	10	0	080	38.66
8097-015	1-1/2	10	0	080	43.75
8097-020	2	5	0	080	59.36
8097-025	2-1/2	5	0	080	94.36
8097-030	3	5	0	080	110.45
8097-040	4	4	0	080	152.78
8097-060	6	1	0	080	339.52

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002	1/4	25	150	080	27.34
859-003	3/8	25	150	080	27.34
8059-005	1/2	20	120	080	16.55
8059-007	3/4	20	80	080	23.14
8059-010	1	15	90	080	30.77
8059-012	1-1/4	10	0	080	58.78
8059-015	1-1/2	10	0	080	72.76
8059-020	2	5	0	080	112.01
8059-025	2-1/2	5	0	080	199.03
8059-030	3	5	0	080	264.36
8059-040	4	4	0	080	303.81
8059-060	6	1	0	080	675.17

**Union 2000 - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	27.01
899-003	3/8	25	150	080	27.01
8099-005	1/2	20	120	080	16.34
8099-007	3/4	20	80	080	22.85
8099-010	1	15	90	080	30.38
8099-012	1-1/4	10	0	080	58.08
8099-015	1-1/2	10	0	080	71.88
8099-020	2	5	0	080	110.61
8099-025	2-1/2	5	0	080	156.40
8099-030	3	5	0	080	261.04
8099-040	4	4	0	080	299.74
8099-060	6	1	0	080	666.06

**Union 2000 - Socket/Spigot/FKM**

**Socket x Spigot with FKM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005	1/2	20	120	080	13.59
8056-007	3/4	20	160	080	17.26
8056-010	1	15	90	080	19.69
8056-012	1-1/4	10	0	080	39.13
8056-015	1-1/2	10	0	080	44.31
8056-020	2	5	0	080	60.06
8056-025	2-1/2	5	0	080	96.20
8056-030	3	5	0	080	111.84
8056-040	4	4	0	080	155.78
8056-060	6	1	0	080	346.22

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/Spigot/EPDM**

**Socket x Spigot with EPDM O-ring Seal**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005	1/2	20	160	080	13.39
8096-007	3/4	20	80	080	17.04
8096-010	1	15	90	080	19.51
8096-012	1-1/4	10	0	080	38.66
8096-015	1-1/2	10	0	080	43.75
8096-020	2	5	0	080	59.36
8096-025	2-1/2	5	0	080	94.36
8096-030	3	5	0	080	110.45
8096-040	4	4	0	080	152.78
8096-060	6	1	0	080	339.52

**Union 2000 - Special Reinforced Fipt/Spigot/FKM**

**SR Fipt x Spigot with FKM O-ring Seal**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005SR	1/2	20	160	086	24.96
8055-007SR	3/4	20	160	086	26.91
8055-010SR	1	15	90	086	33.08
8055-012SR	1-1/4	10	0	096	61.96
8055-015SR	1-1/2	10	0	086	70.75
8055-020SR	2	5	0	086	80.55
8055-025SR	2-1/2	5	0	086	158.05
8055-030SR	3	5	0	086	177.68
8055-040SR	4	4	0	086	201.52
8055-060SR	6	1	0	086	428.05

**Union 2000 - Special Reinforced Fipt/Spigot/EPDM**

**SR Fipt x Spigot with EPDM O-ring Seal**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005SR	1/2	20	120	086	24.60
8095-007SR	3/4	20	160	086	26.18
8095-010SR	1	15	90	086	31.86
8095-012SR	1-1/4	10	0	086	53.94
8095-015SR	1-1/2	10	0	086	63.86
8095-020SR	2	5	0	086	72.67
8095-025SR	2-1/2	5	0	086	148.82
8095-030SR	3	5	0	086	169.08
8095-040SR	4	4	0	086	193.47
8095-060SR	6	1	0	086	406.07

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/Special Reinforced Fipt/FKM**

**Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005SR	1/2	20	120	086	9.22
8059-007SR	3/4	20	80	086	12.68
8059-010SR	1	15	90	086	16.48
8059-012SR	1-1/4	10	0	086	31.52
8059-015SR	1-1/2	10	0	086	38.88
8059-020SR	2	5	0	086	59.38
8059-025SR	2-1/2	5	0	086	127.63
8059-030SR	3	5	0	086	145.09
8059-040SR	4	4	0	086	166.59
8059-060SR	6	1	0	086	370.20

**Union 2000 - Socket/Special Reinforced Fipt/EPDM**

**Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005SR	1/2	20	160	086	8.86
8099-007SR	3/4	20	80	086	12.63
8099-010SR	1	15	90	086	16.29
8099-012SR	1-1/4	10	0	086	28.35
8099-015SR	1-1/2	10	0	086	36.73
8099-020SR	2	5	0	086	59.12
8099-025SR	2-1/2	5	0	086	126.45
8099-030SR	3	5	0	086	140.77
8099-040SR	4	4	0	086	160.65
8099-060SR	6	1	0	086	357.02

**Union 2000 - Fipt/FKM**

**Fipt x Fipt with FKM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002	1/4	25	150	080	27.34
858-003	3/8	25	150	080	27.34
8058-005	1/2	20	120	080	15.75
8058-007	3/4	20	80	080	22.06
8058-010	1	15	90	080	29.34
8058-012	1-1/4	10	0	080	55.99
8058-015	1-1/2	10	0	080	69.33
8058-020	2	5	0	080	106.66
8058-025	2-1/2	5	0	080	180.41
8058-030	3	5	0	080	270.56
8058-040	4	4	0	080	317.98
8058-060	6	1	0	080	706.60



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002	1/4	25	150	080	27.01
898-003	3/8	25	150	080	27.01
8098-005	1/2	20	240	080	15.56
8098-007	3/4	20	80	080	21.76
8098-010	1	15	90	080	28.99
8098-012	1-1/4	10	0	080	55.28
8098-015	1-1/2	10	0	080	68.45
8098-020	2	5	0	080	105.33
8098-025	2-1/2	5	0	080	141.06
8098-030	3	5	0	080	267.21
8098-040	4	4	0	080	312.52
8098-060	6	1	0	080	694.28

**Union 2000 - Special Reinforced Fipt/FKM**

**SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	9.48
8058-007SR	3/4	20	80	086	12.84
8058-010SR	1	15	90	086	17.19
8058-012SR	1-1/4	10	0	086	32.73
8058-015SR	1-1/2	10	0	086	40.27
8058-020SR	2	5	0	086	62.54
8058-025SR	2-1/2	5	0	086	130.77
8058-030SR	3	5	0	086	148.76
8058-040SR	4	4	0	086	175.12
8058-060SR	6	1	0	086	389.13

**Union 2000 - Special Reinforced Fipt/EPDM**

**SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	9.34
8098-007SR	3/4	20	80	086	12.72
8098-010SR	1	15	90	086	16.84
8098-012SR	1-1/4	10	0	086	31.32
8098-015SR	1-1/2	10	0	086	39.39
8098-020SR	2	5	0	086	61.89
8098-025SR	2-1/2	5	0	086	124.93
8098-030SR	3	5	0	086	147.34
8098-040SR	4	4	0	086	169.14
8098-060SR	6	1	0	086	375.92

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union (Old Style) - Socket/FKM**

**Socket x Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005	1/2	15	90	080	13.59
857-007	3/4	10	60	080	17.26
857-010	1	10	40	080	19.69
857-012	1-1/4	5	20	080	39.13
857-015	1-1/2	5	0	080	44.31
857-020	2	5	0	080	60.06
857-025	2-1/2	5	0	080	96.20
857-030	3	5	0	080	111.84
857-040	4	4	0	080	155.78

**Union (Old Style) - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005	1/2	15	90	080	13.39
897-007	3/4	10	60	080	17.04
897-010	1	10	40	080	19.51
897-012	1-1/4	5	20	080	38.66
897-015	1-1/2	5	0	080	43.75
897-020	2	5	0	080	59.36
897-025	2-1/2	5	0	080	94.36
897-030	3	5	0	080	110.45
897-040	4	4	0	080	152.78

**Union (Old Style) - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005	1/2	15	90	080	16.55
859-007	3/4	10	60	080	23.14
859-010	1	10	40	080	30.77
859-012	1-1/4	5	20	080	58.78
859-015	1-1/2	5	0	080	72.76
859-020	2	5	0	080	112.01
859-025	2-1/2	5	0	080	199.03
859-030	3	5	0	080	264.36
859-040	4	4	0	080	303.81

**Union (Old Style) - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005	1/2	15	90	080	16.34
899-007	3/4	10	60	080	22.85
899-010	1	10	40	080	30.38
899-012	1-1/4	5	20	080	58.08

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Union (Old Style) - Socket/Fipt/EPDM (continued)</b>					
<b>Socket x Fipt with EPDM O-ring Seal</b>					
899-015	1-1/2	5	0	080	71.88
899-020	2	5	0	080	110.61
899-025	2-1/2	5	0	080	156.40
899-030	3	5	0	080	261.04
899-040	4	4	0	080	299.74

**Union (Old Style) - Special Reinforced Fipt/FKM**

**Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002SR	1/4	25	150	086	16.98
859-003SR	3/8	25	100	086	16.98
859-005SR	1/2	10	60	086	9.22
859-007SR	3/4	10	60	086	12.68
859-010SR	1	10	40	086	16.48
859-012SR	1-1/4	5	20	086	31.52
859-015SR	1-1/2	5	0	086	38.88
859-020SR	2	5	0	086	59.38
859-030SR	3	5	0	086	145.09
859-040SR	4	4	0	086	166.59

**Union (Old Style) - Special Reinforced Fipt/EPDM**

**Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	16.75
899-003SR	3/8	25	100	086	16.75
899-005SR	1/2	10	60	086	8.86
899-007SR	3/4	10	40	086	12.63
899-010SR	1	10	40	086	16.29
899-012SR	1-1/4	5	20	086	28.35
899-015SR	1-1/2	5	0	086	36.73
899-020SR	2	5	0	086	59.12
899-030SR	3	5	0	086	140.77
899-040SR	4	4	0	086	160.65

**Union - Socket/Brass Fipt/FKM**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005BR	1/2	10	60	086	38.53
859-007BR	3/4	10	40	086	58.94
859-010BR	1	10	0	086	72.73
859-012BR	1-1/4	5	20	086	125.53
859-015BR	1-1/2	5	0	086	166.14
859-020BR	2	5	0	086	220.79

**Not intended to convey or dispense water for human consumption through drinking or cooking**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Socket/Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005BR	1/2	10	60	086	39.88
899-007BR	3/4	10	60	086	53.14
899-010BR	1	10	0	086	71.66
899-012BR	1-1/4	5	20	086	120.52
899-015BR	1-1/2	5	0	086	159.52
899-020BR	2	5	0	086	212.62

**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union (Old Style) - Fipt/FKM**

**Fipt x Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005	1/2	15	90	080	15.75
858-007	3/4	10	60	080	22.06
858-010	1	10	40	080	29.34
858-012	1-1/4	5	20	080	55.99
858-015	1-1/2	5	0	080	69.33
858-020	2	5	0	080	106.66
858-025	2-1/2	5	0	080	180.41
858-030	3	5	0	080	270.56
858-040	4	4	0	080	317.98

**Union (Old Style) - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005	1/2	15	90	080	15.56
898-007	3/4	10	60	080	21.76
898-010	1	10	40	080	28.99
898-012	1-1/4	5	20	080	55.28
898-015	1-1/2	5	0	080	68.45
898-020	2	5	0	080	105.33
898-025	2-1/2	5	0	080	141.06
898-030	3	5	0	080	267.21
898-040	4	4	0	080	312.52

**Union - Transition JIS to ASTM/FKM**

**JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8258-016	16 DN X 1/2	20	160	197	14.91
8258-020	20 DN X 3/4	20	80	197	20.83
8258-025	25 DN X 1	15	90	197	27.72
8258-030	30 DN X 1-1/4	10	0	197	52.92
8258-040	40 DN X 1-1/2	10	0	197	65.51
8258-075	75 DN X 3	5	0	197	237.92



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Transition JIS to ASTM/FKM (continued)**

**JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**

8258-100	100 DN X 4	4	0	197	273.43
----------	------------	---	---	-----	--------

**Union - Transition JIS to ASTM/EPDM**

**JIS (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8298-016	16 DN X 1/2	20	160	197	14.69
8298-020	20 DN X 3/4	20	80	197	20.57
8298-025	25 DN X 1	15	90	197	27.36
8298-030	30 DN X 1-1/4	10	0	197	52.01
8298-040	40 DN X 1-1/2	10	0	197	64.68
8298-050	50 DN X 2	5	0	197	99.55
8298-075	75 DN X 3	5	0	197	234.94
8298-100	100 DN X 4	4	0	197	269.75

**Union - Transition BSP to ASTM/FKM**

**BSP Thread (in.) x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8359-005	1/2	20	160	197	14.91
8359-007	3/4	20	80	197	20.83
8359-010	1	15	90	197	27.72
8359-012	1-1/4	10	0	197	52.92
8359-015	1-1/2	10	0	197	65.51
8359-020	2	5	0	197	100.79
8359-030	3	5	0	197	237.92
8359-040	4	4	0	197	273.43

**Union - Transition BSP to ASTM/EPDM**

**BSP Thread (in.) x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8399-005	1/2	10	60	197	14.69
8399-007	3/4	20	80	197	20.57
8399-010	1	15	90	197	27.36
8399-012	1-1/4	10	0	197	52.26
8399-015	1-1/2	10	0	197	64.68
8399-020	2	5	0	197	99.55
8399-030	3	5	0	197	234.94
8399-040	4	4	0	197	269.75

**Union - Transition DIN to ASTM/FKM**

**DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	12.20
8657-025	25 d X 3/4	10	60	197	15.54

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Transition DIN to ASTM/FKM (continued)**

**DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal**

8657-032	32 d X 1	10	40	197	17.73
8657-040	40 d X 1-1/4	10	0	197	35.21
8657-050	50 d X 1-1/2	10	0	197	39.87
8657-063	63 d X 2	5	0	197	54.08
8657-090	90 d X 3	5	0	197	100.66
8657-110	110 d X 4	4	0	197	140.21

**Union - Transition DIN to ASTM/EPDM**

**DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8697-020	20 d X 1/2	20	240	197	12.04
8697-025	25 d X 3/4	10	60	197	15.35
8697-032	32d X 1	15	90	197	17.55
8697-040	40 d X 1-1/4	10	0	197	34.79
8697-050	50 d X 1-1/2	10	0	197	39.39
8697-063	63 d X 2	5	0	197	53.42
8697-090	90 d X 3	5	0	197	99.41
8697-110	110 d X 4	4	0	197	137.48

**Union - Transition DIN to ASTM/FKM**

**DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	14.91
8658-025	25 d X 3/4	20	80	197	20.83
8658-032	32 d X 1	15	90	197	27.72
8658-040	40 d X 1-1/4	10	0	197	52.92
8658-050	50 d X 1-1/2	10	0	197	65.51
8658-063	63 d X 2	5	0	197	100.79
8658-090	90 d X 3	5	0	197	237.92
8658-110	110 d X 4	4	0	197	273.43

**Union - Transition DIN to ASTM/EPDM**

**DIN (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8698-020	20 d X 1/2	20	160	197	14.69
8698-025	25 d X 3/4	20	80	197	20.57
8698-032	32 d X 1	15	90	197	27.36
8698-040	40 d X 1-1/4	10	0	197	52.01
8698-050	50 d X 1-1/2	10	0	197	64.68
8698-063	63 d X 2	5	0	197	99.55
8698-090	90 d X 3	5	0	197	234.94
8698-110	110 d X 4	4	0	197	269.75

# PVC Schedule 80 Fittings & Tank Adapters



## Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Union - Transition JIS to ASTM/FKM

JIS (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8257-016	16 DN X 1/2	20	160	197	12.20
8257-020	20 DN X 3/4	10	60	197	15.54
8257-025	25 DN X 1	15	90	197	17.73
8257-030	30 DN X 1-1/4	10	0	197	35.21
8257-040	40 DN X 1-1/2	10	0	197	39.87
8257-050	50 DN X 2	5	0	197	54.08
8257-075	75 DN X 3	5	0	197	100.66
8257-100	100 DN X 4	4	0	197	140.21

### Union - Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	12.04
8297-020	20 DN X 3/4	20	80	197	15.35
8297-025	25 DN X 1	15	90	197	17.55
8297-030	30 DN X 1-1/4	10	0	197	34.79
8297-040	40 DN X 1-1/2	10	0	197	39.39
8297-050	50 DN X 2	5	0	197	53.42
8297-075	75 DN X 3	5	0	197	99.41
8297-100	100 DN X 4	4	0	197	137.48

### Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	14.20
8358-007	3/4	20	80	197	19.84
8358-010	1	15	90	197	26.41
8358-012	1-1/4	10	0	197	50.39
8358-015	1-1/2	10	0	197	62.39
8358-020	2	5	0	197	96.00
8358-030	3	5	0	197	243.51
8358-040	4	4	0	197	286.16

### Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	13.99
8398-007	3/4	10	60	197	19.59
8398-010	1	10	40	197	26.08
8398-012	1-1/4	5	20	197	49.77
8398-015	1-1/2	5	0	197	61.61

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

### Union - Transition BSP to ASTM/EPDM (continued)

BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal

8398-020	2	5	0	197	98.98
8398-030	3	5	0	197	240.48
8398-040	4	4	0	197	281.26

## Tank Adapters

### Tank Adapters, PVC New Style Standard with Neoprene Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	38.05
8170-003	3/8	25	150	100	38.05
8170-005	1/2	25	0	100	38.05
8170-007	3/4	25	0	100	43.38
8170-010	1	25	0	100	48.19
8170-012	1-1/4	20	0	100	58.06
8170-015	1-1/2	20	0	100	63.71
8170-020	2	15	0	100	94.43
8170-025	2-1/2	4	0	100	145.92
8170-030	3	4	0	100	173.71
8170-040	4	2	0	100	342.17
8170-060	6	1	0	100	664.18
8170-080	8	1	0	100	1473.95

### Tank Adapters, PVC New Style Standard with EPDM Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002	1/4	25	150	100	39.21
8170E-003	3/8	25	150	100	39.21
8170E-005	1/2	25	0	100	39.21
8170E-007	3/4	25	0	100	44.24
8170E-010	1	25	0	100	53.34
8170E-012	1-1/4	20	0	100	63.40
8170E-015	1-1/2	20	0	100	69.06
8170E-020	2	15	0	100	101.63
8170E-025	2-1/2	4	0	100	169.38
8170E-030	3	4	0	100	180.19
8170E-040	4	2	0	100	350.81
8170E-060	6	1	0	100	688.02
8170E-080	8	1	0	100	1528.61

### Tank Adapters, PVC New Style Standard with FKM Gaskets



Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002	1/4	25	150	100	64.65
8170V-003	3/8	25	150	100	64.65
8170V-005	1/2	25	0	100	64.65
8170V-007	3/4	25	0	100	70.88