



Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing**

**Socket x Socket x Socket x Socket**



Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338	3X2	5	0	080	474.69
876-420F <sup>2</sup>	4X2	1	2	083	619.94
876-421F <sup>2</sup>	4X2-1/2	1	2	083	701.89
876-422F <sup>2</sup>	4X3	1	2	083	726.01
876-528F <sup>2</sup>	6X2	1	2	083	729.48
876-529F <sup>2</sup>	6X2-1/2	1	2	083	761.95
876-530F <sup>2</sup>	6X3	1	2	083	766.92
876-532F <sup>2</sup>	6X4	1	0	083	914.16
876-578F <sup>2</sup>	8X2	1	2	083	940.96
876-579F <sup>2</sup>	8X2-1/2	1	2	083	985.36
876-580F <sup>2</sup>	8X3	1	0	083	991.39
876-582F <sup>2</sup>	8X4	1	0	083	1023.37
876-585F <sup>2</sup>	8X6	1	0	083	1155.49
876-621F <sup>2</sup>	10X2	1	0	083	1254.68
876-622F <sup>2</sup>	10X2-1/2	1	0	083	1350.59
876-623F <sup>2</sup>	10X3	1	0	083	1358.60
876-624F <sup>2</sup>	10X4	1	0	083	1410.16
876-626F <sup>2</sup>	10X6	1	0	083	1476.06
876-628F <sup>2</sup>	10X8	1	0	083	1897.02
876-661F <sup>2</sup>	12X2	1	0	083	1401.93
876-662F <sup>2</sup>	12X2-1/2	1	0	083	1485.11
876-663F <sup>2</sup>	12X3	1	0	083	1508.55
876-664F <sup>2</sup>	12X4	1	0	083	1606.89
876-666F <sup>2</sup>	12X6	1	0	083	1864.76
876-668F <sup>2</sup>	12X8	1	0	083	2227.37
876-670F <sup>2</sup>	12X10	1	0	083	2540.40

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union 2000 - Socket/FKM**

**Socket X Socket with FKM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002	1/4	25	150	080	26.73
857-003	3/8	25	150	080	26.73
8057-005	1/2	20	120	080	14.31
8057-007	3/4	20	80	080	18.17
8057-010	1	15	90	080	20.73
8057-012	1-1/4	10	0	080	41.19
8057-015	1-1/2	10	0	080	46.64
8057-020	2	5	0	080	63.22

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/FKM (continued)**

**Socket X Socket with FKM O-ring Seal**

8057-025	2-1/2	5	0	080	101.26
8057-030	3	5	0	080	117.73
8057-040	4	4	0	080	163.98
8057-060	6	1	0	080	364.44

**Union 2000 - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002	1/4	25	150	080	26.38
897-003	3/8	25	150	080	26.38
8097-005	1/2	20	120	080	14.09
8097-007	3/4	20	80	080	17.94
8097-010	1	15	90	080	20.54
8097-012	1-1/4	10	0	080	40.69
8097-015	1-1/2	10	0	080	46.05
8097-020	2	5	0	080	62.48
8097-025	2-1/2	5	0	080	99.33
8097-030	3	5	0	080	116.26
8097-040	4	4	0	080	160.82
8097-060	6	1	0	080	357.39

**Union 2000 - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002	1/4	25	150	080	28.78
859-003	3/8	25	150	080	28.78
8059-005	1/2	20	120	080	17.42
8059-007	3/4	20	80	080	24.36
8059-010	1	15	90	080	32.39
8059-012	1-1/4	10	0	080	61.87
8059-015	1-1/2	10	0	080	76.59
8059-020	2	5	0	080	117.91
8059-025	2-1/2	5	0	080	209.51
8059-030	3	5	0	080	278.27
8059-040	4	4	0	080	319.80
8059-060	6	1	0	080	710.71

**Union 2000 - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	28.43
899-003	3/8	25	150	080	28.43
8099-005	1/2	20	120	080	17.20
8099-007	3/4	20	80	080	24.05

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Union 2000 - Socket/Fipt/EPDM (continued)</b>					
<b>Socket x Fipt with EPDM O-ring Seal</b>					
8099-010	1	15	90	080	31.98
8099-012	1-1/4	10	0	080	61.14
8099-015	1-1/2	10	0	080	75.66
8099-020	2	5	0	080	116.43
8099-025	2-1/2	5	0	080	164.63
8099-030	3	5	0	080	274.78
8099-040	4	4	0	080	315.52
8099-060	6	1	0	080	701.12

**Union 2000 - Socket/Spigot/FKM**

**Socket x Spigot with FKM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005	1/2	20	120	080	14.31
8056-007	3/4	20	160	080	18.17
8056-010	1	15	90	080	20.73
8056-012	1-1/4	10	0	080	41.19
8056-015	1-1/2	10	0	080	46.64
8056-020	2	5	0	080	63.22
8056-025	2-1/2	5	0	080	101.26
8056-030	3	5	0	080	117.73
8056-040	4	4	0	080	163.98
8056-060	6	1	0	080	364.44

**Union 2000 - Socket/Spigot/EPDM**

**Socket x Spigot with EPDM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005	1/2	20	160	080	14.09
8096-007	3/4	20	80	080	17.94
8096-010	1	15	90	080	20.54
8096-012	1-1/4	10	0	080	40.69
8096-015	1-1/2	10	0	080	46.05
8096-020	2	5	0	080	62.48
8096-025	2-1/2	5	0	080	99.33
8096-030	3	5	0	080	116.26
8096-040	4	4	0	080	160.82
8096-060	6	1	0	080	357.39

**Union 2000 - Special Reinforced Fipt/Spigot/FKM**

**SR Fipt x Spigot with FKM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005SR	1/2	20	160	086	26.27
8055-007SR	3/4	20	160	086	28.33

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Special Reinforced Fipt/Spigot/FKM (continued)**  
**SR Fipt x Spigot with FKM O-ring Seal**

8055-010SR	1	15	90	086	34.82
8055-012SR	1-1/4	10	0	096	65.22
8055-015SR	1-1/2	10	0	086	74.47
8055-020SR	2	5	0	086	84.79
8055-025SR	2-1/2	5	0	086	166.37
8055-030SR	3	5	0	086	187.03
8055-040SR	4	4	0	086	212.13
8055-060SR	6	1	0	086	450.58

**Union 2000 - Special Reinforced Fipt/Spigot/EPDM**

**SR Fipt x Spigot with EPDM O-ring Seal**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005SR	1/2	20	120	086	25.89
8095-007SR	3/4	20	160	086	27.56
8095-010SR	1	15	90	086	33.54
8095-012SR	1-1/4	10	0	086	56.78
8095-015SR	1-1/2	10	0	086	67.22
8095-020SR	2	5	0	086	76.49
8095-025SR	2-1/2	5	0	086	156.65
8095-030SR	3	5	0	086	177.98
8095-040SR	4	4	0	086	203.65
8095-060SR	6	1	0	086	427.44

**Union 2000 - Socket/Special Reinforced Fipt/FKM**

**Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005SR	1/2	20	120	086	9.71
8059-007SR	3/4	20	80	086	13.35
8059-010SR	1	15	90	086	17.35
8059-012SR	1-1/4	10	0	086	33.18
8059-015SR	1-1/2	10	0	086	40.93
8059-020SR	2	5	0	086	62.51
8059-025SR	2-1/2	5	0	086	134.35
8059-030SR	3	5	0	086	152.73
8059-040SR	4	4	0	086	175.36
8059-060SR	6	1	0	086	389.68

**Union 2000 - Socket/Special Reinforced Fipt/EPDM**

**Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005SR	1/2	20	160	086	9.33
8099-007SR	3/4	20	80	086	13.29
8099-010SR	1	15	90	086	17.15
8099-012SR	1-1/4	10	0	086	29.84



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Union 2000 - Socket/Special Reinforced Fipt/EPDM (continued)</b>					
<b>Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar</b>					
8099-015SR	1-1/2	10	0	086	38.66
8099-020SR	2	5	0	086	62.23
8099-025SR	2-1/2	5	0	086	133.11
8099-030SR	3	5	0	086	148.18
8099-040SR	4	4	0	086	169.11
8099-060SR	6	1	0	086	375.81

**Union 2000 - Fipt/FKM**

**Fipt x Fipt with FKM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002	1/4	25	150	080	28.78
858-003	3/8	25	150	080	28.78
8058-005	1/2	20	120	080	16.58
8058-007	3/4	20	80	080	23.22
8058-010	1	15	90	080	30.88
8058-012	1-1/4	10	0	080	58.94
8058-015	1-1/2	10	0	080	72.98
8058-020	2	5	0	080	112.27
8058-025	2-1/2	5	0	080	189.91
8058-030	3	5	0	080	284.80
8058-040	4	4	0	080	334.72
8058-060	6	1	0	080	743.79

**Union 2000 - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002	1/4	25	150	080	28.43
898-003	3/8	25	150	080	28.43
8098-005	1/2	20	240	080	16.38
8098-007	3/4	20	80	080	22.91
8098-010	1	15	90	080	30.52
8098-012	1-1/4	10	0	080	58.19
8098-015	1-1/2	10	0	080	72.05
8098-020	2	5	0	080	110.87
8098-025	2-1/2	5	0	080	148.48
8098-030	3	5	0	080	281.27
8098-040	4	4	0	080	328.97
8098-060	6	1	0	080	730.82

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Special Reinforced Fipt/FKM**

**SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	9.98
8058-007SR	3/4	20	80	086	13.52
8058-010SR	1	15	90	086	18.09
8058-012SR	1-1/4	10	0	086	34.45
8058-015SR	1-1/2	10	0	086	42.39
8058-020SR	2	5	0	086	65.83
8058-025SR	2-1/2	5	0	086	137.65
8058-030SR	3	5	0	086	156.59
8058-040SR	4	4	0	086	184.34
8058-060SR	6	1	0	086	409.61

**Union 2000 - Special Reinforced Fipt/EPDM**

**SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	9.83
8098-007SR	3/4	20	80	086	13.39
8098-010SR	1	15	90	086	17.73
8098-012SR	1-1/4	10	0	086	32.97
8098-015SR	1-1/2	10	0	086	41.46
8098-020SR	2	5	0	086	65.15
8098-025SR	2-1/2	5	0	086	131.51
8098-030SR	3	5	0	086	155.09
8098-040SR	4	4	0	086	178.04
8098-060SR	6	1	0	086	395.71

**Union (Old Style) - Socket/FKM**

**Socket x Socket with FKM O-ring Seal**

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005	1/2	15	90	080	14.31
857-007	3/4	10	60	080	18.17
857-010	1	10	40	080	20.73
857-012	1-1/4	5	20	080	41.19
857-015	1-1/2	5	0	080	46.64
857-020	2	5	0	080	63.22
857-025	2-1/2	5	0	080	101.26
857-030	3	5	0	080	117.73
857-040	4	4	0	080	163.98

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union (Old Style) - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005	1/2	15	90	080	14.09
897-007	3/4	10	60	080	17.94
897-010	1	10	40	080	20.54
897-012	1-1/4	5	20	080	40.69
897-015	1-1/2	5	0	080	46.05
897-020	2	5	0	080	62.48
897-025	2-1/2	5	0	080	99.33
897-030	3	5	0	080	116.26
897-040	4	4	0	080	160.82

**Union (Old Style) - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005	1/2	15	90	080	17.42
859-007	3/4	10	60	080	24.36
859-010	1	10	40	080	32.39
859-012	1-1/4	5	20	080	61.87
859-015	1-1/2	5	0	080	76.59
859-020	2	5	0	080	117.91
859-025	2-1/2	5	0	080	209.51
859-030	3	5	0	080	278.27
859-040	4	4	0	080	319.80

**Union (Old Style) - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005	1/2	15	90	080	17.20
899-007	3/4	10	60	080	24.05
899-010	1	10	40	080	31.98
899-012	1-1/4	5	20	080	61.14
899-015	1-1/2	5	0	080	75.66
899-020	2	5	0	080	116.43
899-025	2-1/2	5	0	080	164.63
899-030	3	5	0	080	274.78
899-040	4	4	0	080	315.52

**Union (Old Style) - Special Reinforced Fipt/FKM**

**Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002SR	1/4	25	150	086	17.87
859-003SR	3/8	25	100	086	17.87

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union (Old Style) - Special Reinforced Fipt/FKM (continued)**

**Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar**

859-005SR	1/2	10	60	086	9.71
859-007SR	3/4	10	60	086	13.35
859-010SR	1	10	40	086	17.35
859-012SR	1-1/4	5	20	086	33.18
859-015SR	1-1/2	5	0	086	40.93
859-020SR	2	5	0	086	62.51
859-030SR	3	5	0	086	152.73
859-040SR	4	4	0	086	175.36

**Union (Old Style) - Special Reinforced Fipt/EPDM**

**Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	17.63
899-003SR	3/8	25	100	086	17.63
899-005SR	1/2	10	60	086	9.33
899-007SR	3/4	10	40	086	13.29
899-010SR	1	10	40	086	17.15
899-012SR	1-1/4	5	20	086	29.84
899-015SR	1-1/2	5	0	086	38.66
899-020SR	2	5	0	086	62.23
899-030SR	3	5	0	086	148.18
899-040SR	4	4	0	086	169.11

**Union - Socket/Brass Fipt/FKM**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005BR	1/2	10	60	086	40.56
859-007BR	3/4	10	40	086	62.04
859-010BR	1	10	0	086	76.56
859-012BR	1-1/4	5	20	086	132.14
859-015BR	1-1/2	5	0	086	174.88
859-020BR	2	5	0	086	232.41

**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union - Socket/Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005BR	1/2	10	60	086	41.98
899-007BR	3/4	10	60	086	55.94
899-010BR	1	10	0	086	75.43
899-012BR	1-1/4	5	20	086	126.86
899-015BR	1-1/2	5	0	086	167.92
899-020BR	2	5	0	086	223.81

**Not intended to convey or dispense water for human consumption through drinking or cooking**



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union (Old Style) - Fipt/FKM**

**Fipt x Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005	1/2	15	90	080	16.58
858-007	3/4	10	60	080	23.22
858-010	1	10	40	080	30.88
858-012	1-1/4	5	20	080	58.94
858-015	1-1/2	5	0	080	72.98
858-020	2	5	0	080	112.27
858-025	2-1/2	5	0	080	189.91
858-030	3	5	0	080	284.80
858-040	4	4	0	080	334.72

**Union (Old Style) - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005	1/2	15	90	080	16.38
898-007	3/4	10	60	080	22.91
898-010	1	10	40	080	30.52
898-012	1-1/4	5	20	080	58.19
898-015	1-1/2	5	0	080	72.05
898-020	2	5	0	080	110.87
898-025	2-1/2	5	0	080	148.48
898-030	3	5	0	080	281.27
898-040	4	4	0	080	328.97

**Union -Transition JIS to ASTM/FKM**

**JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8258-016	16 DN X 1/2	20	160	197	15.69
8258-020	20 DN X 3/4	20	80	197	21.93
8258-025	25 DN X 1	15	90	197	29.18
8258-030	30 DN X 1-1/4	10	0	197	55.71
8258-040	40 DN X 1-1/2	10	0	197	68.96
8258-075	75 DN X 3	5	0	197	250.44
8258-100	100 DN X 4	4	0	197	287.82

**Union -Transition JIS to ASTM/EPDM**

**JIS (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8298-016	16 DN X 1/2	20	160	197	15.46
8298-020	20 DN X 3/4	20	80	197	21.65
8298-025	25 DN X 1	15	90	197	28.80
8298-030	30 DN X 1-1/4	10	0	197	54.75

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union -Transition JIS to ASTM/EPDM (continued)**

**JIS (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**

8298-040	40 DN X 1-1/2	10	0	197	68.08
8298-050	50 DN X 2	5	0	197	104.79
8298-075	75 DN X 3	5	0	197	247.31
8298-100	100 DN X 4	4	0	197	283.95

**Union - Transition BSP to ASTM/FKM**

**BSP Thread (in.) x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8359-005	1/2	20	160	197	15.69
8359-007	3/4	20	80	197	21.93
8359-010	1	15	90	197	29.18
8359-012	1-1/4	10	0	197	55.71
8359-015	1-1/2	10	0	197	68.96
8359-020	2	5	0	197	106.09
8359-030	3	5	0	197	250.44
8359-040	4	4	0	197	287.82

**Union - Transition BSP to ASTM/EPDM**

**BSP Thread (in.) x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8399-005	1/2	10	60	197	15.46
8399-007	3/4	20	80	197	21.65
8399-010	1	15	90	197	28.80
8399-012	1-1/4	10	0	197	55.01
8399-015	1-1/2	10	0	197	68.08
8399-020	2	5	0	197	104.79
8399-030	3	5	0	197	247.31
8399-040	4	4	0	197	283.95

**Union - Transition DIN to ASTM/FKM**

**DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	12.84
8657-025	25 d X 3/4	10	60	197	16.36
8657-032	32 d X 1	10	40	197	18.66
8657-040	40 d X 1-1/4	10	0	197	37.06
8657-050	50 d X 1-1/2	10	0	197	41.97
8657-063	63 d X 2	5	0	197	56.93
8657-090	90 d X 3	5	0	197	105.96
8657-110	110 d X 4	4	0	197	147.59

**Union - Transition DIN to ASTM/EPDM**

**DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8697-020	20 d X 1/2	20	240	197	12.67
----------	------------	----	-----	-----	-------

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings & Tank Adapters**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Union - Transition DIN to ASTM/EPDM (continued)</b>					
<b>DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal</b>					
8697-025	25 d X 3/4	10	60	197	16.16
8697-032	32d X 1	15	90	197	18.47
8697-040	40 d X 1-1/4	10	0	197	36.62
8697-050	50 d X 1-1/2	10	0	197	41.46
8697-063	63 d X 2	5	0	197	56.23
8697-090	90 d X 3	5	0	197	104.64
8697-110	110 d X 4	4	0	197	144.72

**Union - Transition DIN to ASTM/FKM**

**DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	15.69
8658-025	25 d X 3/4	20	80	197	21.93
8658-032	32 d X 1	15	90	197	29.18
8658-040	40 d X 1-1/4	10	0	197	55.71
8658-050	50 d X 1-1/2	10	0	197	68.96
8658-063	63 d X 2	5	0	197	106.09
8658-090	90 d X 3	5	0	197	250.44
8658-110	110 d X 4	4	0	197	287.82

**Union - Transition DIN to ASTM/EPDM**

**DIN (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8698-020	20 d X 1/2	20	160	197	15.46
8698-025	25 d X 3/4	20	80	197	21.65
8698-032	32 d X 1	15	90	197	28.80
8698-040	40 d X 1-1/4	10	0	197	54.75
8698-050	50 d X 1-1/2	10	0	197	68.08
8698-063	63 d X 2	5	0	197	104.79
8698-090	90 d X 3	5	0	197	247.31
8698-110	110 d X 4	4	0	197	283.95

**Union-Transition JIS to ASTM/FKM**

**JIS (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8257-016	16 DN X 1/2	20	160	197	12.84
8257-020	20 DN X 3/4	10	60	197	16.36
8257-025	25 DN X 1	15	90	197	18.66
8257-030	30 DN X 1-1/4	10	0	197	37.06
8257-040	40 DN X 1-1/2	10	0	197	41.97
8257-050	50 DN X 2	5	0	197	56.93
8257-075	75 DN X 3	5	0	197	105.96
8257-100	100 DN X 4	4	0	197	147.59

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union -Transition JIS to ASTM/EPDM**

**JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	12.67
8297-020	20 DN X 3/4	20	80	197	16.16
8297-025	25 DN X 1	15	90	197	18.47
8297-030	30 DN X 1-1/4	10	0	197	36.62
8297-040	40 DN X 1-1/2	10	0	197	41.46
8297-050	50 DN X 2	5	0	197	56.23
8297-075	75 DN X 3	5	0	197	104.64
8297-100	100 DN X 4	4	0	197	144.72

**Union - Transition BSP to ASTM/FKM**

**BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	14.95
8358-007	3/4	20	80	197	20.88
8358-010	1	15	90	197	27.80
8358-012	1-1/4	10	0	197	53.04
8358-015	1-1/2	10	0	197	65.67
8358-020	2	5	0	197	101.05
8358-030	3	5	0	197	256.33
8358-040	4	4	0	197	301.22

**Union - Transition BSP to ASTM/EPDM**

**BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	14.73
8398-007	3/4	10	60	197	20.62
8398-010	1	10	40	197	27.45
8398-012	1-1/4	5	20	197	52.39
8398-015	1-1/2	5	0	197	64.85
8398-020	2	5	0	197	104.19
8398-030	3	5	0	197	253.14
8398-040	4	4	0	197	296.06

**Tank Adapters**

**Tank Adapters, PVC New Style Standard with Neoprene Gaskets**

**Socket x Socket**



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	40.05
8170-003	3/8	25	150	100	40.05
8170-005	1/2	25	0	100	40.05
8170-007	3/4	25	0	100	45.66
8170-010	1	25	0	100	50.73