



**Schedule 80 PVC Product**  
**PVC Schedule 80 Fittings**

**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap - Special Reinforced (continued)</b>					
<b>SR Fipt - Stainless Steel Collar</b>					
848-005SR	1/2	50	300	086	5.14
848-007SR	3/4	25	300	086	6.59
848-030SR	3	5	0	086	40.63

**Plugs**

**Plug**

**Spigot**



849-005	1/2	50	300	080	6.38
849-007	3/4	50	300	080	7.11
849-010	1	50	200	080	8.01
849-012	1-1/4	25	100	080	10.23
849-015	1-1/2	10	120	080	11.22
849-020	2	10	120	080	14.85
849-025F <sup>4</sup>	2-1/2	1	4	083	34.76
849-030F <sup>4</sup>	3	1	4	083	41.92
849-040F <sup>4</sup>	4	1	4	083	91.69
849-060F <sup>4</sup>	6	1	6	083	254.94
849-080F <sup>4</sup>	8	1	6	083	331.95
849-100F <sup>4</sup>	10	1	2	083	539.78
849-120F <sup>4</sup>	12	1	0	083	999.93

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

**Plug**

**Mipt**



850-002	1/4	50	900	080	7.37
850-003	3/8	50	600	080	7.37
850-005	1/2	50	500	080	6.57
850-007	3/4	50	300	080	6.82
850-010	1	25	150	080	8.37
850-012	1-1/4	10	120	080	12.34
850-015	1-1/2	10	120	080	14.99
850-020	2	10	120	080	15.39
850-025	2-1/2	5	60	080	42.97
850-030	3	5	40	080	50.14
850-040	4	6	0	080	97.61
850-060	6	6	0	080	116.04
850-080	8	6	0	080	167.98
850-080F <sup>4</sup>	8	1	2	083	286.44
850-100F <sup>4</sup>	10	1	3	083	419.80
850-120F <sup>4</sup>	12	1	0	083	574.99

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	15.96
875-007	3/4	25	0	080	16.78
875-010	1	20	0	080	26.83
875-012	1-1/4	20	0	080	41.15
875-015	1-1/2	20	0	080	41.15
875-020	2	10	0	080	118.06
875-025 <sup>1</sup>	2-1/2	6	0	080	291.63
875-030	3	5	0	080	379.52
875-040	4	4	0	080	470.24
875-050F <sup>2</sup>	5	1	2	083	735.63
875-060	6	2	0	080	642.26
875-080	8	1	0	080	1291.61
875-080F	8	1	0	083	995.23
875-100F <sup>2</sup>	10	1	0	083	1561.73
875-120F <sup>2</sup>	12	1	0	083	1985.02
875-140F <sup>2</sup>	14	1	0	083	3315.27
875-160F <sup>2</sup>	16	1	0	083	4355.01
875-180F <sup>2</sup>	18	1	0	083	4882.56
875-200F <sup>2</sup>	20	1	0	083	6522.16
875-240F <sup>2</sup>	24	1	0	083	8680.16

<sup>1</sup> Sized with Bushing

<sup>2</sup> Fiberglass reinforced

**Wye - Reducing**

**Socket x Socket x Socket**



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 <sup>1</sup>	3/4X1/2	25	0	080	19.36
875-130 <sup>1</sup>	1X1/2	20	0	080	33.95
875-131 <sup>1</sup>	1X3/4	20	0	080	33.95
875-166 <sup>1</sup>	1-1/4X1/2	20	0	080	52.29
875-167 <sup>1</sup>	1-1/4X3/4	20	0	080	52.29
875-168 <sup>1</sup>	1-1/4X1	20	0	080	52.29
875-209 <sup>1</sup>	1-1/2X1/2	20	0	080	56.02
875-210 <sup>1</sup>	1-1/2X3/4	20	0	080	56.02
875-211 <sup>1</sup>	1-1/2X1	20	0	080	56.02
875-212 <sup>1</sup>	1-1/2X1-1/4	20	0	080	56.02

Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**



**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Wye - Reducing (continued)</b>					
<b>Socket x Socket x Socket</b>					
875-247 <sup>1</sup>	2X1/2	10	0	080	140.44
875-248 <sup>1</sup>	2X3/4	10	0	080	140.44
875-249 <sup>1</sup>	2X1	10	0	080	140.44
875-250 <sup>1</sup>	2X1-1/4	10	0	080	140.44
875-251 <sup>1</sup>	2X1-1/2	10	0	080	140.44
875-291 <sup>1</sup>	2-1/2X1-1/2	4	0	080	546.74
875-292 <sup>1</sup>	2-1/2X2-1/2X2	5	0	080	546.74
875-335 <sup>1</sup>	3X1	5	0	080	442.36
875-336 <sup>1</sup>	3X1-1/4	5	0	080	442.36
875-337 <sup>1</sup>	3X1-1/2	5	0	080	442.36
875-338 <sup>1</sup>	3X2	4	0	080	442.36
875-339 <sup>1</sup>	3X2-1/2	5	0	080	442.36
875-419 <sup>1</sup>	4X1-1/2	4	0	080	665.67
875-420	4X2	4	0	080	556.16
875-420F <sup>2</sup>	4X2	1	5	083	463.53
875-421 <sup>1</sup>	4X2-1/2	4	0	080	616.46
875-421F <sup>2</sup>	4X2-1/2	1	4	083	517.99
875-422	4X3	4	0	080	556.16
875-525 <sup>1</sup>	6X1	5	0	080	681.89
875-528 <sup>1</sup>	6X2	5	0	080	605.56
875-528F <sup>2</sup>	6X2	1	3	083	476.20
875-530 <sup>1</sup>	6X3	5	0	080	605.56
875-530F <sup>2</sup>	6X3	1	2	083	517.36
875-532	6X4	5	0	080	489.47
875-578 <sup>1</sup>	8X2	2	0	080	1689.63
875-578F <sup>2</sup>	8X2	1	2	083	770.45
875-579F <sup>2</sup>	8X2-1/2	1	2	083	787.73
875-580 <sup>1</sup>	8X3	2	0	080	1689.63
875-580F <sup>2</sup>	8X3	1	2	083	782.56
875-582	8X4	2	0	080	1689.63
875-582F <sup>2</sup>	8X4	1	2	083	829.76
875-585 <sup>1</sup>	8X6	1	0	080	1576.13
875-585F <sup>2</sup>	8X6	1	0	083	978.47
875-621F <sup>2</sup>	10X2	1	0	083	1037.17
875-622F <sup>2</sup>	10X2-1/2	1	0	083	1044.39
875-623 <sup>1</sup>	10X3	1	0	081	1968.09
875-623F <sup>2</sup>	10X3	1	0	083	1057.36
875-624F <sup>2</sup>	10X4	1	0	083	1152.40
875-625F <sup>2</sup>	10X5	1	0	083	1291.54
875-626	10X6	1	0	081	1824.77
875-626F <sup>2</sup>	10X6	1	0	083	1311.34
875-628	10X8	1	0	081	2323.20
875-628F <sup>2</sup>	10X8	1	0	083	1516.58
875-661F <sup>2</sup>	12X2	1	0	083	1150.98
875-662F <sup>2</sup>	12X2-1/2	1	0	083	1254.80
875-663F <sup>2</sup>	12X3	1	0	083	1373.13
875-664F <sup>2</sup>	12X4	1	0	083	1454.19
875-666F <sup>2</sup>	12X6	1	0	083	1658.46
875-668F <sup>2</sup>	12X8	1	0	083	1816.88
875-670F <sup>2</sup>	12X10	1	0	083	1925.41
875-694F <sup>2</sup>	14X4	1	0	083	1799.65

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Wye - Reducing (continued)**  
**Socket x Socket x Socket**

875-696F <sup>2</sup>	14X6	1	0	083	1904.42
875-698F <sup>2</sup>	14X8	1	0	083	1948.35
875-700F <sup>2</sup>	14X10	1	0	083	2175.32
875-702F <sup>2</sup>	14X12	1	0	083	2465.51
875-754F <sup>2</sup>	16X4	1	0	083	1960.02
875-756F <sup>2</sup>	16X6	1	0	083	1968.52
875-758F <sup>2</sup>	16X8	1	0	083	2221.63
875-760F <sup>2</sup>	16X10	1	0	083	2500.99
875-762F <sup>2</sup>	16X12	1	0	083	2724.92
875-764F <sup>2</sup>	16X14	1	0	083	3155.62
875-784F <sup>2</sup>	18X4	1	0	083	3518.62
875-786F <sup>2</sup>	18X6	1	0	083	3973.15
875-788F <sup>2</sup>	18X8	1	0	083	4120.73
875-790F <sup>2</sup>	18X10	1	0	083	4429.00
875-792F <sup>2</sup>	18X12	1	0	083	4445.88
875-794F <sup>2</sup>	18X14	1	0	083	4801.77
875-796F <sup>2</sup>	18X16	1	0	083	4835.62
875-814F <sup>2</sup>	20X4	1	0	083	4348.09
875-816F <sup>2</sup>	20X6	1	0	083	4685.38
875-818F <sup>2</sup>	20X8	1	0	083	4951.39
875-820F <sup>2</sup>	20X10	1	0	083	5119.09
875-822F <sup>2</sup>	20X12	1	0	083	5302.93
875-824F <sup>2</sup>	20X14	1	0	083	5724.64
875-826F <sup>2</sup>	20X16	1	0	083	6198.41
875-828F <sup>2</sup>	20X18	1	0	083	6433.89
875-904F <sup>2</sup>	24X4	1	0	083	5409.66
875-906F <sup>2</sup>	24X6	1	0	083	5595.78
875-908F <sup>2</sup>	24X8	1	0	083	5739.01
875-910F <sup>2</sup>	24X10	1	0	083	5998.73
875-912F <sup>2</sup>	24X12	1	0	083	6380.02
875-914F <sup>2</sup>	24X14	1	0	083	6627.49
875-916F <sup>2</sup>	24X16	1	0	083	7070.58
875-918F <sup>2</sup>	24X18	1	0	083	8153.82
875-920F <sup>2</sup>	24X20	1	0	083	8535.77

<sup>1</sup> Sized with Bushing  
<sup>2</sup> Fiberglass reinforced



**Double Wye**

**Socket x Socket x Socket x Socket**

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-020F <sup>2</sup>	2	1	4	083	390.34
876-030F <sup>2</sup>	3	1	4	083	491.94
876-040F <sup>2</sup>	4	1	2	083	893.34
876-060F <sup>2</sup>	6	1	0	083	1044.16
876-080F <sup>2</sup>	8	1	0	083	1244.04
876-100F <sup>2</sup>	10	1	0	083	2216.77
876-120F <sup>2</sup>	12	1	0	083	3121.72

For larger sizes please contact your Regional Spears® Distribution Center.

2-Fiberglass Reinforced



Schedule 80 PVC Product  
**PVC Schedule 80 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing**

**Socket x Socket x Socket x Socket**



Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338	3X2	5	0	080	474.69
876-420F <sup>2</sup>	4X2	1	2	083	619.94
876-421F <sup>2</sup>	4X2-1/2	1	2	083	701.89
876-422F <sup>2</sup>	4X3	1	2	083	726.01
876-528F <sup>2</sup>	6X2	1	2	083	729.48
876-529F <sup>2</sup>	6X2-1/2	1	2	083	761.95
876-530F <sup>2</sup>	6X3	1	2	083	766.92
876-532F <sup>2</sup>	6X4	1	0	083	914.16
876-578F <sup>2</sup>	8X2	1	2	083	940.96
876-579F <sup>2</sup>	8X2-1/2	1	2	083	985.36
876-580F <sup>2</sup>	8X3	1	0	083	991.39
876-582F <sup>2</sup>	8X4	1	0	083	1023.37
876-585F <sup>2</sup>	8X6	1	0	083	1155.49
876-621F <sup>2</sup>	10X2	1	0	083	1254.68
876-622F <sup>2</sup>	10X2-1/2	1	0	083	1350.59
876-623F <sup>2</sup>	10X3	1	0	083	1358.60
876-624F <sup>2</sup>	10X4	1	0	083	1410.16
876-626F <sup>2</sup>	10X6	1	0	083	1476.06
876-628F <sup>2</sup>	10X8	1	0	083	1897.02
876-661F <sup>2</sup>	12X2	1	0	083	1401.93
876-662F <sup>2</sup>	12X2-1/2	1	0	083	1485.11
876-663F <sup>2</sup>	12X3	1	0	083	1508.55
876-664F <sup>2</sup>	12X4	1	0	083	1606.89
876-666F <sup>2</sup>	12X6	1	0	083	1864.76
876-668F <sup>2</sup>	12X8	1	0	083	2227.37
876-670F <sup>2</sup>	12X10	1	0	083	2540.40

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union 2000 - Socket/FKM**

**Socket X Socket with FKM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002	1/4	25	150	080	26.73
857-003	3/8	25	150	080	26.73
8057-005	1/2	20	120	080	14.31
8057-007	3/4	20	80	080	18.17
8057-010	1	15	90	080	20.73
8057-012	1-1/4	10	0	080	41.19
8057-015	1-1/2	10	0	080	46.64
8057-020	2	5	0	080	63.22

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union 2000 - Socket/FKM (continued)**

**Socket X Socket with FKM O-ring Seal**

8057-025	2-1/2	5	0	080	101.26
8057-030	3	5	0	080	117.73
8057-040	4	4	0	080	163.98
8057-060	6	1	0	080	364.44

**Union 2000 - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002	1/4	25	150	080	26.38
897-003	3/8	25	150	080	26.38
8097-005	1/2	20	120	080	14.09
8097-007	3/4	20	80	080	17.94
8097-010	1	15	90	080	20.54
8097-012	1-1/4	10	0	080	40.69
8097-015	1-1/2	10	0	080	46.05
8097-020	2	5	0	080	62.48
8097-025	2-1/2	5	0	080	99.33
8097-030	3	5	0	080	116.26
8097-040	4	4	0	080	160.82
8097-060	6	1	0	080	357.39

**Union 2000 - Socket/Fipt/FKM**

**Socket x Fipt with FKM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002	1/4	25	150	080	28.78
859-003	3/8	25	150	080	28.78
8059-005	1/2	20	120	080	17.42
8059-007	3/4	20	80	080	24.36
8059-010	1	15	90	080	32.39
8059-012	1-1/4	10	0	080	61.87
8059-015	1-1/2	10	0	080	76.59
8059-020	2	5	0	080	117.91
8059-025	2-1/2	5	0	080	209.51
8059-030	3	5	0	080	278.27
8059-040	4	4	0	080	319.80
8059-060	6	1	0	080	710.71

**Union 2000 - Socket/Fipt/EPDM**

**Socket x Fipt with EPDM O-ring Seal**



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	28.43
899-003	3/8	25	150	080	28.43
8099-005	1/2	20	120	080	17.20
8099-007	3/4	20	80	080	24.05