

Schedule 80 PVC Product
PVC Schedule 80 Fittings



Plugs

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug

Mipt



850-002	1/4	50	900	080	6.65
850-003	3/8	50	600	080	6.65
850-005	1/2	50	500	080	5.93
850-007	3/4	50	300	080	6.16
850-010	1	25	150	080	7.55
850-012	1-1/4	10	120	080	11.13
850-015	1-1/2	10	120	080	13.53
850-020	2	10	120	080	13.89
850-025	2-1/2	5	60	080	38.78
850-030	3	5	40	080	45.25
850-040	4	6	0	080	88.09
850-060	6	6	0	080	104.73
850-080	8	6	0	080	151.60
850-080F ⁴	8	1	2	083	258.51
850-100F ⁴	10	1	3	083	378.87
850-120F ⁴	12	1	0	083	518.93

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)



875-005	1/2	25	100	080	14.40
875-007	3/4	25	0	080	15.14
875-010	1	20	0	080	24.22
875-012	1-1/4	20	0	080	37.14
875-015	1-1/2	20	0	080	37.14
875-020	2	10	0	080	106.55
875-025 ¹	2-1/2	6	0	080	263.20
875-030	3	5	0	080	342.51
875-040	4	4	0	080	424.39
875-050F ²	5	1	2	083	663.91
875-060	6	2	0	080	579.64
875-080	8	1	0	080	1165.68
875-080F	8	1	0	083	898.20
875-100F ²	10	1	0	083	1409.46
875-120F ²	12	1	0	083	1791.48
875-140F ²	14	1	0	083	2992.03
875-160F ²	16	1	0	083	3930.40
875-180F ²	18	1	0	083	4406.51

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

875-200F ²	20	1	0	083	5886.25
875-240F ²	24	1	0	083	7833.84

¹ Sized with Bushing

² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	17.47
875-130 ¹	1X1/2	20	0	080	30.64
875-131 ¹	1X3/4	20	0	080	30.64
875-166 ¹	1-1/4X1/2	20	0	080	47.20
875-167 ¹	1-1/4X3/4	20	0	080	47.20
875-168 ¹	1-1/4X1	20	0	080	47.20
875-209 ¹	1-1/2X1/2	20	0	080	50.56
875-210 ¹	1-1/2X3/4	20	0	080	50.56
875-211 ¹	1-1/2X1	20	0	080	50.56
875-212 ¹	1-1/2X1-1/4	20	0	080	50.56
875-247 ¹	2X1/2	10	0	080	126.75
875-248 ¹	2X3/4	10	0	080	126.75
875-249 ¹	2X1	10	0	080	126.75
875-250 ¹	2X1-1/4	10	0	080	126.75
875-251 ¹	2X1-1/2	10	0	080	126.75
875-291 ¹	2-1/2X1-1/2	4	0	080	493.43
875-292 ¹	2-1/2X2-1/2X2	5	0	080	493.43
875-335 ¹	3X1	5	0	080	399.23
875-336 ¹	3X1-1/4	5	0	080	399.23
875-337 ¹	3X1-1/2	5	0	080	399.23
875-338 ¹	3X2	4	0	080	399.23
875-339 ¹	3X2-1/2	5	0	080	399.23
875-419 ¹	4X1-1/2	4	0	080	600.77
875-420	4X2	4	0	080	501.93
875-420F ²	4X2	1	5	083	418.33
875-421 ¹	4X2-1/2	4	0	080	556.36
875-421F ²	4X2-1/2	1	4	083	467.49
875-422 ¹	4X3	4	0	080	501.93
875-525 ¹	6X1	5	0	080	615.41
875-528 ¹	6X2	5	0	080	546.52
875-528F ²	6X2	1	3	083	429.77
875-530 ¹	6X3	5	0	080	546.52
875-530F ²	6X3	1	2	083	466.92
875-532	6X4	5	0	080	441.75
875-578 ¹	8X2	2	0	080	1524.89
875-578F ²	8X2	1	2	083	695.33
875-579F ²	8X2-1/2	1	2	083	710.92
875-580 ¹	8X3	2	0	080	1524.89
875-580F ²	8X3	1	2	083	706.26



Schedule 80 PVC Product
PVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye - Reducing (continued)					
Socket x Socket x Socket					
875-582	8X4	2	0	080	1524.89
875-582F ²	8X4	1	2	083	748.86
875-585 ¹	8X6	1	0	080	1422.45
875-585F ²	8X6	1	0	083	883.07
875-621F ²	10X2	1	0	083	936.04
875-622F ²	10X2-1/2	1	0	083	942.56
875-623 ¹	10X3	1	0	081	1776.21
875-623F ²	10X3	1	0	083	954.27
875-624F ²	10X4	1	0	083	1040.04
875-625F ²	10X5	1	0	083	1165.61
875-626	10X6	1	0	081	1646.85
875-626F ²	10X6	1	0	083	1183.48
875-628	10X8	1	0	081	2096.69
875-628F ²	10X8	1	0	083	1368.71
875-661F ²	12X2	1	0	083	1038.76
875-662F ²	12X2-1/2	1	0	083	1132.46
875-663F ²	12X3	1	0	083	1239.25
875-664F ²	12X4	1	0	083	1312.41
875-666F ²	12X6	1	0	083	1496.76
875-668F ²	12X8	1	0	083	1639.74
875-670F ²	12X10	1	0	083	1737.68
875-694F ²	14X4	1	0	083	1624.19
875-696F ²	14X6	1	0	083	1718.74
875-698F ²	14X8	1	0	083	1758.38
875-700F ²	14X10	1	0	083	1963.22
875-702F ²	14X12	1	0	083	2225.12
875-754F ²	16X4	1	0	083	1768.92
875-756F ²	16X6	1	0	083	1776.59
875-758F ²	16X8	1	0	083	2005.02
875-760F ²	16X10	1	0	083	2257.14
875-762F ²	16X12	1	0	083	2459.24
875-764F ²	16X14	1	0	083	2847.95
875-784F ²	18X4	1	0	083	3175.56
875-786F ²	18X6	1	0	083	3585.77
875-788F ²	18X8	1	0	083	3718.96
875-790F ²	18X10	1	0	083	3997.17
875-792F ²	18X12	1	0	083	4012.41
875-794F ²	18X14	1	0	083	4333.60
875-796F ²	18X16	1	0	083	4364.15
875-814F ²	20X4	1	0	083	3924.16
875-816F ²	20X6	1	0	083	4228.55
875-818F ²	20X8	1	0	083	4468.63
875-820F ²	20X10	1	0	083	4619.98
875-822F ²	20X12	1	0	083	4785.89
875-824F ²	20X14	1	0	083	5166.49
875-826F ²	20X16	1	0	083	5594.07
875-828F ²	20X18	1	0	083	5806.59
875-904F ²	24X4	1	0	083	4882.22
875-906F ²	24X6	1	0	083	5050.19
875-908F ²	24X8	1	0	083	5179.46
875-910F ²	24X10	1	0	083	5413.85

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-912F ²	24X12	1	0	083	5757.97
875-914F ²	24X14	1	0	083	5981.31
875-916F ²	24X16	1	0	083	6381.20
875-918F ²	24X18	1	0	083	7358.82
875-920F ²	24X20	1	0	083	7703.53

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-020F	2	1	4	083	352.28
876-030F	3	1	4	083	443.97
876-040F	4	1	2	083	806.24
876-060F	6	1	0	083	942.35
876-080F	8	1	0	083	1122.75
876-100F	10	1	0	083	2000.63
876-120F	12	1	0	083	2817.35

For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338	3X2	5	0	080	428.41
876-420F ²	4X2	1	2	083	559.49
876-421F ²	4X2-1/2	1	2	083	633.46
876-422F ²	4X3	1	2	083	655.22
876-528F ²	6X2	1	2	083	658.36
876-529F ²	6X2-1/2	1	2	083	687.66
876-530F ²	6X3	1	2	083	692.14
876-532F ²	6X4	1	0	083	825.03
876-578F ²	8X2	1	2	083	849.21
876-579F ²	8X2-1/2	1	2	083	889.29
876-580F ²	8X3	1	0	083	894.73
876-582F ²	8X4	1	0	083	923.59
876-585F ²	8X6	1	0	083	1042.83
876-621F ²	10X2	1	0	083	1132.35
876-622F ²	10X2-1/2	1	0	083	1218.91
876-623F ²	10X3	1	0	083	1226.14
876-624F ²	10X4	1	0	083	1272.67
876-626F ²	10X6	1	0	083	1332.15
876-628F ²	10X8	1	0	083	1712.06
876-661F ²	12X2	1	0	083	1265.24
876-662F ²	12X2-1/2	1	0	083	1340.31
876-663F ²	12X3	1	0	083	1361.46
876-664F ²	12X4	1	0	083	1450.22
876-666F ²	12X6	1	0	083	1682.94
876-668F ²	12X8	1	0	083	2010.20
876-670F ²	12X10	1	0	083	2292.71

Schedule 80 PVC Product
PVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket X Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure rating @ 73°F (23°C)

857-002	1/4	25	150	080	24.12
857-003	3/8	25	150	080	24.12
8057-005	1/2	20	120	080	12.91
8057-007	3/4	20	80	080	16.40
8057-010	1	15	90	080	18.71
8057-012	1-1/4	10	0	080	37.17
8057-015	1-1/2	10	0	080	42.09
8057-020	2	5	0	080	57.06
8057-025	2-1/2	5	0	080	91.39
8057-030	3	5	0	080	106.25
8057-040	4	4	0	080	147.99
8057-060	6	1	0	080	328.91

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure rating @ 73°F (23°C)

897-002	1/4	25	150	080	23.81
897-003	3/8	25	150	080	23.81
8097-005	1/2	20	120	080	12.72
8097-007	3/4	20	80	080	16.19
8097-010	1	15	90	080	18.53
8097-012	1-1/4	10	0	080	36.73
8097-015	1-1/2	10	0	080	41.56
8097-020	2	5	0	080	56.39
8097-025	2-1/2	5	0	080	89.64
8097-030	3	5	0	080	104.93
8097-040	4	4	0	080	145.14
8097-060	6	1	0	080	322.54

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002	1/4	25	150	080	25.97
859-003	3/8	25	150	080	25.97
8059-005	1/2	20	120	080	15.72
8059-007	3/4	20	80	080	21.98

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Fipt/FKM (continued)

Socket x Fipt with FKM O-ring Seal

8059-010	1	15	90	080	29.23
8059-012	1-1/4	10	0	080	55.84
8059-015	1-1/2	10	0	080	69.12
8059-020	2	5	0	080	106.41
8059-025	2-1/2	5	0	080	189.08
8059-030	3	5	0	080	251.14
8059-040	4	4	0	080	288.62
8059-060	6	1	0	080	641.41

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	25.66
899-003	3/8	25	150	080	25.66
8099-005	1/2	20	120	080	15.52
8099-007	3/4	20	80	080	21.71
8099-010	1	15	90	080	28.86
8099-012	1-1/4	10	0	080	55.18
8099-015	1-1/2	10	0	080	68.29
8099-020	2	5	0	080	105.08
8099-025	2-1/2	5	0	080	148.58
8099-030	3	5	0	080	247.99
8099-040	4	4	0	080	284.75
8099-060	6	1	0	080	632.76

Union 2000 - Socket/Spigot/FKM

Socket x Spigot with FKM O-ring Seal



235 psi Maximum Internal Pressure rating @ 73°F (23°C)

8056-005	1/2	20	120	080	12.91
8056-007	3/4	20	160	080	16.40
8056-010	1	15	90	080	18.71
8056-012	1-1/4	10	0	080	37.17
8056-015	1-1/2	10	0	080	42.09
8056-020	2	5	0	080	57.06
8056-025	2-1/2	5	0	080	91.39
8056-030	3	5	0	080	106.25
8056-040	4	4	0	080	147.99
8056-060	6	1	0	080	328.91

Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal



235 psi Maximum Internal Pressure rating @ 73°F (23°C)

8096-005	1/2	20	160	080	12.72
8096-007	3/4	20	80	080	16.19
8096-010	1	15	90	080	18.53
8096-012	1-1/4	10	0	080	36.73
8096-015	1-1/2	10	0	080	41.56