



Schedule 80 PVC Product
PVC Schedule 80 Fittings

Plugs

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug

Mipt



850-002	1/4	50	900	080	7.00
850-003	3/8	50	600	080	7.00
850-005	1/2	50	500	080	6.24
850-007	3/4	50	300	080	6.48
850-010	1	25	150	080	7.95
850-012	1-1/4	10	120	080	11.72
850-015	1-1/2	10	120	080	14.24
850-020	2	10	120	080	14.62
850-025	2-1/2	5	60	080	40.82
850-030	3	5	40	080	47.63
850-040	4	6	0	080	92.73
850-060	6	6	0	080	110.24
850-080	8	6	0	080	159.58
850-080F ⁴	8	1	2	083	272.12
850-100F ⁴	10	1	3	083	398.81
850-120F ⁴	12	1	0	083	546.24

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	15.16
875-007	3/4	25	0	080	15.94
875-010	1	20	0	080	25.49
875-012	1-1/4	20	0	080	39.09
875-015	1-1/2	20	0	080	39.09
875-020	2	10	0	080	112.16
875-025 ¹	2-1/2	6	0	080	277.05
875-030	3	5	0	080	360.54
875-040	4	4	0	080	446.73
875-050F ²	5	1	2	083	698.85
875-060	6	2	0	080	610.15
875-080	8	1	0	080	1227.03
875-080F	8	1	0	083	945.47
875-100F ²	10	1	0	083	1483.64
875-120F ²	12	1	0	083	1885.77
875-140F ²	14	1	0	083	3149.51
875-160F ²	16	1	0	083	4137.26
875-180F ²	18	1	0	083	4638.43

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

875-200F ²	20	1	0	083	6196.05
875-240F ²	24	1	0	083	8246.15

¹ Sized with Bushing
² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	18.39
875-130 ¹	1X1/2	20	0	080	32.25
875-131 ¹	1X3/4	20	0	080	32.25
875-166 ¹	1-1/4X1/2	20	0	080	49.68
875-167 ¹	1-1/4X3/4	20	0	080	49.68
875-168 ¹	1-1/4X1	20	0	080	49.68
875-209 ¹	1-1/2X1/2	20	0	080	53.22
875-210 ¹	1-1/2X3/4	20	0	080	53.22
875-211 ¹	1-1/2X1	20	0	080	53.22
875-212 ¹	1-1/2X1-1/4	20	0	080	53.22
875-247 ¹	2X1/2	10	0	080	133.42
875-248 ¹	2X3/4	10	0	080	133.42
875-249 ¹	2X1	10	0	080	133.42
875-250 ¹	2X1-1/4	10	0	080	133.42
875-251 ¹	2X1-1/2	10	0	080	133.42
875-291 ¹	2-1/2X1-1/2	4	0	080	519.40
875-292 ¹	2-1/2X2-1/2X2	5	0	080	519.40
875-335 ¹	3X1	5	0	080	420.24
875-336 ¹	3X1-1/4	5	0	080	420.24
875-337 ¹	3X1-1/2	5	0	080	420.24
875-338 ¹	3X2	4	0	080	420.24
875-339 ¹	3X2-1/2	5	0	080	420.24
875-419 ¹	4X1-1/2	4	0	080	632.39
875-420	4X2	4	0	080	528.35
875-420F ²	4X2	1	5	083	440.35
875-421 ¹	4X2-1/2	4	0	080	585.64
875-421F ²	4X2-1/2	1	4	083	492.09
875-422 ¹	4X3	4	0	080	528.35
875-525 ¹	6X1	5	0	080	647.80
875-528 ¹	6X2	5	0	080	575.28
875-528F ²	6X2	1	3	083	452.39
875-530 ¹	6X3	5	0	080	575.28
875-530F ²	6X3	1	2	083	491.49
875-532	6X4	5	0	080	465.00
875-578 ¹	8X2	2	0	080	1605.15
875-578F ²	8X2	1	2	083	731.93
875-579F ²	8X2-1/2	1	2	083	748.34
875-580 ¹	8X3	2	0	080	1605.15
875-580F ²	8X3	1	2	083	743.43

Schedule 80 PVC Product
PVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)
Socket x Socket x Socket

875-582	8X4	2	0	080	1605.15
875-582F ²	8X4	1	2	083	788.27
875-585 ¹	8X6	1	0	080	1497.32
875-585F ²	8X6	1	0	083	929.55
875-621F ²	10X2	1	0	083	985.31
875-622F ²	10X2-1/2	1	0	083	992.17
875-623 ¹	10X3	1	0	081	1869.69
875-623F ²	10X3	1	0	083	1004.49
875-624F ²	10X4	1	0	083	1094.78
875-625F ²	10X5	1	0	083	1226.96
875-626	10X6	1	0	081	1733.53
875-626F ²	10X6	1	0	083	1245.77
875-628	10X8	1	0	081	2207.04
875-628F ²	10X8	1	0	083	1440.75
875-661F ²	12X2	1	0	083	1093.43
875-662F ²	12X2-1/2	1	0	083	1192.06
875-663F ²	12X3	1	0	083	1304.47
875-664F ²	12X4	1	0	083	1381.48
875-666F ²	12X6	1	0	083	1575.54
875-668F ²	12X8	1	0	083	1726.04
875-670F ²	12X10	1	0	083	1829.14
875-694F ²	14X4	1	0	083	1709.67
875-696F ²	14X6	1	0	083	1809.20
875-698F ²	14X8	1	0	083	1850.93
875-700F ²	14X10	1	0	083	2066.55
875-702F ²	14X12	1	0	083	2342.23
875-754F ²	16X4	1	0	083	1862.02
875-756F ²	16X6	1	0	083	1870.09
875-758F ²	16X8	1	0	083	2110.55
875-760F ²	16X10	1	0	083	2375.94
875-762F ²	16X12	1	0	083	2588.67
875-764F ²	16X14	1	0	083	2997.84
875-784F ²	18X4	1	0	083	3342.69
875-786F ²	18X6	1	0	083	3774.49
875-788F ²	18X8	1	0	083	3914.69
875-790F ²	18X10	1	0	083	4207.55
875-792F ²	18X12	1	0	083	4223.59
875-794F ²	18X14	1	0	083	4561.68
875-796F ²	18X16	1	0	083	4593.84
875-814F ²	20X4	1	0	083	4130.69
875-816F ²	20X6	1	0	083	4451.11
875-818F ²	20X8	1	0	083	4703.82
875-820F ²	20X10	1	0	083	4863.14
875-822F ²	20X12	1	0	083	5037.78
875-824F ²	20X14	1	0	083	5438.41
875-826F ²	20X16	1	0	083	5888.49
875-828F ²	20X18	1	0	083	6112.20
875-904F ²	24X4	1	0	083	5139.18
875-906F ²	24X6	1	0	083	5315.99
875-908F ²	24X8	1	0	083	5452.06
875-910F ²	24X10	1	0	083	5698.79

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)
Socket x Socket x Socket

875-912F ²	24X12	1	0	083	6061.02
875-914F ²	24X14	1	0	083	6296.12
875-916F ²	24X16	1	0	083	6717.05
875-918F ²	24X18	1	0	083	7746.13
875-920F ²	24X20	1	0	083	8108.98

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-020F	2	1	4	083	370.82
876-030F	3	1	4	083	467.34
876-040F	4	1	2	083	848.67
876-060F	6	1	0	083	991.95
876-080F	8	1	0	083	1181.84
876-100F	10	1	0	083	2105.93
876-120F	12	1	0	083	2965.63

For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338	3X2	5	0	080	450.96
876-420F ²	4X2	1	2	083	588.94
876-421F ²	4X2-1/2	1	2	083	666.80
876-422F ²	4X3	1	2	083	689.71
876-528F ²	6X2	1	2	083	693.01
876-529F ²	6X2-1/2	1	2	083	723.85
876-530F ²	6X3	1	2	083	728.57
876-532F ²	6X4	1	0	083	868.45
876-578F ²	8X2	1	2	083	893.91
876-579F ²	8X2-1/2	1	2	083	936.09
876-580F ²	8X3	1	0	083	941.82
876-582F ²	8X4	1	0	083	972.20
876-585F ²	8X6	1	0	083	1097.72
876-621F ²	10X2	1	0	083	1191.95
876-622F ²	10X2-1/2	1	0	083	1283.06
876-623F ²	10X3	1	0	083	1290.67
876-624F ²	10X4	1	0	083	1339.65
876-626F ²	10X6	1	0	083	1402.26
876-628F ²	10X8	1	0	083	1802.17
876-661F ²	12X2	1	0	083	1331.83
876-662F ²	12X2-1/2	1	0	083	1410.85
876-663F ²	12X3	1	0	083	1433.12
876-664F ²	12X4	1	0	083	1526.55
876-666F ²	12X6	1	0	083	1771.52
876-668F ²	12X8	1	0	083	2116.00



Schedule 80 PVC Product
PVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

876-670F ²	12X10	1	0	083	2413.38
-----------------------	-------	---	---	-----	---------

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM



Socket X Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
857-002	1/4	25	150	080	25.39
857-003	3/8	25	150	080	25.39
8057-005	1/2	20	120	080	13.59
8057-007	3/4	20	80	080	17.26
8057-010	1	15	90	080	19.69
8057-012	1-1/4	10	0	080	39.13
8057-015	1-1/2	10	0	080	44.31
8057-020	2	5	0	080	60.06
8057-025	2-1/2	5	0	080	96.20
8057-030	3	5	0	080	111.84
8057-040	4	4	0	080	155.78
8057-060	6	1	0	080	346.22

Union 2000 - Socket/EPDM



Socket x Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
897-002	1/4	25	150	080	25.06
897-003	3/8	25	150	080	25.06
8097-005	1/2	20	120	080	13.39
8097-007	3/4	20	80	080	17.04
8097-010	1	15	90	080	19.51
8097-012	1-1/4	10	0	080	38.66
8097-015	1-1/2	10	0	080	43.75
8097-020	2	5	0	080	59.36
8097-025	2-1/2	5	0	080	94.36
8097-030	3	5	0	080	110.45
8097-040	4	4	0	080	152.78
8097-060	6	1	0	080	339.52

Union 2000 - Socket/Fipt/FKM



Socket x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
859-002	1/4	25	150	080	27.34
859-003	3/8	25	150	080	27.34
8059-005	1/2	20	120	080	16.55

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Fipt/FKM (continued)

Socket x Fipt with FKM O-ring Seal

8059-007	3/4	20	80	080	23.14
8059-010	1	15	90	080	30.77
8059-012	1-1/4	10	0	080	58.78
8059-015	1-1/2	10	0	080	72.76
8059-020	2	5	0	080	112.01
8059-025	2-1/2	5	0	080	199.03
8059-030	3	5	0	080	264.36
8059-040	4	4	0	080	303.81
8059-060	6	1	0	080	675.17

Union 2000 - Socket/Fipt/EPDM



Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	27.01
899-003	3/8	25	150	080	27.01
8099-005	1/2	20	120	080	16.34
8099-007	3/4	20	80	080	22.85
8099-010	1	15	90	080	30.38
8099-012	1-1/4	10	0	080	58.08
8099-015	1-1/2	10	0	080	71.88
8099-020	2	5	0	080	110.61
8099-025	2-1/2	5	0	080	156.40
8099-030	3	5	0	080	261.04
8099-040	4	4	0	080	299.74
8099-060	6	1	0	080	666.06

Union 2000 - Socket/Spigot/FKM



Socket x Spigot with FKM O-ring Seal

235 psi Maximum Internal Pressure rating @ 73°F (23°C)

8056-005	1/2	20	120	080	13.59
8056-007	3/4	20	160	080	17.26
8056-010	1	15	90	080	19.69
8056-012	1-1/4	10	0	080	39.13
8056-015	1-1/2	10	0	080	44.31
8056-020	2	5	0	080	60.06
8056-025	2-1/2	5	0	080	96.20
8056-030	3	5	0	080	111.84
8056-040	4	4	0	080	155.78
8056-060	6	1	0	080	346.22

Union 2000 - Socket/Spigot/EPDM



Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal

235 psi Maximum Internal Pressure rating @ 73°F (23°C)

8096-005	1/2	20	160	080	13.39
8096-007	3/4	20	80	080	17.04
8096-010	1	15	90	080	19.51
8096-012	1-1/4	10	0	080	38.66