



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings**

**Reducer Bushing**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Reducer Bushing Flush Style (continued)**

**Spigot x Fipt**

438-534	<b>6X5</b>	5	0	040	58.56
---------	------------	---	---	-----	-------

**Reducer Bushing - Special Reinforced Flush Style**

**Spigot x SR Fipt - Stainless Steel Collar**

438-128SR	<b>1X1/4</b>	25	150	046	3.48
438-166SR	<b>1-1/4X1/2</b>	25	100	046	6.36
438-207SR	<b>1-1/2X1/4</b>	25	100	046	8.87
438-209SR	<b>1-1/2X1/2</b>	25	100	046	8.87
438-210SR	<b>1-1/2X3/4</b>	25	100	046	8.87
438-247SR	<b>2X1/2</b>	10	80	046	10.86
438-248SR	<b>2X3/4</b>	10	80	046	10.86
438-249SR	<b>2X1</b>	10	120	046	10.86
438-334SR	<b>3X3/4</b>	10	0	046	42.51
438-335SR	<b>3X1</b>	10	0	046	42.51
438-336SR	<b>3X1-1/4</b>	10	0	046	42.51
438-337SR	<b>3X1-1/2</b>	10	0	046	42.51
438-420SR	<b>4X2</b>	6	0	046	65.34
438-421SR	<b>4X2-1/2</b>	6	0	046	73.54
438-528SR	<b>6X2</b>	5	0	046	75.24
438-530SR	<b>6X3</b>	5	0	046	67.74
438-532SR	<b>6X4</b>	5	0	046	75.24



**Reducer (T.T.) Bushing**

**Mipt x Fipt**

439-052	<b>3/8X1/4</b>	50	450	040	3.20
439-071	<b>1/2X1/8</b>	50	300	040	3.20
439-072	<b>1/2X1/4</b>	50	300	040	3.20
439-073	<b>1/2X3/8</b>	50	300	040	3.20
439-098	<b>3/4X1/4</b>	50	300	040	1.98
439-099	<b>3/4X3/8</b>	50	300	040	1.98
439-101	<b>3/4X1/2</b>	50	300	040	1.98
439-128	<b>1X1/4</b>	25	150	040	2.78
439-130	<b>1X1/2</b>	50	300	040	2.78
439-131	<b>1X3/4</b>	50	800	040	2.78
439-166	<b>1-1/4X1/2</b>	25	150	040	4.14
439-167	<b>1-1/4X3/4</b>	25	150	040	4.14
439-168	<b>1-1/4X1</b>	25	150	040	4.14
439-209	<b>1-1/2X1/2</b>	25	300	040	5.00
439-210	<b>1-1/2X3/4</b>	25	300	040	5.00
439-211	<b>1-1/2X1</b>	25	300	040	5.00
439-212	<b>1-1/2X1-1/4</b>	25	300	040	5.00
439-247	<b>2X1/2</b>	10	60	040	5.35
439-248	<b>2X3/4</b>	10	60	040	5.35
439-249	<b>2X1</b>	10	60	040	5.35
439-250	<b>2X1-1/4</b>	10	60	040	5.35
439-251	<b>2X1-1/2</b>	10	60	040	5.35
439-292	<b>2-1/2X2</b>	10	80	040	18.71



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Reducer (T.T.) Bushing (continued)**

**Mipt x Fipt**

439-337	<b>3X1-1/2</b>	10	0	040	22.13
439-338	<b>3X2</b>	10	0	040	22.13
439-339	<b>3X2-1/2</b>	10	0	040	22.13
439-420	<b>4X2</b>	6	0	040	66.14
439-422	<b>4X3</b>	6	0	040	51.15

**Reducer Bushing - Special Reinforced Flush Style**

**Mipt X SR Fipt - Stainless Steel Collar**

439-209SR	<b>1-1/2X1/2</b>	25	300	046	9.20
439-210SR	<b>1-1/2X3/4</b>	25	300	046	9.20
439-247SR	<b>2X1/2</b>	10	60	046	5.35
439-248SR	<b>2X3/4</b>	10	60	046	8.33
439-249SR	<b>2X1</b>	10	120	046	13.51
439-420SR	<b>4X2</b>	6	0	046	51.15



**Caps**

**Cap**

**Socket**

447-003	<b>3/8</b>	50	1000	040	1.73
447-005	<b>1/2</b>	50	300	040	.61
447-007	<b>3/4</b>	50	300	040	.71
447-010	<b>1</b>	50	200	040	1.12
447-012	<b>1-1/4</b>	25	100	040	1.59
447-015	<b>1-1/2</b>	25	0	040	1.73
447-020	<b>2</b>	25	0	040	2.08
447-025	<b>2-1/2</b>	10	0	040	6.64
447-030	<b>3</b>	10	0	040	7.25
447-040	<b>4</b>	6	0	040	16.49
447-045F	<b>4-1/2</b>	10	0	047	53.02
447-050	<b>5</b>	5	0	040	27.71
447-060	<b>6</b>	4	0	040	39.55
447-080	<b>8</b>	3	0	040	99.35
447-100F	<b>10</b>	1	5	047	221.46
447-120F	<b>12</b>	1	5	047	321.75
447-140F	<b>14</b>	1	2	047	403.80
447-160F	<b>16</b>	1	2	047	481.96
447-180F	<b>18</b>	1	2	047	849.26
447-200F	<b>20</b>	1	0	047	1289.59
447-240F	<b>24</b>	1	0	047	2052.54



**Cap**

**Fipt**

448-003	<b>3/8</b>	50	1000	040	2.33
448-005	<b>1/2</b>	50	300	040	1.28
448-007	<b>3/4</b>	50	300	040	1.48
448-010	<b>1</b>	50	200	040	2.24



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings**



**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap (continued)</b>					
<b>Fipt</b>					
448-012	1-1/4	25	100	040	2.66
448-015	1-1/2	25	100	040	2.78
448-020	2	10	120	040	4.92
448-025	2-1/2	10	0	040	7.25
448-030	3	10	0	040	9.48
448-040	4	6	0	040	16.64
448-050	5	5	0	040	32.24
448-060	6	8	0	040	39.34
448-080F	8	1	2	047	191.98
448-100F	10	1	2	047	390.13
448-120F	12	1	0	047	779.51

**Cap - Special Reinforced**

**SR Fipt - Stainless Steel Collar**

448-012SR	1-1/4	25	100	046	7.09
-----------	-------	----	-----	-----	------

**Plugs**

**Plug**

**Spigot**

449-003	3/8	50	700	040	1.83
449-005	1/2	50	1000	040	1.48
449-007	3/4	50	300	040	1.73
449-010	1	50	200	040	2.08
449-012	1-1/4	25	150	040	2.78
449-015	1-1/2	25	100	040	3.54
449-020	2	10	120	040	4.38
449-025	2-1/2	10	0	040	7.51
449-030	3	10	0	040	9.91
449-040	4	6	0	040	22.43
449-060	6	6	0	040	30.37
449-060F <sup>4</sup>	6	1	6	047	76.84
449-080F <sup>4</sup>	8	1	6	047	118.31
449-100F <sup>4</sup>	10	1	0	047	271.59
449-120F <sup>4</sup>	12	1	0	047	444.07
449-140F <sup>4</sup>	14	1	2	047	486.83
449-160F <sup>4</sup>	16	1	0	047	538.36
449-180F <sup>4</sup>	18	1	0	047	960.72
449-200F <sup>4</sup>	20	1	0	047	1757.60
449-240F <sup>4</sup>	24	1	0	047	2339.60

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Plug - Counter Sunk**

**Spigot**

449-007CS	3/4	50	300	040	1.73
449-010CS	1	50	300	040	2.08

**Plug**

**Mipt**

450-003	3/8	50	700	040	1.99
450-005	1/2	50	300	040	1.83
450-007	3/4	50	300	040	1.97
450-010	1	50	300	040	3.20
450-012	1-1/4	25	300	040	3.37
450-015	1-1/2	25	150	040	3.62
450-020	2	10	120	040	4.67
450-025	2-1/2	10	80	040	6.49
450-030	3	10	0	040	9.83
450-040	4	6	0	040	22.18
450-060	6	6	0	040	65.03
450-080	8	6	0	040	79.46
450-080F <sup>4</sup>	8	1	4	047	172.40
450-100F <sup>4</sup>	10	1	3	047	343.54
450-120F <sup>4</sup>	12	1	0	047	479.61

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)  
2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)  
8" - Larger & All Fabricated Sizes- 80 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	2.91
475-007	3/4	20	0	040	4.56
475-010	1	25	0	040	6.38
475-012	1-1/4	20	0	040	9.81
475-015	1-1/2	20	0	040	12.58
475-020	2	10	0	040	37.74
475-025	2-1/2	8	0	040	86.27
475-030	3	5	0	040	63.58
475-040	4	4	0	040	119.92
475-050F	5	1	3	047	467.96
475-060	6	3	0	040	253.71
475-080	8	1	0	040	408.07
475-100	10	1	0	041	1352.18
475-100F <sup>2</sup>	10	1	0	047	1134.64