



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Fipt					
448-012	1-1/4	25	100	040	2.80
448-015	1-1/2	25	100	040	2.93
448-020	2	10	120	040	5.18
448-025	2-1/2	10	0	040	7.63
448-030	3	10	0	040	9.98
448-040	4	6	0	040	17.52
448-050	5	5	0	040	33.94
448-060	6	8	0	040	41.41
448-080F	8	1	2	047	202.08
448-100F	10	1	2	047	410.66
448-120F	12	1	0	047	820.54

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	7.46
-----------	-------	----	-----	-----	------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	1.93
449-005	1/2	50	1000	040	1.56
449-007	3/4	50	300	040	1.82
449-010	1	50	200	040	2.19
449-012	1-1/4	25	150	040	2.93
449-015	1-1/2	25	100	040	3.73
449-020	2	10	120	040	4.61
449-025	2-1/2	10	0	040	7.91
449-030	3	10	0	040	10.43
449-040	4	6	0	040	23.61
449-060	6	6	0	040	31.97
449-060F ⁴	6	1	6	047	80.88
449-080F ⁴	8	1	6	047	124.54
449-100F ⁴	10	1	0	047	285.88
449-120F ⁴	12	1	0	047	467.44
449-140F ⁴	14	1	2	047	512.45
449-160F ⁴	16	1	0	047	566.69
449-180F ⁴	18	1	0	047	1011.28
449-200F ⁴	20	1	0	047	1850.11
449-240F ⁴	24	1	0	047	2462.74

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	1.82
449-010CS	1	50	300	040	2.19

Plug

Mipt

450-003	3/8	50	700	040	2.09
450-005	1/2	50	300	040	1.93
450-007	3/4	50	300	040	2.07
450-010	1	50	300	040	3.37
450-012	1-1/4	25	300	040	3.55
450-015	1-1/2	25	150	040	3.81
450-020	2	10	120	040	4.92
450-025	2-1/2	10	80	040	6.83
450-030	3	10	0	040	10.35
450-040	4	6	0	040	23.35
450-060	6	6	0	040	68.45
450-080	8	6	0	040	83.64
450-080F ⁴	8	1	4	047	181.47
450-100F ⁴	10	1	3	047	361.62
450-120F ⁴	12	1	0	047	504.85

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	3.06
475-007	3/4	20	0	040	4.80
475-010	1	25	0	040	6.72
475-012	1-1/4	20	0	040	10.33
475-015	1-1/2	20	0	040	13.24
475-020	2	10	0	040	39.73
475-025	2-1/2	8	0	040	90.81
475-030	3	5	0	040	66.93
475-040	4	4	0	040	126.23
475-050F	5	1	3	047	492.59
475-060	6	3	0	040	267.06
475-080	8	1	0	040	429.55
475-100	10	1	0	041	1423.35
475-100F ²	10	1	0	047	1194.36