

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Caps

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|------------------------|-------|--------|----------|-----------|--------|
| Cap (continued) | | | | | |
| Fipt | | | | | |
| 448-012 | 1-1/4 | 25 | 100 | 040 | 2.66 |
| 448-015 | 1-1/2 | 25 | 100 | 040 | 2.78 |
| 448-020 | 2 | 10 | 120 | 040 | 4.92 |
| 448-025 | 2-1/2 | 10 | 0 | 040 | 7.25 |
| 448-030 | 3 | 10 | 0 | 040 | 9.48 |
| 448-040 | 4 | 6 | 0 | 040 | 16.64 |
| 448-050 | 5 | 5 | 0 | 040 | 32.24 |
| 448-060 | 6 | 8 | 0 | 040 | 39.34 |
| 448-080F | 8 | 1 | 2 | 047 | 191.98 |
| 448-100F | 10 | 1 | 2 | 047 | 390.13 |
| 448-120F | 12 | 1 | 0 | 047 | 779.51 |

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

| | | | | | |
|-----------|-------|----|-----|-----|------|
| 448-012SR | 1-1/4 | 25 | 100 | 046 | 7.09 |
|-----------|-------|----|-----|-----|------|

Plugs

Plug

Spigot

| | | | | | |
|-----------------------|-------|----|------|-----|---------|
| 449-003 | 3/8 | 50 | 700 | 040 | 1.83 |
| 449-005 | 1/2 | 50 | 1000 | 040 | 1.48 |
| 449-007 | 3/4 | 50 | 300 | 040 | 1.73 |
| 449-010 | 1 | 50 | 200 | 040 | 2.08 |
| 449-012 | 1-1/4 | 25 | 150 | 040 | 2.78 |
| 449-015 | 1-1/2 | 25 | 100 | 040 | 3.54 |
| 449-020 | 2 | 10 | 120 | 040 | 4.38 |
| 449-025 | 2-1/2 | 10 | 0 | 040 | 7.51 |
| 449-030 | 3 | 10 | 0 | 040 | 9.91 |
| 449-040 | 4 | 6 | 0 | 040 | 22.43 |
| 449-060 | 6 | 6 | 0 | 040 | 30.37 |
| 449-060F ⁴ | 6 | 1 | 6 | 047 | 76.84 |
| 449-080F ⁴ | 8 | 1 | 6 | 047 | 118.31 |
| 449-100F ⁴ | 10 | 1 | 0 | 047 | 271.59 |
| 449-120F ⁴ | 12 | 1 | 0 | 047 | 444.07 |
| 449-140F ⁴ | 14 | 1 | 2 | 047 | 486.83 |
| 449-160F ⁴ | 16 | 1 | 0 | 047 | 538.36 |
| 449-180F ⁴ | 18 | 1 | 0 | 047 | 960.72 |
| 449-200F ⁴ | 20 | 1 | 0 | 047 | 1757.60 |
| 449-240F ⁴ | 24 | 1 | 0 | 047 | 2339.60 |

⁴ Plug fabricated using Cap and pipe spigot.

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Plug - Counter Sunk

Spigot

| | | | | | |
|-----------|-----|----|-----|-----|------|
| 449-007CS | 3/4 | 50 | 300 | 040 | 1.73 |
| 449-010CS | 1 | 50 | 300 | 040 | 2.08 |

Plug

Mipt

| | | | | | |
|-----------------------|-------|----|-----|-----|--------|
| 450-003 | 3/8 | 50 | 700 | 040 | 1.99 |
| 450-005 | 1/2 | 50 | 300 | 040 | 1.83 |
| 450-007 | 3/4 | 50 | 300 | 040 | 1.97 |
| 450-010 | 1 | 50 | 300 | 040 | 3.20 |
| 450-012 | 1-1/4 | 25 | 300 | 040 | 3.37 |
| 450-015 | 1-1/2 | 25 | 150 | 040 | 3.62 |
| 450-020 | 2 | 10 | 120 | 040 | 4.67 |
| 450-025 | 2-1/2 | 10 | 80 | 040 | 6.49 |
| 450-030 | 3 | 10 | 0 | 040 | 9.83 |
| 450-040 | 4 | 6 | 0 | 040 | 22.18 |
| 450-060 | 6 | 6 | 0 | 040 | 65.03 |
| 450-080 | 8 | 6 | 0 | 040 | 79.46 |
| 450-080F ⁴ | 8 | 1 | 4 | 047 | 172.40 |
| 450-100F ⁴ | 10 | 1 | 3 | 047 | 343.54 |
| 450-120F ⁴ | 12 | 1 | 0 | 047 | 479.61 |

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 80 psi Max Internal Pressure Rating @ 73°F (23°C)

| | | | | | |
|-----------------------|-------|----|-----|-----|---------|
| 475-005 | 1/2 | 25 | 100 | 040 | 2.91 |
| 475-007 | 3/4 | 20 | 0 | 040 | 4.56 |
| 475-010 | 1 | 25 | 0 | 040 | 6.38 |
| 475-012 | 1-1/4 | 20 | 0 | 040 | 9.81 |
| 475-015 | 1-1/2 | 20 | 0 | 040 | 12.58 |
| 475-020 | 2 | 10 | 0 | 040 | 37.74 |
| 475-025 | 2-1/2 | 8 | 0 | 040 | 86.27 |
| 475-030 | 3 | 5 | 0 | 040 | 63.58 |
| 475-040 | 4 | 4 | 0 | 040 | 119.92 |
| 475-050F | 5 | 1 | 3 | 047 | 467.96 |
| 475-060 | 6 | 3 | 0 | 040 | 253.71 |
| 475-080 | 8 | 1 | 0 | 040 | 408.07 |
| 475-100 | 10 | 1 | 0 | 041 | 1352.18 |
| 475-100F ² | 10 | 1 | 0 | 047 | 1134.64 |