



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings**

**Caps**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Cap (continued)</b>					
<b>Fipt</b>					
448-012	1-1/4	25	100	040	2.95
448-015	1-1/2	25	100	040	3.08
448-020	2	10	120	040	5.45
448-025	2-1/2	10	0	040	8.03
448-030	3	10	0	040	10.51
448-040	4	6	0	040	18.44
448-050	5	5	0	040	35.73
448-060	6	8	0	040	43.59
448-080F	8	1	2	047	212.72
448-100F	10	1	2	047	432.27
448-120F	12	1	0	047	863.73

**Cap - Special Reinforced**

**SR Fipt - Stainless Steel Collar**

448-012SR	1-1/4	25	100	046	7.85
-----------	-------	----	-----	-----	------

**Plugs**

**Plug**

**Spigot**

449-003	3/8	50	700	040	2.03
449-005	1/2	50	1000	040	1.64
449-007	3/4	50	300	040	1.92
449-010	1	50	200	040	2.31
449-012	1-1/4	25	150	040	3.08
449-015	1-1/2	25	100	040	3.93
449-020	2	10	120	040	4.85
449-025	2-1/2	10	0	040	8.33
449-030	3	10	0	040	10.98
449-040	4	6	0	040	24.85
449-060	6	6	0	040	33.65
449-060F <sup>4</sup>	6	1	6	047	85.14
449-080F <sup>4</sup>	8	1	6	047	131.09
449-100F <sup>4</sup>	10	1	0	047	300.93
449-120F <sup>4</sup>	12	1	0	047	492.04
449-140F <sup>4</sup>	14	1	2	047	539.42
449-160F <sup>4</sup>	16	1	0	047	596.52
449-180F <sup>4</sup>	18	1	0	047	1064.51
449-200F <sup>4</sup>	20	1	0	047	1947.48
449-240F <sup>4</sup>	24	1	0	047	2592.36

<sup>4</sup> Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Plug - Counter Sunk**

**Spigot**

449-007CS	3/4	50	300	040	1.92
449-010CS	1	50	300	040	2.31

**Plug**

**Mipt**

450-003	3/8	50	700	040	2.20
450-005	1/2	50	300	040	2.03
450-007	3/4	50	300	040	2.18
450-010	1	50	300	040	3.55
450-012	1-1/4	25	300	040	3.74
450-015	1-1/2	25	150	040	4.01
450-020	2	10	120	040	5.18
450-025	2-1/2	10	80	040	7.19
450-030	3	10	0	040	10.89
450-040	4	6	0	040	24.58
450-060	6	6	0	040	72.05
450-080	8	6	0	040	88.04
450-080F <sup>4</sup>	8	1	4	047	191.02
450-100F <sup>4</sup>	10	1	3	047	380.65
450-120F <sup>4</sup>	12	1	0	047	531.42

<sup>4</sup> Plug fabricated using Cap and threaded pipe.

**Wyes**

**Wye**

**Socket x Socket x Socket**

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)  
2 - 1/2" - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)  
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	3.22
475-007	3/4	20	0	040	5.05
475-010	1	25	0	040	7.07
475-012	1-1/4	20	0	040	10.87
475-015	1-1/2	20	0	040	13.94
475-020	2	10	0	040	41.82
475-025	2-1/2	8	0	040	95.59
475-030	3	5	0	040	70.45
475-040	4	4	0	040	132.87
475-050F <sup>2</sup>	5	1	3	047	518.52
475-060	6	3	0	040	281.12
475-080	8	1	0	040	452.16
475-100	10	1	0	041	1498.26
475-100F <sup>2</sup>	10	1	0	047	1257.22