

Schedule 40 Fittings Product
PVC Schedule 40 Fittings & Schedule 40 Tank Adapters



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Fipt/Buna

Fipt x Fipt with Buna O-ring Seal

150 psi 73°F (23°C)

458-005	1/2	20	120	040	7.82
458-007	3/4	15	90	040	13.07
458-010	1	10	60	040	17.86
458-012	1-1/4	5	30	040	30.66
458-015	1-1/2	5	30	040	31.34
458-020	2	5	20	040	38.47
458-025	2-1/2	5	0	040	54.79
458-030	3	5	0	040	87.95
458-040	4	4	0	040	116.71
458-060	6	1	0	040	259.38



Union - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	8.62
498-007	3/4	15	90	040	14.40
498-010	1	10	60	040	19.62
498-012	1-1/4	5	30	040	33.68
498-015	1-1/2	5	30	040	34.49
498-020	2	5	20	040	42.36
498-025	2-1/2	5	0	040	59.32
498-030	3	5	0	040	95.59
498-040	4	4	0	040	128.82
498-060	6	1	0	040	286.28



Union - Special Reinforced Fipt/Buna

Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	16.98
459-003SR	3/8	25	100	046	16.98
459-005SR	1/2	10	60	046	9.22
459-007SR	3/4	10	60	046	12.68
459-010SR	1	10	40	046	16.88
459-012SR	1-1/4	5	20	046	32.23
459-015SR	1-1/2	5	0	046	39.91
459-020SR	2	5	0	046	61.45
459-030SR	3	5	0	046	145.09
459-040SR	4	4	0	046	166.59
459-060SR	6	1	0	046	370.20



Union - Special Reinforced Fipt/EPDM

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	18.64
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Special Reinforced Fipt/EPDM (continued)

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

499-003SR	3/8	25	100	046	18.64
499-005SR	1/2	10	60	046	10.13
499-007SR	3/4	10	40	046	13.95
499-010SR	1	10	40	046	18.54
499-012SR	1-1/4	5	20	046	35.42
499-015SR	1-1/2	5	0	046	43.85
499-020SR	2	5	0	046	67.54
499-030SR	3	5	0	046	159.45
499-040SR	4	4	0	046	183.06
499-060SR	6	1	0	046	406.82

Union - Brass Fipt/Buna

Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	71.74
459-012BR	1-1/4	5	20	046	120.51
459-015BR	1-1/2	5	0	046	159.43
459-020BR	2	5	0	046	212.67



Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	71.74
499-012BR	1-1/4	5	20	046	120.51
499-015BR	1-1/2	5	0	046	159.43
499-020BR	2	5	0	046	212.67



Not intended to convey or dispense water for human consumption through drinking or cooking

Schedule 40 Tank Adapters

Tank Adapters with EPDM Gasket, Schedule 40

Socket (Male Pipe Thread)

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	34.40
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	40.43
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	46.83
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	58.08
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	65.02
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	83.96
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	139.74



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.