

**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings & Schedule 40 Tank Adapters**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Fipt/Buna**

**Fipt x Fipt with Buna O-ring Seal**

150 psi 73°F (23°C)

458-005	1/2	20	120	040	8.23
458-007	3/4	15	90	040	13.76
458-010	1	10	60	040	18.80
458-012	1-1/4	5	30	040	32.27
458-015	1-1/2	5	30	040	32.99
458-020	2	5	20	040	40.49
458-025	2-1/2	5	0	040	57.67
458-030	3	5	0	040	92.58
458-040	4	4	0	040	122.85
458-060	6	1	0	040	273.03



**Union - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	9.07
498-007	3/4	15	90	040	15.16
498-010	1	10	60	040	20.65
498-012	1-1/4	5	30	040	35.45
498-015	1-1/2	5	30	040	36.31
498-020	2	5	20	040	44.59
498-025	2-1/2	5	0	040	62.44
498-030	3	5	0	040	100.62
498-040	4	4	0	040	135.60
498-060	6	1	0	040	301.35



**Union - Special Reinforced Fipt/Buna**

**Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	17.87
459-003SR	3/8	25	100	046	17.87
459-005SR	1/2	10	60	046	9.71
459-007SR	3/4	10	60	046	13.35
459-010SR	1	10	40	046	17.77
459-012SR	1-1/4	5	20	046	33.93
459-015SR	1-1/2	5	0	046	42.01
459-020SR	2	5	0	046	64.68
459-030SR	3	5	0	046	152.73
459-040SR	4	4	0	046	175.36
459-060SR	6	1	0	046	389.68



**Union - Special Reinforced Fipt/EPDM**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	19.62
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Special Reinforced Fipt/EPDM (continued)**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

499-003SR	3/8	25	100	046	19.62
499-005SR	1/2	10	60	046	10.66
499-007SR	3/4	10	40	046	14.68
499-010SR	1	10	40	046	19.52
499-012SR	1-1/4	5	20	046	37.28
499-015SR	1-1/2	5	0	046	46.16
499-020SR	2	5	0	046	71.09
499-030SR	3	5	0	046	167.84
499-040SR	4	4	0	046	192.69
499-060SR	6	1	0	046	428.23

**Union - Brass Fipt/Buna**

**Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal**

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	75.52
459-012BR	1-1/4	5	20	046	126.85
459-015BR	1-1/2	5	0	046	167.82
459-020BR	2	5	0	046	223.86



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union - Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	75.52
499-012BR	1-1/4	5	20	046	126.85
499-015BR	1-1/2	5	0	046	167.82
499-020BR	2	5	0	046	223.86



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Schedule 40 Tank Adapters**

**Tank Adapters with EPDM Gasket, Schedule 40**

**Socket (Male Pipe Thread)**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	36.21
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	42.56
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	49.29
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	61.14
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	68.44
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	88.38
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	147.09



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.