



Schedule 40 Fittings Product
PVC Schedule 40 Fittings & Schedule 40 Tank Adapters

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Fipt/Buna

Fipt x Fipt with Buna O-ring Seal

150 psi 73°F (23°C)

458-005	1/2	20	120	040	7.43
458-007	3/4	15	90	040	12.42
458-010	1	10	60	040	16.97
458-012	1-1/4	5	30	040	29.13
458-015	1-1/2	5	30	040	29.77
458-020	2	5	20	040	36.55
458-025	2-1/2	5	0	040	52.05
458-030	3	5	0	040	83.55
458-040	4	4	0	040	110.87
458-060	6	1	0	040	246.41



Union - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	8.19
498-007	3/4	15	90	040	13.68
498-010	1	10	60	040	18.64
498-012	1-1/4	5	30	040	32.00
498-015	1-1/2	5	30	040	32.77
498-020	2	5	20	040	40.24
498-025	2-1/2	5	0	040	56.35
498-030	3	5	0	040	90.81
498-040	4	4	0	040	122.38
498-060	6	1	0	040	271.97



Union - Special Reinforced Fipt/Buna

Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	16.13
459-003SR	3/8	25	100	046	16.13
459-005SR	1/2	10	60	046	8.76
459-007SR	3/4	10	60	046	12.05
459-010SR	1	10	40	046	16.04
459-012SR	1-1/4	5	20	046	30.62
459-015SR	1-1/2	5	0	046	37.91
459-020SR	2	5	0	046	58.38
459-030SR	3	5	0	046	137.84
459-040SR	4	4	0	046	158.26
459-060SR	6	1	0	046	351.69



Union - Special Reinforced Fipt/EPDM

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	17.71
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Special Reinforced Fipt/EPDM (continued)

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

499-003SR	3/8	25	100	046	17.71
499-005SR	1/2	10	60	046	9.62
499-007SR	3/4	10	40	046	13.25
499-010SR	1	10	40	046	17.61
499-012SR	1-1/4	5	20	046	33.65
499-015SR	1-1/2	5	0	046	41.66
499-020SR	2	5	0	046	64.16
499-030SR	3	5	0	046	151.48
499-040SR	4	4	0	046	173.91
499-060SR	6	1	0	046	386.48

Union - Brass Fipt/Buna

Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	68.15
459-012BR	1-1/4	5	20	046	114.48
459-015BR	1-1/2	5	0	046	151.46
459-020BR	2	5	0	046	202.04



Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	68.15
499-012BR	1-1/4	5	20	046	114.48
499-015BR	1-1/2	5	0	046	151.46
499-020BR	2	5	0	046	202.04



Not intended to convey or dispense water for human consumption through drinking or cooking

Schedule 40 Tank Adapters

Tank Adapters with EPDM Gasket, Schedule 40

Socket(Male Pipe Thread)

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	32.68
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	38.41
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	44.49
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	55.18
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	61.77
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	79.76
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	132.75



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.