



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Wye - Reducing (continued)</b>					
<b>Socket x Socket x Socket</b>					
475-903F <sup>2</sup>	24X3	1	0	047	1967.01
475-904F <sup>2</sup>	24X4	1	0	047	2021.23
475-906F <sup>2</sup>	24X6	1	0	047	3557.57
475-908F <sup>2</sup>	24X8	1	0	047	3880.76
475-910F <sup>2</sup>	24X10	1	0	047	3921.75
475-912F <sup>2</sup>	24X12	1	0	047	4151.32
475-914F <sup>2</sup>	24X14	1	0	047	4293.75
475-916F <sup>2</sup>	24X16	1	0	047	4496.60
475-918F <sup>2</sup>	24X18	1	0	047	4888.34
475-920F <sup>2</sup>	24X20	1	0	047	5343.36
<sup>1</sup> Sized with Bushing					
<sup>2</sup> Fiberglass reinforced					



**Double Wye**

**Socket x Socket x Socket x Socket**

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F <sup>2</sup>	2	1	4	047	308.51
476-030F <sup>2</sup>	3	1	3	047	508.15
476-040F <sup>2</sup>	4	1	2	047	566.03
476-060F <sup>2</sup>	6	1	0	047	644.61
476-080F <sup>2</sup>	8	1	0	047	785.02
476-100F <sup>2</sup>	10	1	0	047	1439.52
476-120F <sup>2</sup>	12	1	0	047	1713.76
476-140F <sup>2</sup>	14	1	0	047	2494.22
<sup>2</sup> Fiberglass reinforced					
For larger sizes please contact your Regional Spears® Distribution Center.					



**Double Wye - Reducing**

**Socket x Socket x Socket x Socket**

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	111.56
476-420F <sup>2</sup>	4X2	1	4	047	501.11
476-421F <sup>2</sup>	4X2-1/2	1	2	047	522.82
476-422F <sup>2</sup>	4X3	1	3	047	537.86
476-528F <sup>2</sup>	6X2	1	2	047	504.61
476-529F <sup>2</sup>	6X2-1/2	1	2	047	549.35
476-530F <sup>2</sup>	6X3	1	2	047	570.94
476-532F <sup>2</sup>	6X4	1	0	047	579.86
476-578F <sup>2</sup>	8X2	1	2	047	615.60
476-579F <sup>2</sup>	8X2-1/2	1	2	047	640.07
476-580F <sup>2</sup>	8X3	1	0	047	688.80
476-582F <sup>2</sup>	8X4	1	0	047	697.66
476-585F <sup>2</sup>	8X6	1	0	047	731.40
476-621F <sup>2</sup>	10X2	1	0	047	917.19
476-622F <sup>2</sup>	10X2-1/2	1	0	047	971.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing (continued)**

**Socket x Socket x Socket x Socket**

476-623F <sup>2</sup>	10X3	1	0	047	999.62
476-624F <sup>2</sup>	10X4	1	0	047	1098.34
476-626F <sup>2</sup>	10X6	1	0	047	1232.00
476-628F <sup>2</sup>	10X8	1	0	047	1284.72
476-661F <sup>2</sup>	12X2	1	0	047	1308.55
476-662F <sup>2</sup>	12X2 1/2	1	0	047	1323.40
476-663F <sup>2</sup>	12X3	1	0	047	1394.43
476-664F <sup>2</sup>	12X4	1	0	047	1421.66
476-666F <sup>2</sup>	12X6	1	0	047	1502.33
476-668F <sup>2</sup>	12X8	1	0	047	1540.86
476-670F <sup>2</sup>	12X10	1	0	047	1632.39
476-756F	16X6	1	0	047	2742.91
476-786F	18X6	1	0	047	1536.64

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union - Socket/Buna**

**Socket x Socket with Buna-N O-ring Seal**

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	6.99
457-007	3/4	15	90	040	7.95
457-010	1	10	60	040	8.19
457-012	1-1/4	5	30	040	26.38
457-015	1-1/2	5	20	040	27.46
457-020	2	5	0	040	37.06
457-025	2-1/2	5	0	040	51.87
457-030	3	5	0	040	82.85
457-040	4	4	0	040	114.72
457-060	6	1	0	040	254.91



**Union - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	7.69
497-007	3/4	15	90	040	8.80
497-010	1	10	60	040	8.99
497-012	1-1/4	5	30	040	29.01
497-015	1-1/2	5	20	040	30.24
497-020	2	5	0	040	40.78
497-025	2-1/2	5	0	040	57.08
497-030	3	5	0	040	91.04
497-040	4	4	0	040	122.48
497-060	6	1	0	040	272.18



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings & Schedule 40 Tank Adapters**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Fipt/Buna**

**Fipt x Fipt with Buna O-ring Seal**

150 psi 73°F (23°C)

458-005	1/2	20	120	040	7.82
458-007	3/4	15	90	040	13.07
458-010	1	10	60	040	17.86
458-012	1-1/4	5	30	040	30.66
458-015	1-1/2	5	30	040	31.34
458-020	2	5	20	040	38.47
458-025	2-1/2	5	0	040	54.79
458-030	3	5	0	040	87.95
458-040	4	4	0	040	116.71
458-060	6	1	0	040	259.38



**Union - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	8.62
498-007	3/4	15	90	040	14.40
498-010	1	10	60	040	19.62
498-012	1-1/4	5	30	040	33.68
498-015	1-1/2	5	30	040	34.49
498-020	2	5	20	040	42.36
498-025	2-1/2	5	0	040	59.32
498-030	3	5	0	040	95.59
498-040	4	4	0	040	128.82
498-060	6	1	0	040	286.28



**Union - Special Reinforced Fipt/Buna**

**Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	16.98
459-003SR	3/8	25	100	046	16.98
459-005SR	1/2	10	60	046	9.22
459-007SR	3/4	10	60	046	12.68
459-010SR	1	10	40	046	16.88
459-012SR	1-1/4	5	20	046	32.23
459-015SR	1-1/2	5	0	046	39.91
459-020SR	2	5	0	046	61.45
459-030SR	3	5	0	046	145.09
459-040SR	4	4	0	046	166.59
459-060SR	6	1	0	046	370.20



**Union - Special Reinforced Fipt/EPDM**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	18.64
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Special Reinforced Fipt/EPDM (continued)**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

499-003SR	3/8	25	100	046	18.64
499-005SR	1/2	10	60	046	10.13
499-007SR	3/4	10	40	046	13.95
499-010SR	1	10	40	046	18.54
499-012SR	1-1/4	5	20	046	35.42
499-015SR	1-1/2	5	0	046	43.85
499-020SR	2	5	0	046	67.54
499-030SR	3	5	0	046	159.45
499-040SR	4	4	0	046	183.06
499-060SR	6	1	0	046	406.82

**Union - Brass Fipt/Buna**

**Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal**

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	71.74
459-012BR	1-1/4	5	20	046	120.51
459-015BR	1-1/2	5	0	046	159.43
459-020BR	2	5	0	046	212.67



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union - Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	71.74
499-012BR	1-1/4	5	20	046	120.51
499-015BR	1-1/2	5	0	046	159.43
499-020BR	2	5	0	046	212.67



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Schedule 40 Tank Adapters**

**Tank Adapters with EPDM Gasket, Schedule 40**

**Socket (Male Pipe Thread)**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	34.40
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	40.43
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	46.83
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	58.08
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	65.02
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	83.96
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	139.74



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.