



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings**

**Wyes**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Wye - Reducing (continued)</b>					
<b>Socket x Socket x Socket</b>					
475-903F <sup>2</sup>	24X3	1	0	047	2070.54
475-904F <sup>2</sup>	24X4	1	0	047	2127.61
475-906F <sup>2</sup>	24X6	1	0	047	3744.81
475-908F <sup>2</sup>	24X8	1	0	047	4085.01
475-910F <sup>2</sup>	24X10	1	0	047	4128.16
475-912F <sup>2</sup>	24X12	1	0	047	4369.81
475-914F <sup>2</sup>	24X14	1	0	047	4519.74
475-916F <sup>2</sup>	24X16	1	0	047	4733.26
475-918F <sup>2</sup>	24X18	1	0	047	5145.62
475-920F <sup>2</sup>	24X20	1	0	047	5624.59
<sup>1</sup> Sized with Bushing					
<sup>2</sup> Fiberglass reinforced					



**Double Wye**

**Socket x Socket x Socket x Socket**

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F <sup>2</sup>	2	1	4	047	324.75
476-030F <sup>2</sup>	3	1	3	047	534.89
476-040F <sup>2</sup>	4	1	2	047	595.82
476-060F <sup>2</sup>	6	1	0	047	678.54
476-080F <sup>2</sup>	8	1	0	047	826.34
476-100F <sup>2</sup>	10	1	0	047	1515.28
476-120F <sup>2</sup>	12	1	0	047	1803.96
476-140F <sup>2</sup>	14	1	0	047	2625.49
<sup>2</sup> Fiberglass reinforced					
For larger sizes please contact your Regional Spears® Distribution Center.					



**Double Wye - Reducing**

**Socket x Socket x Socket x Socket**

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	117.43
476-420F <sup>2</sup>	4X2	1	4	047	527.48
476-421F <sup>2</sup>	4X2-1/2	1	2	047	550.34
476-422F <sup>2</sup>	4X3	1	3	047	566.17
476-528F <sup>2</sup>	6X2	1	2	047	531.17
476-529F <sup>2</sup>	6X2-1/2	1	2	047	578.26
476-530F <sup>2</sup>	6X3	1	2	047	600.99
476-532F <sup>2</sup>	6X4	1	0	047	610.38
476-578F <sup>2</sup>	8X2	1	2	047	648.00
476-579F <sup>2</sup>	8X2-1/2	1	2	047	673.76
476-580F <sup>2</sup>	8X3	1	0	047	725.05
476-582F <sup>2</sup>	8X4	1	0	047	734.38
476-585F <sup>2</sup>	8X6	1	0	047	769.89
476-621F <sup>2</sup>	10X2	1	0	047	965.46
476-622F <sup>2</sup>	10X2-1/2	1	0	047	1022.91

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Double Wye - Reducing (continued)**

**Socket x Socket x Socket x Socket**

476-623F <sup>2</sup>	10X3	1	0	047	1052.23
476-624F <sup>2</sup>	10X4	1	0	047	1156.15
476-626F <sup>2</sup>	10X6	1	0	047	1296.84
476-628F <sup>2</sup>	10X8	1	0	047	1352.34
476-661F <sup>2</sup>	12X2	1	0	047	1377.42
476-662F <sup>2</sup>	12X2 1/2	1	0	047	1393.05
476-663F <sup>2</sup>	12X3	1	0	047	1467.82
476-664F <sup>2</sup>	12X4	1	0	047	1496.48
476-666F <sup>2</sup>	12X6	1	0	047	1581.40
476-668F <sup>2</sup>	12X8	1	0	047	1621.96
476-670F <sup>2</sup>	12X10	1	0	047	1718.31
476-756F <sup>2</sup>	16X6	1	0	047	2887.27
476-786F <sup>2</sup>	18X6	1	0	047	1617.52

<sup>2</sup> Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

**Unions**

**Union - Socket/Buna**

**Socket x Socket with Buna-N O-ring Seal**

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	7.36
457-007	3/4	15	90	040	8.37
457-010	1	10	60	040	8.62
457-012	1-1/4	5	30	040	27.77
457-015	1-1/2	5	20	040	28.91
457-020	2	5	0	040	39.01
457-025	2-1/2	5	0	040	54.60
457-030	3	5	0	040	87.21
457-040	4	4	0	040	120.76
457-060	6	1	0	040	268.33



**Union - Socket/EPDM**

**Socket x Socket with EPDM O-ring Seal**

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	8.09
497-007	3/4	15	90	040	9.26
497-010	1	10	60	040	9.46
497-012	1-1/4	5	30	040	30.54
497-015	1-1/2	5	20	040	31.83
497-020	2	5	0	040	42.93
497-025	2-1/2	5	0	040	60.08
497-030	3	5	0	040	95.83
497-040	4	4	0	040	128.93
497-060	6	1	0	040	286.51



**Schedule 40 Fittings Product**  
**PVC Schedule 40 Fittings & Schedule 40 Tank Adapters**



**Unions**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Fipt/Buna**

**Fipt x Fipt with Buna O-ring Seal**

150 psi 73°F (23°C)

458-005	1/2	20	120	040	8.23
458-007	3/4	15	90	040	13.76
458-010	1	10	60	040	18.80
458-012	1-1/4	5	30	040	32.27
458-015	1-1/2	5	30	040	32.99
458-020	2	5	20	040	40.49
458-025	2-1/2	5	0	040	57.67
458-030	3	5	0	040	92.58
458-040	4	4	0	040	122.85
458-060	6	1	0	040	273.03



**Union - Fipt/EPDM**

**Fipt x Fipt with EPDM O-ring Seal**

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	9.07
498-007	3/4	15	90	040	15.16
498-010	1	10	60	040	20.65
498-012	1-1/4	5	30	040	35.45
498-015	1-1/2	5	30	040	36.31
498-020	2	5	20	040	44.59
498-025	2-1/2	5	0	040	62.44
498-030	3	5	0	040	100.62
498-040	4	4	0	040	135.60
498-060	6	1	0	040	301.35



**Union - Special Reinforced Fipt/Buna**

**Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	17.87
459-003SR	3/8	25	100	046	17.87
459-005SR	1/2	10	60	046	9.71
459-007SR	3/4	10	60	046	13.35
459-010SR	1	10	40	046	17.77
459-012SR	1-1/4	5	20	046	33.93
459-015SR	1-1/2	5	0	046	42.01
459-020SR	2	5	0	046	64.68
459-030SR	3	5	0	046	152.73
459-040SR	4	4	0	046	175.36
459-060SR	6	1	0	046	389.68



**Union - Special Reinforced Fipt/EPDM**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	19.62
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Special Reinforced Fipt/EPDM (continued)**

**Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar**

499-003SR	3/8	25	100	046	19.62
499-005SR	1/2	10	60	046	10.66
499-007SR	3/4	10	40	046	14.68
499-010SR	1	10	40	046	19.52
499-012SR	1-1/4	5	20	046	37.28
499-015SR	1-1/2	5	0	046	46.16
499-020SR	2	5	0	046	71.09
499-030SR	3	5	0	046	167.84
499-040SR	4	4	0	046	192.69
499-060SR	6	1	0	046	428.23

**Union - Brass Fipt/Buna**

**Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal**

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	75.52
459-012BR	1-1/4	5	20	046	126.85
459-015BR	1-1/2	5	0	046	167.82
459-020BR	2	5	0	046	223.86



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union - Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	75.52
499-012BR	1-1/4	5	20	046	126.85
499-015BR	1-1/2	5	0	046	167.82
499-020BR	2	5	0	046	223.86



**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Schedule 40 Tank Adapters**

**Tank Adapters with EPDM Gasket, Schedule 40**

**Socket(Male Pipe Thread)**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	36.21
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	42.56
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	49.29
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	61.14
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	68.44
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	88.38
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	147.09



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.