

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-903F ²	24X3	1	0	047	1868.66
475-904F ²	24X4	1	0	047	1920.17
475-906F ²	24X6	1	0	047	3379.69
475-908F ²	24X8	1	0	047	3686.72
475-910F ²	24X10	1	0	047	3725.66
475-912F ²	24X12	1	0	047	3943.75
475-914F ²	24X14	1	0	047	4079.06
475-916F ²	24X16	1	0	047	4271.77
475-918F ²	24X18	1	0	047	4643.92
475-920F ²	24X20	0	0	047	5076.19

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	293.08
476-030F ²	3	1	3	047	482.74
476-040F ²	4	1	2	047	537.73
476-060F ²	6	1	0	047	612.38
476-080F ²	8	1	0	047	745.77
476-100F ²	10	1	0	047	1367.54
476-120F ²	12	1	0	047	1628.07
476-140F ²	14	1	0	047	2369.51

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	105.98
476-420F ²	4X2	1	4	047	476.05
476-421F ²	4X2-1/2	1	2	047	496.68
476-422F ²	4X3	1	3	047	510.97
476-528F ²	6X2	1	2	047	479.38
476-529F ²	6X2-1/2	1	2	047	521.88
476-530F ²	6X3	1	2	047	542.39
476-532F ²	6X4	1	0	047	550.87
476-578F ²	8X2	1	2	047	584.82
476-579F ²	8X2-1/2	1	2	047	608.07
476-580F ²	8X3	1	0	047	654.36
476-582F ²	8X4	1	0	047	662.78
476-585F ²	8X6	1	0	047	694.83
476-621F ²	10X2	1	0	047	871.33
476-622F ²	10X2-1/2	1	0	047	923.17

Made in the U.S.A.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas
See MSRP-1 Sheet or Check Spears® On-line Catalog @ www.spearsmfg.com for Pricing

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	949.64
476-624F ²	10X4	1	0	047	1043.42
476-626F ²	10X6	1	0	047	1170.40
476-628F ²	10X8	1	0	047	1220.48
476-661F ²	12X2	1	0	047	1243.12
476-662F ²	12X2 1/2	1	0	047	1257.23
476-663F ²	12X3	1	0	047	1324.71
476-664F ²	12X4	1	0	047	1350.58
476-666F ²	12X6	1	0	047	1427.21
476-668F ²	12X8	1	0	047	1463.82
476-670F ²	12X10	1	0	047	1550.77
476-756F	16X6	1	0	047	2605.76
476-786F	18X6	1	0	047	1459.81

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	6.64
457-007	3/4	15	90	040	7.55
457-010	1	10	60	040	7.78
457-012	1-1/4	5	30	040	25.06
457-015	1-1/2	5	20	040	26.09
457-020	2	5	0	040	35.21
457-025	2-1/2	5	0	040	49.28
457-030	3	5	0	040	78.71
457-040	4	4	0	040	108.98
457-060	6	1	0	040	242.16



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	7.31
497-007	3/4	15	90	040	8.36
497-010	1	10	60	040	8.54
497-012	1-1/4	5	30	040	27.56
497-015	1-1/2	5	20	040	28.73
497-020	2	5	0	040	38.74
497-025	2-1/2	5	0	040	54.23
497-030	3	5	0	040	86.49
497-040	4	4	0	040	116.36
497-060	6	1	0	040	258.57





Schedule 40 Fittings Product
PVC Schedule 40 Fittings & Schedule 40 Tank Adapters

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Fipt/Buna

Fipt x Fipt with Buna O-ring Seal

150 psi 73°F (23°C)

458-005	1/2	20	120	040	7.43
458-007	3/4	15	90	040	12.42
458-010	1	10	60	040	16.97
458-012	1-1/4	5	30	040	29.13
458-015	1-1/2	5	30	040	29.77
458-020	2	5	20	040	36.55
458-025	2-1/2	5	0	040	52.05
458-030	3	5	0	040	83.55
458-040	4	4	0	040	110.87
458-060	6	1	0	040	246.41



Union - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	8.19
498-007	3/4	15	90	040	13.68
498-010	1	10	60	040	18.64
498-012	1-1/4	5	30	040	32.00
498-015	1-1/2	5	30	040	32.77
498-020	2	5	20	040	40.24
498-025	2-1/2	5	0	040	56.35
498-030	3	5	0	040	90.81
498-040	4	4	0	040	122.38
498-060	6	1	0	040	271.97



Union - Special Reinforced Fipt/Buna

Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	16.13
459-003SR	3/8	25	100	046	16.13
459-005SR	1/2	10	60	046	8.76
459-007SR	3/4	10	60	046	12.05
459-010SR	1	10	40	046	16.04
459-012SR	1-1/4	5	20	046	30.62
459-015SR	1-1/2	5	0	046	37.91
459-020SR	2	5	0	046	58.38
459-030SR	3	5	0	046	137.84
459-040SR	4	4	0	046	158.26
459-060SR	6	1	0	046	351.69



Union - Special Reinforced Fipt/EPDM

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	17.71
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Special Reinforced Fipt/EPDM (continued)

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

499-003SR	3/8	25	100	046	17.71
499-005SR	1/2	10	60	046	9.62
499-007SR	3/4	10	40	046	13.25
499-010SR	1	10	40	046	17.61
499-012SR	1-1/4	5	20	046	33.65
499-015SR	1-1/2	5	0	046	41.66
499-020SR	2	5	0	046	64.16
499-030SR	3	5	0	046	151.48
499-040SR	4	4	0	046	173.91
499-060SR	6	1	0	046	386.48

Union - Brass Fipt/Buna

Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	68.15
459-012BR	1-1/4	5	20	046	114.48
459-015BR	1-1/2	5	0	046	151.46
459-020BR	2	5	0	046	202.04



Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	68.15
499-012BR	1-1/4	5	20	046	114.48
499-015BR	1-1/2	5	0	046	151.46
499-020BR	2	5	0	046	202.04



Not intended to convey or dispense water for human consumption through drinking or cooking

Schedule 40 Tank Adapters

Tank Adapters with EPDM Gasket, Schedule 40

Socket(Male Pipe Thread)

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	32.68
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	38.41
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	44.49
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	55.18
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	61.77
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	79.76
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	132.75



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.