



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye - Reducing (continued)					
Socket x Socket x Socket					
475-903F ²	24X3	1	0	047	1967.01
475-904F ²	24X4	1	0	047	2021.23
475-906F ²	24X6	1	0	047	3557.57
475-908F ²	24X8	1	0	047	3880.76
475-910F ²	24X10	1	0	047	3921.75
475-912F ²	24X12	1	0	047	4151.32
475-914F ²	24X14	1	0	047	4293.75
475-916F ²	24X16	1	0	047	4496.60
475-918F ²	24X18	1	0	047	4888.34
475-920F ²	24X20	1	0	047	5343.36
¹ Sized with Bushing					
² Fiberglass reinforced					



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	308.51
476-030F ²	3	1	3	047	508.15
476-040F ²	4	1	2	047	566.03
476-060F ²	6	1	0	047	644.61
476-080F ²	8	1	0	047	785.02
476-100F ²	10	1	0	047	1439.52
476-120F ²	12	1	0	047	1713.76
476-140F ²	14	1	0	047	2494.22
² Fiberglass reinforced					
For larger sizes please contact your Regional Spears® Distribution Center.					



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	111.56
476-420F ²	4X2	1	4	047	501.11
476-421F ²	4X2-1/2	1	2	047	522.82
476-422F ²	4X3	1	3	047	537.86
476-528F ²	6X2	1	2	047	504.61
476-529F ²	6X2-1/2	1	2	047	549.35
476-530F ²	6X3	1	2	047	570.94
476-532F ²	6X4	1	0	047	579.86
476-578F ²	8X2	1	2	047	615.60
476-579F ²	8X2-1/2	1	2	047	640.07
476-580F ²	8X3	1	0	047	688.80
476-582F ²	8X4	1	0	047	697.66
476-585F ²	8X6	1	0	047	731.40
476-621F ²	10X2	1	0	047	917.19
476-622F ²	10X2-1/2	1	0	047	971.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	999.62
476-624F ²	10X4	1	0	047	1098.34
476-626F ²	10X6	1	0	047	1232.00
476-628F ²	10X8	1	0	047	1284.72
476-661F ²	12X2	1	0	047	1308.55
476-662F ²	12X2 1/2	1	0	047	1323.40
476-663F ²	12X3	1	0	047	1394.43
476-664F ²	12X4	1	0	047	1421.66
476-666F ²	12X6	1	0	047	1502.33
476-668F ²	12X8	1	0	047	1540.86
476-670F ²	12X10	1	0	047	1632.39
476-756F	16X6	1	0	047	2742.91
476-786F	18X6	1	0	047	1536.64

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	6.99
457-007	3/4	15	90	040	7.95
457-010	1	10	60	040	8.19
457-012	1-1/4	5	30	040	26.38
457-015	1-1/2	5	20	040	27.46
457-020	2	5	0	040	37.06
457-025	2-1/2	5	0	040	51.87
457-030	3	5	0	040	82.85
457-040	4	4	0	040	114.72
457-060	6	1	0	040	254.91



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	7.69
497-007	3/4	15	90	040	8.80
497-010	1	10	60	040	8.99
497-012	1-1/4	5	30	040	29.01
497-015	1-1/2	5	20	040	30.24
497-020	2	5	0	040	40.78
497-025	2-1/2	5	0	040	57.08
497-030	3	5	0	040	91.04
497-040	4	4	0	040	122.48
497-060	6	1	0	040	272.18



Schedule 40 Fittings Product
PVC Schedule 40 Fittings & Schedule 40 Tank Adapters



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Fipt/Buna

Fipt x Fipt with Buna O-ring Seal

150 psi 73°F (23°C)

458-005	1/2	20	120	040	7.82
458-007	3/4	15	90	040	13.07
458-010	1	10	60	040	17.86
458-012	1-1/4	5	30	040	30.66
458-015	1-1/2	5	30	040	31.34
458-020	2	5	20	040	38.47
458-025	2-1/2	5	0	040	54.79
458-030	3	5	0	040	87.95
458-040	4	4	0	040	116.71
458-060	6	1	0	040	259.38



Union - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

150 psi @ 73°F (23°C)

498-005	1/2	10	60	040	8.62
498-007	3/4	15	90	040	14.40
498-010	1	10	60	040	19.62
498-012	1-1/4	5	30	040	33.68
498-015	1-1/2	5	30	040	34.49
498-020	2	5	20	040	42.36
498-025	2-1/2	5	0	040	59.32
498-030	3	5	0	040	95.59
498-040	4	4	0	040	128.82
498-060	6	1	0	040	286.28



Union - Special Reinforced Fipt/Buna

Socket x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	16.98
459-003SR	3/8	25	100	046	16.98
459-005SR	1/2	10	60	046	9.22
459-007SR	3/4	10	60	046	12.68
459-010SR	1	10	40	046	16.88
459-012SR	1-1/4	5	20	046	32.23
459-015SR	1-1/2	5	0	046	39.91
459-020SR	2	5	0	046	61.45
459-030SR	3	5	0	046	145.09
459-040SR	4	4	0	046	166.59
459-060SR	6	1	0	046	370.20



Union - Special Reinforced Fipt/EPDM

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	18.64
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Special Reinforced Fipt/EPDM (continued)

Socket x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

499-003SR	3/8	25	100	046	18.64
499-005SR	1/2	10	60	046	10.13
499-007SR	3/4	10	40	046	13.95
499-010SR	1	10	40	046	18.54
499-012SR	1-1/4	5	20	046	35.42
499-015SR	1-1/2	5	0	046	43.85
499-020SR	2	5	0	046	67.54
499-030SR	3	5	0	046	159.45
499-040SR	4	4	0	046	183.06
499-060SR	6	1	0	046	406.82

Union - Brass Fipt/Buna

Socket x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	71.74
459-012BR	1-1/4	5	20	046	120.51
459-015BR	1-1/2	5	0	046	159.43
459-020BR	2	5	0	046	212.67



Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	71.74
499-012BR	1-1/4	5	20	046	120.51
499-015BR	1-1/2	5	0	046	159.43
499-020BR	2	5	0	046	212.67



Not intended to convey or dispense water for human consumption through drinking or cooking

Schedule 40 Tank Adapters

Tank Adapters with EPDM Gasket, Schedule 40

Socket (Male Pipe Thread)

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

4170E-005	1/2 Soc(1 MPT)	25	0	029	34.40
4170E-007	3/4 Soc(1-1/4 MPT)	25	0	029	40.43
4170E-010	1 Soc(1-1/2 MPT)	25	0	029	46.83
4170E-012	1-1/4 Soc(2 MPT)	20	0	029	58.08
4170E-015	1-1/2 Soc(2 MPT)	30	0	029	65.02
4170E-020	2 Soc(2-1/2 MPT)	10	0	029	83.96
4170E-025	2-1/2 Soc(3 MPT)	8	0	029	139.74



Note: These tank adapters have both Socket and size larger Male Pipe Thread connection on external end. End lugs allow holding body when tightening Adapter Nut.