

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Fipt					
448-012	1-1/4	25	100	040	2.66
448-015	1-1/2	25	100	040	2.78
448-020	2	10	120	040	4.92
448-025	2-1/2	10	0	040	7.25
448-030	3	10	0	040	9.48
448-040	4	6	0	040	16.64
448-050	5	5	0	040	32.24
448-060	6	8	0	040	39.34
448-080F	8	1	2	047	191.98
448-100F	10	1	2	047	390.13
448-120F	12	1	0	047	779.51

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	7.09
-----------	-------	----	-----	-----	------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	1.83
449-005	1/2	50	1000	040	1.48
449-007	3/4	50	300	040	1.73
449-010	1	50	200	040	2.08
449-012	1-1/4	25	150	040	2.78
449-015	1-1/2	25	100	040	3.54
449-020	2	10	120	040	4.38
449-025	2-1/2	10	0	040	7.51
449-030	3	10	0	040	9.91
449-040	4	6	0	040	22.43
449-060	6	6	0	040	30.37
449-060F ⁴	6	1	6	047	76.84
449-080F ⁴	8	1	6	047	118.31
449-100F ⁴	10	1	0	047	271.59
449-120F ⁴	12	1	0	047	444.07
449-140F ⁴	14	1	2	047	486.83
449-160F ⁴	16	1	0	047	538.36
449-180F ⁴	18	1	0	047	960.72
449-200F ⁴	20	1	0	047	1757.60
449-240F ⁴	24	1	0	047	2339.60

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	1.73
449-010CS	1	50	300	040	2.08

Plug

Mipt

450-003	3/8	50	700	040	1.99
450-005	1/2	50	300	040	1.83
450-007	3/4	50	300	040	1.97
450-010	1	50	300	040	3.20
450-012	1-1/4	25	300	040	3.37
450-015	1-1/2	25	150	040	3.62
450-020	2	10	120	040	4.67
450-025	2-1/2	10	80	040	6.49
450-030	3	10	0	040	9.83
450-040	4	6	0	040	22.18
450-060	6	6	0	040	65.03
450-080	8	6	0	040	79.46
450-080F ⁴	8	1	4	047	172.40
450-100F ⁴	10	1	3	047	343.54
450-120F ⁴	12	1	0	047	479.61

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 80 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	2.91
475-007	3/4	20	0	040	4.56
475-010	1	25	0	040	6.38
475-012	1-1/4	20	0	040	9.81
475-015	1-1/2	20	0	040	12.58
475-020	2	10	0	040	37.74
475-025	2-1/2	8	0	040	86.27
475-030	3	5	0	040	63.58
475-040	4	4	0	040	119.92
475-050F	5	1	3	047	467.96
475-060	6	3	0	040	253.71
475-080	8	1	0	040	408.07
475-100	10	1	0	041	1352.18
475-100F ²	10	1	0	047	1134.64



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

475-120	12	1	0	041	1997.92
475-120F ²	12	1	0	047	1542.44
475-140F ²	14	1	0	047	2185.24
475-160F ²	16	1	0	047	2824.68
475-180F ²	18	1	0	047	3616.59
475-200F ²	20	1	0	047	4275.83
475-240F ²	24	1	0	047	5317.76

¹ Sized with Bushing
² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 80 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040	8.99
475-130 ¹	1X1/2	20	0	040	11.43
475-131 ¹	1X3/4	20	0	040	11.43
475-166 ¹	1-1/4X1/2	20	0	040	15.38
475-167 ¹	1-1/4X3/4	20	0	040	15.38
475-168 ¹	1-1/4X1	20	0	040	15.38
475-209 ¹	1-1/2X1/2	20	0	040	18.31
475-210 ¹	1-1/2X3/4	20	0	040	18.31
475-211 ¹	1-1/2X1	20	0	040	18.31
475-212 ¹	1-1/2X1-1/4	20	0	040	18.31
475-247 ¹	2X1/2	10	0	040	41.59
475-248 ¹	2X3/4	10	0	040	41.59
475-249 ¹	2X1	10	0	040	41.59
475-250 ¹	2X1-1/4	10	0	040	41.59
475-251 ¹	2X1-1/2	10	0	040	41.59
475-292 ¹	2-1/2X2	4	0	040	92.66
475-334 ¹	3X3/4	5	0	040	72.21
475-335 ¹	3X1	5	0	040	72.21
475-336 ¹	3X1-1/4	5	0	040	72.21
475-337 ¹	3X1-1/2	5	0	040	72.21
475-338 ¹	3X2	5	0	040	72.21
475-339 ¹	3X2-1/2	5	0	040	72.21
475-420	4X2	4	0	040	138.72
475-421 ¹	4X2-1/2	4	0	040	138.72
475-422 ¹	4X3	4	0	040	138.72
475-488F ²	5X3	1	4	047	372.20
475-490F ²	5X4	1	4	047	387.58
475-528 ¹	6X2	4	0	040	299.40
475-529 ¹	6X2-1/2	5	0	040	299.40
475-530 ¹	6X3	5	0	040	299.40
475-532	6X4	5	0	040	326.20
475-578F ²	8X2	1	2	047	560.22

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047	594.49
475-580F ²	8X3	1	2	047	608.68
475-582	8X4	2	0	040	558.75
475-582F ²	8X4	1	2	047	627.84
475-585F ²	8X6	1	0	047	646.87
475-621F ²	10X2	1	0	047	673.44
475-622F ²	10X2-1/2	1	0	047	685.02
475-623F ²	10X3	1	0	047	721.59
475-624F ²	10X4	1	0	047	763.61
475-626	10X6	1	0	041	1158.78
475-626F ²	10X6	1	0	047	843.17
475-628	10X8	1	0	041	1287.54
475-628F ²	10X8	1	0	047	902.20
475-661F ²	12X2	1	0	047	914.13
475-663F ²	12X3	1	0	047	935.94
475-664F ²	12X4	1	0	047	979.53
475-666F ²	12X6	1	0	047	984.23
475-668F ²	12X8	1	0	047	1141.40
475-670F ²	12X10	1	0	047	1305.05
475-691F ²	14X2	1	0	047	1086.68
475-693F ²	14X3	1	0	047	1176.17
475-694F ²	14X4	1	0	047	1233.48
475-696F ²	14X6	1	0	047	1389.71
475-698F ²	14X8	1	0	047	1592.37
475-700F ²	14X10	1	0	047	1778.76
475-702F ²	14X12	1	0	047	1992.89
475-751F ²	16X2	1	0	047	1262.54
475-753F ²	16X3	1	0	047	1364.83
475-754F ²	16X4	1	0	047	1419.34
475-756F ²	16X6	1	0	047	1597.21
475-758F ²	16X8	1	0	047	1818.94
475-760F ²	16X10	1	0	047	2024.44
475-762F ²	16X12	1	0	047	2255.96
475-764F ²	16X14	1	0	047	2553.42
475-781F ²	18X2	1	0	047	1377.55
475-783F ²	18X3	1	0	047	1440.60
475-784F ²	18X4	1	0	047	1461.99
475-786F ²	18X6	1	0	047	2801.08
475-788F ²	18X8	1	0	047	2090.51
475-790F ²	18X10	1	0	047	2325.26
475-792F ²	18X12	1	0	047	2697.52
475-794F ²	18X14	1	0	047	2961.72
475-796F ²	18X16	1	0	047	3106.14
475-811F ²	20X2	1	0	047	1448.52
475-813F ²	20X3	1	0	047	1569.71
475-814F ²	20X4	1	0	047	1590.04
475-816F ²	20X6	1	0	047	1619.87
475-818F ²	20X8	1	0	047	2189.68
475-820F ²	20X10	1	0	047	2434.28
475-822F ²	20X12	1	0	047	2933.68
475-824F ²	20X14	1	0	047	3283.15
475-826F ²	20X16	1	0	047	3639.02
475-828F ²	20X18	0	0	047	3906.19
475-901F ²	24X2	1	0	047	1828.44

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-903F ²	24X3	1	0	047	1868.66
475-904F ²	24X4	1	0	047	1920.17
475-906F ²	24X6	1	0	047	3379.69
475-908F ²	24X8	1	0	047	3686.72
475-910F ²	24X10	1	0	047	3725.66
475-912F ²	24X12	1	0	047	3943.75
475-914F ²	24X14	1	0	047	4079.06
475-916F ²	24X16	1	0	047	4271.77
475-918F ²	24X18	1	0	047	4643.92
475-920F ²	24X20	0	0	047	5076.19

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	293.08
476-030F ²	3	1	3	047	482.74
476-040F ²	4	1	2	047	537.73
476-060F ²	6	1	0	047	612.38
476-080F ²	8	1	0	047	745.77
476-100F ²	10	1	0	047	1367.54
476-120F ²	12	1	0	047	1628.07
476-140F ²	14	1	0	047	2369.51

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	105.98
476-420F ²	4X2	1	4	047	476.05
476-421F ²	4X2-1/2	1	2	047	496.68
476-422F ²	4X3	1	3	047	510.97
476-528F ²	6X2	1	2	047	479.38
476-529F ²	6X2-1/2	1	2	047	521.88
476-530F ²	6X3	1	2	047	542.39
476-532F ²	6X4	1	0	047	550.87
476-578F ²	8X2	1	2	047	584.82
476-579F ²	8X2-1/2	1	2	047	608.07
476-580F ²	8X3	1	0	047	654.36
476-582F ²	8X4	1	0	047	662.78
476-585F ²	8X6	1	0	047	694.83
476-621F ²	10X2	1	0	047	871.33
476-622F ²	10X2-1/2	1	0	047	923.17

Made in the U.S.A.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas
See MSRP-1 Sheet or Check Spears® On-line Catalog @ www.spearsmfg.com for Pricing

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	949.64
476-624F ²	10X4	1	0	047	1043.42
476-626F ²	10X6	1	0	047	1170.40
476-628F ²	10X8	1	0	047	1220.48
476-661F ²	12X2	1	0	047	1243.12
476-662F ²	12X2 1/2	1	0	047	1257.23
476-663F ²	12X3	1	0	047	1324.71
476-664F ²	12X4	1	0	047	1350.58
476-666F ²	12X6	1	0	047	1427.21
476-668F ²	12X8	1	0	047	1463.82
476-670F ²	12X10	1	0	047	1550.77
476-756F	16X6	1	0	047	2605.76
476-786F	18X6	1	0	047	1459.81

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	6.64
457-007	3/4	15	90	040	7.55
457-010	1	10	60	040	7.78
457-012	1-1/4	5	30	040	25.06
457-015	1-1/2	5	20	040	26.09
457-020	2	5	0	040	35.21
457-025	2-1/2	5	0	040	49.28
457-030	3	5	0	040	78.71
457-040	4	4	0	040	108.98
457-060	6	1	0	040	242.16



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	7.31
497-007	3/4	15	90	040	8.36
497-010	1	10	60	040	8.54
497-012	1-1/4	5	30	040	27.56
497-015	1-1/2	5	20	040	28.73
497-020	2	5	0	040	38.74
497-025	2-1/2	5	0	040	54.23
497-030	3	5	0	040	86.49
497-040	4	4	0	040	116.36
497-060	6	1	0	040	258.57

